

SYT Series

100KW to 136KW



The SYT Series infuses capacity with higher efficiency in a lightweight compact design. The option ranges from 100KW to 136KW that yields high performance for longer generation.

- ✓ Best Compatible with Bifacial PV and N-Type TOPCON Modules
- ✓ PV String Current Monitoring
- ✓ AFCI Function
- ✓ IP66 and C5 Protection
- ✓ 40A Input Current



PV String
Current Monitoring



PID Recovery



Ip66 Rating



LED, Wi-Fi + App

- ✓ Smart Air Cooling
- ✓ Surge Protection Type II (DC & AC)

- ✓ Max. Efficiency 98.6%
- ✓ Insulation Monitoring

THREE PHASE INVERTERS

Model SYT INPUT (DC)	100KW	110KW	125KW	136KW
Max. Input Voltage [V]	1100			
Start-up Input Voltage [V]	250			
Rated Input Voltage [V]	600			
MPPT Operating Voltage Range [Vdc]	200 ~ 1000			
No. of Independent MPP Trackers	9/2	9/2	10/2	10/2
Max. Input Current [A]	40			
Max. Short-circuit Current [A]	50			
OUTPUT (AC)				
Rated Output Power [kW]	100	110	125	136
Max. Output Current [A]	166.7	183.3	189.4	200
Rated Grid Voltage [Vac]	400, 3W+N+PE			
Grid Voltage Range [Vac]	320 ~ 460			
Grid Frequency Range [HZ]	45 ~ 55 / 55 ~ 65			
Adjustable Power Factor	0.8 Leading ~ 0.8 Lagging			
THDi [%]	<3			
EFFICIENCY				
Max. Efficiency [%]	98.6			
Euro. Efficiency [%]	98.2			
PROTECTION				
DC Switch	Yes			
DC Reverse Polarity Protection	Yes			
AC Overcurrent Protection	Yes			
AC Short-circuit Protection	Yes			
Surge Protection	DC Type II / AC Type II			
PID Recovery	Yes			
Insulation Monitoring	Yes			
Residual Current Monitoring	Yes			
AFCI	Optional			
PV String Current Monitoring	Optional			
GENERAL DATA				
Dimensions (W*H*D) [mm]	975*630*360			
Weight [kg]	90			
Operating Temperature [°C]	-30 ~ 60			
Cooling Method	Smart Air Cooling			
Operating Altitude [m]	4000 (>3000m Derating)			
Relative Humidity Range [%]	0 ~ 100 (non-Condensing)			
Ingress Protection Rating	IP66			
Isolation Method	Transformerless			
Display	LED, Wi-Fi + APP			
Communication	RS485 / USB / Wi-Fi + LAN / 4G			
DC Connection Type	MC4 Similar			
AC Connection Type	OT Terminal			
Warranty	As per the company standard policy (inverters + accessories)			
STANDARD				
Certificates	IEC 62109, IEC 61727, IEC 62116, IEC 60068, IEC 61683, IEC 61000-6-3, EN 50549			

HowD Innovation Private Limited : 22, Shantimangal, RS No. 91/2/2, TP. 32, Opp. Silver Gardenia, Nr. Gota Over Bridge, Sarkhej - Gandhinagar Hwy, Gota, Ahmedabad, Gujarat. 382481 Contact : (+91) 89800 16948 / (+91) 95104 20676. E-mail : info@howd.in