



SYT Series

5KW to 25KW

The SYT series of our company fuses higher capacity in a lightweight compact design. Best for commercial uses, our three-phase inverters function at smart string levels, which makes monitoring and diagnosis seamless.

Best compatible with Bifacial PV and N-Type TOPCON modules



DC Input 200% with a higher MPPT Range with inbuilt global MPP scan for higher yield efficiency



AC/DC built-in Type II SPD (Optional) and I-V curve diagnosis supported.



10s level interval of data update (Optional) and multiple interfaces for presenting data.



IP 65 rated, engineered to last with maximum flexibility, making it suitable for outdoor installation.

Three Phase Inverters

Model SYT		5KW	6KW	7KW	8KW	8.8KW	10KW	12KW	15KW	17KW	20KW	25KW
DC INPUT												
Max. Input Voltage[V]		1100	1100	1100	1100	1100	1100	1100	1100	1100	1100	1100
Start-up Input Voltage[V]		140	140	140	140	140	140	140	140	140	140	140
Rated Input Voltage[V]		600	600	600	600	600	600	600	600	600	600	600
MPPT Operating Voltage Range[V]		140 ~ 1000										
Max. Input Current[A]		16	16	16	16	16	16	16	32	32	32	32
Max. Short-circuit Current[A]		20	20	20	20	20	20	20	40	40	40	40
No. of Independent MPP Trackers		2										
No. of Strings per MPP Tracker		1+1	1+1	1+1	1+1	1+1	1+1	1+1	2+2	2+2	2+2	2+2
OUTPUT (AC)												
Rated Grid Voltage[V]		3/N/PE, 220/380, 230/400, 240/415										
Rated Output Power[W]		5000	6000	7000	8000	8800	10000	12000	15000	17000	20000	25000
Rated Grid Frequency [Hz]		50/60										
Rated Output Current[A]		7.2	8.7	9.96	11.6	12.5	14.5	17.4	21.7	24.6	29.0	36.2
Max. Output Current[A]		8.0	9.6	10.95	12.8	13.75	15.9	19.1	23.9	27.1	31.9	39.9
Power Factor		1 (Adjustable from 0.8 leading to 0.8 lagging)										
Total Harmonic Distortion [THDi] [%]		<3										
EFFICIENCY												
Peak efficiency		99.8										
Euro efficiency		97.8										
MPPT efficiency		98.6										
PROTECTION												
Insulation Monitoring		YES										
Residual Current Monitoring		YES										
PV String Current Monitoring		Optional										
DC Reverse Polarity Protection		YES										
Anti-islanding Protection		YES										
AC Short-circuit Protection		YES										
AC Overcurrent Protection		YES										
AC Overvoltage Protection		YES										
Surge Protection		DC/AC: Type II										
DC Switch		Optional										
AFCI		Optional										
GENERAL DATA												
Dimensions (WxHxD) [mm]		370*480*183.5										
Weight [kg]		21										
Cooling Method		Natural Convection										
Topology		Transformerless										
Noise Emission (typical) [dB]		<30										
Max. Operating Altitude [m]		3000										
Operating Temperature Range [°C]		-25 ~ 60										
Humidity [%]		0 ~ 100 (No Condensation)										
Protection Degree		IP65										
Internal Consumption at Night [W]		<3										
Monitoring Module		WIFI / 4G (Optional)										
Communication		RS485, Meter, DRM, Estop										
Display		LCD, Touch Key, App, Website										
STANDARD COMPLIANCE (MORE AVAILABLE UPON REQUEST)												
Safety		EN 62109-1/2, BIS IS 16169, BIS IS 16221-1/2										
EMC		EN 61000-6-1/2/3/4										
Grid Regulation		AS/NZS-4777.2, C10/11, EN50549-1, PN EN-50549-1, VDE-AR- N4105, RD 1699, CEI 0-21, NB/T 32004, VDE V 0126-1-1, UTE C 15-712-1										
WARRANTY												
On Inverters and Accessories		As per the company standard policy (inverters + accessories)										