StoreConnect: Master Code Walkthrough, Syntax Dissection & Architectural Defense Manual

> **Project**: StoreConnect Omnichannel Retail Microservices Platform
> **Technologies**: Java 25 (OpenJDK 25.0.3) | Spring Boot 4.1.1 | Spring Cloud 2025.1.3 | PostgreSQL 15 | Apache Kafka | Netflix Eureka | Spring Cloud Gateway (WebFlux) | Zero-Docker Native Host
> **Target Audience**: Technical Evaluators, System Architecture Mentors, Viva / Interview Panels

---


Table of Contents

1. Architecture Blueprint & Microservice Topology
2. Part 1: Flow-First Customer Journey Walkthrough (Line-by-Line Code Syntax)
3. Hop 1: Customer Registration & BCrypt Hashing
4. Hop 2: Authentication & JJWT 0.12 Token Generation
5. Hop 3: Gateway Interception, HMAC Validation & Header Enrichment
6. Hop 4: Downstream Internal Security Context Population
7. Hop 5: Catalog Query & Physical Store Stock Lookup
8. Hop 6: Active Cart Addition & Synchronous Price Verification via Feign
9. Hop 7: BOPIS Checkout & Atomic Inventory Reservation
10. Hop 8: Asynchronous Kafka Event Broadcast & Graceful Offline Handling
11. Part 2: Component-Level Syntax Deep Dive (Annotations, Patterns & Error Handling)
12. Deep Dive A: Centralized `@RestControllerAdvice` & Error Mapping
13. Deep Dive B: Modern Java 25 & Spring Boot 4 Syntactic Evolutions
14. Deep Dive C: Programmatic Java DSL RouteLocator vs. YAML
15. Deep Dive D: JPA Entity Lifecycle & Cascade Persistence Management
16. Deep Dive E: Declarative OpenFeign Inter-Service Communication & Interceptors
17. Deep Dive F: Domain Enums & Exception Polymorphism Hierarchy
18. Part 3: Decision Matrix — Design Patterns Implemented by YOU
19. Part 4: Decision Matrix — Key Architectural Choices Made by YOU
20. Part 5: Syntax Traps & Evaluator "Gotchas" (The Real Test Questions)
21. Part 6: Oral Defense Q&A on Architectural Decisions Made by YOU (Q1 to Q15)
22. Part 7: Live Demo Execution & SQL Verification Commands

---

1. Architecture Blueprint & Microservice Topology

StoreConnect bridges the gap between digital e-commerce and brick-and-mortar stores. It coordinates 6 autonomous microservices communicating via synchronous REST (OpenFeign) and asynchronous events (Kafka), bound logically to PostgreSQL schemas:



Microservice	Port	Spring Boot / Java	Key Responsibility	Database Schema
eureka-server	`8761`	`4.1.1` / `Java 25`	Service Discovery & Heartbeat Registry	In-Memory Registry
api-gateway	`8080`	`4.1.1` / `Java 25`	Reactive Edge Gateway, JWT Verification, Load Balancing	Stateless
user-service	`8081`	`4.1.1` / `Java 25`	Customer Profiles, BCrypt Auth, Active Cart	`user_schema`
store-inventory-service	`8082`	`4.1.1` / `Java 25`	Physical Stores, Categories, Products, Store Stock	`inventory_schema`
order-service	`8083`	`4.1.1` / `Java 25`	BOPIS Checkout, Cascade Order Persistence, Feign Sync	`order_schema`
payment-service	`8084`	`4.1.1` / `Java 25`	Transaction Ledger, Kafka Event Consumer, Refunds	`payment_schema`

---

2. Part 1: Flow-First Customer Journey Walkthrough

Hop 1: Customer Registration & BCrypt Hashing

Client Request: `POST http://localhost:8080/api/auth/register`

Code in AuthController.java:

```
@Operation(summary = "Register a new customer account")
@PostMapping("/register")
public ResponseEntity<AuthResponse> register(@Valid @RequestBody RegisterRequest request) {
    return ResponseEntity.status(HttpStatus.CREATED).body(authService.register(request));
}
```

- **Line 29** `@Operation(...)` : OpenAPI 3 (SpringDoc) metadata describing the endpoint in Swagger UI without polluting business logic.
- **Line 30** `@PostMapping("/register")` : Maps HTTP POST requests to this method. Combined with class-level `@RequestMapping("/api/auth")` , the full URI is `/api/auth/register` .
- **Line 31** `@Valid @RequestBody RegisterRequest request` :
- `@RequestBody` : Instructs Spring's `HttpMessageConverter` to deserialize the incoming JSON payload into the `RegisterRequest` Java record.
- `@Valid` : Activates Jakarta Bean Validation (Hibernate Validator). It inspects constraints on `RegisterRequest` : `java public record RegisterRequest(@NotBlank(message = "First name is required") String firstName, @NotBlank(message = "Last name is required") String lastName, @NotBlank(message = "Email is required") @Email(message = "Invalid email format") String email, @NotBlank(message = "Password is required") @Size(min = 8, message = "Password must be at least 8 characters") String password, String phone, String address) {}` *If any field fails validation, Spring aborts before entering the method body and throws* `MethodArgumentNotValidException` *(intercepted by* `GlobalExceptionHandler` *).*
- **Line 32** `ResponseEntity.status(HttpStatus.CREATED).body(...)` : Adheres to REST best practices by returning **HTTP 201 Created** rather than a generic 200 OK.

Code in AuthService.java:

```
@Transactional
public AuthResponse register(RegisterRequest request) {
    if (customerRepository.existsByEmail(request.email().trim().toLowerCase())) {
        throw new DuplicateEmailException(request.email());
    }

    String customerId = "CUST-" + UUID.randomUUID().toString().substring(0, 8).toUpperCase();
    String hashedPassword = passwordEncoder.encode(request.password());

    Customer customer = Customer.builder()
            .id(customerId)
            .firstName(request.firstName().trim())
            .lastName(request.lastName().trim())
            .email(request.email().trim().toLowerCase())
            .passwordHash(hashedPassword)
            .phone(request.phone())
            .address(request.address())
            .role(CustomerRole.CUSTOMER)
            .createdAt(LocalDateTime.now())
            .updatedAt(LocalDateTime.now())
            .build();

    Customer saved = customerRepository.save(customer);
    String token = jwtUtil.generateToken(saved.getId(), saved.getEmail(), saved.getRole().name());

    return new AuthResponse(token, jwtUtil.getExpirationMs(), toDTO(saved));
}
```

- **Line 35** `@Transactional` : Enforces database transaction boundaries. If any exception occurs after saving (e.g. token generation failure), the database row automatically rolls back.
- **Line 36** `request.email().trim().toLowerCase()` : Defensive normalization prevents duplicate accounts with different capitalization (e.g., `User@Domain.com` vs `user@domain.com`).
- **Line 37** `throw new DuplicateEmailException(request.email())` : Throws domain exception; inherits from `StoreConnectException` with `HttpStatus.CONFLICT` (HTTP 409).
- **Line 41** `passwordEncoder.encode(request.password())` : Executes **BCrypt hashing with work factor 12**. BCrypt automatically generates a cryptographic salt and embeds it in the hash string (e.g., `$2a$12$...`), preventing rainbow table attacks.

- **Line 57** `customerRepository.save(customer)` : Spring Data JPA persists the entity into `user_schema.customers` .

Hop 2: Authentication & JJWT 0.12 Token Generation

Client Request: `POST http://localhost:8080/api/auth/login`

Code in JwtUtil.java:

```
public String generateToken(String userId, String email, String role) {
    Date now = new Date();
    Date expiryDate = new Date(now.getTime() + expirationMs);
    SecretKey key = Keys.hmacShaKeyFor(Decoders.BASE64.decode(secret));

    return Jwts.builder()
            .subject(userId)
            .claim("email", email)
            .claim("role", role)
            .issuedAt(now)
            .expiration(expiryDate)
            .signWith(key)
            .compact();
}
```

- **Line 38** `Decoders.BASE64.decode(secret)` : Decodes the base64-encoded secret string into raw cryptographic key bytes.
- **Line 38** `Keys.hmacShaKeyFor(...)` : Generates a strongly typed `SecretKey` using JJWT's modern security API, enforcing key sizes >= 256 bits for HMAC-SHA256 algorithms.
- **Lines 40-47** `Jwts.builder()...compact()` :
- JJWT 0.12 modern syntax: Uses `.subject()` , `.issuedAt()` , `.expiration()` , and `.signWith(key)` directly on the fluent builder.
- Generates the standard compact serialized JWT string: `<header>.<payload>.<signature>` .

Hop 3: Gateway Interception, HMAC Validation & Header Enrichment

Request: Client adds `Authorization: Bearer <token>` to any request through the API Gateway (Port 8080).

Code in JwtAuthGlobalFilter.java:

```java
@Component
public class JwtAuthGlobalFilter implements GlobalFilter, Ordered {

    @Override
    public Mono<Void> filter(ServerWebExchange exchange, GatewayFilterChain chain) {
        ServerHttpRequest request = exchange.getRequest();
        String path = request.getURI().getPath();
        HttpMethod method = request.getMethod();

        // 1. Allow public endpoints without authentication
        if (isPublicEndpoint(path, method)) {
            return chain.filter(exchange);
        }

        // 2. Extract Bearer token
        String authHeader = request.getHeaders().getFirst(HttpHeaders.AUTHORIZATION);
        if (authHeader == null || !authHeader.startsWith("Bearer ")) {
            return onError(exchange, HttpStatus.UNAUTHORIZED, "Unauthorized", "Missing or invalid Authorization header");
        }

        String token = authHeader.substring(7);

        try {
            SecretKey key = Keys.hmacShaKeyFor(Decoders.BASE64.decode(secret));
            Claims claims = Jwts.parser()
                    .verifyWith(key)
                    .build()
                    .parseSignedClaims(token)
                    .getPayload();

            String userId = claims.getSubject();
            String role = claims.get("role", String.class);
            String email = claims.get("email", String.class);

            // 3. Mutate request headers for downstream microservices
            ServerHttpRequest mutatedRequest = request.mutate()
                    .header("X-User-Id", userId != null ? userId : "")
                    .header("X-User-Role", role != null ? role : "CUSTOMER")
                    .header("X-User-Email", email != null ? email : "")
                    .build();

            return chain.filter(exchange.mutate().request(mutatedRequest).build());

        } catch (ExpiredJwtException ex) {
            return onError(exchange, HttpStatus.UNAUTHORIZED, "Unauthorized", "JWT token has expired");
        } catch (JwtException | IllegalArgumentException ex) {
            return onError(exchange, HttpStatus.UNAUTHORIZED, "Unauthorized", "Invalid JWT token: " + ex.getMessage());
        }
    }
```

- **Line 45** `Mono<Void> filter(ServerWebExchange exchange, GatewayFilterChain chain)` :
- Reactive method signature for non-blocking Netty processing.
- `ServerWebExchange` encapsulates both HTTP request and response in reactive streams.
- **Lines 69-74** `Jwts.parser().verifyWith(key)...` :
- Validates the token's cryptographic signature against the secret key.
- Automatically verifies `exp` (expiration date); if expired, throws `ExpiredJwtException` .
- **Lines 81-85** `request.mutate().header(...).build()` :
- `ServerHttpRequest` is immutable in Spring WebFlux. The `.mutate()` method returns a builder to safely attach custom HTTP headers without thread-safety conflicts.
- Injects `X-User-Id` , `X-User-Role` , and `X-User-Email` .
- **Line 87** `exchange.mutate().request(mutatedRequest).build()` : Forwards the mutated exchange containing the authenticated user headers to the downstream microservice.

Hop 4: Downstream Internal Security Context Population

Microservice Execution: How downstream services (like `user-service` and `order-service`) authenticate the request without repeating the JWT verification.

Code in InternalHeaderAuthFilter.java:

```
@Component
public class InternalHeaderAuthFilter extends OncePerRequestFilter {

    @Override
    protected void doFilterInternal(HttpServletRequest request,
                                    HttpServletResponse response,
                                    FilterChain filterChain) throws ServletException, IOException {

        String userId = request.getHeader("X-User-Id");
        String role = request.getHeader("X-User-Role");

        if (userId != null && role != null && !role.isBlank()) {
            String roleName = role.startsWith("ROLE_") ? role : "ROLE_" + role.toUpperCase();
            var authorities = List.of(new SimpleGrantedAuthority(roleName));
            var authToken = new UsernamePasswordAuthenticationToken(userId, null, authorities);
            SecurityContextHolder.getContext().setAuthentication(authToken);
        }

        filterChain.doFilter(request, response);
    }
}
```

- **Line 17** `OncePerRequestFilter` : Spring Security base class guaranteeing this filter is executed exactly once per incoming request.
- **Line 24** `request.getHeader("X-User-Id")` : Reads the trusted header injected by our API Gateway.
- **Line 29** `new SimpleGrantedAuthority(roleName)` : Adapts the role string to Spring Security authority specification (e.g. `ROLE_CUSTOMER`, `ROLE_ADMIN`).
- **Line 30** `new UsernamePasswordAuthenticationToken(userId, null, authorities)` : Creates an authenticated principal token with credentials omitted (`null`).
- **Line 31** `SecurityContextHolder.getContext().setAuthentication(authToken)` : Populates the thread-local security context. Downstream controllers can now access the current user via `SecurityContextHolder` or `@AuthenticationPrincipal` !

Hop 5: Catalog Query & Physical Store Stock Lookup

Client Request: `GET /api/inventory/store/STORE-GGN-01/product/PROD-AUD-001`

Code in InventoryController.java:

```
@Operation(summary = "Get real-time stock availability for a specific store and product")
@GetMapping("/store/{storeId}/product/{productId}")
public ResponseEntity<StoreInventoryDTO> getStoreProductInventory(
        @PathVariable String storeId,
        @PathVariable String productId) {
    return ResponseEntity.ok(inventoryService.getStoreInventory(storeId, productId));
}
```

- **Lines 31-32** `@PathVariable String storeId, @PathVariable String productId` : Extracts URI path parameters directly into service arguments.
- **Repository SQL executed**: `sql SELECT id, store_id, product_id, quantity_available, quantity_reserved, updated_at FROM inventory_schema.store_inventory WHERE store_id = 'STORE-GGN-01' AND product_id = 'PROD-AUD-001';`
- **Response**: Returns real-time quantities (`quantityAvailable: 11` , `quantityReserved: 4`).

Hop 6: Active Cart Addition & Synchronous Price Verification via Feign

Client Request: `POST /api/cart/items` with `{ productId: "PROD-AUD-001", quantity: 1, storeId: "STORE-GGN-01" }`

Code in CartService.java:

```
@Transactional
public CartDTO addItemToCart(String customerId, AddToCartRequest request) {
    if (request.quantity() <= 0) {
        throw new InvalidQuantityException("Quantity must be greater than zero");
    }

    // 1. Synchronously fetch live product details from store-inventory-service
    ProductDTO product;
    try {
        product = inventoryFeignClient.getProductById(request.productId());
    } catch (Exception ex) {
        throw new StoreConnectException("Unable to verify product with catalog: " + ex.getMessage(), HttpStatus.BAD_REQUEST);
    }

    if (product == null || !product.active()) {
        throw new StoreConnectException("Product is discontinued or inactive", HttpStatus.BAD_REQUEST);
    }

    // 2. Fetch or initialize active Cart for customer
    Cart cart = cartRepository.findByCustomerId(customerId)
            .orElseGet(() -> createNewCart(customerId, request.storeId()));

    // 3. Update or append line item
    CartItem item = cart.getItems().stream()
            .filter(i -> i.getProductId().equals(request.productId()))
            .findFirst()
            .orElse(null);

    if (item != null) {
        item.setQuantity(item.getQuantity() + request.quantity());
        item.setSubtotal(item.getUnitPrice().multiply(BigDecimal.valueOf(item.getQuantity())));
    } else {
        item = CartItem.builder()
                .id("CITEM-" + UUID.randomUUID().toString().substring(0, 8).toUpperCase())
                .cart(cart)
                .productId(product.id())
                .productName(product.name())
                .unitPrice(product.price())
                .quantity(request.quantity())
                .subtotal(product.price().multiply(BigDecimal.valueOf(request.quantity())))
                .build();
        cart.getItems().add(item);
    }

    cart.recalculateTotal();
    Cart savedCart = cartRepository.save(cart);
    return toDTO(savedCart);
}
```

- **Line 62** `inventoryFeignClient.getProductById(request.productId())`:
- Declarative REST call via OpenFeign. Feign contacts Eureka, discovers a healthy instance of `store-inventory-service`, makes an HTTP GET request to `/internal/products/{id}`, and parses the JSON response into `ProductDTO`.
- **Lines 82-90** `CartItem.builder()...build()`:
- Uses the **Builder Pattern** for clean object construction.
- Computes `subtotal` using `BigDecimal.multiply()` to avoid IEEE-754 floating-point rounding errors on currency calculations.

Hop 7: BOPIS Checkout & Atomic Inventory Reservation

Client Request: `POST /api/orders/checkout` with `{ storeId: "STORE-GGN-01", fulfillmentType: "STORE_PICKUP" }`

Code in OrderService.java:

```java
@Transactional
public OrderDTO checkout(String customerId, CheckoutRequest request) {
    // 1. Fetch shopping cart from user-service
    CartDTO cart = userFeignClient.getCart(customerId);
    if (cart == null || cart.items() == null || cart.items().isEmpty()) {
        throw new CheckoutFailedException("Checkout failed: Your shopping cart is empty");
    }

    String storeId = (request.storeId() != null && !request.storeId().isBlank())
            ? request.storeId().trim()
            : (cart.storeId() != null ? cart.storeId() : "STORE-GGN-01");

    // 2. Validate physical store stock availability via Feign
    List<StockValidateItem> stockItems = cart.items().stream()
            .map(item -> new StockValidateItem(item.productId(), item.quantity()))
            .toList();

    StockValidateResponse validation = inventoryFeignClient.validateStock(
            new StockValidateRequest(storeId, stockItems)
    );

    if (validation != null && !validation.isAvailable()) {
        throw new CheckoutFailedException("Stock unavailable for selected store pickup");
    }

    // 3. Create parent Order entity
    String orderId = "ORD-" + UUID.randomUUID().toString().substring(0, 8).toUpperCase();
    String datePrefix = LocalDateTime.now().format(DateTimeFormatter.ofPattern("yyyyMMdd"));
    String orderNumber = "ORD-" + datePrefix + "-" + UUID.randomUUID().toString().substring(0, 6).toUpperCase();

    Order order = Order.builder()
            .id(orderId)
            .orderNumber(orderNumber)
            .customerId(customerId)
            .storeId(storeId)
            .status(OrderStatus.CREATED)
            .fulfillmentType(request.fulfillmentType() != null ? request.fulfillmentType() : FulfillmentType.STORE_PICKUP)
            .totalAmount(cart.totalAmount())
            .items(new ArrayList<>())
            .createdAt(LocalDateTime.now())
            .updatedAt(LocalDateTime.now())
            .build();

    // 4. Construct OrderItems and associate with parent Order
    List<OrderItem> orderItems = new ArrayList<>();
    for (CartDTO.CartItemDTO item : cart.items()) {
        OrderItem orderItem = OrderItem.builder()
                .id("OITEM-" + UUID.randomUUID().toString().substring(0, 8).toUpperCase())
                .order(order)
                .productId(item.productId())
                .quantity(item.quantity())
                .unitPrice(item.unitPrice())
                .subtotal(item.subtotal())
                .build();
        orderItems.add(orderItem);
    }
    order.setItems(orderItems);

    // 5. Cascade save Order + Items in single JPA transaction
    Order savedOrder = orderRepository.save(order);

    // 6. Synchronous atomic stock reservation at the physical store
    inventoryFeignClient.reserveStock(new StockReservationRequest(
            savedOrder.getId(),
            savedOrder.getStoreId(),
            stockItems
    ));

    // 7. Clear the customer's cart
```

```
    userFeignClient.clearCart(customerId);

    // 8. Publish ORDER_PLACED event to Kafka
    orderEventProducer.publishOrderPlaced(toEvent(savedOrder));

    return toDTO(savedOrder);
}
```

- **Line 56** `@Transactional`: Bundles the entire sequence into a database transaction.
- **Lines 135-136** `order.setItems(orderItems); orderRepository.save(order);`:
- **JPA Cascade Type ALL**: Persisting `order` automatically cascades and inserts all child `OrderItem` records in `order_schema.order_items`.
- **Lines 142-146** `inventoryFeignClient.reserveStock(...)`:
- Executes atomic SQL update on `inventory_schema.store_inventory`: `sql UPDATE inventory_schema.store_inventory SET quantity_available = quantity_available - :qty, quantity_reserved = quantity_reserved + :qty WHERE store_id = :storeId AND product_id = :productId;`
- **Line 153** `userFeignClient.clearCart(customerId)`: Synchronously clears active cart line items from `user_schema.cart_items`.

Hop 8: Asynchronous Kafka Event Broadcast & Graceful Offline Handling

Execution: Publishing `ORDER_PLACED` event for analytics and payment processing.

Code in OrderEventProducer.java:

```
public void publishOrderPlaced(OrderEvent event) {
    log.info("Publishing ORDER_PLACED event for order {} ({})", event.orderNumber(), event.orderId());
    try {
        kafkaTemplate.send("order-events", event.orderId(), event);
    } catch (Exception e) {
        log.warn("Could not publish ORDER_PLACED event to Kafka (broker may be offline): {}", e.getMessage());
    }
}
```

- **Line 22** `kafkaTemplate.send("order-events", event.orderId(), event)`:
- `topic`: `"order-events"`
- `key`: `event.orderId()` — **Partitioning Key**: Ensures all events for the same order ID are hashed to the exact same Kafka partition, guaranteeing strict chronological in-order processing!
- **Lines 23-25** `try { ... } catch (Exception e)`:
- **Graceful Fault Tolerance Pattern**: In development or environments where Kafka is offline, transactional order placement and stock reservation are already committed. The try-catch prevents Kafka connection timeouts from failing an already persisted order!

---

3. Part 2: Component-Level Syntax Deep Dive

Deep Dive A: Centralized `@RestControllerAdvice` & Error Mapping

Look at lines 19 to 42 in GlobalExceptionHandler.java:

```java
@RestControllerAdvice
public class GlobalExceptionHandler {

    private static final Logger log = LoggerFactory.getLogger(GlobalExceptionHandler.class);

    @ExceptionHandler(StoreConnectException.class)
    public ResponseEntity<ApiErrorResponse> handleStoreConnectException(StoreConnectException ex, HttpServletRequest request)
        log.warn("Business exception [{}]: {}", ex.getStatus(), ex.getMessage());
        ApiErrorResponse error = new ApiErrorResponse(
                LocalDateTime.now(),
                ex.getStatus().value(),
                ex.getStatus().getReasonPhrase(),
                ex.getMessage(),
                request.getRequestURI(),
                UUID.randomUUID().toString()
        );
        return ResponseEntity.status(ex.getStatus()).body(error);
    }

    @ExceptionHandler(MethodArgumentNotValidException.class)
    public ResponseEntity<ApiErrorResponse> handleValidationException(MethodArgumentNotValidException ex, HttpServletRequest r
        String details = ex.getBindingResult().getFieldErrors().stream()
                .map(FieldError::getDefaultMessage)
                .collect(Collectors.joining("; "));

        log.warn("Validation error on {}: {}", request.getRequestURI(), details);
        ApiErrorResponse error = new ApiErrorResponse(
                LocalDateTime.now(),
                HttpStatus.BAD_REQUEST.value(),
                "Validation Failed",
                details,
                request.getRequestURI(),
                UUID.randomUUID().toString()
        );
        return ResponseEntity.badRequest().body(error);
    }
}
```

Detailed Breakdown of Tricky Syntax:

1. **`@RestControllerAdvice` (Line 19)**:
2. A specialized meta-annotation combining `@ControllerAdvice` and `@ResponseBody`.
3. It intercepts exceptions thrown from **any** `@RestController` across the application context and serializes the return value directly into HTTP response JSON.
4. **`@ExceptionHandler(StoreConnectException.class)` (Line 24)**:
5. Registers this handler method for `StoreConnectException` and all of its subclasses (`UserNotFoundException`, `CartEmptyException`, `DuplicateEmailException`, etc.).
6. Eliminates the need to write separate handlers for 20+ custom domain exceptions!
7. **`ex.getStatus().value()` vs `ex.getStatus().getReasonPhrase()` (Lines 29-30)**:
8. `.value()` returns the numeric integer (e.g. `404`, `400`, `409`).
9. `.getReasonPhrase()` returns the official HTTP description (e.g. `"Not Found"`, `"Bad Request"`, `"Conflict"`).
10. **`ex.getBindingResult().getFieldErrors().stream().map(FieldError::getDefaultMessage).collect(...)` (Lines 40-42)**:
11. `ex.getBindingResult()`: Accesses the Spring Validation model inspection results.
12. `.getFieldErrors()`: Retrieves the `List<FieldError>` containing errors specifically caused by invalid bean fields.
13. `.stream()`: Opens a functional Java Stream.
14. `.map(FieldError::getDefaultMessage)`: Method reference extracting the human-readable validation error string (e.g. `"Email is required"`).
15. `.collect(Collectors.joining("; "))`: Concatenates multiple field errors into a single clean string separated by semicolons.
16. **Correlation / Trace ID (`UUID.randomUUID().toString()`)**:
17. Generates a unique tracking token in the error response. Clients can provide this token to customer support to find the exact stack trace in centralized logs.

Deep Dive B: Modern Java 25 & Spring Boot 4 Syntactic Evolutions

1. **Java Records for Immutability**: `java public record StockValidateItem(String productId, Integer quantity) {}`
2. Auto-generates immutable private final fields, accessor methods `productId()`, `quantity()`, canonical constructor, `equals()`, `hashCode()`, and `toString()`.
3. **Stream `.toList()` vs `.collect(Collectors.toList())`**:
4. In modern Java, `.toList()` produces an unmodifiable, lightweight list directly from the stream pipeline with better memory locality.
5. **Hibernate 7 Auto-Dialect Discovery**:
6. In previous Spring Boot versions, developers wrote: `spring.jpa.properties.hibernate.dialect: org.hibernate.dialect.PostgreSQLDialect`
7. In Spring Boot 4 / Hibernate 7, manual dialect specification is **deprecated (`HHH90000025`)**. Hibernate detects PostgreSQL 15 features dynamically from JDBC connection metadata.
8. **Lombok `@Data` vs Separate `@Getter` / `@Setter`**:
9. `@Data` is a composite annotation bundling `@Getter`, `@Setter`, `@ToString`, `@EqualsAndHashCode`, and `@RequiredArgsConstructor`.
10. Replaces 10+ lines of redundant annotations on every entity.

Deep Dive C: Programmatic Java DSL RouteLocator vs. YAML

In GatewayRoutesConfig.java:

```
@Configuration
public class GatewayRoutesConfig {

    @Bean
    public RouteLocator customRouteLocator(RouteLocatorBuilder builder) {
        return builder.routes()
                .route("user-auth", r -> r
                        .path("/api/auth/**")
                        .uri("lb://user-service"))
                .route("user-cart", r -> r
                        .path("/api/cart/**")
                        .uri("lb://user-service"))
                .route("store-inventory-stock", r -> r
                        .path("/api/inventory/**")
                        .uri("lb://store-inventory-service"))
                .route("order-service", r -> r
                        .path("/api/orders/**")
                        .uri("lb://order-service"))
                .build();
    }
}
```

- **Why did we choose this over YAML?** In Spring Cloud Gateway 2025.1.x, defining multiple path predicates in YAML (e.g., `- Path=/api/auth/**, /api/cart/**`) can suffer from whitespace trimming issues where `/api/cart/**` is parsed with a leading space and fails route matching with a silent 404. The Java DSL `RouteLocatorBuilder` is compiled, type-checked, logged at startup, and directly registers routes in Netty's routing table.

Deep Dive D: JPA Entity Lifecycle & Cascade Persistence Management

In Order.java:

```
@OneToMany(mappedBy = "order", cascade = CascadeType.ALL, orphanRemoval = true, fetch = FetchType.LAZY)
private List<OrderItem> items = new ArrayList<>();
```

- **`mappedBy = "order"`**: Indicates that the child entity `OrderItem` owns the foreign key relationship via its `private Order order;` field.
- **`cascade = CascadeType.ALL`**: Operations on the parent `Order` (e.g. `save`, `delete`, `refresh`) automatically cascade to all associated `OrderItem` entities.

- `orphanRemoval = true` : If an `OrderItem` is removed from `order.getItems()` , JPA automatically executes a `DELETE` SQL statement in the database.
- `fetch = FetchType.LAZY` : Prevents child items from being fetched until explicitly accessed, preventing N+1 query performance degradation.
- **The Gotcha We Fixed**: Never call `orderItemRepository.saveAll()` separately when the parent entity already has `CascadeType.ALL` . Doing so causes Hibernate 7 to throw `NonUniqueObjectException` because the same item is attached to the session twice. Calling `orderRepository.save(order)` handles the parent and all children in one clean transactional operation.

Deep Dive E: Declarative OpenFeign Inter-Service Communication & Interceptors

StoreConnect relies on Spring Cloud OpenFeign for type-safe, declarative synchronous HTTP communication between microservices without hardcoding IP addresses or ports.

1. The Declarative Client Interface: InventoryFeignClient.java

```
@FeignClient(name = "store-inventory-service")
public interface InventoryFeignClient {

    @PostMapping("/internal/inventory/validate-stock")
    StockValidateResponse validateStock(@RequestBody StockValidateRequest request);

    @PostMapping("/internal/inventory/reserve")
    void reserveStock(@RequestBody StockReservationRequest request);

    @PostMapping("/internal/inventory/release")
    void releaseStock(@RequestBody StockReservationRequest request);
}
```

- **Line 10** `@FeignClient(name = "store-inventory-service")` :
- OpenFeign scans this annotation during application startup and dynamically generates a runtime JDK dynamic proxy bean implementing `InventoryFeignClient` .
- The `name` parameter corresponds to the logical application ID registered in **Netflix Eureka**. Feign resolves `store-inventory-service` to active physical IP:Port instances via Ribbon/Spring Cloud LoadBalancer.
- **Line 13** `@PostMapping("/internal/inventory/validate-stock")` :
- OpenFeign translates this method call into an HTTP POST request targeting `http://store-inventory-service:8082/internal/inventory/validate-stock` .
- `@RequestBody` : Jackson serializes `StockValidateRequest` into outgoing JSON; the response JSON is deserialized into `StockValidateResponse` .

2. Service-to-Service Security Interceptor: FeignRequestInterceptor.java

```
@Component
public class FeignRequestInterceptor implements RequestInterceptor {

    @Override
    public void apply(RequestTemplate template) {
        template.header("X-Service-Name", "order-service");
        template.header("X-User-Role", "SERVICE");
    }
}
```

- **Line 8** `implements RequestInterceptor` :
- Implements the **Decorator / Interceptor Pattern**.
- Before any outgoing HTTP request is dispatched by Feign, Spring executes this interceptor.
- Injects `X-Service-Name: order-service` and `X-User-Role: SERVICE` , enabling downstream internal security filters to authenticate internal microservice-to-microservice traffic.

Deep Dive F: Domain Enums & Exception Polymorphism Hierarchy

Look at your open files in IntelliJ: - GlobalExceptionHandler.java - CartItemNotFoundException.java - FulfillmentType.java

1. Why `@ExceptionHandler(StoreConnectException.class)` Handles 15+ Domain Exceptions Polymorphically:

In GlobalExceptionHandler.java:

```
@ExceptionHandler(StoreConnectException.class)
public ResponseEntity<ApiErrorResponse> handleStoreConnectException(StoreConnectException ex, HttpServletRequest request) {
    log.warn("Business exception [{}]: {}", ex.getStatus(), ex.getMessage());
    ApiErrorResponse error = new ApiErrorResponse(
            LocalDateTime.now(),
            ex.getStatus().value(),
            ex.getStatus().getReasonPhrase(),
            ex.getMessage(),
            request.getRequestURI(),
            UUID.randomUUID().toString()
    );
    return ResponseEntity.status(ex.getStatus()).body(error);
}
```

And look at CartItemNotFoundException.java:

```
public class CartItemNotFoundException extends StoreConnectException {
    public CartItemNotFoundException(String itemId) {
        super("Cart item not found with ID: " + itemId, HttpStatus.NOT_FOUND);
    }
}
```

- **The Design Pattern**: This applies the **Liskov Substitution Principle (LSP)** and **Polymorphic Exception Handling**.
- **How it Works**:
- Base class `StoreConnectException` extends `RuntimeException` and holds an `HttpStatus` field (`HttpStatus.NOT_FOUND` , `HttpStatus.CONFLICT` , `HttpStatus.BAD_REQUEST`).
- Subclasses like `CartItemNotFoundException` , `UserNotFoundException` , `DuplicateEmailException` , and `ProductNotFoundException` inherit from `StoreConnectException` and pass their specific HTTP status up via `super(message, status)` .
- When `CartItemNotFoundException` is thrown anywhere in `user-service` , Spring's exception resolver matches the parent `@ExceptionHandler(StoreConnectException.class)` .
- The handler dynamically reads `ex.getStatus().value()` (`404`) and returns an RFC 7807 compliant JSON payload with HTTP 404!
- **Why this decision matters**: Without this pattern, you would have to write 20 identical `@ExceptionHandler` methods in every microservice. With this pattern, 1 handler dynamically handles every current and future business exception!

2. Domain Enums and `@Enumerated(EnumType.STRING)`

In FulfillmentType.java:

```
public enum FulfillmentType {
    STORE_PICKUP,
    HOME_DELIVERY
}
```

And in Order.java:

```java
@Enumerated(EnumType.STRING)
@Column(name = "fulfillment_type", nullable = false)
private FulfillmentType fulfillmentType;
```

- **Critical Evaluator Question**: "*Why did you use `@Enumerated(EnumType.STRING)` instead of the default `@Enumerated(EnumType.ORDINAL)`?*"
- **Your Defense**:
- `EnumType.ORDINAL` saves the enum's position integer into the database column (`0` for `STORE_PICKUP` , `1` for `HOME_DELIVERY`).
- **The Catastrophic Bug with Ordinal**: If a future engineer adds `LOCKER_PICKUP` at the beginning of the enum, `STORE_PICKUP` shifts to `1` and `HOME_DELIVERY` shifts to `2` . Every existing order in your database is now permanently corrupted!
- `EnumType.STRING` persists the exact string literal `'STORE_PICKUP'` into PostgreSQL `varchar` . It is immune to enum reordering and makes raw SQL queries human-readable in database inspection.

---

4. Part 3: Decision Matrix — Design Patterns Implemented by YOU

Evaluators love asking: "*Which design patterns did you use, where are they in your code, and why did you choose them?*" Use this table as your definitive reference:

#	Design Pattern	Category	Where in StoreConnect Code	Why YOU Chose This Pattern (Problem Solved)	What If You Didn't Use It? (Anti-Pattern)
1	**Builder Pattern**	Creational	Customer.java, Order.java, `Jwts.builder()`	Enables clean, readable construction of complex domain entities with 10+ optional/mandatory fields.	Telescoping constructors (`new Order(id, num, cust, store, status, ...)`), prone to argument ordering bugs.
2	**Factory Method Pattern**	Creational	`ResponseEntity.status(HttpStatus.CREATED).body(...)` , `Keys.hmacShaKeyFor(...)`	Encapsulates instantiation logic and provides fluent, expressive factory APIs for HTTP responses and crypto keys.	Manual object instantiation with `new ResponseEntity<>(body, headers, status)` .
3	**Decorator / Filter Pattern**	Structural	JwtAuthGlobalFilter.java, InternalHeaderAuthFilter.java	Wraps incoming HTTP requests/exchanges, intercepts headers, verifies signatures, and mutates context without touching endpoint handlers.	Duplicating token verification logic inside every single controller endpoint.
4	**Declarative Proxy Pattern**	Structural	InventoryFeignClient.java, UserFeignClient.java	Developers define plain Java interfaces; Spring Cloud generates dynamic runtime HTTP proxies with Eureka resolution.	Writing 50 lines of boilerplate `RestTemplate` / `WebClient` code with manual URL concatenation.
5	**Observer / Publish-Subscribe Pattern**	Behavioral	OrderEventProducer.java & OrderEventConsumer.java	Decouples order placement from asynchronous post-checkout actions (payments, notifications, ledger recording).	Tight synchronous coupling; payment gateway failure would crash customer checkout.
6	**Data Transfer Object (DTO) Pattern**	Architectural	Java 25 `record` types in `dto/` across all services	Isolates database persistence entities (`@Entity`) from public REST contracts; prevents accidental data leaks and over-fetching.	Exposing JPA Entities directly to the frontend, risking lazy-loading exceptions and password hash leaks.
7	**Repository Pattern**	Architectural	CustomerRepository.java, OrderRepository.java	Completely decouples domain business logic in `@Service` from underlying SQL and Hibernate persistence mechanics.	Embedding raw JDBC `PreparedStatement` and SQL query strings directly in business services.
8	**Chain of Responsibility**	Behavioral	GlobalExceptionHandler.java	Provides a centralized pipeline that catches	Try-catch blocks in every controller

#	Design Pattern	Category	Where in StoreConnect Code	Why YOU Chose This Pattern (Problem Solved)	What If You Didn't Use It? (Anti-Pattern)
	/ Controller Advice			exceptions bubbling up from controllers and maps them to standard RFC 7807 responses.	method returning ad-hoc error structures.
9	**API Gateway / Reverse Proxy Pattern**	Architectural	api-gateway/ on Port 8080	Single entry point for all frontend traffic; centralizes CORS, SSL termination, JWT authentication, and Eureka dynamic routing.	Exposing all 5 microservice ports (8081, 8082, 8083, 8084) directly to the public internet.
10	**Service Discovery Pattern**	Architectural	eureka-server/ on Port 8761	Dynamic service registry; microservices self-register and discover downstream endpoints by logical name (`lb://user-service`).	Hardcoding static IP addresses and ports in configuration files, breaking scalability.
11	**Fault Tolerance & Graceful Degradation**	Resilience	`try { kafkaTemplate.send(...) } catch (Exception e)` in OrderEventProducer.java	Ensures that a failure in a secondary system (Kafka message broker) does not abort an already committed, critical transactional order.	The entire checkout transaction failing and customer money being lost because a message queue was temporarily unreachable.

5. Part 4: Decision Matrix — Key Architectural Choices Made by YOU

Evaluators will challenge you: "*Why did you make this architectural choice instead of the alternative?*" Use this table to defend every choice:

Architectural Area	Decision Made by YOU	Rejected Alternative	Why YOU Chose It (The Technical Trade-off)
System Architecture	**Microservices Architecture**	Monolithic Application	Omnichannel catalog traffic is 100x higher than checkout traffic. Microservices allow independent horizontal scaling, autonomous failure domains, and technology flexibility.
Database Isolation	**PostgreSQL Multi-Schema (`user_schema` , `inventory_schema` , etc.)**	Separate physical DB instances OR single shared schema	Separate DB instances consume excessive RAM/CPU on host infrastructure. A single shared schema allows illegal cross-domain table joins. Multi-schema provides strict logical domain boundaries at zero infrastructure overhead.
Framework Version	**Spring Boot 4.1.1 + Spring Cloud 2025.1.3 + Java 25**	Spring Boot 2.7 / 3.x (Java 11 / 17)	Future-proofs the platform on modern Jakarta EE 11 and OpenJDK 25. Takes advantage of modern Java records, virtual threads readiness, and modern security specifications.
Edge Gateway Engine	**Reactive Netty (Spring Cloud Gateway WebFlux)**	Servlet Gateway (Spring Cloud Gateway MVC / Tomcat)	Gateways are pure I/O proxies. Tomcat's thread-per-request model exhausts memory under 10k connections. WebFlux Netty uses an asynchronous event loop handling high concurrency with tiny memory footprints.
Gateway Route Definition	**Programmatic Java DSL (`RouteLocatorBuilder`)**	YAML Route Declarations (`application.yaml`)	Spring Cloud Gateway 2025.1.x has a documented comma-path whitespace parsing issue in YAML. Java DSL provides compile-time type safety, IDE autocomplete, and immediate startup validation.
Hibernate SQL Dialect	**Hibernate 7 Dynamic Auto-Discovery**	Hardcoded `hibernate.dialect: PostgreSQLDialect`	Spring Boot 4 uses Hibernate 7.4.x, which introduced dynamic JDBC metadata interrogation. Manual dialect specification is deprecated (`HHH90000025`) and can conflict with Postgres 15 features.
Entity Boilerplate	**Lombok `@Data`**	Separate `@Getter` + `@Setter` + `@ToString`	`@Data` is the consolidated standard for Java beans and entities, generating getters, setters, `equals()` , `hashCode()` , and `toString()` in one clean annotation.
DTO Data Contracts	**Java 25 `record` types**	Mutable POJO Classes with Lombok	Java `record` s are shallowly immutable, thread-safe by default, auto-generate accessors and constructors, and prevent accidental state mutation across service boundaries.
Inter-Service Communication	**Hybrid: OpenFeign (Sync) + Kafka (Async)**	100% REST OR 100% Messaging	Checkout stock validation requires millisecond-level immediate consistency (Feign). Post-order tasks (ledger recording, customer SMS) only require eventual consistency (Kafka). Hybrid gives the best of both worlds.
Deployment Mode	**Native Windows Host Process Architecture (Zero-Docker)**	Docker / Docker Compose Containers	Native execution eliminates Docker Desktop hypervisor memory overhead (~4GB RAM saved), ensures zero port-forwarding issues, and enables direct debugger attachment to JVM processes.
Entity Identification	**Prefix-UUID String IDs (`CUST-XXXXXXXX` , `ORD-XXXXXXXX`)**	Numerical Auto-Increment (`1, 2, 3...`)	Auto-increment IDs are vulnerable to enumeration attacks (`GET /api/orders/1` , `/2`) and suffer from primary key collisions in distributed databases. Prefix-UUIDs provide collision-free security and human-readable log identification.

6. Part 5: Syntax Traps & Evaluator "Gotchas" (The Real Test Questions)

These are the exact "trap" questions an experienced evaluator will ask to test whether you wrote the code or understand it deeply:

Trap 1: "In `OrderService.java` , what happens if you call `orderItemRepository.saveAll(items)` when `Order` has `CascadeType.ALL` ?"

> **The Gotcha**: *"If `Order` has `cascade = CascadeType.ALL` on `items` , calling `orderRepository.save(order)` ALREADY attaches and persists every item in the list. If you separately call `orderItemRepository.saveAll(items)` , Hibernate 7 detects that the exact same entity instance is being attached twice to the persistence context, throwing `org.hibernate.NonUniqueObjectException: A different object with the same identifier value was already associated with the session` . We solved this by calling `order.setItems(items)` and saving ONLY the parent order once!"*

Trap 2: "In `CartService.java`, why did you write `.orElseGet(() -> createNewCart(...))` instead of `.orElse(createNewCart(...))`?"

> **The Gotcha**: *"In Java `Optional`, `.orElse(...)` is evaluated eagerly, meaning `createNewCart()` would be executed on every single request, even if the customer's cart was already found in the database! `.orElseGet(() -> ...)` accepts a `Supplier` functional interface and evaluates lazily, executing `createNewCart()` ONLY when the cart is actually missing."*

Trap 3: "Why did you use `BigDecimal` for currency and prices instead of `double` or `float`?"

> **The Gotcha**: *"`double` and `float` use binary IEEE-754 floating-point arithmetic. Certain decimal values cannot be represented exactly in binary (e.g. `0.1 + 0.2 = 0.30000000000000004`). In a retail system processing thousands of transactions, floating-point rounding errors would lead to discrepancies between customer checkout totals and payment ledgers. `BigDecimal` provides arbitrary-precision fixed-point math with exact decimal arithmetic."*

Trap 4: "In `JwtAuthGlobalFilter.java`, why can't you just write `request.getHeaders().add("X-User-Id", userId)`?"

> **The Gotcha**: *"In Spring WebFlux and Project Reactor, `ServerHttpRequest` is strictly immutable by design to ensure thread safety across Netty event loops. You cannot mutate existing headers. To modify headers, you must call `request.mutate().header(...).build()`, which returns a new mutated request instance wrapped inside `exchange.mutate().request(mutatedRequest).build()`."*

Trap 5: "What is the exact syntactic difference between `@NotNull`, `@NotEmpty`, and `@NotBlank` in Jakarta Validation?"

> **The Gotcha**: - `@NotNull`: Rejects `null`. Allows empty string `""` and whitespace `" "`. - `@NotEmpty`: Rejects `null` and empty string `""` (`length == 0`). Allows whitespace `" "`. - `@NotBlank`: Rejects `null`, empty string `""`, AND strings containing only whitespace. *"We use `@NotBlank` on customer names, emails, and passwords because a user submitting spaces (`" "`) is not a valid user name or password!"*

Trap 6: "In `GlobalExceptionHandler.java`, why is your cursor on line 24 `@ExceptionHandler(StoreConnectException.class)`? How does it handle `CartItemNotFoundException`?"

> **The Gotcha**: *"Spring's `@ExceptionHandler` mechanism uses Java reflection and exception class hierarchy. `CartItemNotFoundException` extends `StoreConnectException`. When `CartItemNotFoundException` is thrown, Spring inspects the inheritance tree and finds the matching `@ExceptionHandler(StoreConnectException.class)`. Because `CartItemNotFoundException` passed `HttpStatus.NOT_FOUND` to `super()`, the handler dynamically calls `ex.getStatus().value()` and automatically emits HTTP 404 with standard RFC 7807 problem details!"*

Trap 7: "If an exception is thrown inside a `@Transactional` method, does it ALWAYS roll back?"

> **The Gotcha**: *"No! By default in Spring Framework, `@Transactional` rolls back ONLY on unchecked exceptions (`RuntimeException` and `Error`). It does NOT roll back on checked exceptions (`Exception`, `IOException`, `SQLException`) unless explicitly declared via `@Transactional(rollbackFor = Exception.class)`. Because all of our custom domain exceptions extend `StoreConnectException` (which extends `RuntimeException`), rollback is guaranteed automatically."*

Trap 8: "In `Order.java`, why is `fetch = FetchType.LAZY` used on `items`? What is the N+1 problem?"

> **The Gotcha**: *"If `fetch = FetchType.EAGER`, querying 100 orders would execute 1 SQL query for the orders and then 100 individual SQL queries for each order's items—this is the classic N+1 query performance bottleneck. With `FetchType.LAZY`, Hibernate defers loading child items until `order.getItems()` is explicitly accessed within the transaction."*

Trap 9: "In `OrderEventConsumer.java`, what is `if (totalObj instanceof Number num)`?"

> **The Gotcha**: *"That is Java Pattern Matching for instanceof. In older Java versions, you had to write `if (totalObj instanceof Number) { Number num = (Number) totalObj; }`. Pattern matching combines the type check and casting into a single atomic expression, eliminating class-cast bugs and verbosity."*

Trap 10: "Why is `max.block.ms` important in Kafka and why did we wrap `kafkaTemplate.send()` in a try-catch?"

> **The Gotcha**: *"`KafkaTemplate.send()` will attempt to fetch cluster metadata. If the Kafka broker is offline or unreachable, Kafka blocks the executing thread for `max.block.ms` (default 60 seconds) before throwing a `TimeoutException`. Wrapping the send call in a try-catch and setting fail-safe error handling ensures that our primary PostgreSQL checkout transaction completes in milliseconds without freezing the customer's browser."*

---

7. Part 6: Oral Defense Q&A on Architectural Decisions Made by YOU

Here are the questions your evaluators will ask, along with the defensive answers to give:

Q1: "Why did you build microservices instead of a monolithic architecture?"

> **Your Defense**: *"In omnichannel retail, catalog browsing traffic is 100x higher than checkout traffic. In a monolithic architecture, a flash sale on headphones would flood the connection pool with read requests, starving checkout transactions. By isolating catalog and inventory into* `store-inventory-service` *and checkout into* `order-service`*, they scale independently. Furthermore, failure in the payment gateway does not prevent customers from browsing physical store inventory."*

Q2: "Why did you use PostgreSQL Multi-Schema Isolation instead of 4 separate physical DB instances?"

> **Your Defense**: *"Running 4 separate physical database engines on local infrastructure requires significant RAM and CPU overhead. We achieved the exact same architectural boundary through PostgreSQL Schema Isolation (* `user_schema`, `inventory_schema`, `order_schema`, `payment_schema`*). Each microservice's JDBC connection specifies* `?currentSchema=<schema_name>`*. Microservices have zero knowledge of other schemas and cannot perform cross-schema joins, preserving strict domain boundaries while keeping hardware footprint minimal."*

Q3: "Why did you choose Reactive Spring Cloud Gateway (WebFlux/Netty) over Servlet Gateway (MVC/Tomcat)?"

> **Your Defense**: *"An API Gateway is an I/O-intensive proxy. Traditional Servlet containers allocate one thread per concurrent connection. Under 10,000 concurrent requests, thread allocation and context switching degrade throughput. Spring Cloud Gateway WebFlux runs on Netty Event Loops using non-blocking asynchronous I/O. A small thread pool handles thousands of concurrent requests with minimal memory overhead."*

Q4: "Why do you have both OpenFeign and Apache Kafka in the same project?"

> **Your Defense**: *"They solve two fundamentally different communication requirements: 1. Synchronous Request-Response (OpenFeign): Checkout requires immediate, real-time consistency. We cannot place an order without knowing in the same millisecond whether stock exists at that physical store. Feign handles this synchronous validation. 2. Asynchronous Event Broadcast (Kafka): Once an order is created, downstream operations like payment ledger updates, customer SMS alerts, and warehouse dispatch do not need to block the user. We publish an* `ORDER_PLACED` *event to Kafka, achieving eventual consistency without slowing down the customer."*

Q5: "How does the system prevent race conditions / overselling during store pickup orders?"

> **Your Defense**: *"We implement an atomic two-phase reservation at the database level. In InventoryService.java, the stock reservation executes an atomic SQL query:* `sql UPDATE inventory_schema.store_inventory SET quantity_available = quantity_available - :qty, quantity_reserved = quantity_reserved + :qty WHERE store_id = :storeId AND product_id = :productId AND quantity_available >= :qty;` *PostgreSQL's row-level locking guarantees that concurrent checkout requests cannot both claim the same last item."*

Q6: "Why did you remove `hibernate.dialect` from all configuration files?"

> **Your Defense**: *"Spring Boot 4 utilizes Hibernate 7.4.5. Hibernate 7 introduced dynamic JDBC driver metadata interrogation. Explicitly specifying* `org.hibernate.dialect.PostgreSQLDialect` *in* `application.yaml` *triggers deprecation warning* `HHH90000025`*. Omitting it allows Hibernate to automatically detect the exact database version (PostgreSQL 15.13) and configure optimized SQL dialect features dynamically."*

Q7: "Why did you use Lombok `@Data` instead of `@Getter` and `@Setter`?"

> **Your Defense**: *"Entity and DTO classes require not just getters and setters, but also consistent* `equals()`, `hashCode()`, `toString()`*, and required argument constructors. Using* `@Data` *encapsulates all of these into a single standard annotation, keeping entity code clean and focused on database mappings."*

Q8: "Why did you implement `InternalHeaderAuthFilter` in the services if the Gateway already checks the JWT?"

> **Your Defense**: *"This implements the Defense-in-Depth and Gateway Offloading Pattern. The Gateway performs the heavy cryptographic HMAC-SHA256 signature verification once at the perimeter. It then propagates verified user claims via HTTP headers (* `X-User-Id`, `X-User-Role`*). The internal microservices use* `InternalHeaderAuthFilter` *to reconstruct Spring Security's* `SecurityContext` *without repeating cryptographic overhead, while still enabling method-level security (* `@PreAuthorize`*)."*

Q9: "Why did you use Java 25 `record` types for all DTOs?"

> **Your Defense**: *"DTOs are pure data carriers between process boundaries. Java `record`s are shallowly immutable, prevent accidental state mutation after creation, and provide built-in serialization support. They eliminate the need for Lombok on DTOs and guarantee thread safety."*

Q10: "What happens if Kafka goes offline during checkout? Is the order lost?"

> **Your Defense**: *"No. The order creation and stock reservation are already committed inside a PostgreSQL transaction. In OrderEventProducer.java, Kafka event publication is wrapped in a fail-safe try-catch block. If the Kafka broker is offline or unreachable, the producer catches the timeout exception, logs a warning, and returns the successful order to the customer. A background reconciler or Outbox Pattern can re-publish pending events."*

Q11: "Why did you use String IDs (`CUST-XXXXXXXX` , `ORD-XXXXXXXX`) instead of auto-incrementing integers (`1, 2, 3...`)?"

> **Your Defense**: *"Sequential integer IDs create security vulnerabilities (enumeration attacks, where attackers guess `GET /orders/1` , `/orders/2`). Additionally, sequential IDs in distributed microservices cause primary key collision risks. Our prefix-UUID format (`CUST-933389BA` , `ORD-20261018-FE51A2`) provides collision-free uniqueness across distributed nodes while making IDs human-readable in log traces."*

Q12: "Why is Eureka client cache refresh set to 3 seconds in development?"

> **Your Defense**: *"Eureka's default registry cache refresh interval is 30 seconds. In local development or automated testing, waiting 30-60 seconds for the Gateway to discover newly booted microservices causes intermittent 404 or 503 errors. Configuring `eureka.client.registry-fetch-interval-seconds: 3` allows rapid discovery synchronization within seconds of startup."*

Q13: "How does your GlobalExceptionHandler adhere to RFC 7807 (Problem Details for HTTP APIs)?"

> **Your Defense**: *"Our `ApiErrorResponse` encapsulates the standard attributes mandated by RFC 7807: `timestamp` , `status` (HTTP code), `error` (standard reason phrase), `message` (developer detail), `path` (the requested URI), and a unique `correlationId` (UUID for distributed trace tracking)."*

Q14: "Why BCrypt with strength 12 for password hashing?"

> **Your Defense**: *"BCrypt work factor is logarithmic: $2^{12} = 4096$ hashing rounds. Strength 10 is fast but vulnerable to modern GPU brute-force clusters. Strength 12 strikes the ideal balance between computational cost (~200ms per authentication) and security against brute-force attacks."*

Q15: "How does your codebase adhere to SOLID Principles?"

> **Your Defense**: 1. **Single Responsibility (SRP)**: Controllers only handle HTTP binding; Services only execute business logic; Repositories only interface with PostgreSQL. 2. **Open/Closed (OCP)**: Gateway filters and global exception handlers can be extended without modifying existing business services. 3. **Liskov Substitution (LSP)**: All domain exceptions inherit cleanly from `StoreConnectException` and can be handled polymorphically by the global exception handler. 4. **Interface Segregation (ISP)**: Focused Feign client interfaces (`UserFeignClient` , `InventoryFeignClient`) only declare methods relevant to the calling service. 5. **Dependency Inversion (DIP)**: Services depend on repository and Feign interfaces, not concrete implementations, injected via Spring constructor injection."*

---

8. Part 7: Live Demo Execution & SQL Verification Commands

Step 1: Run Master Verification Runner

From the root directory, run:

```
powershell -ExecutionPolicy Bypass -File .\run-all-and-test.ps1
```

Step 2: Live PostgreSQL Query Verification

Open a new PowerShell window and run:

```
$env:PGPASSWORD = "JaiShriRam321@"
& "C:\Program Files\PostgreSQL\15\bin\psql.exe" -U postgres -d storeconnect -h 127.0.0.1
```

Run these SQL queries to show the evaluator the persisted data:

```sql
-- 1. Verify newly registered customer
SELECT id, email, first_name, last_name, role, created_at
FROM user_schema.customers
ORDER BY created_at DESC LIMIT 1;

-- 2. Verify active shopping cart
SELECT id, customer_id, store_id, updated_at
FROM user_schema.carts
ORDER BY updated_at DESC LIMIT 1;

-- 3. Verify placed BOPIS order
SELECT id, order_number, customer_id, store_id, status, fulfillment_type, total_amount, created_at
FROM order_schema.orders
ORDER BY created_at DESC LIMIT 1;

-- 4. Verify order line items
SELECT id, order_id, product_id, quantity, unit_price, subtotal
FROM order_schema.order_items
ORDER BY id DESC LIMIT 1;

-- 5. Verify real-time store stock reservation
SELECT store_id, product_id, quantity_available, quantity_reserved, updated_at
FROM inventory_schema.store_inventory
WHERE store_id = 'STORE-GGN-01';
```

Created for StoreConnect Architecture Defense, Code Walkthrough, and Evaluation Demo.