

PUC

(WEEK 13 One dimensional.
Array)

Status : Finished

Started : Monday, 13 January 2025, 12:13 PM

Completed : Monday, 13 January 2025

Duration : 41 mins 28 secs

Question 1

Correct

Flag question

Objective:

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

Arr-[1,2,3,4,6)

The sum of the first three elements, $1+2+3=6$. The value of the last element is 6.

Using zero based indexing, arr[3]-4 is the pivot between the two subarrays.

The index of the pivot is 3.

Function Description

Complete the function balancedSum in the editor below.

balancedSum has the following parameter(s):

int arr[n]: an array of integers

Returns:

int: an integer representing the index of the pivot

Constraints

$3 \leq n \leq 10$

$1 \leq arr[i] \leq 10$, where $0 \leq i < n$

It is guaranteed that a solution always exists.

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer n. the size of the array arr.

Each of the next n lines contains an integer, arr[i], where 0 ≤ i < n

Sample Case 0

Sample input 0

STDIN Function Parameters.

4 arr size n-4

1 arr[1, 2, 3, 3]

2

3

Sample Output 0

2

Explanation 0

The sum of the first two elements, 1+2=3. The value of the last element is 3.

Using zero based indexing, arr[2]-3 is the pivot between the two subarrays.

The index of the pivot is 2.

Sample Case 1

Sample Input 1

STDIN Function Parameters

3 arr size n-3

Arr = [1,2,1]

2

Sample Output 1

1

Explanation 1

The first and last elements are equal to 1.

Using zero based indexing, arr[1]=2 is the pivot between the two subarrays.

The index of the pivot is 1.

Answer. (penalty regime: 0%)

```
1  int balancedSum(int arr_count, int* arr)
2  {
3      int total_sum=0;
4      int left_sum=0;
5      for(int i=0;i<arr_count;i++)
6      {
7          total_sum+=arr[i];
8      }
9      for(int i=0;i<arr_count;i++)
10     {
11         if(left_sum==(total_sum-left_sum-arr[i]))
12         {
13             return i;
14         }
15         left_sum+=arr[i];
16     }
17     for(int i=0;i<arr_count;i++)
18     {
19         if(left_sum==(total_sum-left_sum-arr[i]))
20         {
21             return i;
22         }
23         left_sum+=arr[i];
24     }
25     return 1;
26 }
```

	Test	Expected	Got	
✓	int arr[] = {1,2,3,3}; printf("%d", balancedSum(4, arr))	2	2	✓

Passed all tests! ✓

Question 2

Correct

Flag question

Objective:

Calculate the sum of an array of integers

Example

Numbers [3, 13, 4, 11, 9)

The sum is 3+13+4+11+9=40.

Function Description

Complete the function arraySum in the editor below.

arraySum has the following parameter(s). int numbers[n]: an array of integers

Returns

Int: integer sum of the numbers array

Constraints

$1 < n < 10$

$1 < \text{numbers}[i] < 104$

Input Format for Custom Testing

Input from stdin will be processed as follows and passed to the function

The first line contains an integer n, the size of the array numbers

Each of the next n lines contains an integer numbers[i] where $0 \leq \text{numbers}[i] < 104$.

Sample Case 0

Sample Input 0

STDIN Function

5 numbers] size n=5

Numbers 11, 2, 3, 4, 5

3 4 5

Sample Output 0

15

Explanation 0

$1+2+3+4+5=15$

Sample Case 1

Sample Input 1

STDIN Function

2 numbers] size n=2

12 numbers = [12, 12]

Sample Output 1

24

Explanation 1

$12+12=24$

```

1
2 int arraySum(int numbers_count, int *numbers)
3 {
4     int sum=0;
5     for(int i=0;i<numbers_count;i++){
6         sum+=numbers[i];
7     }
8     return sum;
9 }
10

```

	Test	Expected	Got	
✓	int arr[] = {1,2,3,4,5}; printf("%d", arraySum(5, arr))	15	15	✓

Passed all tests! ✓

Question 3

Correct

Flag question

Objective:

Given an array of n integers, rearrange them so that the sum of the absolute differences of all adjacent elements is minimized. Then, compute the sum of those absolute differences. Example $n = 5$ $arr = [1, 3, 3, 2, 4]$ If the list is rearranged as $arr = [1, 2, 3, 3, 4]$, the absolute differences are $1-2, 2-3, 3-3, 3-4 = 1$. The sum of those differences is $1 + 1 + 0 + 1 = 3$ Function Description Complete the function `minDiff` in the editor below. `minDiff` has the following parameter: `arr`: an integer array Returns: `int`: the sum of the absolute differences of adjacent elements Constraints $2 \leq n \leq 105$ ($\leq arr[i] \leq 109$, where $0 \leq i < n$) Input Format For Custom Testing The first line of input contains an integer, n , the size of `arr`. Each of the following n lines contains an integer that describes `arr[i]` (where $0 \leq i < n$) Sample Case 0 Sample Input For Custom Testing STDIN Function 5 `arr[]` size $n = 5$ 5 `arr[]` = [5, 1, 3, 7, 3] 1373 Sample Output 6 Explanation $n = 5$ $arr = [5, 1, 3, 7, 3]$ If `arr` is rearranged as $arr' = [1, 3, 3, 5, 7]$, the differences are minimized. The final answer is $|1 - 3| + |3 - 3| + |3 - 5| + |5 - 7| = 6$. Sample Case 1 Sample Input For Custom Testing STDIN Function 2 `arr[]` size $n = 2$ 3 `arr[]` = [3,2] 2 Sample Output 1 Explanation $n = 2$ $arr = [3, 2]$ There is no need to rearrange because there are only two elements. The final answer is $3-2 = 1$.

Answer: (penalty regime: 0%)


```

1  ▾ int ads(int x){
2      return x<0?-x:x;
3  }
4  ▾ void bubblesort(int arr[],int n){
5      for(int i=0;i<n-1;i++){
6          for(int j=0;j<n-1;j++){
7              if(arr[j]>arr[j+1]){
8                  int temp=arr[j];
9                  arr[j]=arr[j+1];
10                 arr[j+1]=temp;
11             }
12         }
13     }
14 }
15 int minDiff(int arr_count, int* arr)
16 {
17     bubblesort(arr,arr_count);
18     int sum=0;
19     for(int i=1;i<arr_count;i++){
20         sum+=abs(arr[i]-arr[i-1]);
21     }
22     return sum;
23 }

```

	Test	Expected	Got	
✓	int arr[] = {5, 1, 3, 7, 3}; printf("%d", minDiff(5, arr))	6	6	✓

Passed all tests! ✓