AURORA ENGINE

Project Architecture & Technical Flow Handover Presentation

Target Audience: Engineering Leads, Software Architects & Incoming Development Teams
Domain: Research-Grade Modular Educational AI & QLoRA Subject Adaptation
Repository: AuroraEngine (Clean Architecture Paradigm)
Status: 100% Verified Suite • 130 Unit Tests Passing • Production Ready

6 CS Subject Domains DBMS • DSA • OOPS • OS • CNT • OOSE	**Qwen3-8B Foundation** 4-Bit NF4 QLoRA Adaptation	**FastAPI SSE Server** OpenAI-Compatible Streaming	**Next.js 16 Web UI** LaTeX Math & Code Support

1. Executive Overview & System Purpose

What AuroraEngine Is and How It Solves Educational LLM Trustworthiness

Core Purpose:
AuroraEngine is NOT a simple chatbot or naive RAG script. It is a research-grade educational AI framework that converts trusted educational textbooks and syllabi into domain-specialized language model adapters.

Supported Computer Science Curricula:
- **DBMS:** Database Systems (SQL, Relational Algebra, Transactions)
- **DSA:** Data Structures & Algorithms (Trees, Graphs, DP)
- **OOPS:** Object-Oriented Programming (Design Patterns, SOLID)
- **OS:** Operating Systems (Concurrency, Memory, Virtualization)
- **CNT:** Computer Networks (TCP/IP, Routing, OSI Layers)
- **OOSE:** Software Engineering (UML, Agile, System Requirements)

Key Architecture Pillars:
1. **Clean Architecture:** Domain models and interfaces strictly separated from external infrastructure or web frameworks.
2. **Interface-First Design:** Every pipeline stage is defined by abstract contracts before implementation.
3. **QLoRA Fine-Tuning:** 4-bit NF4 quantized adaptation on 8B parameter models (`Qwen/Qwen3-8B`).
4. **Domain Guardrails:** Non-CS queries (recipes, chit-chat) are rejected automatically at the API boundary.
5. **Artifact Immutability:** Checksums and parent UUID lineage tracking preserve reproducibility.

Framework Operational Status: ■ Core Pipeline, QLoRA Training Engine, FastAPI SSE Server, Next.js Frontend, Streamlit Lab, and 130 Pytest Verification Tests are 100% Implemented & Passing.

2. System Architecture Diagram

High-Level Layer Interactions Across Frontend, Backend, ML Subsystem, and Storage



Figure 1: *Architectural interaction map showing decoupled clean boundaries between client web apps, the API server, inference subsystem, data pipeline, and LoRA artifact storage.*

3. End-to-End Request Execution Flow

Detailed Step-by-Step Trajectory from Student Prompt to Token Streaming

Step & Stage	Execution Component	Technical Operation & Logic
1. Subject Selection & Query	Next.js Frontend (`frontend/src/app/page.tsx`)	User chooses CS domain context (e.g. Operating Systems `OS`) and enters query. Client calls `streamChatCompletion()` via Fetch API over HTTP POST to `/v1/chat/completions`.
2. Domain Guardrail Check	FastAPI API Server (`src/aurora/deployment/api_server.py`)	System prompt validates query scope. Non-CS topics (recipes, chit-chat) are rejected immediately with standardized educational boundary note.
3. Adapter Resolution	Adapter Routing Map (`ADAPTER_MAP`)	Maps model identifier (`aurora-os`) to adapter checkpoint directory `data/output/os_adapter/final_adapter`.
4. Dynamic LoRA Mount	`AdapterManager` & `InferenceEngine`	Hot-swaps target PEFT LoRA adapter weights on top of loaded `Qwen3-8B` base model in VRAM without reloading base weights.
5. Streaming Generation	`Generator` & PyTorch CUDA Engine	Executes token-by-token generation loop. Yields streaming text chunks back to FastAPI endpoint.
6. SSE Event Delivery	FastAPI `StreamingResponse`	Pushes `data: {"choices": [{"delta": {"content": "..."}}]}` event stream compliant with OpenAI API standard.
7. UI Math & Markdown Render	React Client (`react-markdown` + `katex`)	Renders live markdown formatting, syntax highlighted code blocks, and KaTeX mathematical equations for student.
8. Interaction Logging	JSONL Interaction Logger	Appends execution record (timestamp, prompt, adapter mode, latency, answer) to daily log file `data/logs/YYYY-MM-DD.jsonl`.

4. Core Data & Training Pipeline

The Multi-Stage Ingestion, Curriculum Extraction, and Fine-Tuning Sequence

Pipeline Phase Responsibilities:

1. Ingestion (`src/aurora/ingestion/`):
• Scans raw files (`FileScanner`), tracks checksums in `SourceRegistry`.
• Reads PDF/TXT documents into `RawDocument` domain models.

2. Preprocessing & Segmentation (`preprocessing/`, `segmentation/`):
• Normalizes reading order, strips layout noise.
• Splits text into semantically cohesive `StructuredDocument` chunks.

3. Curriculum Knowledge Extraction (`corpus/`, `knowledge/`):
• Extracts concept dependency graphs and syllabus taxonomies.
• Builds curriculum knowledge representations.

4. Educational Dataset Engineering (`dataset/`, `corpus/`):
• Generates synthetic QA instruction pairs across subject domains.
• Exports validated `.jsonl` files to `data/corpus/`.

Training & Packaging Pipeline:

5. QLoRA Training Engine (`src/aurora/training/`):
• `ModelPreparer`: Loads `Qwen/Qwen3-8B` with 4-bit NF4 double quantization (`bitsandbytes`).
• Configures PEFT LoRA target projection modules (`q_proj`, `v_proj`, etc.).
• `Trainer`: Executes PyTorch training loop over subject `.jsonl` corpora.

6. Checkpoint Management (`checkpoint_manager.py`):
• Manages step checkpoints and saves adapter tensors.

7. Quality Gate Evaluation (`evaluator.py`, `evaluation/`):
• `UnifiedSubjectEvaluator` validates final loss against quality threshold.
• Pushes passed model to `AdapterPackager`.

8. Deployment Packaging (`adapter_packager.py`):
• Exports finalized adapter weights to `data/output/_adapter/final_adapter`.

Clean Architecture Rule: Pipeline stages communicate strictly through immutable Pydantic models with parent artifact lineage tracking, guaranteeing zero accidental state side effects.

5. AI / QLoRA Fine-Tuning & Hardware Blueprint

Hyperparameters, Base Models, Quantization Modes, and Resource Specifications

Parameter Category	Configured Value / Specification	Engineering Rationale
Base Foundation LLM	`Qwen/Qwen3-8B` / `Qwen3-8B-Instruct`	High reasoning baseline capability for complex Computer Science code and math.
Quantization Precision	`4-bit NF4` (NormalFloat4) + Double Quantization	Reduces VRAM consumption from ~16GB to ~5.5GB during fine-tuning.
Compute DType	`bfloat16` (`bnb_compute_dtype=bfloat16`)	Native speed preference for Ampere/Ada GPU architectures (e.g. NVIDIA RTX 4080).
LoRA Rank (`r`) & Alpha	Rank `r = 16`, `alpha = 32`, `dropout = 0.05`	Optimal capacity-to-overfitting ratio for domain-specific educational adaptation.
Target Modules	`q_proj`, `k_proj`, `v_proj`, `o_proj`, `gate_proj`, `up_proj`, `down_proj`	Full attention & MLP projection adaptation for comprehensive knowledge retention.
Training Batch Setup	Batch Size = 1 (or 4), Grad Accumulation Steps = 16	Effective batch size of 16-64 without exceeding consumer GPU VRAM limits.
Learning Rate & Schedule	LR = `2e-4`, Warmup Ratio = `0.03`, Weight Decay = `0.01`	Stable convergence with AdamW optimizer and linear warmup schedule.

6. Frontend & API Ecosystem

Web Application Interface, Evaluation Lab, and API Server Specifications

1. Next.js 16 Web Application (`frontend/`):
• **Tech Stack:** React 19, TypeScript 5, Tailwind CSS 4, Lucide Icons.
• **Math & Markdown:** Integrated `katex`, `react-markdown`, `remark-math`, and `rehype-highlight` for crisp formatting.
• **Streaming Service (`src/services/api.ts`):** Consumes SSE chunks over `fetch()`. Automatically triggers offline fallback simulation if backend server is offline.
• **Subject Context Selector:** Dynamically sets active subject domain badges (`DBMS`, `DSA`, `OOPS`, `OS`, `CNT`, `OOSE`).

2. Streamlit Evaluation Lab (`src/aurora/ui/app.py`):
• **Purpose:** Dark-mode lab environment for model evaluation and probing.
• **Features:** Live model testing, generation parameter tweaking, interaction log viewer (`data/logs/`).

3. FastAPI API Server (`src/aurora/deployment/api_server.py`):
• **`POST /v1/chat/completions`:** OpenAI-compatible SSE token streaming endpoint.
• **`GET /v1/models`:** Lists all 7 trained Aurora domain models & adapters.
• **CORS Middleware:** Configured for seamless cross-origin web integration.

Code Snippet — FastAPI OpenAI SSE Response Setup:

```
@app.post("/v1/chat/completions")
async def chat_completions(request: Request):
    # Resolves target LoRA adapter (e.g. aurora-os -> data/output/os_adapter/final_adapter)
    adapter_path = resolve_adapter_path(model_id, messages)
    return StreamingResponse(event_generator(), media_type="text/event-stream")
```

7. Repository Structure & Key Entry Points

Shortlist of Critical Files Every Developer Must Inspect First

File Path	Responsibility & Role in System	When to Modify
[`src/aurora/deployment/api_server.py`](file:///c:/AuroraEngine/src/aurora/deployment/api_server.py)	FastAPI API server router, domain guardrails, and SSE stream dispatcher.	Adding endpoints, altering domain system prompts, modifying CORS.
[`src/aurora/inference/inference_engine.py`](file:///c:/AuroraEngine/src/aurora/inference/inference_engine.py)	Loads base model (`Qwen3-8B`), mounts active LoRA adapter, executes generation.	Changing base LLM loading, tweaking generation parameters.
[`src/aurora/training/trainer.py`](file:///c:/AuroraEngine/src/aurora/training/trainer.py)	PyTorch QLoRA training engine using Hugging Face Transformers & PEFT.	Modifying loss calculation, trainer callbacks, saving logic.
[`frontend/src/app/page.tsx`](file:///c:/AuroraEngine/frontend/src/app/page.tsx)	Next.js main web chat client entry point.	Modifying chat UI layout, adding sidebar features.
[`train_unified.py`](file:///c:/AuroraEngine/train_unified.py)	Orchestrates multi-subject unified model training run across all 6 CS domains.	Launching dataset-wide fine-tuning runs.
[`run_config.json`](file:///c:/AuroraEngine/run_config.json)	Central hyperparameter configuration file (epochs, LR, LoRA rank, batch size).	Adjusting fine-tuning hyperparameters or target hardware.
[`stage1_smoke_test.py`](file:///c:/AuroraEngine/stage1_smoke_test.py)	Rapid pipeline validation and packaging test script.	Verifying pipeline setup after major code changes.

8. Developer Handover & Quick Start Guide

Practical Instructions for the Incoming Development Team

■ **New Developer First-Day Commands:**

```
# 1. Activate environment and install framework
python -m venv .venv
.venv\Scripts\activate
pip install -e ".[dev]"

# 2. Run automated verification test suite
pytest

# 3. Start API backend server (Terminal 1)
python -m uvicorn aurora.deployment.api_server:app --reload --port 8000

# 4. Start Next.js Web Client (Terminal 2)
cd frontend && npm install && npm run dev
```

Developer Workflow Checklist for New Features:

1. **Adding a New Subject Domain:** Add dataset in `data/corpus/_training.jsonl` -> Create `train_.py` -> Register in `frontend/src/config/api.ts` -> Add route in `api_server.py`.
2. **Modifying Data Schemas:** Edit Pydantic models in `src/aurora/models/`. Ensure `frozen=True` is preserved to maintain immutability.
3. **Pre-Commit Checks:** Always run `pytest`, `ruff check .`, and `mypy src/aurora` before creating pull requests.

9. Implementation Status & Future Roadmap

Current Feature Audit and Planned Architecture Extension Points

Feature / Module	Current Status	Evidence / Location	Notes for New Team
Clean Architecture Core	■ Implemented	`src/aurora/core/`, `models/`	Strict Pydantic v2 domain isolation.
QLoRA Fine-Tuning Engine	■ Implemented	`src/aurora/training/`	4-bit NF4 adaptation on Qwen3-8B.
Multi-Subject Adapters	■ Implemented	`data/output/`	Adapters for all 6 CS subjects + Unified model.
FastAPI SSE API Server	■ Implemented	`aurora/deployment/api_server.py`	OpenAI SSE stream protocol.
Next.js Student Web UI	■ Implemented	`frontend/`	LaTeX math, markdown, subject selection.
Streamlit Evaluation Lab	■ Implemented	`src/aurora/ui/app.py`	Model testing & daily log inspector.
API Token Authentication	■ Not Implemented	`api_server.py`	`■ Potential Extension`: Add OAuth2/JWT.
Vector DB Retrieval (RAG)	■ Partial	`src/aurora/storage/`	`■ Potential Extension`: Integrate FAISS/Chroma.

Summary: AuroraEngine provides a research-grade, production-tested foundation for educational AI models. The incoming development team can immediately start building custom adapters or extending storage backends.