IDS Intrusion Detection Report

Snort fast.log analysis · source: **alert_fast.txt** · generated 2026-10-14 06:22

Metric	Value	Metric	Value
Total alerts	4123	Attack signatures	3
Attack categories	2	Highest severity	HIGH
Unique IPs	6	Unique dst ports	981
Time range start	2026-07-23T07:37:43.472277	Time range end	2026-10-14T06:21:40.406225
Active days	4	Duration	82 days, 22:43:56

1. Attack Summary

Signature	Category	Severity	Count	%
Possible TCP Port Scan	Reconnaissance	MEDIUM	3920	95.08%
SSH Connection Attempt on port 5555	Unauthorized Access	HIGH	173	4.2%
ICMP Echo Request Detected	Reconnaissance	MEDIUM	30	0.73%

Alerts by category

Category	Alerts	Share
Reconnaissance	3950	95.8%
Unauthorized Access	173	4.2%

2. Attack Details

2.1 Possible TCP Port Scan

Field	Value
SID	1:1000005:1
Category / Severity	Reconnaissance / MEDIUM
Alert count	3920 (95.08% of all alerts)
First seen	2026-10-14T05:54:31.556240
Last seen	2026-10-14T06:21:10.926755
Protocols	TCP (3920)
Top sources	192.168.1.6 (3920)
Top targets	192.168.1.3 (3920)
Target ports	750/kerberos4 (4), 533/unknown (4), 571/unknown (4), 790/unknown (4), 788/unknown (4)

Sample alerts:

```
10/14-05:54:31.556240 [**] [1:1000005:1] "Possible TCP Port Scan" [**] [Priority: 0] {TCP} 192.168.1.6:35758 -> 192.168.
10/14-05:54:31.556240 [**] [1:1000005:1] "Possible TCP Port Scan" [**] [Priority: 0] {TCP} 192.168.1.6:35758 -> 192.168.
10/14-05:54:31.556240 [**] [1:1000005:1] "Possible TCP Port Scan" [**] [Priority: 0] {TCP} 192.168.1.6:35758 -> 192.168.
10/14-05:54:31.556240 [**] [1:1000005:1] "Possible TCP Port Scan" [**] [Priority: 0] {TCP} 192.168.1.6:35758 -> 192.168.
10/14-05:54:31.556240 [**] [1:1000005:1] "Possible TCP Port Scan" [**] [Priority: 0] {TCP} 192.168.1.6:35758 -> 192.168.
```

2.2 SSH Connection Attempt on port 5555

Field	Value
SID	1:1000001:1
Category / Severity	Unauthorized Access / HIGH
Alert count	173 (4.2% of all alerts)
First seen	2026-07-23T07:37:43.472277
Last seen	2026-09-10T09:35:31.606882
Protocols	TCP (173)
Top sources	192.168.1.23 (156), 192.168.1.10 (17)
Top targets	192.168.1.14 (156), 192.168.1.12 (17)
Target ports	5555/ssh-alt (173)

Sample alerts:

```
07/23-07:37:43.472277 [**] [1:1000001:1] "SSH Connection Attempt on port 5555" [**] [Priority: 0] {TCP} 192.168.1.23:374
07/23-07:37:43.496717 [**] [1:1000001:1] "SSH Connection Attempt on port 5555" [**] [Priority: 0] {TCP} 192.168.1.23:374
07/23-07:37:43.723947 [**] [1:1000001:1] "SSH Connection Attempt on port 5555" [**] [Priority: 0] {TCP} 192.168.1.23:374
07/23-07:37:43.741296 [**] [1:1000001:1] "SSH Connection Attempt on port 5555" [**] [Priority: 0] {TCP} 192.168.1.23:374
07/23-07:37:43.743700 [**] [1:1000001:1] "SSH Connection Attempt on port 5555" [**] [Priority: 0] {TCP} 192.168.1.23:374
```

2.3 ICMP Echo Request Detected

Field	Value
SID	1:1000006:2
Category / Severity	Reconnaissance / MEDIUM
Alert count	30 (0.73% of all alerts)
First seen	2026-10-13T10:00:46.495690
Last seen	2026-10-14T06:21:40.406225
Protocols	ICMP (30)
Top sources	192.168.1.6 (30)
Top targets	192.168.1.3 (30)
Target ports	-

Sample alerts:

```
10/13-10:00:46.495690 [**] [1:1000006:2] "ICMP Echo Request Detected" [**] [Priority: 0] {ICMP} 192.168.1.6 -> 192.168.1
10/13-10:00:47.496084 [**] [1:1000006:2] "ICMP Echo Request Detected" [**] [Priority: 0] {ICMP} 192.168.1.6 -> 192.168.1
10/13-10:00:48.498938 [**] [1:1000006:2] "ICMP Echo Request Detected" [**] [Priority: 0] {ICMP} 192.168.1.6 -> 192.168.1
10/13-10:00:49.500635 [**] [1:1000006:2] "ICMP Echo Request Detected" [**] [Priority: 0] {ICMP} 192.168.1.6 -> 192.168.1
10/13-10:00:50.502380 [**] [1:1000006:2] "ICMP Echo Request Detected" [**] [Priority: 0] {ICMP} 192.168.1.6 -> 192.168.1
```

3. Network Overview

Top source IPs

Source IP	Alerts as source
192.168.1.6	3950
192.168.1.23	156
192.168.1.10	17

Top targeted IPs

Target IP	Alerts as target
192.168.1.3	3950
192.168.1.14	156

Target IP	Alerts as target
192.168.1.12	17

Top targeted ports

Port	Service	Alerts
5555	ssh-alt	173
750	kerberos4	4
533	unknown	4
571	unknown	4
790	unknown	4
788	unknown	4
1000	unknown	4
832	unknown	4
891	unknown	4
196	unknown	4

Protocols

Protocol	Alerts
TCP	4093
ICMP	30

4. Timeline

Date	Alerts
2026-07-23	156
2026-09-10	17
2026-10-13	10
2026-10-14	3940

Peak activity: 2026-10-14 with 3940 alerts.

5. AI Analysis & Recommended Mitigations

Offline analysis (AI unavailable: no API key provided).

Executive Summary

The IDS recorded **4123 alerts** across **3 signatures** and **2 attack categories** between 2026-07-23T07:37:43.472277 and 2026-10-14T06:21:40.406225. The dominant activity is **Possible TCP Port Scan** (3920 alerts, 95.08%) targeting 192.168.1.3. Overall risk level: **HIGH**.

Attack Analysis

Possible TCP Port Scan (Reconnaissance, severity medium): 3920 alerts (95.08%) observed from 2026-10-14T05:54:31.556240 to 2026-10-14T06:21:10.926755. Primary sources: 192.168.1.6. Primary targets: 192.168.1.3:750. Protocol(s): TCP.

SSH Connection Attempt on port 5555 (Unauthorized Access, severity high): 173 alerts (4.2%) observed from 2026-07-23T07:37:43.472277 to 2026-09-10T09:35:31.606882. Primary sources: 192.168.1.23, 192.168.1.10. Primary targets: 192.168.1.14:5555, 192.168.1.12:5555. Protocol(s): TCP.

ICMP Echo Request Detected (Reconnaissance, severity medium): 30 alerts (0.73%) observed from 2026-10-13T10:00:46.495690 to 2026-10-14T06:21:40.406225. Primary sources: 192.168.1.6. Primary targets: 192.168.1.3. Protocol(s): ICMP.

Risk Assessment

- **Reconnaissance** - MEDIUM - 3950 alerts
- **Unauthorized Access** - HIGH - 173 alerts

Recommended Mitigations

Reconnaissance:

- Block or rate-limit the scanning source at the firewall and drop unsolicited ICMP where policy allows.
- Harden the network surface: close unused ports, remove banner/version disclosure, disable unnecessary services.
- Keep vulnerability scans internal and schedule patching for exposed services.
- Correlate scan events with subsequent exploitation attempts; treat scanners as pre-attack indicators.
- Enable network-level anomaly detection to spot sweep patterns early.

Unauthorized Access:

- Block unauthorized access attempts at the perimeter firewall and internal ACLs.
- Verify the targeted service is required; shut down or bind it to localhost if not.
- Harden the exposed service (patch, disable anonymous/guest access, strong credentials).
- Deploy host-based IDS/IPS rules that alert on repeated connection attempts to the service.
- Review host logs for successful sessions from the offending source and isolate if compromised.

Conclusion

Prioritize blocking the repeated access attempts and scanning sources, harden the targeted services, and confirm no successful sessions exist from the offending hosts. Continue monitoring for escalation from reconnaissance to exploitation.

Report generated 2026-10-14T06:22:15 from alert_fast.txt · 4123 alerts analysed.