

# GE23131-Programming Using C-2024

Quiz navigation

1

2

3

4

Show one page at a time

Finish review

Status	Finished
Started	Sunday, 29 December 2024, 8:48 PM
Completed	Sunday, 29 December 2024, 9:36 PM
Duration	47 mins 35 secs

Question 1

Correct

Marked out of 1.00

Flag question

Given a string, *s*, consisting of alphabets and digits, find the frequency of each digit in the given string.

Input Format

The first line contains a string, *num* which is the given number.

Constraints

$1 \leq len(num) \leq 1000$

All the elements of num are made of English alphabets and digits.

Output Format

**Sample Input 0**

a11472o5t6

**Sample Output 0**

0 2 1 0 1 1 1 1 0 0

**Explanation 0**

In the given string:

- **1** occurs two times.
- **2, 4, 5, 6** and **7** occur one time each.

The remaining digits **0, 3, 8** and **9** don't occur at all.

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     char str[1000];
4     scanf("%s",str);
5     int hash[10]={0,0,0,0,0,0,0,0,0,0};
6     int temp;
7     for(int i=0;str[i]!='\0';i++)
8     {
9         temp=str[i]-'0';
10        if(temp<=9 && temp>=0)
11        {
12            hash[temp]++;
13        }
```

```
16 |         printf("%d",hash[l]);
17 |     }
18 | }
```

	Input	Expected	Got	
✓	a11472o5t6	0 2 1 0 1 1 1 1 0 0	0 2 1 0 1 1 1 1 0 0	✓
✓	lw4n88j12n1	0 2 1 0 1 0 0 0 2 0	0 2 1 0 1 0 0 0 2 0	✓
✓	1v88886l256338ar0ekk	1 1 1 2 0 1 2 0 5 0	1 1 1 2 0 1 2 0 5 0	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of 1.00

Flag question

Today, Monk went for a walk in a garden. There are many trees in the garden and each tree has an English alphabet on it. While Monk was walking, he noticed that all trees with vowels on it are not in good state. He decided to take care of them. So, he asked you to tell him the count of such trees in the garden.

**Note:** The following letters are vowels: 'A', 'E', 'I', 'O', 'U', 'a', 'e', 'i', 'o' and 'u'.

**Input:**

Each test case consists of only one string, each character of string denoting the alphabet (may be lowercase or uppercase) on a tree in the garden.

**Output:**

For each test case, print the count in a new line.

**Constraints:**

$1 \leq T \leq 10$   
 $1 \leq \text{length of string} \leq 10^5$

**SAMPLE INPUT**

2  
nBBZLaosnm  
JHklsnZtTL

**SAMPLE OUTPUT**

2  
1

**Explanation**

Answer: (penalty regime: 0 %)

```
1 |
2 | #include<stdio.h>
3 | int main()
4 | {
5 |     int t;
6 |     scanf("%d",&t);
7 |     while(t-->0)
8 |     {
9 |         char str[100000];
10 |        int count=0;
11 |        scanf("%s",str);
12 |        for(int i=0;str[i]!='\0';i++)
13 |        {
14 |            char c=str[i];
15 |            if((c=='a')||(c=='e')||(c=='i')||(c=='o')||(c=='u'))
16 |                count++;
17 |        }
18 |        printf("%d\n",count);
19 |    }
20 |    return 0;
21 | }
```

	Input	Expected	Got	
✓	2 nBBZLaosnm JHkIsnZtTL	2 1	2 1	✓
✓	2 nBBZLaosnm JHkIsnZtTL	2 1	2 1	✓

Passed all tests! ✓

Marked out of  
1.00

 [Flag  
question](#)

### Input Format

The first and only line contains a sentence, **s**.

### Constraints

$$1 \leq \text{len}(s) \leq 1000$$

### Output Format

Print each word of the sentence in a new line.

### Sample Input 0

This is C

### Sample Output 0

This  
is  
C

### Explanation 0

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     char s[1000];
5     scanf("%[^\n]s",s);
6     for(int i=0;s[i]!='\0';i++)
7     {
8         if(s[i]!=' ')
9             printf("%c",s[i]);
10        else
11            printf("\n");
12    }return 0;
13 }
```

	Input	Expected	Got	
✓	This is C	This is C	This is C	✓
✓	Learning C is fun	Learning C is fun	Learning C is fun	✓

Question **4**

Correct

Marked out of  
1.00[Flag  
question](#)

### Input Format

You are given two strings, ***a*** and ***b***, separated by a new line. Each string will consist of lower case Latin characters ('a'-'z').

### Output Format

In the first line print two space-separated integers, representing the length of ***a*** and ***b*** respectively.

In the second line print the string produced by concatenating ***a*** and ***b*** (***a + b***).

In the third line print two strings separated by a space, ***a'*** and ***b'***. ***a'*** and ***b'*** are the same as ***a*** and ***b***, respectively, except that their first characters are swapped.

### Sample Input

```
abcd
```

```
ef
```

### Sample Output

```
4 2
```

```
abcdef
```

```
ebcd af
```



a = "abcd"

b = "ef"

|a| = 4

|b| = 2

a + b = "abcdef"

a' = "ebcd"

b' = "af"

**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     char str1[10],str2[10],t;
4     int i=0,j=0;
5     int count1=0,count2=0;
6     scanf("%s",str1);
7     scanf("%s",str2);
8     while(str1[i]!='\0')
9     {
10         count1++;
11         i++;
12     }
13     while(str2[j]!='\0')
14     {
15         count2++;
16         j++;
17     }printf("%d %d\n",count1,count2);
18     printf("%s%s\n",str1,str2);
19     t=str1[0];
20     str1[0]=str2[0];
21     str2[0]=t;
22     printf("%s %s",str1,str2);
23     return 0;}
24
```

	Input	Expected	Got	
✓	abcd ef	4 2 abcdef ebcd af	4 2 abcdef ebcd af	✓

Passed all tests! ✓

Finish review