

	<p>dividing a program's workload into separate threads, it can perform tasks concurrently, leading to improved performance and responsiveness.</p> <ol style="list-style-type: none"> 2. Enhanced Responsiveness: Multithreading enables applications to remain responsive even when executing time-consuming operations. By offloading these operations to separate threads, the main thread can continue to respond to user input or handle other tasks, preventing the application from becoming unresponsive or frozen. 3. Efficient Resource Utilization: Multithreading allows for efficient utilization of system resources, such as CPU cores and memory. By distributing tasks across multiple threads, a program can make better use of available resources, maximizing throughput and minimizing resource idle time. 4. Concurrency and Scalability: Multithreading enables the concurrent execution of multiple tasks, providing better concurrency in applications. It allows for efficient handling of multiple client requests or simultaneous processing of independent tasks. Additionally, multithreading facilitates scalability by allowing applications to handle increased workloads by leveraging additional threads. 5. Asynchronous Operations: Multithreading facilitates asynchronous programming, which is crucial for handling tasks that involve waiting for external events or performing time-consuming operations. By running such operations in separate threads, the main thread can continue execution without being blocked, enabling better resource utilization and improved responsiveness. 6. Modularity and Maintainability: Multithreading promotes modular design and improves code maintainability. By dividing a program into separate threads, each responsible for a specific task or module, developers can achieve better code organization, separation of concerns, and easier maintenance and debugging. 7. Real-time Applications: Multithreading is essential for developing real-time applications that require timely execution and responsiveness. Examples include multimedia processing, gaming, robotics, and critical systems that demand quick and continuous responses. 8. Parallel Computing: Multithreading enables parallel computing, which is valuable for tasks involving intensive computations, data processing, and complex algorithms. By splitting the workload across threads, programs can achieve significant performance gains by utilizing multiple CPU cores.
<p>3.</p> <p>Ans.</p>	<p>What is Thread in Java?</p> <p>In Java, a thread refers to a lightweight unit of execution that represents an independent flow of control within a program. Threads allow concurrent execution of multiple tasks within a single program. The Java programming language provides built-in support for multithreading through the java.lang.Thread class.</p> <p>A thread can be thought of as a separate path of execution within a program, with its own stack and program counter. Each thread runs independently, performing its own set of instructions in parallel or concurrently with other threads. Threads can be used to</p>

execute different parts of a program simultaneously, allowing for improved performance, responsiveness, and concurrency.

4. What are the two ways of implementing thread in Java?

Ans. In Java, there are two main ways to implement threads: by extending the **Thread** class and by implementing the **Runnable** interface. Both approaches allow you to create and execute threads, but they differ in the inheritance structure and flexibility.

1. Extending the **Thread** class:

- Create a new class that extends the **Thread** class.
- Override the **run()** method within the subclass to define the thread's behavior.
- Create an instance of the subclass and call the **start()** method to start the execution of the thread.

2. Implementing the **Runnable** interface:

- Create a class that implements the **Runnable** interface.
- Implement the **run()** method defined in the **Runnable** interface to specify the thread's behavior.
- Create an instance of the class and pass it to a **Thread** object as a parameter.
- Call the **start()** method on the **Thread** object to start the execution of the thread.

5. What's the difference between thread and process?

Ans.

	Thread	Process
Definition	A thread is a unit of execution within a process.	A process is an instance of a running program.
Relationship	Threads exist within a process.	Processes are independent of each other.
Memory	Threads of the same process share memory.	Processes have separate memory spaces.
Communication	Threads communicate through shared memory.	Processes typically use inter-process communication mechanisms.
Resource Usage	Threads within a process share resources.	Processes have their own set of system resources.

	Context Switching	Context switching between threads is faster.	Context switching between processes is slower.
	Concurrency	Threads allow for concurrent execution of tasks.	Processes can run concurrently on multiple CPUs or cores.
	Creation	Threads are lightweight and created within a process.	Processes are heavyweight and created using process creation API.
	Control	Threads are controlled by the process that owns them.	Processes have their own process control block (PCB).
6.	How can we create daemon threads?		
Ans.	<p>In Java, you can create daemon threads by using the setDaemon() method provided by the Thread class. A daemon thread is a thread that runs in the background and does not prevent the JVM from exiting when all non-daemon threads have completed their execution.</p> <p>To create a daemon thread, follow these steps:</p> <ol style="list-style-type: none"> 1. Create an instance of the Thread class and provide the desired behavior by either extending the Thread class or implementing the Runnable interface. 2. Before starting the thread by calling the start() method, invoke the setDaemon(true) method on the Thread object to mark it as a daemon thread. 3. Start the thread using the start() method. 		
7.	What are the wait() and sleep() methods?		
Ans.	<p>In Java, the wait() and sleep() methods are used for different purposes related to thread synchronization and timing. Here's an explanation of each method:</p> <ol style="list-style-type: none"> 1. wait(): The wait() method is used for inter-thread communication and synchronization. It is called on an object within a synchronized context and causes the current thread to wait until another thread notifies it or a specified timeout period elapses. When a thread calls wait(), it releases the lock on the object, allowing other threads to proceed with their execution. <p>The wait() method has three forms:</p> <ul style="list-style-type: none"> • wait(): Causes the current thread to wait indefinitely until it is notified by another thread using the notify() or notifyAll() methods, or interrupted. • wait(long timeout): Causes the current thread to wait for the specified timeout period (in milliseconds) until it is notified or interrupted. • wait(long timeout, int nanos): Similar to the previous form, but allows specifying an additional timeout in nanoseconds. 		

sleep(): The **sleep()** method is used to pause the execution of a thread for a specified amount of time. Unlike **wait()**, **sleep()** is a static method defined in the **Thread** class and does not require synchronization or a lock on an object. When a thread calls **sleep()**, it does not release any locks or resources and will resume execution after the specified sleep duration.

The **sleep()** method has two forms:

- **sleep(long millis):** Suspends the execution of the current thread for the specified number of milliseconds.
- **sleep(long millis, int nanos):** Suspends the execution of the current thread for the specified number of milliseconds plus nanoseconds.