Ex No: 6 (a) FIRST COME FIRST SERVE (FCFS)

Date: 25.02.25

Aim:

To implement First-Come First-Serve (FCFS) scheduling technique.

Algorithm:

- 1. Start the program.
- 2. Input the number of processes.
- 3. Read the burst time for each process.
- 4. Calculate the waiting time for each process:
 - Waiting time of process 0 is 0.
 - o For others:

```
WaitingTime[i] = WaitingTime[i-1] + BurstTime[i-1]
```

5. Calculate the turnaround time for each process:

```
TurnAroundTime[i] = WaitingTime[i] + BurstTime[i]
```

- 6. Calculate the total and average waiting time and turnaround time.
- 7. Display process details, total and average times.
- 8. End.

Program Code (in C):

```
#include <stdio.h>
int main() {
  int n, i;
  int burst_time[20], waiting_time[20],turn_around_time[20];
  int total_wt = 0, total_tat = 0;

printf("Enter the number of process:\n");
scanf("%d", &n);
```

```
printf("Enter the burst time of the processes:\n");
for (i = 0; i < n; i++) {
  scanf("%d", &burst_time[i]);
}
waiting_time[0] = 0;
for (i = 1; i < n; i++) {
  waiting_time[i] = waiting_time[i - 1] + burst_time[i - 1];
}
for (i = 0; i < n; i++) {
  turn_around_time[i] = waiting_time[i] + burst_time[i];
  total_wt += waiting_time[i];
  total_tat += turn_around_time[i];
}
printf("Process\tBurst Time\tWaiting Time\tTurn Around Time\n");
for (i = 0; i < n; i++) {
  printf("%d\t\d\t\t%d\n", i, burst_time[i], waiting_time[i],
turn around time[i]); }
printf("Average Waiting Time is: %.1f\n", (float)total wt / n);
printf("Average Turn Around Time is: %.1f\n", (float)total_tat / n);
return 0;
```

SampleOutput:

}

Enter the number of process:

3

Enter the burst time of the processes:

24 3 3

Process Burst Time Waiting Time Turn Around Time

0 24 0 24

1 3 24 27

2 3 27 30

Average Waiting Time is: 17.0

Average Turn Around Time is: 27.0

Result:

The FCFS Scheduling algorithm was successfully implemented. The program calculated the waiting time and turnaround time for each process and displayed the average times.