

Ex No: 6(d) ROUND ROBIN SCHEDULING**Date: 26.03.2025****Aim:**

To implement the Round Robin (RR) scheduling technique using C programming.

Algorithm:

1. Start.
2. Get the number of processes and the time quantum from the user.
3. Read the process burst time (arrival time is assumed 0 for simplicity).
4. Initialize an array rem_bt[] (remaining burst time) as a copy of burst time.
5. Initialize an array wt[] (waiting time) as 0 for all processes.
6. Set current time t = 0.
7. Repeat while all processes are not completed:
 - For each process i:
 - If rem_bt[i] > 0:
 - If rem_bt[i] > quantum:
 - t += quantum
 - rem_bt[i] -= quantum
 - Else:
 - t += rem_bt[i]
 - wt[i] = t - bt[i]
 - rem_bt[i] = 0
8. Calculate Turnaround Time for each process as:
 $tat[i] = bt[i] + wt[i]$
9. Compute Average Waiting Time and Average Turnaround Time.
10. Display the process-wise result.
11. End.

Program Code (C):

```
#include <stdio.h>
```

```
int main() {
```

```
    int i, n, time = 0, quantum;
```

```

int bt[20], rem_bt[20], wt[20], tat[20];

float avg_wt = 0, avg_tat = 0;

printf("Enter total number of processes: ");
scanf("%d", &n);

printf("Enter burst time for each process:\n");
for (i = 0; i < n; i++) {
    printf("P[%d]: ", i + 1);
    scanf("%d", &bt[i]);
    rem_bt[i] = bt[i];
    wt[i] = 0;
}

printf("Enter Time Quantum: ");
scanf("%d", &quantum);

int done;

do {
    done = 1;
    for (i = 0; i < n; i++) {
        if (rem_bt[i] > 0) {
            done = 0;
            if (rem_bt[i] > quantum) {
                time += quantum;
                rem_bt[i] -= quantum;
            } else {
                time += rem_bt[i];
                wt[i] = time - bt[i];

                rem_bt[i] = 0;
            }
        }
    }
} while (done == 0);

```

```

        }
    }
}
} while (!done);

printf("\nProcess\tBurst Time\tWaiting Time\tTurnaround Time\n");
for (i = 0; i < n; i++) {
    tat[i] = bt[i] + wt[i];
    avg_wt += wt[i];
    avg_tat += tat[i];
    printf("P[%d]\t%d\t%d\t%d\n", i + 1, bt[i], wt[i], tat[i]);
}

avg_wt /= n;
avg_tat /= n;

printf("\nAverage Waiting Time = %.2f", avg_wt);
printf("\nAverage Turnaround Time = %.2f\n", avg_tat);

return 0;
}

```

Sample Output:

Enter total number of processes: 4

Enter burst time for each process:

P[1]: 5

P[2]: 15

P[3]: 4

P[4]: 3

Enter Time Quantum: 5

Process	Burst Time	Waiting Time	Turnaround Time
---------	------------	--------------	-----------------

P[1]	5	0	5
------	---	---	---

P[2]	15	12	27
------	----	----	----

P[3]	4	5	9
------	---	---	---

P[4]	3	9	12
------	---	---	----

Average Waiting Time = 6.50

Average Turnaround Time = 13.25

Result:

The Round Robin Scheduling algorithm was successfully implemented and tested. It correctly calculated the waiting and turnaround times based on the given time quantum.