(3) ALERT TRIAGE PRACTICE:

Triage Simulation:

- Goto wazuh dashboard and search for bruteforce
- Then run in ubuntu terminal

  for i in {1..10}; do ssh fakeuser@localhost; done

  this creates failed ssh login attempts



Figure 11: ssh brute force alert detected

- Identify alert details

  Rule ID: 100002

  Description: SSH brute force detected: 3 failed logins in 2 minutes

  Source ip: 127.0.0.1

  Timestamp: march 20,2026 06:11:03.557

  Agent name: UBUNTULINUX

- Triage Simulation document:

Alert ID	Description	Source IP	Priority	status
100002	SSH brute force detected: 3 failed logins in 2 minutes	127.0.0.1	medium	open

- Threat Intelligence Validation:
  Goto virus total and paste ip



Figure 12: checking ip in virustotal



Figure 13: ip details in virus total

During the simulated incident response exercise, an SSH brute force attack was detected on the host 127.0.0.1 (loopback address). The alert indicated 3 failed login attempts within 2 minutes, classifying it as a medium-priority event.
Analysis through a threat intelligence platform showed that 1 out of 94 security vendors flagged this IP as potentially malicious, but further details confirmed that 127.0.0.1 is a loopback address reserved for local testing, meaning this alert was likely a false positive or test scenario.

Summarizing findings:
The brute-force SSH alert originated from localhost 127.0.0.1, a loopback address indicating internal activity. VirusTotal analysis showed 1/94 detections with most vendors marking it clean. As the IP is non-routable and used for local communication, the alert is considered a false positive and safely closed.