

Contents

1	Shell Script	
2	Libraries	
2.1	cstdlib	1
2.2	algorithm	1
2.3	map	1
2.4	set	2
2.5	vector	2
2.6	string	2
3	Algorithms	
3.1	最短路	
3.1.1	Bellman-Ford	2
3.1.2	Dijkstra's	2
3.2	LIS - Longest Increasing Subsequence	2
4	Formula	
4.1	thm	2

1 Shell Script

```

1 #!/bin/bash
2 clear
3 g++ $1.cpp -DDBG -o $1
4 if [[ "$?" == "0" ]]; then
5     echo Running
6     ./$1 <$1.in> $1.out
7     echo END
8 fi

```

2 Libraries

2.1 cstdlib

```

1 #include <cstdlib>
2 using namespace std;
3 {
4     // Function: String conversion
5     double atof(const char* str);
6         // char* 轉 double
7     int atoi(const char * str);
8         // char* 轉 int
9     long int atol(const char * str);
10        // char* 轉 long int
11    long long int atoll(const char * str);
12        // char* 轉 long long int
13    double strtod(const char* str, char** endptr);
14        // char* 轉 double;
15    float strtof(const char* str, char** endptr);
16        // char* 轉 float
17    long int strtol(const char* str, char** endptr,
18        int base);
19        // char*(base) 轉 long int
20        // 且指向轉換子字串之末
21    long double strtold(const char* str, char**
22        endptr);
23        // char*(base) 轉 long double
24        // 且指向轉換子字串之末
25    long long int strtoll(const char* str, char**
26        endptr, int base);
27        // char*(base) 轉 long long int
28        // 且指向轉換子字串之末
29    unsigned long int strtoul(const char* str, char**
30        endptr, int base);
31        // char*(base) 轉 unsigned long int
32        // 且指向轉換子字串之末
33    unsigned long long int strtoull(const char* str,
34        char** endptr, int base);
35        // char*(base) 轉 unsigned long long int
36        // 且指向轉換子字串之末

```

```

27 // Function: Integer arithmetics
28 int abs(int n);
29 long int labs(long int n);
30 long long int llabs(long long int n);
31 // Absolute value
32 }

```

2.2 algorithm

```

2 #include <algorithm>
2 using namespace std;
3 {
4     // FI(ForwardIterator)
5     // RAI(RandomAccessIterator)
6     // BI(BidirectionalIterator)
7     void sort(RAI first, RAI last);
8
9     FI lower_bound(FI first, FI last, const T& k);
10    /* 最左邊 ≥ k 的位置 */
11
12    FI upper_bound(FI first, FI last, const T& k);
13    /* 最左邊 > k 的位置 */
14
15    pair<FI,FI> equal_range(FI first, FI last, const
16        T& k);
17    /* 等於 k 的範圍 [lower_bound, upper_bound) */
18
19    bool next_permutation(BI first, BI last);
20    /* 使用已經排序(由小到大)的資料，產生下一組排列 */
21
22    bool prev_permutation(BI first, BI last);
23    /* 針對逆向排序(由大到小)的資料，產生上一組排序 */
24 }

```

2.3 map

```

1 #include <map>
2 using namespace std;
3 {
4     /* Associative containers that store elements by a
5     combination
6     * of a key value and a mapped value, in a specific
7     order
8     * associated with key value.
9     * [Key values] are used to sort and uniquely
10    identify elements
11    * [Mapped values] store the content associated to
12    this key.
13    */
14    // Constructor
15    map<char,int> mp1; // empty
16    map<char,int> mp2 (mp1.begin(),mp1.end()); //
17    range
18    map<char,int> mp3 (mp1); // copy
19    // Operator
20    mp1['a'] = 3;
21    mp1['b'] = 1;
22    mp1['c'] = 2;
23    // [] Access element by reference or insert
24    new element if not found
25    // = Assign new content by replacing
26    // Iterator
27    iterator begin(); // Return iterator to beginning
28    iterator end(); // Return iterator to end
29    iterator rbegin(); // Return reverse iterator to
30    reverse beginning
31    iterator rend(); // Return reverse iterator to
32    reverse end
33    // Capacity
34    bool empty(); // test if empty
35    size_type size(); // return size
36    size_type max_size(); // return maximum size

```

```

30 // Element access
31 ['a'] // operator []
32 at('a');// by reference / const
33 // Modifiers
34 // Insert element
35 pair<map::iterator,bool> insert(value_type&
    val);
36 // value_type eg. for mp1 is
    pair<char,int>('x', 10)
37 iterator insert(mp1.begin(),mp1.find('c'));
38 // range
39 // Clear content
40 void clear();
41 // Erase element
42 void erase(iterator k); // by iterator
43 size_type erase(const key_type& k); // by key
44 // eg. mp1.erase('x') return erased
    element num
45 void erase(iterator first, iterator last); //
    by range
46 // Swap content of 2 same type map
47 void swap (map& x);
48 // Operations
49 // Find element by key, end() if none
50 iterator find(const key_type& k);
51 // Count elements with a specific key (max_val =
    1)
52 size_type count (const key_type& k) const;
53 // Iterator to lower bound
54 iterator lower_bound(const key_type& k);
55 // Iterator to upper bound
56 iterator upper_bound(const key_type& k);
57 // Get range of equal elements
58 pair<iterator,iterator> equal_range(const
    key_type& k);
59 }

```

2.4 set

```

1 #include <set>
2 using namespace std;
3 {
4 /* Containers that store unique elements following a
    specific order
5 * The value of an element each must be unique(like a
    key)
6 * The value of the elements cannot be modified, but
    can be inserted or removed
7 * Elements are sorted in order by their key
8 */
9
10 // Constructor
11 set<int> first;
12 // empty
13 int myints[] = {10,20,30,40,50};
14 set<int> second (myints,myints+5);
15 // range
16 set<int> third (second);
17 // copy
18 // Operator
19 set& operator = (const set& x); // copy
20 // Iterators
21 begin(); // Return iterator to beginning
22 end(); // Return iterator to end
23 rbegin(); // Return reverse iterator to reverse
    beginning
24 rend(); // Return reverse iterator to reverse end
25 // Capacity:
26 bool empty();
27 //Test whether container is empty
28 size_type size();
29 // Return container size
30 size_type max_size();
31 // Return maximum size
32 // Modifiers:
33 pair<iterator,bool> insert(val);

```

```

34 // Insert element true if inserted false if
    existed
35 void/size_type/void erase(val/iterator/range);
36 // Erase elements
37 void swap (set& x);
38 // Swap content
39 void clear();
40 // Clear content
41 // Operations
42 iterator find(val) const;
43 // Get iterator to element, end if none
44 size_type count(val) const;
45 // Count elements with a specific value
46 iterator lower_bound(val) const;
47 // Return iterator to lower bound
48 iterator upper_bound(val) const;
49 // Return iterator to upper bound
50 pair<iterator,iterator> equal_range(val) const;
51 // Get range of equal elements
52 }

```

2.5 vector

2.6 string

3 Algorithms

3.1 最短路

3.1.1 Bellman-Ford

3.1.2 Dijkstra's

3.2 LIS - Longest Increasing Subsequence

4 Formula

4.1 thm

· 中文測試

$$\cdot \sum_{i=1}^n i^2 = \frac{n(n+1)(2n+1)}{6}$$