Contents

- Vincent Purcell HW 8 ECE487
- EVAL Clusters
- Eval Clusters Function

Vincent Purcell - HW 8 - ECE487

```
clear; clc; close all;
```

EVAL Clusters

```
X = [mvnrnd([1 1], 1.*eye(2), 100); ...
    mvnrnd([3 2], 1.*eye(2), 100); ...
    mvnrnd([4 5], 1.*eye(2), 100); ...
     mvnrnd([0 5], 1.*eye(2), 100)];
evalFunc(X,4)
X = [mvnrnd([1 1], 1.*eye(2), 100); ...
     mvnrnd([5 5], 1.*eye(2), 100); ...
    mvnrnd([10 10], 1.*eye(2), 100)];
evalFunc(X,3)
X = [mvnrnd([2 6], 1.*eye(2), 100); ...
    mvnrnd([1 6], 1.*eye(2), 100); ...
    mvnrnd([1 0], 1.*eye(2), 100); ...
    mvnrnd([3 0], 1.*eye(2), 100)];
evalFunc(X,4)
X = [mvnrnd([0\ 0],\ 0.5.*eye(2),\ 100);\ ...
     mvnrnd([2 2], 0.5.*eye(2), 100); ...
    mvnrnd([4 4], 0.5.*eye(2), 100); ...
    mvnrnd([6 6], 0.5.*eye(2), 100); ...
    mvnrnd([8 8], 0.5.*eye(2), 100); ...
    mvnrnd([10 10], 0.5.*eye(2), 100)];
evalFunc(X,6)
X = [mvnrnd([3 6], 0.5.*eye(2), 100); ...
    mvnrnd([0 6], 1.*eye(2), 10); ...
    mvnrnd([2 4], 1.*eye(2), 10)];
evalFunc(X,3)
X = [mvnrnd([3 4], 0.5.*eye(2), 50); ...
     mvnrnd([0 4], 1.*eye(2), 15); ...
     mvnrnd([2 1], 1.*eye(2), 15)];
evalFunc(X,3)
```


Eval Clusters Function

```
function evalFunc(X,k)
  eva = evalclusters(X,'kmeans','gap','KList',1:6); %eval clusters
  figure;
  hold on
  subplot(2,2,[2 4]);plot(eva)
  ClusterGroup = eva.OptimalY; % optimal clusters
```


```
subplot(2,2,[1 3]);gscatter(X(:,1),X(:,2),ClusterGroup,'rbgkcmy','xod^*s+h');
title_str = "EvalClusters - Guassian Distributions=" + num2str(k);
sgtitle(title_str)
hold off
end
```

11/21/2019 vdp29_HW8_Code

EvalClusters - Guassian Distributions=4




EvalClusters - Guassian Distributions=3




11/21/2019 vdp29_HW8_Code


EvalClusters - Guassian Distributions=4




EvalClusters - Guassian Distributions=6



EvalClusters - Guassian Distributions=3



EvalClusters - Guassian Distributions=3



Published with MATLAB® R2019b