

## **10 - Searching & Sorting**

**For example:**

Input	Result
5 6 5 4 3 8	3 4 5 6 8

**Ex. No. : 10.1**

**Date:**

**Register No.:**

**Name:**

---

### **Merge Sort**

Write a Python program to sort a list of elements using the merge sort algorithm.

```
n = int(input())
array = input().split()
for i in range(n):
    array[i] = int(array[i])
for i in range(n):
    swapped = False
    for j in range(0, n - i - 1):
        if array[j] > array[j + 1]:
            array[j], array[j + 1] = array[j + 1], array[j]
            swapped = True
    if not swapped:
        break
for i in range(n):
    print(array[i], end=' ')
print()
```

### Input Format

The first line contains an integer,  $n$ , the size of the [list](#)  $a$ .  
The second line contains  $n$ , space-separated integers  $a[i]$ .

### Constraints

- $2 \leq n \leq 600$
- $1 \leq a[i] \leq 2 \times 10^6$ .

### Output Format

You must print the following three lines of output:

1. [List](#) is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted [list](#).
3. Last Element: lastElement, the *last* element in the sorted [list](#).

### Sample Input 0

```
3
1 2 3
```

### Sample Output 0

[List](#) is sorted in 0 swaps.  
First Element: 1  
Last Element: 3

### For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9

Ex. No. : 10.2

Date:

Register No.:

Name:

---

### Bubble Sort

Given an listof integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

1. [List](#) is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted [list](#).
3. Last Element: lastElement, the *last* element in the sorted [list](#).

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

Array is sorted in 3 swaps.

First Element: 1

Last Element: 6

```
def bubble_sort(arr):  
  
    n = len(arr)  
  
    swaps = 0  
  
    for i in range(n):  
  
        for j in range(n - 1):  
  
            if arr[j] > arr[j + 1]:  
  
                arr[j], arr[j + 1] = arr[j + 1], arr[j]  
  
                swaps += 1  
  
    return swaps
```

### Input Format

The first line contains a single integer  $n$  , the length of  $A$  .  
The second line contains  $n$  space-separated integers, $A[i]$ .

### Output Format

**Print** peak numbers separated by space.

### Sample Input

5  
8 9 10 2 6

### Sample Output

10 6

**For example:**

Input	Result
4 12 3 6 8	12 8

**Ex. No. : 10.3**

**Date:**

**Register No.:**

**Name:**

---

### **Peak Element**

Given an list, find peak element in it. A peak element is an element that is greater than its neighbors.

An element  $a[i]$  is a peak element if

$A[i-1] \leq A[i] \geq A[i+1]$  for middle elements.  $[0 < i < n-1]$

$A[i-1] \leq A[i]$  for last element  $[i=n-1]$

$A[i] \geq A[i+1]$  for first element  $[i=0]$

```
n = int(input(""))
```

```
arr = list(map(int, input("").split()))
```

```
peaks = []
```

```
if n > 1 and arr[0] >= arr[1]:
```

```
    peaks.append(arr[0])
```

```
for i in range(1, n - 1):
```

```
    if arr[i - 1] <= arr[i] >= arr[i + 1]:
```

```
        peaks.append(arr[i])
```

```
if n > 1 and arr[-1] >= arr[-2]:
```

```
    peaks.append(arr[-1])
```

```
print(" ".join(map(str, peaks)))
```

**For example:**

Input	Result
1 2 3 5 8 6	False
3 5 9 45 42 42	True



**Ex. No. : 10.4**

**Date:**

**Register No.:**

**Name:**

---

### **Binary Search**

Write a Python program for binary search.

```
def binary_search(arr, x):  
    left = 0  
    right = len(arr) - 1  
    while left <= right:  
        mid = left + (right - left) // 2  
        if arr[mid] == x:  
            return True  
        elif arr[mid] < x:  
            left = mid + 1  
        else:  
            right = mid - 1  
    return False  
  
def main():  
    arr = list(map(int, input().strip().split(',')))  
    x = int(input().strip())  
    result = binary_search(sorted(arr), x)  
    print(result)  
  
main()
```

**Input:**

1 68 79 4 90 68 1 4 5

**output:**

1 2

4 2

5 1

68 2

79 1

90 1

**For example:**

Input	Result
4 3 5 3 4 5	3 2 4 2 5 2

**Ex. No. : 10.5**

**Date:**

**Register No.:**

**Name:**

---

### **Frequency of Elements**

To find the frequency of numbers in a list and display in sorted order.

**Constraints:**

$1 \leq n$ ,  $\text{arr}[i] \leq 100$

```
num=input()
```

```
num=num.split()
```

```
numbers=[]
```

```
for i in num:
```

```
    numbers.append(int(i))
```

```
frequency_dict = { }
```

```
for num in numbers:
```

```
    frequency_dict[num] = frequency_dict.get(num, 0) + 1
```

```
sorteds = {k: v for k, v in sorted(frequency_dict.items())}
```

```
for num, freq in sorteds.items():
```

```
    print(num,freq)
```