

Document Effective Date
07/12/2021



QatarEnergy–IS HAZARD COMMUNICATION PROCEDURE

DOC NO: IS-HSE-PRC-006

Rev: 01

Quality Reviewed By: OIH/14

NE

Digitally signed by
Neeraj Tiwari
Date: 2021.12.07
10:03:10 +03'00'

CUSTODIAN DEPARTMENT	DOCUMENT AUTHOR	DOCUMENT OWNER
HEALTH, SAFETY & ENVIRONMENT (IDD EL-SHARGI)	 Digitally signed by Adam Azzi Date: 2021.12.07 10:09:15 +03'00'	 Digitally signed by Adam Azzi Date: 2021.12.07 10:09:45 +03'00'
	OIH/15	A/OIH/1

FINAL APPROVAL
 Digitally signed by Stephane Gri Date: 2021.12.07 10:40:01 +03'00'
OIH



TABLE OF CONTENTS

Page No.

1.0 PURPOSE	3
2.0 SCOPE AND APPLICABILITY.....	3
3.0 ROLES AND RESPONSIBILITIES.....	3
4.0 PROCEDURAL STEPS.....	4
4.1 GENERAL	4
4.2 HAZARD COMMUNICATION COORDINATORS (HCC)/ CHEMICAL INVENTORY LIST	4
4.3 MASTER CHEMICAL INDEX	4
4.4 MATERIALS SAFETY DATA SHEETS (MSDS).....	5
4.5 PURCHASING CONTROLS.....	5
4.6 DESIGNATED STORAGE AREAS.....	5
4.7 CONTAINER LABELS / WARNINGS	6
4.8 INFORMATION AND TRAINING.....	6
4.9 REPORTING OF INCIDENTS AND TASK OBSERVATIONS.....	7
4.10 NON-ROUTINE TASKS/ EMERGENCIES/ UNLABELLED PIPES	7
4.11 CONTRACT WORKERS.....	7
5.0 REFERENCES	7
6.0 DEFINITIONS.....	8
APPENDIX A - METHOD FOR DETERMINING IF A CHEMICAL IS HAZARDOUS.....	9
APPENDIX B - BASEL CONVENTION 1989	11
APPENDIX C - CHEMICAL INVENTORY LIST	14
APPENDIX D - MASTER CHEMICAL INDEX	15
APPENDIX E: SAMPLE MSDS REQUEST LETTER.....	15
APPENDIX F - REPRESENTATIVE LABELS UN HAZARD WARNING LABELS	16
APPENDIX G - SAMPLE LABELS FOR NORM MATERIALS	17
APPENDIX H - SAMPLE LABEL FOR HAZARDOUS WASTES AT RAS LAFFAN CITY.....	18
APPENDIX I - CHEMICAL HAZARD LABELLING FOR VENDORS	19
APPENDIX J – REVISION HISTORY LOG.....	20



QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE

DOC NO: IS-HSE-PRC-006

REV. 01

1.0 PURPOSE

This Procedure is designed to provide a system to ensure that relevant information on hazardous materials is collected and disseminated to personnel who handle, or are responsible for the handling of such materials.

2.0 SCOPE AND APPLICABILITY

The requirements of this program apply to all chemicals used, stored or transported across QatarEnergy-IS operated location including those materials produced on site as products or by-products and those which may be produced under emergency conditions.

3.0 ROLES AND RESPONSIBILITIES

FILED OPERATIONS MANAGER

- Ensure that an effective, formal written Hazard Communication (Hazcom) Program, specific to QatarEnergy-IS operations, is developed and implemented.
- Appoint a Program Coordinator.

HSE MANAGER

- Administer the training program and provide internal monitoring and feedback on the compliance with and effectiveness of this program.
- Ensure that all aspects of the Hazcom Program are in place and functioning.
- Act a central reference point for all queries related to this program

SUPPLY CHAIN DEPARTMENT

- Maintain the Master Chemical List and the MSDS database.
- Ensure all hazardous materials are delivered with an MSDS

OFFSHORE INSTALLATION SUPERINTENDENT/ PRODUCTION SUPERVISORS /OFFSHORE DRILLING SUPERVISORS/ OFFSHORE CONSTRUCTION SUPERVISORS

- Ensure that the relevant MSDS is available for all materials in use at their locations and that the MSDS has been read and understood and the necessary protective actions initiated.
- Act as a HCC (Hazard Communication Coordinator) to ensure a Chemical Inventory list is maintained for their location and liaise with the HSE Manager when additional guidance / information is required.
- Initiate a JSA where required to determine the risk of exposure to personnel using the hazardous material and, apply the intrinsic / additional controls to eliminate or minimize that risk.

QatarEnergy-IS EMPLOYEES AND CONTRACTOR

- Ensure the correct handling systems and protective equipment are used when working with hazardous materials. This requires familiarity with the requirements and location of the MSDS relevant to work sites.



QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE

DOC NO: IS-HSE-PRC-006

REV. 01

4.0 PROCEDURAL STEPS

4.1 GENERAL

- Each person shall be made aware by issue of the MSDS, of the chemical(s) he/she may come into contact with during the task. This information shall describe the nature of the hazard(s) that chemical presents, and how to take appropriate precautions when handling the chemical.
- Contracted drilling rigs, work barges and construction barges shall have a program in place which meets or exceeds the intent of this program. They shall submit a complete copy of their MSDS file to QatarEnergy Supply Chain Department.
- Hazard communication and hazardous material control shall be affected through the following avenues:
 - Hazcom Boards
 - Appointed Hazard Communication Coordinators (HCC)
 - Chemical Master List
 - Chemical Inventory List
 - MSDS File
 - Purchasing Controls
 - Designated Storage Areas
 - Container Labels/Warnings
 - Information and Training

4.2 HAZARD COMMUNICATION COORDINATORS (HCC)/ CHEMICAL INVENTORY LIST

- The following location persons shall act as/or designate at least one employee (two where employee rotation is applicable) as their facility as HCC

○ PS1	Offshore Installation Supervisor
○ Halul Island	Operations Supervisor (Halul-PWHF)
○ RLIC Warehouse	Warehouse Supervisor
○ Main Office	Facilities management
- The HCC is responsible for completing a Chemical Inventory List (Appendix C) for the relevant location.
- The chemical inventory list shall include natural and produced products e.g. crude oil, LNG, and by-products, e.g. off-gasses, etc., as well as purchased materials and welding rods.

4.3 MASTER CHEMICAL INDEX

- Supply Chain Department shall maintain an overall Master Chemical Index for all chemicals used and produced by QatarEnergy-IS. Where appropriate this will include chemicals used on contracted work barges, drilling rigs and construction barges.
- This Index is a permanent list, no chemical is removed from the list but the date when QatarEnergy-IS last used/purchased the chemical shall be indicated.



QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE

DOC NO: IS-HSE-PRC-006

REV. 01

- The Master Chemical Index (Appendix D) shall include the trade and common names, the manufacturer and the date of the latest revision of MSDS sheet held.
- The current Master Chemical Index shall be available as a minimum at the following operating locations:
 - PS1 Control Room
 - Halul Island Control Room
 - RLIC Warehouse Main Office (Master List)
 - Main Office Facilities Management office on site

Note: Supply Chain maintains a database which is both a complete Master Chemical Index and also a complete file of MSDS.

4.4 MATERIALS SAFETY DATA SHEETS (MSDS)

- MSDS shall be available for all hazardous materials and preferably for all materials on the Chemical Master List.
- New or revised versions of existing MSDS shall be submitted to the Supply Chain Department, Port Warehouse, for inclusion in the K Drive Folder.
- The MSDS File shall be available as a minimum in the following locations:
 - PS1 Control Room
 - Halul Island Control Room
 - RLIC Warehouse Main Office (Master List)
 - Main Office Reception Area

The relevant MSDS shall be available at each working location where a hazardous material is used

Note: As detailed above there is a database incorporating all the MSDS. Operating locations shall maintain a hardcopy file of relevant materials to safeguard against loss of information during power outages.

4.5 PURCHASING CONTROLS

- The Supply Chain Department shall include the following statement within their purchase orders: "Chemicals shipped without a MSDS shall not be received."
- A person specifying, or ordering, a chemical shall ensure that there is a MSDS sheet on file for that material. If there is no sheet, the chemical requester shall request that Supply Chain Department specifically note the requirement of an MSDS with shipment using the proscribed letter (Appendix E).

4.6 DESIGNATED STORAGE AREAS

- Each QatarEnergy-IS location shall have designated storage area(s) for hazardous materials.
- Care shall be taken to ensure that incompatible materials are not stored side-by-side e.g. oxygen with fuel gases, oxidizers with flammables, acids with caustics, and so on.
- HSE Department shall advise on material compatibility as required.
- Materials shall be returned to the designated storage area after use.
- For PS1, a plot plan showing the designated chemical storage areas shall be submitted by the HCC with a chemical inventory to the Field Operations Team

	QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE DOC NO: IS-HSE-PRC-006 REV. 01
--	---

Leader. This information shall be kept up to date as it may be required in the case of a platform emergency.

4.7 CONTAINER LABELS / WARNINGS

- It is essential that all chemical containers are suitably labelled. This requirement applies to “immediate use” containers also.
- All employees are responsible for ensuring adequate labelling and any person finding a container unlabelled, or with a damaged label, will endeavour to identify the material concerned and apply a new label.
- Material being transported into and out of Ras Laffan shall carry Hazard Warning labels, examples of which are shown in Appendix F.
- Labelling shall show the trade and common names where known, the hazard e.g. corrosive, flammable, etc. and the manufacturer’s name and telephone number as a minimum.
- Replacement custom made labels may be used provided they carry the required information i.e. Chemical name, Product name, Hazards and any Risk/Safety Phrases)
- Special labels are required for containers of NORM (Appendix G).
- All hazardous waste materials imported into Ras Laffan City shall be labelled (Appendix H & I).
- Labels shall be applied to all containers whether permanent e.g. bulk storage tanks or temporary e.g. transport tote tanks.
- Unless otherwise required (by specific hazard assessment) process pipe work and process vessels do not require to be labelled. However, such pipe work and vessels shall be colour coded and/or shall be identified (as a minimum with a line identification number or vessel number).
- Containers such as drinking cups, water bottles and other items which may be recognized as drinks or food containers shall not be used for the permanent or temporary storage of any chemical.

4.8 INFORMATION AND TRAINING

All personnel designated through Learning Management System (LMS) shall receive introductory training, and on required retraining schedule as per QatarEnergy requirement basis which will include:

- Where to find this program
- The Master Chemical Index
- How to read and interpret MSDS sheets
- Where to find the MSDS file
- The classification of hazard for a particular material
- The requirement for Personal Protective Equipment (PPE)
- The effects of exposure and the necessary first aid steps

In addition, employees shall receive training in the handling of specific materials, immediately before the first use of such materials. This information may be disseminated at tool-box talks, project safety meetings, etc.



QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE

DOC NO: IS-HSE-PRC-006

REV. 01

4.9 REPORTING OF INCIDENTS AND TASK OBSERVATIONS

- All incidents/near misses to be reported as per QatarEnergy procedure for HSE incident reporting, investigation & learning (QP-HSE-PRC-022). This requirement applies equally to incidents involving hazardous materials as it does to incidents involving personal injury or equipment failure.
- Task Observations shall be reported through Safety Observation Card (SOC), particularly examine the way in which any materials are being transported, stored and used to determine if the requirements of this Procedure and the relevant MSDS sheet are being observed.

4.10 NON-ROUTINE TASKS/ EMERGENCIES/ UNLABELLED PIPES

- All potential chemical or physical hazards associated with a non-routine task, such as entering a vessel or breaking open an unlabelled pipe shall be communicated to all personnel likely to be exposed to the hazard. The permit to work system and specific safety/training meetings shall be the vehicle for this communication.
- Necessary protective measures to minimize the hazards shall be communicated on the permit and via tool-box talks.
- If the contents of an Equipment/pipe are unknown, all attempts at identification shall be exhausted prior to the start of work. If the contents of the pipe remain unknown, then maximum protective measures shall be in place prior to work commencing (i.e. respiratory protection, chemical resistant clothing, etc.).

4.11 CONTRACT WORKERS

- Contractors and sub-contractors shall provide QatarEnergy-IS with any MSDS sheets applicable to materials they bring to site.
- Hazard communication to the contractor shall follow the guidelines of this program and regular contractors shall receive training specified above, and receive specific training, if required, prior to the use of any QatarEnergy-IS provided chemicals.

5.0 REFERENCES

Title	Document Number	Internal/ External	Document Referencing
Waste Management Procedure	IS-HSE-PRC-012	Internal Document	Sideways
QatarEnergy procedure for HSE incident reporting, investigation & learning	QP-HSE-PRC-022	Internal Document	Sideways
Procedure for Handling NORM Contaminated Materials and Equipment	IS-FOP-PRD-247	Internal Document	Sideways

	QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE DOC NO: IS-HSE-PRC-006 REV. 01
--	---

6.0 DEFINITIONS

Term	Definition
Container	Any vessel, barrel, tank, drum, bucket, can, bottle, etc. as well as any other apparatus, which has as its primary, purpose the holding of chemicals. For the purposes of this program, pipes and piping systems as well as vehicle fuel tanks, engines or other operating systems are not classed as containers.
Hazardous Material	A material is considered hazardous if it or any of its components present a physical or health hazard as defined in Appendix A
Hazardous Waste	Any waste material deemed unrecoverable/unusable and classified as hazardous under the terms of the Basel Convention (Appendix B) becomes a "Hazardous Waste". The handling of hazardous wastes is controlled under IS-HSE-PRC-012 "Waste Management Procedure".
Health Hazard	a chemical substance or exposure to a condition for which there is statistically significant evidence from a study (studies) based on established scientific principles that acute or chronic health effects may occur in exposed personnel.
Immediate Use	Chemicals under the control of one person, transferred by that person from one container to another smaller container for use during that work shift.
Materials Safety Data Sheet (MSDS)	A Document, provided by the manufacturer detailing various chemical and physical properties of the material supplied.
NORM Contaminated materials	Any material (whether it be inherently hazardous or not) which has become hazardous by virtue of being contaminated by the presence of <u>N</u> aturally <u>O</u> ccurring <u>R</u> adioactive <u>M</u> aterial. PRD 247 provides guidance and instruction in the specific requirements for handling NORM.
QatarEnergy-IS Operations/Operating Locations	QatarEnergy-IS operates the ISND Fields for the purposes of hydrocarbons production. In support of this production there are wellhead maintenance, construction, drilling, logistic and administrative support activities at ISND, Ras Laffan Industrial City, Halul Island and additionally, from time to time, at other sites within Qatar. These activities, undertaken to enable hydrocarbon production, are performed by QatarEnergy-IS staff, general contractors and service contractors.
Physical Hazard	a substance for which there is scientifically valid evidence that it is a combustible liquid, compressed gas, explosive, flammable, an organic peroxide, an oxidizer, pyrophoric, unstable (reactive) or water-reactive.

	QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE DOC NO: IS-HSE-PRC-006 REV. 01
--	---

APPENDIX

APPENDIX A - METHOD FOR DETERMINING IF A CHEMICAL IS HAZARDOUS

A chemical is considered hazardous if any of its components present a physical hazard or a health hazard.

A chemical which is a **PHYSICAL HAZARD**: means a chemical for which there is scientifically valid evidence that it is:

COMBUSTIBLE LIQUID:

A liquid having a flash point at or above 100deg F (37.8 °C) but below 200deg F (93.3 °C).

COMPRESSED GAS:

A gas or mixture of gases having, in a container, an absolute pressure exceeding 40 psia at 70deg F (21.1 °C),

a gas or mixture of gases having, in a container, an absolute pressure exceeding 104 psia at 130deg F (54.4 °C) regardless of the pressure at 70deg F (21.1 °C), or

A liquid having a vapor pressure exceeding 40 psia at 100deg F (37.8 °C) as determined by ASTM D-323-72.

EXPLOSIVE:

A chemical that causes sudden, almost instantaneous release of pressure, gas, and heat when subjected to sudden pressure, shock, or high temperatures

FLAMMABLE AEROSOL:

An aerosol that, when tested by the method described in 16 CFR 1500.45, yields a flame projection exceeding 18 inches at full valve opening, or a flashback (a flame extending back to the valve) at any degree of valve opening.

FLAMMABLE GAS:

A gas that, at ambient temperature and pressure, forms a flammable mixture with air at a concentration of 13% by volume or less, or a gas that, at ambient temperature and pressure, forms a range of flammable mixtures with air wider than 12% by volume, regardless of the lower limit.

FLAMMABLE LIQUID:

A liquid having a flash point below 100deg F (37.8 °C).

FLAMMABLE SOLID:

A solid, other than a blasting agent or explosive, that is liable to cause fire through friction, absorption of moisture, spontaneous chemical change, or retained heat from manufacturing or processing, or which can be ignited readily and when ignited burns so vigorously and persistently as to create a serious hazard.

ORGANIC PEROXIDE:

An organic compound that may be considered to be a structural derivative of hydrogen peroxide where one or both of the hydrogen atoms has been replaced by an organic radical.

	QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE DOC NO: IS-HSE-PRC-006 REV. 01
--	---

OXIDIZER:

A chemical other than a blasting agent or explosive that initiates or promotes combustion in other chemicals, thereby causing fire either of itself or through the release of oxygen or other gases.

PYROPHORIC CHEMICAL:

A chemical that will ignite spontaneously in air at a temperature of 130deg F (54.4 °C) or below.

UNSTABLE (REACTIVE) CHEMICAL:

A chemical which in the pure state, or as produced or transported, will vigorously polymerize, decompose, condense, or will become self-reactive under conditions of shock, pressure or temperature.

WATER-REACTIVE CHEMICAL:

A chemical that reacts with water to release a gas that is either flammable or presents a health hazard.

A chemical which is a **HEALTH HAZARD**: means a chemical for which there is statistically significant evidence based on at least one study conducted in accordance with established principles that acute or chronic health effects may occur in exposed employees. The term "Health Hazard" includes a chemical that is:

CARCINOGEN:

A chemical or agent that has been evaluated by the International Agency for Research on Cancer (IARC) and found to cause cancer or is a potential carcinogen, is listed as cancer causing or a potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP), is listed by OSHA as a carcinogen.

CORROSIVE :

A chemical that causes visible destruction of or irreversible alterations in, living tissue by chemical action at the site of contact.

HIGHLY TOXIC:

A chemical meeting any of the following, a material having a median lethal dose (LD50) of 50 mg or less per kg of body weight when administered orally to albino rats weighing between 200 and 300 grams each, a material that has a median lethal dose (LD50) of 200 mg or less per kg of body weight when administered by continuous contact for 24 hours (or less if death occurs in less than 24 hours) with the bare skin of albino rabbits weighing between 2 and 3 kg each, a material that has a median lethal concentration (LC50) in air of 200 ppm by volume or less of gas or vapor, or 2 mg per liter or less of mist, fume or dust, when administered by continuous inhalation for one hour (or less if death occurs within one hour) to albino rats weighing between 200 and 300 g each

IRRITANT:

A material which is not corrosive, but which causes a reversible inflammatory effect on living tissue by chemical action at the site of contact. An eye irritant is determined by the Procedure listed in 16 CFR 1500.42 or other appropriate techniques. A material is a skin irritant when tested on the intact skin of albino rabbits by the method specified in 16 CFR 1500.41 for

	QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE DOC NO: IS-HSE-PRC-006 REV. 01
--	---

four-hour exposures or by other appropriate Procedures and results in an empirical score of 5 or more.

SENSITIZER:

A material that, causes a substantial proportion of exposed people or animals to develop an allergic reaction in normal tissue after repeated exposure to the material

TOXIC:

A material meeting any of the following, a material that has a median lethal dose (LD50) of more than 50 mg per kg but not more than 500 mg per kg of body weight when administered orally to albino rats weighing between 200 and 300 grams each, a material that has a median lethal dose (LD50) of more than 200 mg per kg but not more than 1000 mg per kg of body weight when administered by continuous contact for 24 hours (or less if death occurs within 24 hours) with the bare skin of albino rabbits weighing between 2 and 3 kg each, a material that has a median lethal concentration (LC50) in air of more than 200 ppm but not more than 2000 ppm by volume of gas or vapor, or more than 2 mg per liter but not more than 20 mg per liter of mist, dust or fume, when administered by continuous inhalation for one hour (or less if death occurs within 1 hour) to albino rabbits weighing between 200 and 300 grams each. A material that affects TARGET ORGANS; e.g.

Agents that act on the blood or hematopoietic system, i.e. decreases hemoglobin function; deprives the body tissues of oxygen, Agents which damage the lungs, eyes, or mucous membranes, i.e. chemicals which irritate or damage the pulmonary tissue, affect eyes or visual capacity, or irritate nose,

Cutaneous hazards, i.e. chemicals which damage the dermal layer of the body,

Hepatotoxins, i.e. chemicals which produce liver damage,

Nephrotoxins, i.e. chemicals which produce kidney damage,

Neurotoxins, i.e. chemicals which produce their primary toxic effect on the nervous system,

Reproductive Toxins, i.e. chemicals which affect the reproductive capabilities including chromosome damage (mutations) and effects on fetuses (teratogenesis).

Any material listed by the U.S. Occupational Safety and Health Administration (OSHA) in 29 CFR Z, Toxic and Hazardous Substances. Those being:

Asbestos, Coal tar pitch volatiles, 4-Nitrobiphenyl, alpha-Naphthylamine, Methyl chloromethyl ether, 3,3'-Dichlorobenzidine, bis-Chloromethyl ether beta-Naphthylamin, Cotton dust, 1,2-dibromo-3-chloropropane, Acrylonitrile, Ethylene oxide, Formaldehyde, Methylenedianiline, Bloodborne pathogens, Nitrosodimethylamine, Vinyl Chloride, Inorganic arsenic, Lead, Cadmium, Benzene, Coke oven emissions, Benzidine, 4-Aminodiphenyl, Ethyleneimine, beta-Propiolactone, 2-Acetylaminofluorene, 4-Dimethylaminoazobenzene

APPENDIX B - BASEL CONVENTION 1989

CLASSIFICATION OF HAZARDOUS CHARACTERISTICS

2.4 Hazard criteria (H codes) Annex III to the Convention lists the hazardous characteristics which wastes included in Annex I may exhibit. There are 13 classes of hazardous characteristics numbered H3 to H33 as follows:

	QatarEnergy-IS HAZARD COMMUNICATION PROCEDURE DOC NO: IS-HSE-PRC-006 REV. 01
--	---

List of Hazardous Characteristics UN Class Code Characteristics

1 H3 EXPLOSIVE

An explosive substance or waste is a solid or liquid substance or waste (or mixture of substances or wastes) which is in itself capable by chemical reaction of producing gas at such a temperature and pressure and at such speed as to cause damage to the surroundings.

3 H3 Flammable liquids

The word "flammable" has the same meaning as "inflammable." Flammable liquids are liquids, or mixtures of liquids, or liquids containing solids in solution or suspension (for example, paints, varnishes, lacquers, etc., but not including substances or wastes otherwise classified on account of their dangerous characteristics) which give off a flammable vapour at temperatures of not more than 60.5°C, closed-cup test, or not more than 65.6°C, open-cup test. (Since the results of open-cup tests and of closed-cup tests are not strictly comparable and even individual results by the same test are often variable, regulations varying from the above figures to make allowance for such differences would be within the spirit of this definition).

4.1 H4.1 Flammable solids

Solids, or waste solids, other than those classed as explosives, which under conditions encountered in transport are readily combustible, or may cause or contribute to fire through friction.

4.2 H4.2 Substances or waste liable to spontaneous combustion

Substances or wastes which are liable to spontaneous heating under normal conditions encountered in transport, or to heating up on contact with air, and being then liable to catch fire.

4.3 H4.3 Substances or wastes which, in contact with water emit flammable gases

Substances or wastes which, by interaction with water, are liable to become spontaneously flammable or to give off flammable gases in dangerous quantities.

5.1 H5.1 Oxidizing

Substances or wastes which, while in themselves not necessarily combustible, may, generally by yielding oxygen cause, or contribute to, the combustion of other materials.

5.2 H5.2 Organic Peroxides

Organic substances or wastes which contain the bivalent-O-O-structure are thermally unstable substances which may undergo exothermic self-accelerating decomposition.

6.1 H6.1 Poisonous (Acute)

Substances or wastes liable either to cause death or serious injury or to harm human health if swallowed or inhaled or by skin contact.

6.2 H6.2 Infectious substances

Substances or wastes containing viable micro-organisms or their toxins which are known or suspected to cause disease in animals or humans.

8 H8 Corrosives



Substances or wastes which, by chemical action, will cause severe damage when in contact with living tissue, or, in the case of leakage, will materially damage, or even destroy, other goods or the means of transport; they may also cause other hazards.

9 H30 Liberation of toxic gases in contact with air or water

Substances or wastes which, by interaction with air or water, are liable to give off toxic gases in dangerous quantities.

9 H31 Toxic (Delayed or Chronic)

Substances or wastes which, if they are inhaled or ingested or if they penetrate the skin, may involve delayed or chronic effects, including carcinogenicity.

9 H32 ECOTOXIC

Substances or wastes which if released present or may present immediate or delayed adverse impacts to the environment by means of bioaccumulation and/or toxic effects upon biotic systems.

9 H33 Capable, by means, after disposal, of yielding another material, e.g., leachate, which possesses any of the characteristics listed above.

APPENDIX C - CHEMICAL INVENTORY LIST

Location:

Revision Date:

Material name	Material location at facility	Purchased	Produced	Intermediate By-Product	Created under foreseeable emergency conditions	Material uses

**HAZARD COMMUNICATION PROCEDURE****DOC NO: IS-HSE-PRC-006****REV. 01****APPENDIX D - MASTER CHEMICAL INDEX**

Please note that Supply Chain maintain a Master MSDS Database which also acts as a Master Chemical Index.

APPENDIX E: SAMPLE MSDS REQUEST LETTER

Date:

To whom it may concern,

Please furnish us with a Material Safety Data Sheet (MSDS) for the product(s) listed below:

Please ensure that the MSDS contains the following information:

- The chemical name used on the manufacturer's label;
- Physical and chemical characteristics (vapor pressure, flash point, etc.);
- The physical hazards including the potential for fire, explosion and reactivity;
- The health hazards including signs and symptoms of exposure, and any medical conditions which are generally recognized as being aggravated by exposure to the chemical;
- The primary routes of entry;
- The U.S. Occupational Safety and Health Administration (OSHA) Permissible Exposure Limit (PEL), the American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), or other recognized exposure limit as recommended by the manufacturer;
- Whether the chemical is a carcinogen or not;
- Safe handling precautions
- Any applicable control measures such as engineering controls, personal protective equipment, and work practices;
- Emergency and first-aid Procedures;
- The revision date of the MSDS; and
- The name, address, and telephone number of the manufacturer, supplier, etc

We require receipt of the MSDS(s) within two weeks of the date of this letter.

Thank you for your cooperation.

Name

Signature

QatarEnergy

	HAZARD COMMUNICATION PROCEDURE DOC NO: IS-HSE-PRC-006 REV. 01
--	--

APPENDIX F - REPRESENTATIVE LABELS UN HAZARD WARNING LABELS



**APPENDIX G - SAMPLE LABELS FOR NORM MATERIALS**

“NORM Contaminated.....

Do not disturb, do not loiter.

Keep closed so as to retain moisture.

Activity when first stored:

Date first stored:

Secondary Hazard:

(e.g. flammable, corrosive, etc.)”



	HAZARD COMMUNICATION PROCEDURE DOC NO: IS-HSE-PRC-006	REV. 01
--	---	-----------------------

APPENDIX H - SAMPLE LABEL FOR HAZARDOUS WASTES AT RAS LAFFAN CITY

	IF FOUND PLEASE CONTACT POLICE AND RAS LAFFAN INDUSTRIAL CITY MANAGEMENT. Emergency Contact Telephone No.: 135 HAZARDOUS WASTE IMPROPER DISPOSAL PROHIBITED Waste Identification No..... Waste Name:..... Characteristics:..... Additional Information:..... Transporter:..... Disposer:..... Date transported to RLIC:.....	



HAZARD COMMUNICATION PROCEDURE

DOC NO: IS-HSE-PRC-006

REV. 01

APPENDIX I - CHEMICAL HAZARD LABELLING FOR VENDORS**For all Vendors and Contractors**

- It is mandatory that vendors and contractors comply with QATARENERGY-IS Hazard Communication Program
- Ensure that all chemical and lubricant containers supplied to QatarEnergy-IS have:
 1. Name of manufacturer
 2. Name of product
 3. The appropriate hazard label
 4. MSDS.
- Ensure that proper **labelling has been applied on all chemical** products whether shipped in the original manufacturer's container or in containers that have been decanted from the original container
- Supply QatarEnergy-IS Ras Laffan warehouse with extra labels to replace missing or damaged labels
- The requirement for hazard labelling of containers does not change the requirement for the MSDS to accompany all chemicals shipped via QatarEnergy-IS
- Hazard labelling requirements are not universal – QatarEnergy-IS has a very strict program that complies with USA Federal OSHA 29 CFR 1910.1200(f)
- QatarEnergy-IS HSE Department is available to answer questions regarding compliance at **+974-40149597**

For Proponent Departments

- Ensure that all contractors and vendors are aware and comply with QatarEnergy-IS Hazard labelling requirements.
- Conduct self-audits of materials shipped for appropriate hazard labels

For all Employees

- Never handle drum or container with chemicals or lubricants that do not have hazard labels.
- **Whenever any such drum or container is found, bring it to the immediate attention of your supervisor.**
- Use of appropriate PPE as recommended by the respective chemical/fluid/material MSDS is mandatory.
- Always properly label any secondary container that you decant chemicals into.
- **WARNING: Do not decant different chemicals into the same container. Some chemicals may react violently when mixed.**

	HAZARD COMMUNICATION PROCEDURE DOC NO: IS-HSE-PRC-006 REV. 01
--	--

APPENDIX J – REVISION HISTORY LOG**Revision Number: 01****Date: 06/12/2021**

Item Revised	Revision Description	Page No.
Common	Updated based on new Management system Document format and the current organizational structure	
Remarks :		