



Document Effective Date
16/04/2025

IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC NO: IS-HSE-PRC-010

Rev: 02

Quality Reviewed By: OMB/4(I)

CUSTODIAN DEPARTMENT	DOCUMENT AUTHOR	DOCUMENT OWNER
HEALTH, SAFETY & ENVIRONMENT (IDD EL-SHARGI)		
	OHO/1(I)	OHO(I)

FINAL APPROVAL
OH(I)

	IS CONTRACTOR HSE REQUIREMENTS PROCEDURE DOC. No. IS-HSE-PRC-010 Rev. 02
---	---

TABLE OF CONTENTS

1.0	PURPOSE.....	3
2.0	SCOPE AND APPLICABILITY	3
3.0	ROLES AND RESPONSIBILITIES	3
3.1	QatarEnergy-IS.....	3
3.2	Contractor.....	3
3.3	Individual Contractor Personnel.....	4
4.0	PROCEDURAL STEPS	4
4.1	Health, Safety & Environment Commitment	4
4.2	Contractor Safety Officers.	4
4.3	Personal Fitness/Personal Hygiene.....	4
4.4	HSE Orientation.....	6
4.5	QatarEnergy Life Saving Rules	6
4.6	HSE Incident Reporting and Investigation	7
4.7	Reporting Hazards, Unsafe Conditions, and Near Misses.....	7
4.8	Substance Abuse, Dangerous Materials and Firearms	7
4.9	Horseplay	8
4.10	Housekeeping.....	8
4.11	Clothing and Other Apparel	8
4.12	Compressed Gas Cylinders.....	8
4.13	Storage, Use and Labelling of Chemicals, Solvents and Paint	8
4.14	Personal Protective Equipment	8
4.15	Overhead work	9
4.16	Lifting Operations	9
4.17	Scaffolds and Platforms.....	9
4.18	Safety Harnesses and Lifelines	9
4.19	Non-Destructive Testing (NDT)	9
4.20	QatarEnergy Permit to Work system	10
4.21	Hydrogen Sulfide	10
4.22	Fire Protection	11
4.23	Safety Training	11
4.24	Supervision.....	11
4.25	Safety Meetings.....	11
4.26	English Language Proficiency	12
4.27	Electrical Safety.....	12

	IS CONTRACTOR HSE REQUIREMENTS PROCEDURE DOC. No. IS-HSE-PRC-010	Rev. 02
---	---	----------------

4.28 Emergencies..... 12

4.29 Onshore Transportation..... 13

4.30 Asbestos..... 14

4.31 Environmental Management..... 14

4.32 HSE Performance Monitoring..... 15

4.33 Marine..... 15

4.34 Pre-Marine Mobilization Review of Hired Vessels 15

4.35 Worksite Safety Inspections..... 16

4.36 Spill Response: 16

4.37 Handling of Portable Hand & Power Tools: 16

4.38 Other HSE Requirements..... 16

5.0 REFERENCES TO OTHER DOCUMENTS16

APPENDICES19

APPENDIX A: REVISION HISTORY LOG19

APPENDIX B: LIST OF ABBREVIATIONS19



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

1.0 PURPOSE

This procedure defines Health Safety and Environment (HSE) responsibilities and requirements for the Contractors' and Subcontractors' of QatarEnergy performing any work at or in connection with activities at the Idd El-Shargi Asset. This procedure contains a summary of the applicable HSE system, which shall be the minimum applicable requirements during the performance of any work or services by such Contractors and Subcontractors.

This procedure defines Contractor HSE requirements in addition to the requirements as per Managing HSE in Contracts (CORP-HSE-STD-080).

Note: In case if any conflict between this procedure and QatarEnergy Corporate Standard for Managing HSE in Contracts (CORP-HSE-STD-080), the more stringent requirements shall be applicable.

2.0 SCOPE AND APPLICABILITY

The Procedure applies to all Contractors and Subcontractors, whether engaged directly by QatarEnergy or by others, who will perform work or services of any kind at any of QatarEnergy-IS facilities, or any Contractors and Subcontractors, whether engaged directly by QatarEnergy or by others, who whilst in in QatarEnergy-IS will perform work or services of any kind in connection with QatarEnergy-IS from other QatarEnergy facilities and/or locations.

This procedure shall be applicable for all the new QatarEnergy-IS Contracts / shared Contacts and for renewed Contracts for which Scope of work / Tender documents has not finalized, at the date of issue of this procedure.

3.0 ROLES AND RESPONSIBILITIES

3.1 QatarEnergy-IS

Communicate HSE expectations, including its HSE system and programs to the Contractor. Communicate amendments to existing or new HSE system to the Contractor.

3.2 Contractor

Compliance with QatarEnergy-IS system and requirements related to HSE. Compliance with its own policies and procedures related to HSE. Ensure Subcontractors comply with QatarEnergy-IS and Contractors own policies and procedures and regularly verifies Subcontractor compliance and HSE performance. Monitoring and reporting of HSE performance and ensuring supervisory personnel at the worksite, at all times, are competent and have the authority to implement the Contractor HSE system accordingly. Ensure that QatarEnergy-IS HSE expectations, HSE practices and procedures are communicated and available for all its personnel. Compliance with all HSE related laws, regulations, requirements and permits that become effective during the duration of the contract. In line with Corporate Procedure for Enhancing Contractors' HSE Performance - CORP-SAF-PRC-006 defines activities and processes for contractor HSE requirements implementation through a rigorous audit process for utilizing contractors, and



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

subcontractors involved in work conducted for and on behalf of QatarEnergy. QatarEnergy will deploy Seven Start Audit for all Medium-High Risk Contractors.

3.3 Individual Contractor Personnel

Personnel shall comply with QatarEnergy Corporate, QatarEnergy-IS and Contractor established HSE policy, procedures, guidelines, rules and initiatives during the execution of work under QatarEnergy-IS contract and compliance with QatarEnergy Life Saving Rules.

4.0 PROCEDURAL STEPS

4.1 Health, Safety & Environment Commitment

Contractor shall demonstrate a strong commitment to HSE matters and have established HSE management systems, preferably based on internationally recognized Management system standards e.g. ISO 45001 & ISO 14001. During the tendering process, copies of Contractor's HSE policies and procedures shall be submitted to QatarEnergy-IS for review. Contractor HSE plan shall include a statement of intention to comply with QatarEnergy HSSEQ Policy.

Contractor shall be responsible for maintaining all facilities and associated services under Contractor's direction or responsibility in a manner that does not create or otherwise contribute to an unsafe or unhealthy work/living conditions or environment.

4.2 Contractor Safety Officers.

The number of Safety officers to be provided at site by the Contractor shall be as per QatarEnergy Corporate Standard for Managing HSE in Contracts (CORP-HSE-STD-080). In case additional Contractor Safety officers are required, the same shall specified by Sponsoring Department / Contract Holder in the Tender and Contract documents.

4.3 Personal Fitness/Personal Hygiene

Contractor shall ensure its personnel who are utilized in the performance of the contracted work are medically fit, healthy and physically qualified to perform such work. Contractor, if requested by QatarEnergy-IS shall provide health certificates for all of Contractor's personnel according to the guidance below.

Medical Fitness Assessment

Established minimum assessment requirements are detailed within QatarEnergy Procedure for Conducting Offshore Medical Fitness (BH-BHO-PRC-100) and QatarEnergy Standard for Fitness to Work (QP-OHH-STD-011).

Catering staff shall possess a valid Medical Fitness certificate. All food handlers shall possess a valid Food Handlers Medical certificate from Ministry of Public Health. Qatar.

Personnel assigned for offshore duties shall undergo offshore medical fitness assessment prior to mobilizing for offshore. All personnel visiting offshore shall obtain

**IS CONTRACTOR HSE REQUIREMENTS PROCEDURE****DOC. No. IS-HSE-PRC-010****Rev. 02**

Offshore medical fitness card from QatarEnergy Healthcare Department. Medical assessment shall be repeated as per the validity on the card.

Prescription Medication

Personnel shall inform the offshore medic or QatarEnergy-IS representative, on arrival, of any prescription medication that may be taken during the work duration.

Personal Hygiene

Contractor shall ensure that personnel maintain high standards of personal hygiene in connection with the performance of the work.

Contractor shall establish a health and hygiene inspection program relative to accommodations where personnel prepare and consume food and beverage, and sleep, irrespective of whether at an offshore or onshore facility.

Audits shall be performed at QatarEnergy sites in an effort to confirm high standards are effectively implemented. All corrective actions shall be tracked to closure.

Facility Health & Hygiene

Contractor shall ensure all requirements of IS-HSE-PRC-019 (Health and Hygiene Inspection procedure) and other applicable Healthcare Department procedures and guidelines are met:

- Good housekeeping standards and follow strict hygiene practices.
- A vermin/pest control program is implemented and managed to ensure all facilities are free of infestation.
- Potable water systems are operated and managed to ensure adequate and safe supply. Testing records shall be maintained for review by the QatarEnergy. Offshore facilities shall meet the requirements in line with IS-HSE-PRC-016 (Guidelines for Offshore Water Sampling)
- Protection during high temperatures shall be in accordance with IS-HSE-PRC-031 (Heat Stress Procedure).
- Contractors shall perform monthly self-inspections of work vessels in the QatarEnergy-IS operating fields and accommodation barges. Copies of self-inspections shall be kept and made available for QatarEnergy-IS review quarterly. An inspection by the QatarEnergy-IS Site Supervisor, Remote Safety Officer or his delegate shall be done and reported utilizing a Health & Hygiene audit form. Completed reports shall be submitted to Senior Site Supervisor, Service Contractor and Industrial Hygienist (Heat Stress Procedure). Contents of the Health & Hygiene Audit shall cover the following minimum requirements:
 - Fitness Certificates
 - Temperature Control
 - Training & Competency
 - Pest Control
 - Cleaning Records



- Fire Protection
- Food Safety Notices
- First Aid
- Welfare Facilities
- Workplace Safety
- Food Contamination Prevention

4.4 HSE Orientation

Contractor shall ensure personnel who are utilized in the contracted work are provided with QatarEnergy HSE orientation, regardless of prior experience. The HSE orientation address mandatory HSE requirements, rules and regulations. The orientation as a minimum will include the following elements:

- Location specific induction videos (where applicable)
- QatarEnergy Life Saving Rules
- ISSOW / E-PTW General Awareness
- QatarEnergy-IS Safety observation card (SOC)
- Stop Work Authority

For personnel visiting offshore locations, the QatarEnergy-IS Offshore Travel Checklist shall be completed and complied. The checklist confirms understanding of HSE requirements such as:

- PPE Selection, green hat and jewellery policy IS-HSE-PRC-005 (Procedure for Personal Protective Equipment Selection and Use)
- Facial Hair Policy within IS-HSE-PRC-023 (Hydrogen Sulfide Safety Procedure)

4.5 QatarEnergy Life Saving Rules

Contractor shall ensure personnel who are utilized for the contracted work recognize and adhere to QatarEnergy Life Saving Rules. The nine rules set the key actions to prevent workplace injuries and incidents. The following are the summary of Life Saving Rules:

- **Permit to Work** : Work with a valid permit when required
- **Transport Safety** : Obey transport safety rules
- **Gas Hazards** : Follow hazardous area requirements
- **Line of Fire** : Position yourself and others out of the line of fire
- **Personal Protective Equipment**: Wear the required Personal Protective Equipment
- **Working at Heights** : Protect yourself against a fall when working at height or overwater
- **Safety Critical Equipment** : Bypass safety critical equipment only with approval
- **Lifting Operations** : Plan lifting operations and control the area
- **Smoking** : Only smoke in designated areas



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

Adherence is mandatory by all personnel at every location and facility. Failure to comply may result in disciplinary action up to and including termination and disqualification for contractors. Supervisors are accountable for communicating QatarEnergy Life Saving Rules and for ensuring day-to-day compliance.

4.6 HSE Incident Reporting and Investigation

Contractor shall immediately notify QatarEnergy of all HSE incidents and illnesses and comply with QatarEnergy applicable procedures. The notification, investigation and other requirements related to the incident shall be as per QatarEnergy Procedure for HSE Incident Reporting Investigation Learning (QP-HSE-PRC-022).

The Contractor shall ensure a full incident investigation is performed, as required and a draft report is provided to QatarEnergy complete with root cause identification, recommendations and corrective actions.

The Contractor shall allow QatarEnergy-IS personnel to participate in incident investigations upon request and fully comply with any investigation carried out by QatarEnergy-IS.

4.7 Reporting Hazards, Unsafe Conditions, and Near Misses

The Contractor shall report any unsafe conditions and unsafe act immediately to QatarEnergy-IS. This also includes Near-miss incidents that could have resulted in injury or damage in order that necessary corrective action is taken.

Contractor shall either participate in QatarEnergy-IS Safety Observations (SOC) as detailed in IS-HSE-PRC-041 (Behavioural based Safety Observation procedure) or utilize their own program.

Where a Contractor utilizes their own Safety Observations program whilst performing work for QatarEnergy-IS, the Contractor is responsible to ensure a specific bridging plan is documented and communicated to QatarEnergy-IS. The plan shall define responsibility for communicating Safety Observations on a minimum of a daily basis to the agreed QatarEnergy-IS representative.

Reference: QatarEnergy Lifesaving Rule (Line of Fire) - Position yourself and others out of the line of fire

4.8 Substance Abuse, Dangerous Materials and Firearms

Possession of illegal drugs, drug paraphernalia, intoxicating beverages, firearms or other weapons is prohibited. Persons found to be in possession of such items or under the influence of drugs or alcohol shall face strict Disciplinary action as per QatarEnergy policies. Entry to QatarEnergy-IS locations shall be conditional upon QatarEnergy-IS right to conduct unannounced searches for such contraband.

**4.9 Horseplay**

Horseplay, such as wrestling, practical jokes, etc., can be dangerous and is prohibited.

4.10 Housekeeping

Contractor shall use good housekeeping maintenance practices. Work areas shall be maintained in a neat and orderly manner. Trash, spills, etc., shall be cleaned up as soon as possible. Aisles, emergency exits, and controls shall be kept free of materials at all times. All wastes shall be properly and safely disposed of. Contractor shall leave work sites clean, orderly and in a safe condition.

4.11 Clothing and Other Apparel

Contractor shall ensure clothing suitable for the job is worn. The PPE shall be in compliance with IS-HSE-PRC-005 (Procedure for Personal Protective Equipment Selection & Use) as well as CORP-SAF-STD-036 Corporate Standard for Personal Protective Equipment (PPE). Ragged or loose clothing and jewellery (rings, metal-strapped watches, necklaces, etc.) shall not be worn. Any clothing that becomes saturated with petroleum products or hazardous chemicals shall be promptly changed.

4.12 Compressed Gas Cylinders

Contractor shall comply with IS-FOP-WKI-020 (Safe transportation, handling and Storage of Compressed Gas Cylinders).

4.13 Storage, Use and Labelling of Chemicals, Solvents and Paint

Contractor shall comply with IS-HSE-PRC-006 (Hazard Communications procedure) and shall ensure personnel are protected from exposure to hazardous substances in accordance with IS-HSE-PRC-024 (Industrial Hygiene Protection The Control of Exposure to Hazardous Substances)

4.14 Personal Protective Equipment

Contractor shall ensure appropriate Personal Protective Equipment (PPE) is provided and worn by Contractor's personnel at the worksite as per IS-PRC-HSE-005 (Procedure for Personal Protective Equipment Selection and Use), IS-HSE-PRC-013 (Respiratory Protection Procedure) as well as CORP-SAF-STD-036 Corporate Standard for Personal Protective Equipment (PPE). General PPE life span shall be strictly followed such as Hard Hats 5 years, Safety Glasses 1 year, Coverall 1 year, Body Harness 4 years, Boots 3 years and life jacket 5 years. Impact-resistant gloves are selected as standard PPE. The selection of hand protection shall follow the Corporate Standard for Hand Protection, Doc. No.: CORP-SAF-STD-017, and be based on a risk assessment that considers the performance characteristics of the gloves in relation to the task(s), existing conditions, duration of use, and identified potential hazards. Hand gloves shall be embedded/tagged with applicable standards.



Reference: QatarEnergy Lifesaving Rule (Personal Protective Equipment)- Wear the required Personal Protective Equipment

4.15 Overhead work

Contractor shall ensure when working overhead that the area below has been barricaded, or other equivalent measures taken to protect workers on the Worksite. Signs reading “Danger—Work Overhead” shall be conspicuously posted. Contractor’s personnel shall never pass under a suspended load. Prior to undertaking overhead work, contractor shall conduct and document a dropped objects inspection or audit.

4.16 Lifting Operations

Lifting Operations and Equipment shall follow QP-PAI-STD-005 (QatarEnergy Standard For Lifting Equipment and Operations) and CORP-ENG-PRC-038 (Corporate Procedure for Lifting Equipment and Operations).

Reference: QatarEnergy Lifesaving Rule (Lifting Operations) - Plan lifting operations and control the area

4.17 Scaffolds and Platforms

All scaffolds or platforms shall be constructed, maintained, and used in compliance with the applicable occupational health and safety construction regulations and IS-FOP-PRC-216 (Scaffolding Operation Procedure). All scaffolds are to be erected, dismantled and modified by certified personnel only (scaffolders, foreman and supervisors). All scaffolds will be inspected, and tagged (SCAFTAG) by certified Inspectors only.

4.18 Safety Harnesses and Lifelines

Contractor shall ensure compliance with IS-PRC-HSE-048 (Fall Protection Procedure) and shall ensure that inspected and certified Full-body safety harnesses and lifelines are supplied and maintained by contractor and worn by all of contractor’s personnel to accomplish 100% tie-off when working above six (6) feet where it is impractical to provide adequate work platforms; double lifelines (lanyards) shall be used so that, during moves, at least one lanyard is attached to a suitable anchor point at all times.

Reference: QatarEnergy Lifesaving Rule (Working at Heights)- Protect yourself against a fall when working at height or overwater.

4.19 Non-Destructive Testing (NDT)

Any use of radioactive isotopes, X-rays, other radiation emitting devices, etc., shall only be by licensed individuals. All others shall stay clear. NDT may have to be scheduled such that other personnel do not have to work in the affected area. The NDT technicians shall place warning signs, etc., at the required distance from the radioactive source. The activities shall be in compliance to QatarEnergy Corporate Standard for Radiation Safety (CORP-SAF-STD-056).



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

4.20 QatarEnergy Permit to Work system

The Contractor shall comply with QatarEnergy Permit to work system that requires appropriate supervisory oversight and authorization for all work of a potentially hazardous nature and for the control of all non-routine work.

Reference: QatarEnergy Lifesaving Rule (Permit to Work)- Work with a valid permit when required

Reference: QatarEnergy Lifesaving Rule (Safety Critical Equipment)- Bypass safety critical equipment only with approval.

Contractor may also be required to establish and maintain a Permit to Work system, which, as a minimum, shall address the following:

Hot Work

Contractor shall ensure the requirements of IS-HSE-PRC-046 (Procedure for Control of Hot Work) are met or exceeded. Hot work shall be conducted in a designated safe welding area whenever practical.

Confined Space Entry

Contractor shall ensure the requirements of IS-FOP-PRC-206 (Confined Space Entry Procedure) are met or exceeded.

Control of Potentially Hazardous Energy (Lock, Tag, and Try)

Contractor shall ensure the requirements of IS-FOP-PRC-224 (Procedure for Process Valve/Mechanical Isolation, Opening & Closing of Pipping, Vessel & Equipment) and IS-FOP-PRC-500 (Electrical Safety Regulations) are met or exceeded.

4.21 Hydrogen Sulfide

Hydrogen Sulfide (H₂S) can be encountered at QatarEnergy-IS facilities. Contractor is responsible for ensuring that programs are aligned, complying and personnel trained in accordance with IS-HSE-PRC-023 (Hydrogen Sulfide Safety Procedure) when working in areas where hydrogen Sulfide may be encountered due to the nature of the Work. H₂S personal detectors will be assigned upon arrival at QatarEnergy-IS locations. It is the contractor's responsibility to ensure that personnel maintain the detectors in a functioning and calibrated condition, returning them to QatarEnergy-IS prior to departure. Additionally, it is contractors responsibility to provide personal H₂S Detectors to their staff.

Head and Facial Hair Policy

All persons working offshore shall be prohibited from wearing long hair, long side burns, long mustaches, beards, Van Dykes, goatees, etc., as they may interfere with the seal of a respirator. The Contractor shall ensure their personnel are aware of the acceptable and non- acceptable styles of facial hair contained within IS-HSE-PRC-023 (Hydrogen Sulfide Safety Procedure) and detailed on QatarEnergy-IS Offshore Travel Checklist.

Hydrogen Sulfide Contingency Plan



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

QatarEnergy-IS requires that an H₂S contingency plan shall be developed by the Contractor for any fixed or floating installation, which shall include the combined responsibility of QatarEnergy-IS, Contractor and other Contractors.

Reference: QatarEnergy Lifesaving Rule (Gas Hazards) - Follow hazardous area requirements

4.22 Fire Protection

Fire protection and life safety systems (smoke detection and sprinklers), which meet, as minimum, Safety of Life at Sea (SOLAS) and International Maritime Organization (IMO) standards shall be provided, maintained, and regularly inspected. Portable equipment shall be located strategically throughout the Contractor's facilities and is for emergency use only. Any unauthorized use of this equipment for any other purpose is forbidden.

Smoking

Smoking is only be permitted in specifically designated locations. Personnel shall not be permitted to smoke elsewhere whether posted or not. Cigarette lighters and fuel for cigarette lighters are prohibited.

Reference: QatarEnergy Lifesaving Rule (Smoking) - Only smoke in designated areas.

Contractor shall provide adequate safety equipment of an approved type and amount as is required for the execution of the work. The contractor shall maintain and inspect this equipment in a professional manner as dictated by legal and industry standards. In addition, the Contractor shall keep up-to-date records of all said equipment.

4.23 Safety Training

Contractor shall ensure that all personnel have been given the necessary HSE, emergency and job-related training required by industry practice, codes, and standards and contractor's policies. IS-HSE-PRC-002 (HSE Training Procedure) outlines the HSE training required by QatarEnergy-IS. As a minimum, all personnel and visitors travelling to an offshore worksite shall receive a copy of and be in full compliance with the QatarEnergy-IS Offshore Travel Checklist. Contractor shall ensure that personnel attend other HSE training as specified by QatarEnergy-IS.

4.24 Supervision

All contractor on-site supervision shall be trained in and knowledgeable about the contractor's HSE programs and shall work to effectively implement them on site.

4.25 Safety Meetings

Regular meetings shall be held, and a pre-job Tool Box meeting program shall be established. The safety meetings shall be minuted and copies forwarded to the QatarEnergy Safety Officer and onshore HSE representative in a timely manner. Both Tool Box and Safety Meetings attendance shall be documented with the following information at a minimum:

- Date & Time of Meeting
- Contractor's Name



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

- Topic of Meeting
- Meeting Leader's Name and Signature
- Meeting Attendees' Names and Signatures

4.26 English Language Proficiency

It shall be the responsibility of the contractor to have the English language proficiency of their employees. Any person not complying with this requirement may be subject to removal from the work site at the sole discretion of QatarEnergy-IS. The consequences of such removal shall be Contractor's responsibility.

Contractor shall ensure that all key/supervisory personnel are proficient in verbal & written English and able to communicate the HSE requirements, site rules, Instructions to their staff in an effective manner.

All other Contractor personnel shall be able to understand English, so that they can follow and implement the instructions given by their Supervisor or QatarEnergy.

4.27 Electrical Safety

Contractor shall ensure personnel working around electrical equipment shall take precautions to ensure that the equipment is de-energized while work is being conducted on or around such equipment in compliance with IS-FOP-PRC-500 (IS Electrical Safety Regulations). Precautions shall be taken to ensure that all equipment used is properly grounded and that accidental contact with underground electrical sources is prevented.

Overhead Power Lines

Work that is to be conducted near any overhead power line shall be planned such a clearance of no less than ten feet is maintained throughout the duration of the job so as to prevent accidental contact with energized equipment. If work is to be performed within a ten- foot radius of overhead energized equipment, the equipment shall be de-energized prior to starting work, unless adequately controlled by a safe work system.

Ladders

Ladders used around electrical equipment shall be of non-conductive material (thereby excluding metallic, metallic blended or wood) so as not to be a conductor of electricity.

4.28 Emergencies

Contractor shall ensure that personnel are familiar with IS-HSE-PRC-001 (Emergency Management Procedure) and site specific Emergency Response Procedures at QatarEnergy-IS work locations and participate in emergency drills when conducted.

All Contractors shall document and maintain their own emergency plan that complies with and bridges the requirements of IS-HSE-PRC-001 (Emergency Management Procedure). A log of all drills shall be maintained.

Station Bill

Station bill listing shall include emergency assignments and the personnel responsible for carrying them out, as well as addressing the following:



- Muster procedures
- T-Card or other means of personnel on board (POB) control
- Alarms and action

Emergency Layout Plans

Emergency diagrams shall be available, including offices and accommodation showing emergency facilities. These diagrams shall indicate the locations of the following (as applicable):

- Escape routes
- Evacuation and assembly points
- Survival craft
- Breathing apparatuses
- Firefighting equipment and activation points for fixed firefighting systems
- Telephones and radios
- Emergency shutdown activation points
- First-aid kits
- Stretchers
- Navigational aids
- Helicopter landing facilities (crash box, wind sock, etc.)

A composite diagram showing all areas shall also be displayed at one or more central points.

Medical Emergency Response

Contractor shall ensure & provide that the minimum levels of medical assistance as per the following ratio:

No of Contractor Personnel	0-25	25-50	50-100	100+
Basic First Aider	1	2	4	5
Advanced First Aid	-	1	2	3
Registered Nurse	-	-	-	1

4.29 Onshore Transportation

Contractor shall ensure that personnel follow the requirements of IS-HSE-PRC-039 (Transportation Safety Procedure). The transportation of personnel in the cargo beds of Lorries, trucks or pickups is strictly prohibited.

Reference: QatarEnergy Lifesaving Rule (Transport Safety)- Obey transport safety rules



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

4.30 Asbestos

Contractor shall prevent or minimize the exposure of personnel when working with or encountering asbestos-containing material. Contractor Asbestos Management program shall meet or exceed the requirements of IS-HSE-PRC-040 (Procedure for Control of Asbestos).

4.31 Environmental Management

The Contractor shall pay due regard to the environment by acting to responsibly protect the environment from adverse effects resulting from the Work and associated activities performed under this Contract and to minimize any near term impacts that may arise from such work or activities in accordance with IS-HSE-MAN-029 (Environmental Management Manual).

The Contractor shall store all chemicals and hazardous materials and wastes with due regard for compatibility of materials, spill prevention and mitigation. Tanks and vessels shall be properly designed to avoid excessive evaporation, contamination, fire and explosion, or spillage. Spill containment devices shall be inspected daily and accumulation removed to preclude eventual overflow.

The Contractor shall report oil or chemical spills, whether or not into the sea, immediately to the QatarEnergy-IS. Contractor shall produce a specific Oil Spill Plan at the request of the QatarEnergy-IS, if required.

The Contractor shall periodically assess noise levels from operations to ensure there are no detrimental effects being imposed on the Contractor's personnel or other personnel. When requested by the QatarEnergy-IS, the Contractor shall install sound absorption and mitigation devices.

Contractor is responsible for effective waste management of all waste products or chemicals used in any activity under Contractor's control. Wastes shall be properly segregated as per IS-HSE-PRC-012 (Waste Management Procedure). All wastes shall be identified and catalogued.

Chemical Wastes

All unused chemicals / substances not consumed in the execution of the Work shall be kept in stock, returned to the supplier if applicable, recycled, or returned to shore for proper disposal.

Ordinary Wastes

Ordinary wastes (e.g., oily rags, plastic, wraps, etc.) shall be separated from industrial wastes (chemicals, scrap steel, etc.) and returned onshore in a trash skip or other means of containment acceptable to the QatarEnergy-IS. On site incineration shall not be permitted.

Biodegradable kitchen wastes shall be disposed of via kitchen garbage grinders in accordance with the Regional Organization for the Protection of Marine Environment (ROPME) Protocol.

Hydrocarbon Waste



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

All waste liquid hydrocarbons (e.g., lubricating oils, solvents, fuels, etc.) shall be collected in dedicated containers and transported to the terminal on Halul Island or returned onshore for proper disposal.

Naturally Occurring Radioactive Material (NORM) Contaminated Waste

All NORM contaminated waste shall be identified and disposed of in accordance with IS-FOP-PRC-247 (Handling NORM Contaminated Materials and Equipment)

Waste Management Plan

The Contractor shall produce a contract-specific waste management plan at the request of the QatarEnergy-IS, if required.

All fixed or floating installation waste and grey waters from domestic areas shall be treated and disposed of in accordance with the ROPME Protocol.

All wash down water and other water derived from the Work shall be controlled and managed in such a manner as to prevent direct discharge overboard. Oil and grease separators shall be used where necessary.

In the course of their Work, the Contractor and the Contractor's personnel shall not hunt, trap, fish, or trade animals or keep wild animals in captivity.

4.32 HSE Performance Monitoring

Contractors shall conduct regular HSE inspections of its work sites, industrial areas, camps and mess facilities. Planned audits shall also be performed to review HSE management and procedural aspects of its operations.

QatarEnergy-IS reserves the right at any time to independently audit/ inspect Contractor's facilities, equipment, procedures and HSE management systems against the requirements of the contract. The Contractor shall fully co-operate with QatarEnergy in such audits and reviews, and shall implement recommendations in a timely manner at its own cost.

The Contractor provides their monthly HSE performance inputs in Idd El-Shargi Contractor HSE scorecard program and Corporate Monthly Contractors' HSE Performance Submission System (MCHS).

4.33 Marine

The Contractor shall comply with QatarEnergy Marine procedure and Regulation. This includes Idd El-Shargi QP-ISND-MAN-SCM-001 (Marine Operations Manual)

4.34 Pre-Marine Mobilization Review of Hired Vessels

Inspection of Vessel entering in QatarEnergy-IS field shall be conducted by QatarEnergy-IS team as per IS-HSE-PRC-025 (Procedure for Pre-Marine Mobilization Review (PMMR) of Hired Vessels)



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

4.35 Worksite Safety Inspections

Contractor's shall comply with Worksite Safety Inspection Procedure (IS-HSE-PRC-003) and in line with scope of services shall plan, develop, execute, report and perform analysis of their own inspections.

4.36 Spill Response:

Contractor drilling rigs, work over, and construction barges working for QatarEnergy IS shall comply with IS Spill Response Procedure (IS-HSE-PRC-007) in addition, have their own Spill Response Procedure or equivalent, which shall incorporate the reporting and control mechanism of the procedure.

4.37 Handling of Portable Hand & Power Tools:

Contractor's shall comply with this IS Procedure for Handling of Portable Hand & Power Tools (IS-HSE-PRC-051). Contractor's shall use the correct tools for the job and be responsible for the inspection of Portable hand Tools to ensure they are serviceable before their use. They should also be responsible for reporting any defects with Portable Hand Tools. All portable hand tools shall be properly maintained according to the manufacturer's instructions and subject to a formal periodic inspection (no less than annually) to ensure that tools remain in safe operating condition. Mandatory PPE shall be worn at site. Other Personal Protective Equipment (PPE) shall be worn as specified by the risk assessment, Material safety data sheet (MSDS) and Procedure 'Personal Protective Equipment Selection and Use (IS-HSE-PRC-005)'. No hand tool shall be used for any other purpose other than for which it was designed and purchased (Right tool for the right job). During flange bolting, finger saving devices "Finger savers" shall be used if there is an approval to conduct flogging operations as per Procedure 'Flange Bolting (IS-FEC-PRC-234). Training shall be provided in the hazards and safe-operation of portable hand tools. Training should consist of toolbox talks, risk assessments, on the job training, job safety analysis, etc. and in all cases shall be documented.

4.38 Other HSE Requirements

The contractor shall comply with other applicable and associated QatarEnergy procedures and guidelines related to HSE.

5.0 REFERENCES TO OTHER DOCUMENTS

Document Title	Document Number	Internal External Document	Document Referencing
QatarEnergy Occupational Health and Safety Policy	CORP-COC-POL-002	Internal	Upward
IS Emergency Management Procedure	IS-HSE-PRC-	Internal	Sideward

**IS CONTRACTOR HSE REQUIREMENTS PROCEDURE****DOC. No. IS-HSE-PRC-010****Rev. 02**

Document Title	Document Number	Internal External Document	Document Referencing
	001		
IS HSE Training Procedure	IS-HSE-PRC-002	Internal	Sideward
IS Worksite Safety Inspection Procedure	IS-HSE-PRC-003	Internal	Sideward
IS Procedure for Personal Protective Equipment Selection and Use	IS-HSE-PRC-005	Internal	Sideward
IS Hazard Communications Program	IS-HSE-PRC-006	Internal	Sideward
IS Spill Response Procedure	IS-HSE-PRC-007	Internal	Sideward
IS Contractor HSE Management procedure	IS-HSE-PRC-010	Internal	Sideward
IS Waste Management Procedure	IS-HSE-PRC-012	Internal	Sideward
IS Respirator Protection Procedure	IS-HSE-PRC-013	Internal	Sideward
IS Procedure for Offshore Water Sampling	IS-HSE-PRC-016	Internal	Sideward
IS Health and Hygiene Inspection Procedure	IS-HSE-PRC-019	Internal	Sideward
IS Hydrogen Sulfide Safety Procedure	IS-HSE-PRC-023	Internal	Sideward
IS Industrial Hygiene Protection: Procedure for Control of Exposure to Hazardous Substances	IS-HSE-PRC-024	Internal	Sideward
IS Lifting Equipment Control and Operations Procedure	IS-HSE-PRC-027	Internal	Sideward
IS Environmental Management Manual	IS-HSE-MAN-029	Internal	Sideward
IS Heat Stress Procedure	IS-HSE-PRC-031	Internal	Sideward
IS Transportation Safety Procedure	IS-HSE-PRC-039	Internal	Sideward
IS Procedure for Control of Asbestos	IS-HSE-PRC-040	Internal	Sideward
IS Behavioral based Safety Observation Procedure	IS-HSE-PRC-041	Internal	Sideward
IS Procedure for the Control of Hot Work	IS-HSE-PRC-046	Internal	Sideward
IS Fall Protection Procedure	IS-HSE-PRC-048	Internal	Sideward
IS Procedure for Handling of Portable Hand & Power Tools	IS-HSE-PRC-051	Internal	Sideward

**IS CONTRACTOR HSE REQUIREMENTS PROCEDURE****DOC. No. IS-HSE-PRC-010****Rev. 02**

Document Title	Document Number	Internal External Document	Document Referencing
IS Safe Transportation, Handling and Storage of Compressed Gas Cylinders	IS-FOP-WKI-020	Internal	Sideward
IS Confined Space Entry Procedure	IS-FOP-PRC-206	Internal	Sideward
IS Scaffolding Operations Procedure	IS-FOP-PRC-216	Internal	Sideward
IS Procedure for Process Valve / Mechanical Isolation, Opening & Closing of Pipping, Vessel & Equipment's	IS-FOP-PRC-224	Internal	Sideward
IS Handling NORM Contaminated Materials and Equipment	IS-FOP-PRC-247	Internal	Sideward
IS Procedure for Electrical Safety Regulations	IS-FOP-PRC-500	Internal	Sideward
IS Procedure for Pre-Marine Mobilization Review (PMMR) of Hired Vessels	IS-HSE-PRC-025	Internal	Sideward
QatarEnergy Corporate Standard for Radiation Safety	CORP-SAF-STD-056	Internal	Upward
QatarEnergy Standard For Lifting Equipment and Operations	QP-PAI-STD-005	Internal	Upward
Corporate Procedure for Lifting Equipment and Operations.	CORP-ENG-PRC-038	Internal	Upward
Marine Operations Manual	QP-ISND-MAN-SCM-001	Internal	Sideward

Note: The Contractor shall comply with the documents listed in the above References, unless specified in the bridging document agreed by QatarEnergy and the Contractor.



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE

DOC. No. IS-HSE-PRC-010

Rev. 02

APPENDICES

APPENDIX A: REVISION HISTORY LOG

Revision Number: 02

Date: 21/03/2025

Item Revised	Revision Description	Page No:
ALL ITEMS	Replaced old references from HSE Regulations for Contractors (QP-REG-HSE-001) and replaced with QatarEnergy Corporate Standard for Managing HSE in Contracts (CORP-HSE-STD-080). Removed IS Integrated Safe System of Work (retired) IS-FOP-PRC-100.	All pages
3.2	Added Seven Star Audits	3/17
4.3	Updated old reference with new - QatarEnergy Procedure for Conducting Offshore Medical Fitness (BH-BHO-PRC-100) and added self inspections	4/17
4.11	Updated Revised PPE Standard.	8/17
4.14	Updated PPE Requirements	8/17
4.19	Updated old reference	9/17
4.20	Updated PTW Section	10/17
4.21	Updated section for Contractors H2S Monitors	10/17
4.31	Updated old Reference with IS-HSE-MAN-029 (Environmental Management Manual).	14/17
4.35, 4.36, 4.37,	Introduced new sections Worksite Safety Inspections, Spill Response, Handling of Portable and Power Tools,	16/17

APPENDIX B: LIST OF ABBREVIATIONS

Abbreviation	Description
E-PTW	Electronic Permit to Work
H2S	Hydrogen Sulphide
PPE	Personal Protective Equipment
QatarEnergy-IS	Idd El-Shargi Asset of QatarEnergy
ROPME	Regional Organization for the Protection of Marine Environment



IS CONTRACTOR HSE REQUIREMENTS PROCEDURE
DOC. No. IS-HSE-PRC-010

Rev. 02

Abbreviation	Description
SOLAS	Safety Of Life At Sea