Experiment 14

Single-Level Directory Organizationcode:

Code:

```
#include <stdio.h>
#include <string.h>

int main() {
  char files[20][30], name[30];
  int n = 0, choice, i, found;

  while (1) {
    printf("\n1. Create File");
    printf("\n2. List Files");
    printf("\n3. Delete File");
    printf("\n4. Exit");
    printf("\nEnter choice: ");
    scanf("%d", &choice);

    switch (choice) {
    case 1:
      if (n == 20) {
        printf("Directory is full\n");
        break;
      }

      printf("Enter file name: ");
      scanf("%29s", name);

      found = 0;
```

```
    for (i = 0; i < n; i++)
        if (strcmp(files[i], name) == 0)
            found = 1;

    if (found)
        printf("File already exists\n");
    else {
        strcpy(files[n++], name);
        printf("File created successfully\n");
    }
    break;

case 2:
    printf("\nFiles in directory:\n");
    for (i = 0; i < n; i++)
        printf("%s\n", files[i]);

    if (n == 0)
        printf("Directory is empty\n");
    break;

case 3:
    printf("Enter file name to delete: ");
    scanf("%29s", name);

    found = 0;
    for (i = 0; i < n; i++) {
        if (strcmp(files[i], name) == 0) {
            found = 1;

            for (int j = i; j < n - 1; j++)
```

```
                strcpy(files[j], files[j + 1]);

            n--;
            printf("File deleted successfully\n");
            break;
          }
        }

        if (!found)
          printf("File not found\n");
        break;

      case 4:
        return 0;

      default:
        printf("Invalid choice\n");
      }
    }
}
```

Output:

