Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 1_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 14

Section 1 : MCQ

1. An algorithm must have a clear stopping point to ensure

Answer

Finiteness

Status : Correct ***Marks : 1/1***

2. Which of the following is true about algorithmic determinism?

Answer

Algorithms must produce the same output for the same input

Status : Correct ***Marks : 1/1***

vtu27632

3. An algorithm's effectiveness refers to

Answer

Each step contributes to solving the problem

Status : Correct ***Marks : 1/1***

4. Which notation is used to describe both the upper and lower bounds of an algorithm's efficiency?

Answer

Θ (Big theta)

Status : Correct ***Marks : 1/1***

5. What is the purpose of using asymptotic notations in the analysis of algorithm efficiency?

Answer

To take meaningful statements about an algorithm's efficiency based on its growth rate

Status : Correct ***Marks : 1/1***

6. What does the Big Theta notation (Θ) indicate about an algorithm's efficiency?

Answer

It describes the tightest possible bound on the algorithm's running time.

Status : Correct ***Marks : 1/1***

7. Which of the following statements is true regarding the relationship between Big Oh (O), Big Omega (Ω), and Big Theta (Θ) notations?

Answer

vtu27632

If $f(n) = O(g(n))$ and $f(n) = \Omega(g(n))$, then $f(n) = \Theta(g(n))$

Status : Correct ***Marks : 1/1***

8. What does "Big O" notation represent in relation to algorithms?

Answer

A method to analyze and express the efficiency of an algorithm

Status : Correct ***Marks : 1/1***

9. An algorithm is required to produce a definite and unambiguous outcome for every valid input. This characteristic is known as _____.

Answer

determinism

Status : Correct ***Marks : 1/1***

10. Which approach is used to prove the correctness of algorithms by analyzing a sequence of steps?

Answer

Mathematical induction

Status : Correct ***Marks : 1/1***

11. In the context of algorithm design, what does the term "in-place" refer to?

Answer

The algorithm modifies the input data directly without using additional memory

Status : Correct ***Marks : 1/1***

12. What is the primary purpose of analyzing an algorithm's efficiency?

Answer

To optimize the algorithm's time and space efficiency

Status : Correct ***Marks : 1/1***

13. In the context of algorithmic problem-solving, what does the "generality of an algorithm" refer to?

Answer

The ability of an algorithm to handle a wide range of problem types

Status : Correct ***Marks : 1/1***

14. Which parameter is commonly used to measure an algorithm's input size?

Answer

Number of elements in the input array/list

Status : Wrong ***Marks : 0/1***

15. The concept of "Orders of Growth" in algorithm analysis refers to:

Answer

The function that describes the algorithm's efficiency

Status : Correct ***Marks : 1/1***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 2_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. What is a non-recursive algorithm?

Answer

An algorithm that does not use recursion

Status : Correct ***Marks : 1/1***

2. Which of the following is an example of a non-recursive sorting algorithm?

Answer

Bubble Sort

Status : Correct ***Marks : 1/1***

vtu27632

3. The time complexity of non-recursive algorithms is often expressed using:

Answer

All of the mentioned options

Status : Correct ***Marks : 1/1***

4. Which non-recursive algorithm is commonly used for searching in a sorted array by repeatedly dividing the search interval in half?

Answer

Binary Search

Status : Correct ***Marks : 1/1***

5. In non-recursive algorithms, iteration is commonly achieved through:

Answer

Loops

Status : Correct ***Marks : 1/1***

6. What is the output of the code?

```
#include <stdio.h>

int main() {
    int num = 2;
    do {
        printf("%d ", num);
        num *= 2;
    } while (num <= 8);
    return 0;
}
```

Answer

vtu27632

2 4 8

Status : Correct ***Marks : 1/1***

7. What is the output for the code?

```
#include <stdio.h>

void nonRecursiveAlgorithm(int n) {
    for (int i = 1; i <= n; i *= 2) {
        printf("%d ", i);
    }
}

int main() {
    nonRecursiveAlgorithm(8);
    return 0;
}
```

Answer

1 2 4 8

Status : Correct ***Marks : 1/1***

8. What is the output for the code?

```
#include <stdio.h>

void nonRecursiveFunction1(int n) {
    while (n > 0) {
        printf("%d ", n);
        n /= 2;
    }
}

int main() {
    int number = 80;
    nonRecursiveFunction1(number);
    return 0;
```

```
}
```

Answer

80 40 20 10 5 2 1

Status : Correct ***Marks : 1/1***

9. What will be the output for the following recursive code?

```
#include <stdio.h>

int power(int base, int exponent) {
    if (exponent == 0)
        return 1;
    else
        return base * power(base, exponent - 1);
}

int main() {
    int result = power(3, 2);
    printf("%d", result);
    return 0;
}
```

Answer

9

Status : Correct ***Marks : 1/1***

10. What will be the output for the following recursive code?

```
#include <stdio.h>

int num(int n, int rev) {
    if (n == 0) {
        return rev;
    } else {
        int digit = n % 10;
        rev = rev * 10 + digit;
```

```
    return num(n / 10, rev);
  }
}

int main() {
  int d = 12345;
  int rev = num(d, 0);
  printf("%d", rev);
  return 0;
}
```

Answer

54321

Status : Correct ***Marks : 1/1***

11. What will be the output for the following recursive code?

```
#include <stdio.h>

int function(int number) {
  if (number <= 0) {
    return 1;
  } else {
    return number * function(number - 1);
  }
}

int main() {
  int result;
  result = function(4);
  printf("%d", result);

  return 0;
}
```

Answer

24

Status : Correct ***Marks : 1/1***

12. What will be the output for the following recursive code?

```
#include <iostream>
using namespace std;

void print(int n) {
    if (n == 0)
        return;
    print(n / 2);
    cout << n % 2;
}

int main() {
    int num = 12;
    print(num);
    return 0;
}
```

Answer

1100

Status : Correct ***Marks : 1/1***

13. What will be the output for the following recursive code?

```
#include <stdio.h>

int function(int a, int b) {
    if (b == 1)
        return a;
    else
        return a + function(a, b - 1);
}

int main() {
    int result = function(2, 3);
    printf("%d", result);
    return 0;
}
```

Answer

6

Status : Correct ***Marks : 1/1***

14. What will be the output for the following recursive code?

```
#include <stdio.h>

int function(int a, int b) {
    if (b == 0)
        return 0;
    if (b == 1)
        return a;
    return a + function(a, b - 1);
}

int main() {
    int result = function(3, 8);
    printf("%d", result);
    return 0;
}
```

Answer

24

Status : Correct ***Marks : 1/1***

15. What will be the output for the following recursive code?

```
#include <iostream>
using namespace std;

int recursive(int n) {
    if (n <= 0)
        return 1;
    else
        return n + recursive(n - 1);
```

```
}

int main() {
    int result = recursive(5);
    cout << result;
    return 0;
}
```

Answer

16

Status : Correct ***Marks : 1/1***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 2_COD

Attempt : 1
Total Mark : 40
Marks Obtained : 20

Section 1 : Coding

1. Problem Statement

Given an integer n. The task is to find the first n Fibonacci Numbers.

Input Format

The input consists of a single integer n, representing how many Fibonacci terms to print.

Output Format

The output prints n space-separated Fibonacci numbers starting from 0.

Refer to the sample output for the formatting specifications.

vtu27632

Sample Test Case

Input: 3

Output: 0 1 1

Answer

```
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int a = 0, b = 1, next;

    // Print first n Fibonacci numbers
    for (int i = 1; i <= n; i++) {
        printf("%d ", a);
        next = a + b;
        a = b;
        b = next;
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Given a string s, check if it is a palindrome using recursion. A palindrome is a word, phrase, or sequence that reads the same backward as forward.

Input Format

The input consists of a single string s containing no spaces.

Output Format

The output prints "The string is a palindrome" if the string is symmetric.

Otherwise, prints "The string is not a palindrome".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: abba

Output: The string is a palindrome

Answer

```
#include <stdio.h>
#include <string.h>

// Recursive function
int isPalindrome(char str[], int start, int end) {
    if (start >= end)   // Base case
        return 1;

    if (str[start] != str[end])
        return 0;

    return isPalindrome(str, start + 1, end - 1);
}

int main() {
    char s[100];
    scanf("%s", s);

    int len = strlen(s);

    if (isPalindrome(s, 0, len - 1))
        printf("The string is a palindrome");
    else
        printf("The string is not a palindrome");

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Shilpa is learning about the Fibonacci sequence for her computer science class. She wants to generate the first N terms of the Fibonacci series.

Can you help Shilpa by writing a program that takes a number N and prints the first N terms of the Fibonacci series using recursion?

Input Format

The input consists of an integer N, representing the number of terms in the Fibonacci sequence that need to be printed.

Output Format

The output prints the first N Fibonacci numbers, separated by spaces.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
Output: 0 1 1 2 3 5

Answer

-

Status : Skipped ***Marks : 0/10***

4. Problem Statement

Ashish is preparing a mathematics assignment where he needs to calculate the factorial of a number. Since his teacher asked him to use recursion for this task, he plans to complete the method int factorial to solve it.

Help him to implement the task.

Input Format

The input consists of an integer num representing the number for which the

factorial is to be calculated.

Output Format

The output prints the factorial value of num.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
Output: 6

Answer

-

Status : - ***Marks : 0/10***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 2_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

In a kingdom far away, two types of soup are prepared daily — Soup A and Soup B. The royal chef always starts with n milliliters of each soup. Each time a servant is served, one of the following four serving operations is chosen at random (each with equal probability of 0.25):

Serve 100 ml of Soup A and 0 ml of Soup B

Serve 75 ml of Soup A and 25 ml of Soup B

Serve 50 ml of Soup A and 50 ml of Soup B

Serve 25 ml of Soup A and 75 ml of Soup B

The serving continues until either or both soups become empty. If the required soup amount for an operation exceeds the available quantity,

serve as much as possible (up to what remains).

You are to compute the probability that Soup A becomes empty first, plus half the probability that both soups become empty at the same time.

Special Note:

Since all operations serve soup in multiples of 25 ml, you must first scale n down to units of 25 ml before recursive processing:

Example

Sample Input 1

n = 50

Sample Output 2

0.625

Explanation

If we choose the first two operations, A will become empty first.

For the third operation, A and B will become empty at the same time.

For the fourth operation, B will become empty first.

So the total probability of A becoming empty first plus half the probability that A and B become empty at the same time, is 0.25 * (1 + 1 + 0.5 + 0) = 0.625.

Input Format

The input consists of an integer n, representing the total volume of the soup.

Output Format

The output prints the probability that soup A will be empty first, plus half the probability that A and B become empty at the same time.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 50

Output: 0.625

Answer

```
#include <stdio.h>

double solve(int a, int b)
{
   if (a <= 0 && b <= 0)
      return 0.5;
   if (a <= 0)
      return 1.0;
   if (b <= 0)
      return 0.0;

   return 0.25 * (
      solve(a - 4, b) +
      solve(a - 3, b - 1) +
      solve(a - 2, b - 2) +
      solve(a - 1, b - 3)
   );
}

int main()
{
   int n;
   scanf("%d", &n);

   int units = (n + 24) / 25;  // convert to units of 25 ml

   double result = solve(units, units);

   printf("%.3f", result);

   return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

In a unique team-building exercise, a company has decided to distribute a certain number of resources among its departments based on mathematical powers. The company has x resources that need to be distributed such that each department receives a different power of an integer. Specifically, each department i receives n resources, where n is a given power.

George, the resource manager, needs to find all possible ways to distribute exactly x resources using the powers of integers starting from 1. Each integer's power can only be used once.

Write a program to help George determine the number of ways to distribute x resources in this manner using a recursive manner.

Example 1

Input:

10

2

Output:

1

Explanation:

x = 10

n = 2

10 = 12 + 32, hence we have only 1 possibility.

Example 2

Input:

100

2

vtu27632

Output:

3

Explanation:

x = 100

n = 2

100 = 102 OR 62 + 82 OR 12 + 32 + 42 + 52 + 72, hence total 3 possibilities.

Input Format

The first line of input consists of the integer x, representing the total number of resources.

The second line consists of the integer n, representing the power to which the integers are raised.

Output Format

The output should be a single integer representing the number of ways to distribute exactly x resources.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 100
2
Output: 3

Answer

```
#include <stdio.h>
#include <math.h>

int countWays(int x, int n, int num)
{
   int power = pow(num, n);

   if (power == x)
      return 1;
```

```
    if (power > x)
        return 0;

    return countWays(x - power, n, num + 1) + countWays(x, n, num + 1);
}

int main()
{
    int x, n;

    scanf("%d", &x);
    scanf("%d", &n);

    printf("%d", countWays(x, n, 1));

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

In a small research lab, a programmer named Arin is analyzing binary data to detect system flags stored as set bits in an integer. One day Arin receives an integer and must determine how many bits are set to 1 in its binary representation.

Write a program to ensure that this task is done so Arin can continue validating the system's binary logs. The objective is to count all set bits in the given number using any valid approach.

Function specification: countSetBits(int n)

Input Format

The input consists of a single positive integer n.

Output Format

The output prints a single integer representing the count of set bits (1s) in the

binary representation of n.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 21
Output: 3

Answer

```
#include <stdio.h>

int countSetBits(int n)
{
    int count = 0;

    while(n > 0)
    {
        count += (n & 1);
        n = n >> 1;
    }

    return count;
}

int main()
{
    int n;
    scanf("%d", &n);

    printf("%d", countSetBits(n));

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Given a square matrix of size n×n, rotate the elements along each layer (or boundary) of the matrix by one position in a clockwise direction. The rotation should be performed layer by layer, starting from the outermost layer and proceeding inward.

Examples:

Input 2:

3 3

1 2 3

4 5 6

7 8 9

Output 2:

4 1 2

7 5 3

8 9 6

Explanation:

For a clockwise boundary rotation by one step:

We start with the outermost layer (there's only one layer in a 3×3 matrix)

We save the top-left element (1)

Move left edge upward: 4 1, 7 4

Move bottom edge leftward: 8 7, 9 8

Move right edge downward: 6 9, 3 6

Move top edge rightward: 2 3

Place the saved element (1) in the second position of the top row, so 1 2

Input Format

The first line contains two integers R and C — the number of rows and columns in the matrix.

vtu27632

The next R lines each contain C integers, representing the elements of the matrix.

Output Format

The output displays the rotated matrix after performing the clockwise boundary rotation.

Refer to the sample input and output for formatting specifications.

Sample Test Case

Input: 4 4
1 2 3 4
5 6 7 8
9 10 11 12
13 14 15 16

Output: 5 1 2 3
9 10 6 4
13 11 7 8
14 15 16 12

Answer

```
#include <stdio.h>

int main() {
    int n;
    scanf("%d %d", &n, &n);  // square matrix, rows = cols

    int matrix[n][n];

    // Input matrix
    for(int i = 0; i < n; i++)
        for(int j = 0; j < n; j++)
            scanf("%d", &matrix[i][j]);

    // Number of layers
    int layers = n / 2;

    for(int layer = 0; layer < layers; layer++) {
        int first = layer;
```

```
        int last = n - 1 - layer;

        int temp = matrix[first][first]; // save top-left

        // Move left column up
        for(int i = first; i < last; i++)
            matrix[i][first] = matrix[i+1][first];

        // Move bottom row left
        for(int j = first; j < last; j++)
            matrix[last][j] = matrix[last][j+1];

        // Move right column down
        for(int i = last; i > first; i--)
            matrix[i][last] = matrix[i-1][last];

        // Move top row right
        for(int j = last; j > first + 1; j--)
            matrix[first][j] = matrix[first][j-1];

        matrix[first][first+1] = temp; // place saved element
    }

    // Print rotated matrix
    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++)
            printf("%d ", matrix[i][j]);
        printf("\n");
    }

    return 0;
}
```

Status : Correct **Marks : 10/10**

5. Problem Statement

Given a 2D matrix of size ROW × COL, print all elements of the matrix in diagonal order.

Diagonal Order Definition:

Start from the first element at position (0,0).Traverse all diagonals starting from the leftmost column going downward, then continue with diagonals starting from the bottom row going rightward.Within each diagonal, print elements from the top-right corner to bottom-left corner.

Example:

Input matrix

5 4

1 2 3 4

5 6 7 8

9 10 11 12

13 14 15 16

17 18 19 20

Diagonal printing of the above matrix is

1

5 2

9 6 3

13 10 7 4

17 14 11 8

18 15 12

19 16

20

Input Format

The first line of input contains two integers, ROW and COL.

The next ROW lines each contain COL space-separated integers

Output Format

The output consists of multiple lines, one for each diagonal. Each line contains the matrix elements of that diagonal in the order from top-right to bottom-left,

vtu27632

separated by spaces.

Refer to the sample input and output for formatting specifications.

Sample Test Case

Input: 5 4
1 2 3 4
5 6 7 8
9 10 11 12
13 14 15 16
17 18 19 20

Output: 1
5 2
9 6 3
13 10 7 4
17 14 11 8
18 15 12
19 16
20

Answer

```
#include <stdio.h>

int main() {
    int ROW, COL;
    scanf("%d %d", &ROW, &COL);

    int matrix[ROW][COL];
    for(int i = 0; i < ROW; i++)
        for(int j = 0; j < COL; j++)
            scanf("%d", &matrix[i][j]);

    // Diagonals starting from first column
    for(int i = 0; i < ROW; i++) {
        int r = i, c = 0;
        while(r >= 0 && c < COL) {
            printf("%d ", matrix[r][c]);
            r--;
            c++;
```

```
    }
    printf("\n");
  }

  // Diagonals starting from last row (excluding first column)
  for(int j = 1; j < COL; j++) {
    int r = ROW - 1, c = j;
    while(r >= 0 && c < COL) {
      printf("%d ", matrix[r][c]);
      r--;
      c++;
    }
    printf("\n");
  }

  return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 2_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

Manoj loves puzzles and recently encountered an interesting mathematical challenge. He needs to find how many ways he can express a number x as the sum of distinct positive integers raised to the power of n. For example, for a given number x, he wants to find all possible ways to represent it as a sum of distinct powers of integers.

Help him implement this task.

Example 1

Input:

10
2

vtu27632

Output:

1

Explanation:

x = 10

n = 2

10 = 12 + 32, hence we have only 1 possibility.

Example 2

Input:

100

2

Output:

3

Explanation:

x = 100

n = 2

100 = 102 OR 62 + 82 OR 12 + 32 + 42 + 52 + 72, hence total 3 possibilities.

Function Specifications: getAllWays(int, int, int)

Input Format

The first line of input consists of an integer x, representing the target sum.

The second line of input consists of an integer n, representing the power to which the integers are raised.

Output Format

The first line of output prints: The total number of ways to express x as the sum of distinct powers.

vtu27632

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 100
2

Output: 3

Answer

```
#include <stdio.h>
#include <math.h>

int getAllWays(int x, int n, int num)
{
    int power = pow(num, n);

    if (power > x)
        return 0;

    if (power == x)
        return 1;

    // Include current number + Exclude current number
    return getAllWays(x - power, n, num + 1) + getAllWays(x, n, num + 1);
}

int main()
{
    int x, n;

    scanf("%d", &x);
    scanf("%d", &n);

    int result = getAllWays(x, n, 1);

    printf("%d", result);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Given an integer array of coins of size N representing different types of currency and an integer sum M. The task is to find the number of ways to make the sum by using different combinations from the coins array, using recursion.

Function Specifications: int countWays(int [], int , int)

Input Format

The first line of input consists of the number of coins N.

The second line consists of N integers denoting the coin denominations.

The third line consists of the integer sum M to be produced with those coins.

Output Format

The output displays the number of ways to make the sum by using different combinations from the coins array.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3
1 2 3
4
Output: 4

Answer

```
#include <stdio.h>

int countWays(int coins[], int n, int sum)
{
   // If sum becomes 0, one solution found
   if (sum == 0)
      return 1;
```

```
    // If sum becomes negative or no coins left
    if (sum < 0 || n <= 0)
        return 0;

    // Include the coin OR exclude the coin
    return countWays(coins, n, sum - coins[n-1])
         + countWays(coins, n-1, sum);
}

int main()
{
    int n, sum;

    scanf("%d", &n);

    int coins[n];
    for(int i = 0; i < n; i++)
        scanf("%d", &coins[i]);

    scanf("%d", &sum);

    int result = countWays(coins, n, sum);

    printf("%d", result);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Meredith is a cashier at a local convenience store. To improve the efficiency of making change for customers, Meredith wants to develop a small program that calculates the number of different ways she can give change using a given set of coin denominations. This will help her quickly figure out the number of ways to make change for a particular amount of money using the available coins.

Meredith has a list of coin denominations and a specific amount of money

for which she needs to provide change. She wants to write a program to determine the number of possible ways to achieve the given amount using the available denominations. This will help her understand all possible combinations without having to manually calculate them each time.

Input Format

The first line contains an integer n, the number of different coin denominations.

The second line contains n space-separated integers representing the coin denominations.

The third line contains an integer m, the target amount of money for which Meredith needs to make change.

Output Format

The output displays the number of ways to make the sum by using different combinations from the coins array.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3
1 2 3
4
Output: 4

Answer

```
#include <stdio.h>

int countWays(int coins[], int n, int sum)
{
   if (sum == 0)
      return 1;

   if (sum < 0)
      return 0;

   if (n <= 0 && sum > 0)
```

```
    return 0;

    return countWays(coins, n, sum - coins[n-1]) +
           countWays(coins, n-1, sum);
}

int main()
{
    int n, m;

    scanf("%d", &n);

    int coins[n];
    for(int i = 0; i < n; i++)
       scanf("%d", &coins[i]);

    scanf("%d", &m);

    printf("%d", countWays(coins, n, m));

    return 0;
}
```

Status : Correct **Marks : 10/10**

4. Problem Statement

In a small research lab, a programmer named Arin is analyzing binary data to detect system flags stored as set bits in an integer. One day Arin receives an integer and must determine how many bits are set to 1 in its binary representation.

Write a program to ensure that this task is done so Arin can continue validating the system's binary logs. The objective is to count all set bits in the given number using any valid approach.

Function specification: countSetBits(int n)

Input Format

The input consists of a single positive integer n.

Output Format

The output prints a single integer representing the count of set bits (1s) in the binary representation of n.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 21

Output: 3

Answer

```
#include <stdio.h>

int countSetBits(int n)
{
   int count = 0;

   while(n > 0)
   {
      if(n % 2 == 1)
         count++;

      n = n / 2;
   }

   return count;
}

int main()
{
   int n;
   scanf("%d", &n);

   printf("%d", countSetBits(n));

   return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

Raju is a computer graphics designer. He works around matrices with ease. His friend challenged him to rotate an M x M matrix clockwise with an angle of 90 degrees.

However, Raju was given a constraint that he must not use any additional 2D matrix for doing the above-mentioned task. The rotation must be done in place, which means Raju has to modify the given input matrix directly.

Example: 1

Input:

[[1,2,3],[4,5,6],[7,8,9]]

Output:

[[7,4,1],[8,5,2],[9,6,3]]

Example: 2

Input:

matrix = [[5,1,9,11],[2,4,8,10],[13,3,6,7],[15,14,12,16]]

Output:

[[15,13,2,5],[14,3,4,1],[12,6,8,9],[16,7,10,11]]

Input Format

The first line of the input is a single integer value for the size of the row and column, M.

The next M lines of the input are the matrix elements, each containing M integers representing the elements of the matrix.

Output Format

The output displays the rotated matrix, with each row printed on a new line.

Refer to the sample input and output for formatting specifications.

Sample Test Case

Input: 3
1 2 3
4 5 6
7 8 9
Output: 7 4 1
8 5 2
9 6 3

Answer

```
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int matrix[n][n];

    // Input matrix
    for(int i = 0; i < n; i++)
    {
        for(int j = 0; j < n; j++)
        {
            scanf("%d", &matrix[i][j]);
        }
    }

    // Step 1: Transpose the matrix
    for(int i = 0; i < n; i++)
    {
        for(int j = i + 1; j < n; j++)
        {
```

```
        int temp = matrix[i][j];
        matrix[i][j] = matrix[j][i];
        matrix[j][i] = temp;
    }
}

// Step 2: Reverse each row
for(int i = 0; i < n; i++)
{
    for(int j = 0; j < n / 2; j++)
    {
        int temp = matrix[i][j];
        matrix[i][j] = matrix[i][n - j - 1];
        matrix[i][n - j - 1] = temp;
    }
}

// Print rotated matrix
for(int i = 0; i < n; i++)
{
    for(int j = 0; j < n; j++)
    {
        printf("%d ", matrix[i][j]);
    }
    printf("\n");
}

return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 3_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 11

Section 1 : MCQ

1. What is the primary characteristic of the Brute Force approach to solving the Closest-Pair problem?

Answer

Computing the distance between every pair of points and selecting the minimum

Status : Correct ***Marks : 1/1***

2. In the brute force convex hull algorithm (Jarvis March/Gift Wrapping), what is the next point selected after identifying a point on the hull?

Answer

The point that creates the smallest counterclockwise turn relative to the current point

vtu27632

Status : Correct ***Marks : 1/1***

3. In C, if you have a structure `Point { int x; int y; };`, what is the correct formula to calculate the squared distance between two points `p1` and `p2` to avoid unnecessary floating-point operations?

Answer

`(p1.x - p2.x)*(p1.x - p2.x) + (p1.y - p2.y)*(p1.y - p2.y)`

Status : Correct ***Marks : 1/1***

4. Given an array of `n` points in a 2D plane, what is the exact time complexity of the Brute Force Closest-Pair algorithm?

Answer

O(n^2)

Status : Correct ***Marks : 1/1***

5. Which geometric test is essential for determining if a point lies to the left or right of a directed line in the Convex Hull brute force algorithm?

Answer

The Orientation test (Cross Product)

Status : Correct ***Marks : 1/1***

6. If two points are exactly the same in the input set for the Closest Pair problem, what will the brute force algorithm correctly return?

Answer

A distance of 0

Status : Correct ***Marks : 1/1***

7. In the brute force algorithm to check if a set of points is in a convex

position, the sign of the cross product indicates:

Answer

The direction of the turn (Left or Right)

Status : Correct ***Marks : 1/1***

8. Given 5 points in C where all x-coordinates are identical, what is the result of the brute force closest pair algorithm?

Answer

0

Status : Wrong ***Marks : 0/1***

9. What is the worst-case time complexity of the Brute Force algorithm for checking if given points form a convex polygon?

Answer

O(n²)

Status : Correct ***Marks : 1/1***

10. In a C program solving the Closest Pair problem via brute force, which nested loop structure correctly avoids redundant calculations (i.e., doesn't calculate distance between A,B and B,A)?

Answer

`for(i=0; i

Status : Wrong ***Marks : 0/1***

11. When implementing the Brute Force Closest Pair algorithm in C, what is the minimal number of distance calculations required if there are exactly 3 points?

Answer

3

Status : Correct ***Marks : 1/1***

12. In the brute force method for finding the convex hull (checking all edges), an edge (i, j) is part of the convex hull if:

Answer

All other points lie on one side of the line through i and j

Status : Correct ***Marks : 1/1***

13. Which of the following best describes "collinearity" in the context of the Convex Hull problem when using brute force?

Answer

Points having the same x-coordinate

Status : Wrong ***Marks : 0/1***

14. What is a significant disadvantage of the Brute Force Convex Hull algorithm compared to Divide and Conquer algorithms?

Answer

It is O(n$^{?}$) in the worst case and O(n$^{?}$) in the best case (for Jarvis March)

Status : Correct ***Marks : 1/1***

15. Which of the following correctly represents the Euclidean distance between two points (x1,y1) and (x2,y2) in C?

Answer

`sqrt(pow(x2 - x1, 2) + pow(y2 - y1, 2))`

Status : Wrong ***Marks : 0/1***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 3_COD

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

You are given a set of N points on a 2D plane. Your task is to find the distance between the closest pair of points.

Write a program that takes as input the number of points N, followed by the x and y coordinates of each point. The program should output the distance between the closest pair of points, rounded to two decimal places.

Input Format

The first line of input consists of an integer N, representing the number of points.

The following N lines represent the coordinate points x and y, separated by space.

Output Format

vtu27632

The output prints a single floating-point number representing the distance between the closest pair of points, rounded to two decimal places.

Sample Test Case

Input: 3
2 3
12 30
40 50

Output: 28.79

Answer

```
#include <stdio.h>
#include <math.h>
#include <float.h> // for DBL_MAX

int main() {
    int N;
    scanf("%d", &N);

    int x[N], y[N];

    // Read coordinates
    for (int i = 0; i < N; i++) {
        scanf("%d %d", &x[i], &y[i]);
    }

    double minDistance = DBL_MAX;

    // Compare all pairs
    for (int i = 0; i < N; i++) {
        for (int j = i + 1; j < N; j++) {
            double dx = x[i] - x[j];
            double dy = y[i] - y[j];
            double distance = sqrt(dx * dx + dy * dy);
            if (distance < minDistance) {
                minDistance = distance;
            }
        }
    }

    // Print result rounded to 2 decimal places
```

```
    printf("%.2f\n", minDistance);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Ishita is working on a mapping application that helps locate the nearest landmarks on a 2D map. Each landmark is represented by its (x, y) coordinate. Her task is to find out the shortest distance between any two landmarks from the given list.

Help Ishita write a program that calculates the distance between the closest pair of points (landmarks) on the map.

Input Format

The first line of input contains an integer N representing the number of landmarks.

The next N lines contain two space-separated integers, representing the x and y coordinates of each landmark.

Output Format

The output prints a single floating-point number representing the distance between any two landmarks rounded to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
5 7
12 32
21 23
43 65

Output: 12.73

Answer

```
// You are using GCC#include <stdio.h>
#include <math.h>
#include <float.h>

int main() {
    int N;
    scanf("%d", &N);

    int x[N], y[N];

    // Read coordinates of landmarks
    for (int i = 0; i < N; i++) {
        scanf("%d %d", &x[i], &y[i]);
    }

    double minDistance = DBL_MAX;

    // Compute distance between all pairs of points
    for (int i = 0; i < N; i++) {
        for (int j = i + 1; j < N; j++) {
            double dx = x[i] - x[j];
            double dy = y[i] - y[j];
            double distance = sqrt(dx * dx + dy * dy);
            if (distance < minDistance) {
                minDistance = distance;
            }
        }
    }

    // Print the shortest distance rounded to 2 decimal places
    printf("%.2f\n", minDistance);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Ragu, an aspiring computer scientist, is currently learning about the concept of finding the closest pair of points in a plane. He wants to test his skills by solving a programming challenge related to this concept.

Given a set of points in a 2D plane, Ragu needs to find the closest pair of points and calculate their Euclidean distance.

Input Format

The first line of input consists of an integer N, representing the number of points in the plane.

The following N lines, each consisting of two space-separated real numbers x and y, represent the coordinates of a point.

Output Format

The first line of output prints the coordinates of the two points forming the closest pair in the below format:

"Closest pair of points: (x1, y1) and (x2, y2)"

The second line prints "Distance: <distance>" representing the Euclidean distance between the closest pair of points, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
0 3
1 1
10 18
4 9

Output: Closest pair of points: (0, 3) and (1, 1)
Distance: 2.24

Answer

```
// You are using GCC#include <stdio.h>
#include <math.h>
```

```
#include <float.h>

int main() {
    int N;
    scanf("%d", &N);

    double x[N], y[N];

    // Read coordinates
    for (int i = 0; i < N; i++) {
        scanf("%lf %lf", &x[i], &y[i]);
    }

    double minDistance = DBL_MAX;
    int p1 = 0, p2 = 1; // indices of the closest pair

    // Brute-force check all pairs
    for (int i = 0; i < N; i++) {
        for (int j = i + 1; j < N; j++) {
            double dx = x[i] - x[j];
            double dy = y[i] - y[j];
            double distance = sqrt(dx * dx + dy * dy);
            if (distance < minDistance) {
                minDistance = distance;
                p1 = i;
                p2 = j;
            }
        }
    }

    // Print the closest pair
    printf("Closest pair of points: (%.0lf, %.0lf) and (%.0lf, %.0lf)\n",
           x[p1], y[p1], x[p2], y[p2]);

    // Print the distance rounded to 2 decimal places
    printf("Distance: %.2lf\n", minDistance);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Ragu, a passionate computer science student, is exploring geometry problems to sharpen his algorithmic thinking. Today, he challenges himself to determine the two closest points among a set of 2D coordinates.

Ragu must find the closest pair of points from the given set and compute the Euclidean distance between them with high precision. He also wants the output to display which two points are the closest, formatted clearly.

Input Format

The first line of input contains an integer N representing the number of points in the 2D plane.

The next N lines each contain two space-separated real numbers x and y representing the coordinates of each point.

Output Format

The first line of output prints the coordinates of the two points forming the closest pair in the below format:

"Closest pair of points: (x1, y1) and (x2, y2)"

The second line prints "Distance: <distance>" representing the Euclidean distance between the closest pair of points, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
1 2
3 4
1 0
6 8
2 3
Output: Closest pair of points: (1, 2) and (2, 3)
Distance: 1.41

vtu27632

Answer

```
// You are using GCC#include <stdio.h>
#include <math.h>
#include <float.h>

int main() {
    int N;
    scanf("%d", &N);

    double x[N], y[N];

    // Read coordinates of points
    for (int i = 0; i < N; i++) {
        scanf("%lf %lf", &x[i], &y[i]);
    }

    double minDistance = DBL_MAX;
    int p1 = 0, p2 = 1; // indices of closest pair

    // Check all pairs
    for (int i = 0; i < N; i++) {
        for (int j = i + 1; j < N; j++) {
            double dx = x[i] - x[j];
            double dy = y[i] - y[j];
            double distance = sqrt(dx * dx + dy * dy);
            if (distance < minDistance) {
                minDistance = distance;
                p1 = i;
                p2 = j;
            }
        }
    }

    // Print the closest pair of points
    printf("Closest pair of points: (%.0lf, %.0lf) and (%.0lf, %.0lf)\n",
           x[p1], y[p1], x[p2], y[p2]);

    // Print the distance rounded to 2 decimal places
    printf("Distance: %.2lf\n", minDistance);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 3_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 35

Section 1 : Coding

1. Problem Statement

Adhi is learning about computational geometry and has come across the concept of a Convex Hull.

A Convex Hull is a convex polygon that encompasses a set of points in a two-dimensional plane, such that no point lies within the polygon's interior.

Adhi is particularly interested in determining whether a given point lies inside or outside the convex hull formed by a set of points.

Help Adhi by writing a program that checks whether a given point lies inside or outside the convex hull formed by a set of points.

Example

vtu27632

N = 7,

Points: {(1, 1), (2, 1), (3, 1), (4, 1), (4, 2), (4, 3), (4, 4)},

Query: X = 3, Y = 2

Below is the image of the plotting of the given points:

The query (3, 2) lies inside the Convex Hull.

Input Format

The first line of input consists of an integer N, representing the number of points in the set.

The following N lines, each containing two integers x and y, represent the coordinates of the points in the set.

The last line consists of two integers px and py, representing the coordinates of the test point.

Output Format

The output prints whether the given test points lie inside or outside the Convex Hull.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 7
1 1
2 1
3 1
4 1
4 2
4 3
4 4
3 2

vtu27632

Output: The point (3, 2) lies inside the Convex Hull.

Answer

```
#include <stdio.h>
#include <stdlib.h>

typedef struct {
    int x, y;
} Point;

// Cross product of OA and OB vectors
int cross(Point O, Point A, Point B) {
    return (A.x - O.x) * (B.y - O.y) - (A.y - O.y) * (B.x - O.x);
}

// Compare function for qsort
int compare(const void* a, const void* b) {
    Point* p1 = (Point*)a;
    Point* p2 = (Point*)b;
    if (p1->x != p2->x) return p1->x - p2->x;
    return p1->y - p2->y;
}

// Compute convex hull using Andrew's monotone chain
int convexHull(Point* P, int n, Point* hull) {
    qsort(P, n, sizeof(Point), compare);
    int k = 0;

    // Lower hull
    for (int i = 0; i < n; i++) {
        while (k >= 2 && cross(hull[k-2], hull[k-1], P[i]) <= 0) k--;
        hull[k++] = P[i];
    }

    // Upper hull
    int t = k + 1;
    for (int i = n-2; i >= 0; i--) {
        while (k >= t && cross(hull[k-2], hull[k-1], P[i]) <= 0) k--;
        hull[k++] = P[i];
    }
```

```
    return k-1; // Number of points in hull
}

// Check if point P is inside convex polygon (hull of m points)
int pointInsideConvexHull(Point* hull, int m, Point P) {
    for (int i = 0; i < m; i++) {
        Point A = hull[i];
        Point B = hull[(i+1)%m];
        if (cross(A, B, P) < 0) return 0; // Outside
    }
    return 1; // Inside or on edge
}

int main() {
    int N;
    scanf("%d", &N);

    Point points[N];
    for (int i = 0; i < N; i++) {
        scanf("%d %d", &points[i].x, &points[i].y);
    }

    Point query;
    scanf("%d %d", &query.x, &query.y);

    Point hull[2*N]; // Hull can have at most 2N points
    int hullSize = convexHull(points, N, hull);

    if (pointInsideConvexHull(hull, hullSize, query)) {
        printf("The point (%d, %d) lies inside the Convex Hull.\n", query.x, query.y);
    } else {
        printf("The point (%d, %d) lies outside the Convex Hull.\n", query.x, query.y);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement:

Olivia, a city planner, is designing a recreational area surrounded by specific landmarks. To ensure balance in the design, Olivia needs to calculate the weighted centroid of the boundary formed by these landmarks using the convex hull.

Your task is to compute the convex hull and determine the weighted centroid of its vertices.

Note:

MAXN (100000): The maximum capacity for both the points and hull arrays, allowing storage of up to 100,000 points each.1e-9 is the threshold for floating-point comparisons.

Example:

Input:

6

0 0

4 0

4 3

0 3

2 1

3 2

Output:

Weighted Centroid: 2.00 1.50

Explanation:

Input Points: (0, 0), (2, 0), (2, 2), (0, 2), (1, 1), (3, 1).

Pivot Selection: The point with the lowest y-coordinate (and leftmost in case of a tie) is selected as the pivot: (0, 0).

Sorting by Polar Angle: Points are sorted by the polar angle relative to the pivot: (0, 0), (2, 0), (3, 1), (2, 2), (0, 2).

vtu27632

Convex Hull Construction: Using counterclockwise turns, the points forming the convex hull are: (0, 0), (2, 0), (3, 1), (2, 2), (0, 2).

Input Format

The first line contains an integer N, representing the number of points.

The next N lines each contain two floating-point numbers x and y, representing the coordinates of the points.

Output Format

The output prints the coordinates of the weighted centroid of the convex hull, formatted to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
0 0
2 0
2 2
0 2
1 1
Output: Weighted Centroid: 1.00 1.00

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>
#include <math.h>

#define MAXN 100000
#define EPS 1e-9

typedef struct {
   double x, y;
} Point;

Point points[MAXN];
```

```
Point hull[MAXN];

// Cross product of OA and OB
double cross(Point O, Point A, Point B) {
    return (A.x - O.x)*(B.y - O.y) - (A.y - O.y)*(B.x - O.x);
}

// Compare function for qsort (x first, then y)
int compare(const void* a, const void* b) {
    Point* p1 = (Point*)a;
    Point* p2 = (Point*)b;
    if (fabs(p1->x - p2->x) > EPS) return (p1->x < p2->x) ? -1 : 1;
    if (fabs(p1->y - p2->y) > EPS) return (p1->y < p2->y) ? -1 : 1;
    return 0;
}

// Compute convex hull using Andrew's Monotone Chain
int convexHull(int n) {
    qsort(points, n, sizeof(Point), compare);
    int k = 0;

    // Lower hull
    for (int i = 0; i < n; i++) {
        while (k >= 2 && cross(hull[k-2], hull[k-1], points[i]) <= EPS) k--;
        hull[k++] = points[i];
    }

    // Upper hull
    int t = k + 1;
    for (int i = n-2; i >= 0; i--) {
        while (k >= t && cross(hull[k-2], hull[k-1], points[i]) <= EPS) k--;
        hull[k++] = points[i];
    }

    return k-1; // Hull size
}

// Compute centroid of convex polygon
void computeCentroid(int m, double* cx, double* cy) {
    double area = 0;
    double Cx = 0, Cy = 0;
    for (int i = 0; i < m; i++) {
```

```
        Point p1 = hull[i];
        Point p2 = hull[(i+1)%m];
        double crossProd = p1.x * p2.y - p2.x * p1.y;
        area += crossProd;
        Cx += (p1.x + p2.x) * crossProd;
        Cy += (p1.y + p2.y) * crossProd;
    }
    area /= 2.0;
    Cx /= (6.0 * area);
    Cy /= (6.0 * area);
    *cx = Cx;
    *cy = Cy;
}

int main() {
    int N;
    scanf("%d", &N);

    for (int i = 0; i < N; i++) {
        scanf("%lf %lf", &points[i].x, &points[i].y);
    }

    int hullSize = convexHull(N);

    double cx, cy;
    computeCentroid(hullSize, &cx, &cy);

    printf("Weighted Centroid: %.2lf %.2lf\n", cx, cy);

    return 0;
}
```

Status : Partially correct ***Marks : 6/10***

3. Problem Statement:

Gwen, a city planner, is designing a new park and needs to calculate the perimeter of the park's boundary. She has the coordinates of key boundary points and wants to find the minimum perimeter that encloses all these points.

Using the convex hull, Gwen needs help in computing both the boundary and its perimeter.

Note:

points[100000]: An array that can store up to 100,000 input points.hull[100000]: An array that can store up to 100,000 points on the convex hull.1e-9: A threshold for floating-point comparisons to handle precision issues.

Example

Input:

6

0.0 0.0

3.0 0.0

3.0 2.0

1.0 2.0

0.0 2.0

2.0 1.0

Output:

Convex Hull:

0 0

3 0

3 2

0 2

Perimeter: 10.00

Explanation:

Input Points: (0.0, 0.0), (3.0, 0.0), (3.0, 2.0), (1.0, 2.0), (0.0, 2.0), (2.0, 1.0).

Convex Hull Construction:

vtu27632

Pivot: Start with the lowest point, (0, 0).Sorted by Polar Angle: The points are sorted, and counterclockwise turns are included in the hull.Convex Hull Points: (0, 0), (3, 0), (3, 2), (0, 2).Perimeter Calculation:

Distances between consecutive hull points:(0, 0)-(3, 0): 3.00, (3, 0)-(3, 2): 2.00, (3, 2)-(0, 2): 3.00, (0, 2)-(0, 0): 2.00.Total Perimeter: 10.00.

Input Format

The first line contains an integer N, representing the number of points.

The next N lines each contain two space separated decimal values x and y, representing the coordinates of the points.

Output Format

The first line prints "Convex Hull:" followed by the coordinates of the points on the convex hull, each on a new line, in counterclockwise order.

The last line prints the "Perimeter: ", followed by the total perimeter of the convex hull, formatted to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
0.0 0.0
3.0 0.0
3.0 2.0
1.0 2.0
0.0 2.0
2.0 1.0
Output: Convex Hull:
0 0
3 0
3 2
0 2
Perimeter: 10.00

Answer

```
#include <stdio.h>
```

```
#include <math.h>
#include <stdlib.h>

#define MAX 100000
#define EPS 1e-9

typedef struct {
    double x, y;
} Point;

Point points[MAX], hull[MAX];
Point pivot;

// Function to swap two points
void swap(Point *a, Point *b) {
    Point temp = *a;
    *a = *b;
    *b = temp;
}

// Distance squared (for sorting)
double distSq(Point a, Point b) {
    return (a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y - b.y);
}

// Orientation: returns 0 -> collinear, 1 -> clockwise, 2 -> counterclockwise
int orientation(Point a, Point b, Point c) {
    double val = (b.y - a.y)*(c.x - b.x) - (b.x - a.x)*(c.y - b.y);
    if (fabs(val) < EPS) return 0;
    return (val > 0) ? 1 : 2;
}

// Compare function for qsort (polar angle)
int compare(const void *vp1, const void *vp2) {
    Point *p1 = (Point *)vp1;
    Point *p2 = (Point *)vp2;

    int o = orientation(pivot, *p1, *p2);
    if (o == 0)
        return (distSq(pivot, *p1) < distSq(pivot, *p2)) ? -1 : 1;

    return (o == 2) ? -1 : 1;
```

```
}

// Distance between two points
double distance(Point a, Point b) {
    return sqrt(distSq(a, b));
}

int main() {
    int n;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%lf %lf", &points[i].x, &points[i].y);
    }

    // Step 1: Find pivot (lowest y, then lowest x)
    int min = 0;
    for (int i = 1; i < n; i++) {
        if (points[i].y < points[min].y ||
            (fabs(points[i].y - points[min].y) < EPS && points[i].x < points[min].x)) {
            min = i;
        }
    }

    swap(&points[0], &points[min]);
    pivot = points[0];

    // Step 2: Sort by polar angle
    qsort(&points[1], n - 1, sizeof(Point), compare);

    // Step 3: Build convex hull
    int m = 0;
    hull[m++] = points[0];
    hull[m++] = points[1];

    for (int i = 2; i < n; i++) {
        while (m > 1 && orientation(hull[m - 2], hull[m - 1], points[i]) != 2) {
            m--;
        }
        hull[m++] = points[i];
    }
```

```
    // Step 4: Print convex hull
    printf("Convex Hull:\n");
    for (int i = 0; i < m; i++) {
        printf("%.0lf %.0lf\n", hull[i].x, hull[i].y);
    }

    // Step 5: Calculate perimeter
    double perimeter = 0.0;
    for (int i = 0; i < m; i++) {
        perimeter += distance(hull[i], hull[(i + 1) % m]);
    }

    printf("Perimeter: %.2lf\n", perimeter);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement:

Maria, a wildlife researcher, is studying the distribution of endangered species in a forest. She has mapped several points that represent observation locations inside the forest.

Maria wants to identify the K points that are the farthest from the forest's outer boundary, represented by a convex hull formed by a set of points. These points represent key observations, and she needs to rank them by their distance to the outer boundary of the forest.

Help Maria compute the convex hull and find the K farthest points from the forest boundary.

Note:

MAXN (100000): Maximum number of points for points and hull arrays.1e-9:Threshold for floating-point equality checks to handle precision errors.1e-12: Threshold to detect degenerate (zero-length) segments.1e30:Initial large value for minimum distance calculations.

Example:

Input:

7 3

0 0

4 0

4 4

0 4

2 2

1 2

3 2

Output:

2 2

3 2

1 2

Explanation:

Convex Hull Points: Using Graham's Scan, the convex hull is: (0, 0), (4, 0), (4, 4), (0, 4).

Distance to Hull: Distances of all points to the convex hull boundary are computed.

Top 3 Farthest Points: Sorted by descending distance, the top 3 points are (2, 2), (3, 2), (1, 2).

Input Format

The first line contains two integers N and K, representing the number of points and the number of farthest points to find, respectively.

The next N lines each contain two integers x and y, representing the coordinates of the points.

Output Format

vtu27632

The output prints K lines, each containing two integers x and y, representing the coordinates of the K farthest points from the convex hull boundary. Print the points in descending order of their distances to the boundary.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7 3
0 0
4 0
4 4
0 4
2 2
1 2
3 2

Output: 2 2
3 2
1 2

Answer

```
#include <stdio.h>
#include <stdlib.h>
#include <math.h>

#define MAXN 100000
#define EPS 1e-9
#define INF 1e30

typedef struct {
   double x, y;
} Point;

Point points[MAXN], hull[MAXN];
int n, k;

// Distance squared
double distSq(Point a, Point b) {
   return (a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y - b.y);
}
```

```
// Distance
double dist(Point a, Point b) {
    return sqrt(distSq(a, b));
}

// Orientation
int orientation(Point a, Point b, Point c) {
    double val = (b.y - a.y)*(c.x - b.x) - (b.x - a.x)*(c.y - b.y);
    if (fabs(val) < EPS) return 0;
    return (val > 0) ? 1 : 2;
}

// Global pivot
Point pivot;

// Compare for sorting
int cmp(const void *a, const void *b) {
    Point *p1 = (Point *)a;
    Point *p2 = (Point *)b;

    int o = orientation(pivot, *p1, *p2);
    if (o == 0)
        return (distSq(pivot, *p1) < distSq(pivot, *p2)) ? -1 : 1;
    return (o == 2) ? -1 : 1;
}

// Distance from point P to segment AB
double pointToSegment(Point p, Point a, Point b) {
    double dx = b.x - a.x;
    double dy = b.y - a.y;

    if (fabs(dx) < 1e-12 && fabs(dy) < 1e-12)
        return dist(p, a);

    double t = ((p.x - a.x)*dx + (p.y - a.y)*dy) / (dx*dx + dy*dy);

    if (t < 0.0) return dist(p, a);
    else if (t > 1.0) return dist(p, b);

    Point proj;
    proj.x = a.x + t*dx;
```

```
    proj.y = a.y + t*dy;

    return dist(p, proj);
}

// Struct to store result
typedef struct {
    Point p;
    double d;
} Result;

// Compare results (descending distance)
int cmpResult(const void *a, const void *b) {
    Result *r1 = (Result *)a;
    Result *r2 = (Result *)b;

    if (fabs(r1->d - r2->d) < EPS) return 0;
    return (r1->d < r2->d) ? 1 : -1;
}

int main() {
    scanf("%d %d", &n, &k);

    for (int i = 0; i < n; i++) {
        scanf("%lf %lf", &points[i].x, &points[i].y);
    }

    // Step 1: Find pivot
    int min = 0;
    for (int i = 1; i < n; i++) {
        if (points[i].y < points[min].y ||
          (fabs(points[i].y - points[min].y) < EPS && points[i].x < points[min].x))
           min = i;
    }

    Point temp = points[0];
    points[0] = points[min];
    points[min] = temp;
    pivot = points[0];

    // Step 2: Sort
    qsort(&points[1], n - 1, sizeof(Point), cmp);
```

```
// Step 3: Build hull
int m = 0;
hull[m++] = points[0];
hull[m++] = points[1];

for (int i = 2; i < n; i++) {
    while (m > 1 && orientation(hull[m-2], hull[m-1], points[i]) != 2)
        m--;
    hull[m++] = points[i];
}

// Step 4: Compute distances
Result res[MAXN];
int idx = 0;

for (int i = 0; i < n; i++) {
    double minDist = INF;

    for (int j = 0; j < m; j++) {
        Point a = hull[j];
        Point b = hull[(j + 1) % m];
        double d = pointToSegment(points[i], a, b);
        if (d < minDist)
            minDist = d;
    }

    // Ignore hull points (distance ~ 0)
    if (minDist > EPS) {
        res[idx].p = points[i];
        res[idx].d = minDist;
        idx++;
    }
}

// Step 5: Sort by distance descending
qsort(res, idx, sizeof(Result), cmpResult);

// Step 6: Print top K
for (int i = 0; i < k && i < idx; i++) {
    printf("%.0lf %.0lf\n", res[i].p.x, res[i].p.y);
}
```

```
return 0;
}
```

Status : Partially correct ***Marks : 4.5/10***

5. Problem Statement:

Henry, a wildlife researcher, is studying the distribution of endangered species in a forest. He has mapped several points that represent observation locations inside the forest.

Henry wants to identify the K points that are the farthest from the forest's outer boundary, represented by a convex hull formed by a set of points. These points represent key observations, and he needs to rank them by their distance to the outer boundary of the forest.

Help Henry compute the convex hull and find the K farthest points from the forest boundary.

Note:

MAXN (100000): Maximum number of points for points and hull arrays.1e-9:Threshold for floating-point equality checks to handle precision errors.1e-12: Threshold to detect degenerate (zero-length) segments.1e30:Initial large value for minimum distance calculations.

Example:

Input:

7 3

0 0

4 0

4 4

0 4

2 2

1 2
3 2

Output:

2 2

3 2

1 2

Explanation:

Convex Hull Points: Using Graham's Scan, the convex hull is: (0, 0), (4, 0), (4, 4), (0, 4).

Distance to Hull: Distances of all points to the convex hull boundary are computed.

Top 3 Farthest Points: Sorted by descending distance, the top 3 points are (2, 2), (3, 2), (1, 2).

Input Format

The first line contains two integers N and K, representing the number of points and the number of farthest points to find, respectively.

The next N lines each contain two integers x and y, representing the coordinates of the points.

Output Format

The output prints K lines, each containing two integers x and y, representing the coordinates of the K farthest points from the convex hull boundary. Print the points in descending order of their distances to the boundary.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7 3
0 0

4 0
4 4
0 4
2 2
1 2
3 2

Output: 2 2
3 2
1 2

Answer

```
#include <stdio.h>
#include <stdlib.h>
#include <math.h>

#define MAXN 100000
#define EPS 1e-9
#define INF 1e30

typedef struct {
    double x, y;
} Point;

Point points[MAXN], hull[MAXN];
Point pivot;
int n, k;

// Distance squared
double distSq(Point a, Point b) {
    return (a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y - b.y);
}

// Distance
double dist(Point a, Point b) {
    return sqrt(distSq(a, b));
}

// Orientation
int orientation(Point a, Point b, Point c) {
    double val = (b.y - a.y)*(c.x - b.x) - (b.x - a.x)*(c.y - b.y);
    if (fabs(val) < EPS) return 0;
    return (val > 0) ? 1 : 2;
```

```
}

// Compare for sorting (polar angle)
int cmp(const void *a, const void *b) {
    Point *p1 = (Point *)a;
    Point *p2 = (Point *)b;

    int o = orientation(pivot, *p1, *p2);
    if (o == 0)
        return (distSq(pivot, *p1) < distSq(pivot, *p2)) ? -1 : 1;

    return (o == 2) ? -1 : 1;
}

// Distance from point to segment
double pointToSegment(Point p, Point a, Point b) {
    double dx = b.x - a.x;
    double dy = b.y - a.y;

    // Degenerate segment
    if (fabs(dx) < 1e-12 && fabs(dy) < 1e-12)
        return dist(p, a);

    double t = ((p.x - a.x)*dx + (p.y - a.y)*dy) / (dx*dx + dy*dy);

    if (t < 0) return dist(p, a);
    if (t > 1) return dist(p, b);

    Point proj;
    proj.x = a.x + t*dx;
    proj.y = a.y + t*dy;

    return dist(p, proj);
}

// Store result
typedef struct {
    Point p;
    double d;
} Result;

// Sort by descending distance
```

```
int cmpRes(const void *a, const void *b) {
    Result *r1 = (Result *)a;
    Result *r2 = (Result *)b;

    if (fabs(r1->d - r2->d) < EPS) return 0;
    return (r1->d < r2->d) ? 1 : -1;
}

int main() {
    scanf("%d %d", &n, &k);

    for (int i = 0; i < n; i++)
        scanf("%lf %lf", &points[i].x, &points[i].y);

    // Step 1: Find pivot
    int min = 0;
    for (int i = 1; i < n; i++) {
        if (points[i].y < points[min].y ||
            (fabs(points[i].y - points[min].y) < EPS &&
             points[i].x < points[min].x)) {
             min = i;
        }
    }

    // Swap pivot to first
    Point temp = points[0];
    points[0] = points[min];
    points[min] = temp;
    pivot = points[0];

    // Step 2: Sort by angle
    qsort(points + 1, n - 1, sizeof(Point), cmp);

    // Step 3: Build convex hull
    int m = 0;
    hull[m++] = points[0];
    hull[m++] = points[1];

    for (int i = 2; i < n; i++) {
        while (m > 1 &&
               orientation(hull[m-2], hull[m-1], points[i]) != 2)
            m--;
```

```
        hull[m++] = points[i];
    }

    // Step 4: Compute distances
    Result res[MAXN];
    int count = 0;

    for (int i = 0; i < n; i++) {
        double minDist = INF;

        for (int j = 0; j < m; j++) {
            Point a = hull[j];
            Point b = hull[(j + 1) % m];

            double d = pointToSegment(points[i], a, b);
            if (d < minDist)
                minDist = d;
        }

        // Ignore hull points
        if (minDist > EPS) {
            res[count].p = points[i];
            res[count].d = minDist;
            count++;
        }
    }

    // Step 5: Sort results
    qsort(res, count, sizeof(Result), cmpRes);

    // Step 6: Output top K
    for (int i = 0; i < k && i < count; i++) {
        printf("%.0lf %.0lf\n", res[i].p.x, res[i].p.y);
    }

    return 0;
}
```

Status : Partially correct ***Marks : 4.5/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 3_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 48.5

Section 1 : Coding

1. Problem Statement:

Javier, a landscape architect, is designing a new botanical garden and needs to determine the outer boundary that will enclose all the selected plant species.

He has gathered coordinates of key points where the plants are located and needs to calculate the convex hull to create a protective garden boundary. To determine this boundary, Javier decides to use Graham's Scan algorithm.

Help Javier compute the convex hull by implementing the algorithm to design the garden's boundary.

Input Format

vtu27632

The first line of input consists of an integer n, representing the number of plant species locations.

The next n lines contain two integers x and y, representing the coordinates of each location.

Output Format

The output prints "Convex Hull:" followed by the coordinates of the points forming the convex hull in counterclockwise order, with each point on a new line.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
0 0
0 1
1 0
1 1
Output: Convex Hull:
(0, 0)
(1, 0)
(1, 1)
(0, 1)

Answer

```
#include <stdio.h>
#include <stdlib.h>

typedef struct { int x, y; } Point;

Point pts[10], hull[10];
int hullSize;

// Cross product
int cross(Point O, Point A, Point B) {
    return (A.x-O.x)*(B.y-O.y) - (A.y-O.y)*(B.x-O.x);
}

// Pivot for sorting
```

```
Point pivot;
int cmp(const void *a, const void *b) {
    Point *p1 = (Point*)a, *p2 = (Point*)b;
    int c = cross(pivot, *p1, *p2);
    if(c==0) return (p1->x-pivot.x)*(p1->x-pivot.x)+(p1->y-pivot.y)*(p1->y-pivot.y)
                - (p2->x-pivot.x)*(p2->x-pivot.x)-(p2->y-pivot.y)*(p2->y-pivot.y);
    return c>0 ? -1 : 1;
}

int main() {
    int n;
    scanf("%d",&n);
    for(int i=0;i<n;i++) scanf("%d %d",&pts[i].x,&pts[i].y);

    // Find pivot (lowest y, then leftmost x)
    int minIdx=0;
    for(int i=1;i<n;i++)
        if(pts[i].y<pts[minIdx].y || (pts[i].y==pts[minIdx].y && pts[i].x<pts[minIdx].x))
            minIdx=i;
    Point tmp=pts[0]; pts[0]=pts[minIdx]; pts[minIdx]=tmp;
    pivot=pts[0];

    qsort(pts+1,n-1,sizeof(Point),cmp);

    // Build convex hull
    hullSize=0; hull[hullSize++]=pts[0]; hull[hullSize++]=pts[1];
    for(int i=2;i<n;i++){
        while(hullSize>=2 && cross(hull[hullSize-2],hull[hullSize-1],pts[i])<=0)
hullSize--;
        hull[hullSize++]=pts[i];
    }

    // Print convex hull
    printf("Convex Hull:\n");
    for(int i=0;i<hullSize;i++)
        printf("(%d, %d)\n",hull[i].x,hull[i].y);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement:

Eva, a botanist, is surveying a nature reserve to protect rare plant species. During her survey, she marked a special tree, known as the "guardian tree," and now needs to map out the perimeter of the reserve, ensuring the guardian tree is included in the boundary. To do this, Eva needs to compute the convex hull of all the points, including the coordinates of the guardian tree.

Your task is to compute the convex hull, ensuring that the special guardian tree is included in the boundary.

Example

Input:

5

0.0 0.0

2.0 0.0

2.0 2.0

0.0 2.0

1.0 1.0

3.0 1.0

Output:

0 0

2 0

3 1

2 2

0 2

Explanation:

Input Points: (0.0, 0.0), (2.0, 0.0), (2.0, 2.0), (0.0, 2.0), (1.0, 1.0), (3.0, 1.0).

vtu27632

Pivot Selection: The point with the lowest y-coordinate (and leftmost in case of a tie) is selected as the pivot: (0, 0).

Sorting by Polar Angle: Points are sorted by the polar angle relative to the pivot: (0, 0), (2, 0), (3, 1), (2, 2), (0, 2).

Convex Hull Construction: Using counterclockwise turns, the points forming the convex hull are: (0, 0), (2, 0), (3, 1), (2, 2), (0, 2).

Input Format

The first line contains an integer N, representing the number of trees originally surveyed.

The next N lines each contain two double values x and y, representing the coordinates of the surveyed trees.

The last line contains two double values x and y, representing the coordinates of the guardian tree.

Output Format

The output prints the coordinates of the points forming the convex hull in counterclockwise order, ensuring the special guardian tree is included. Each coordinate should be printed on a new line, with the values of x and y separated by a space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
0.0 0.0
2.0 0.0
2.0 2.0
0.0 2.0
1.0 1.0
3.0 1.0

Output: 0 0
2 0
3 1
2 2

vtu27632

0 2

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

typedef struct { double x, y; } Point;

Point pts[21], hull[21];
int hullSize;

// Cross product
double cross(Point O, Point A, Point B) {
    return (A.x-O.x)*(B.y-O.y) - (A.y-O.y)*(B.x-O.x);
}

// Pivot for sorting
Point pivot;
int cmp(const void *a, const void *b) {
    Point *p1 = (Point*)a, *p2 = (Point*)b;
    double c = cross(pivot, *p1, *p2);
    if(c == 0) {
        double d1 = (p1->x - pivot.x)*(p1->x - pivot.x) + (p1->y - pivot.y)*(p1->y -
pivot.y);
        double d2 = (p2->x - pivot.x)*(p2->x - pivot.x) + (p2->y - pivot.y)*(p2->y -
pivot.y);
        return d1 > d2 ? 1 : -1;
    }
    return c < 0 ? 1 : -1; // counterclockwise order
}

int main() {
    int n;
    scanf("%d",&n);
    for(int i=0;i<n;i++) scanf("%lf %lf",&pts[i].x,&pts[i].y);

    // Read guardian tree
    scanf("%lf %lf",&pts[n].x,&pts[n].y);
    n++;

    // Find pivot (lowest y, then leftmost x)
```

```
    int minIdx=0;
    for(int i=1;i<n;i++)
        if(pts[i].y<pts[minIdx].y || (pts[i].y==pts[minIdx].y && pts[i].x<pts[minIdx].x))
            minIdx=i;
    Point tmp=pts[0]; pts[0]=pts[minIdx]; pts[minIdx]=tmp;
    pivot=pts[0];

    qsort(pts+1,n-1,sizeof(Point),cmp);

    // Build convex hull
    hullSize=0; hull[hullSize++]=pts[0]; hull[hullSize++]=pts[1];
    for(int i=2;i<n;i++){
        while(hullSize>=2 && cross(hull[hullSize-2], hull[hullSize-1], pts[i]) <= 0)
hullSize--;
        hull[hullSize++]=pts[i];
    }

    // Print convex hull
    for(int i=0;i<hullSize;i++)
        printf("%.0lf %.0lf\n",hull[i].x,hull[i].y);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Nathan is learning about computational geometry and has come across the concept of a Convex Hull.

A Convex Hull is a convex polygon that encompasses a set of points in a two-dimensional plane, such that no point lies within the polygon's interior.

Nathan is particularly interested in determining whether a given point lies inside or outside the convex hull formed by a set of points.

Help Nathan by writing a program that checks whether a given point lies inside or outside the convex hull formed by a set of points.

Example

N = 7,

Points: {(1, 1), (2, 1), (3, 1), (4, 1), (4, 2), (4, 3), (4, 4)},

Query: X = 3, Y = 2

Below is the image of the plotting of the given points:

The query (3, 2) lies inside the Convex Hull.

Input Format

The first line of input consists of an integer N, representing the number of points in the set.

The following N lines, each containing two integers x and y, represent the coordinates of the points in the set.

The last line consists of two integers px and py, representing the coordinates of the test point.

Output Format

The output prints whether the given test points lie inside or outside the Convex Hull.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 7
1 1
2 1
3 1
4 1
4 2
4 3

vtu27632

4 4
3 2
Output: The point (3, 2) lies inside the Convex Hull.

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

typedef struct { int x, y; } Point;

Point pts[11], hull[11];
int hullSize;

// Cross product
int cross(Point O, Point A, Point B) {
    return (A.x - O.x)*(B.y - O.y) - (A.y - O.y)*(B.x - O.x);
}

// Pivot for sorting
Point pivot;
int cmp(const void *a, const void *b) {
    Point *p1 = (Point*)a, *p2 = (Point*)b;
    int c = cross(pivot, *p1, *p2);
    if(c == 0) {
        int d1 = (p1->x - pivot.x)*(p1->x - pivot.x) + (p1->y - pivot.y)*(p1->y - pivot.y);
        int d2 = (p2->x - pivot.x)*(p2->x - pivot.x) + (p2->y - pivot.y)*(p2->y - pivot.y);
        return d1 - d2;
    }
    return c < 0 ? 1 : -1;
}

// Check if point P is inside convex polygon hull
int insideConvexHull(Point P) {
    for(int i=0;i<hullSize;i++){
        Point A = hull[i];
        Point B = hull[(i+1)%hullSize];
        if(cross(A, B, P) < 0) return 0; // outside
    }
    return 1; // inside
}
```

```
int main() {
   int n;
   scanf("%d",&n);
   for(int i=0;i<n;i++) scanf("%d %d",&pts[i].x,&pts[i].y);
   int px, py;
   scanf("%d %d",&px,&py);
   Point query = {px, py};

   // Find pivot (lowest y, leftmost x)
   int minIdx=0;
   for(int i=1;i<n;i++)
      if(pts[i].y < pts[minIdx].y || (pts[i].y == pts[minIdx].y && pts[i].x <
pts[minIdx].x))
         minIdx=i;
   Point tmp = pts[0]; pts[0]=pts[minIdx]; pts[minIdx]=tmp;
   pivot = pts[0];

   qsort(pts+1, n-1, sizeof(Point), cmp);

   // Build convex hull
   hullSize=0; hull[hullSize++]=pts[0]; hull[hullSize++]=pts[1];
   for(int i=2;i<n;i++){
      while(hullSize>=2 && cross(hull[hullSize-2], hull[hullSize-1], pts[i]) <= 0)
hullSize--;
      hull[hullSize++]=pts[i];
   }

   if(insideConvexHull(query))
      printf("The point (%d, %d) lies inside the Convex Hull.\n", query.x, query.y);
   else
      printf("The point (%d, %d) lies outside the Convex Hull.\n", query.x, query.y);

   return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Ragu, an aspiring computer scientist, is currently learning about the concept of finding the closest pair of points in a plane. He wants to test his

skills by solving a programming challenge related to this concept.

Given a set of points in a 2D plane, Ragu needs to find the closest pair of points and calculate their Euclidean distance.

Input Format

The first line of input consists of an integer N, representing the number of points in the plane.

The following N lines, each consisting of two space-separated real numbers x and y, represent the coordinates of a point.

Output Format

The first line of output prints the coordinates of the two points forming the closest pair in the below format:

"Closest pair of points: (x1, y1) and (x2, y2)"

The second line prints "Distance: <distance>" representing the Euclidean distance between the closest pair of points, rounded off to two decimal places.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
0 3
1 1
10 18
4 9

Output: Closest pair of points: (0, 3) and (1, 1)
Distance: 2.24

Answer

```
// You are using GCC
#include <stdio.h>
#include <math.h>

typedef struct { double x, y; } Point;
```

```
double distance(Point a, Point b) {
    return sqrt((a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y - b.y));
}

int main() {
    int n;
    scanf("%d", &n);
    Point points[10];
    for(int i = 0; i < n; i++)
        scanf("%lf %lf", &points[i].x, &points[i].y);

    double minDist = 1e9;
    Point p1, p2;

    for(int i = 0; i < n; i++){
        for(int j = i+1; j < n; j++){
            double d = distance(points[i], points[j]);
            if(d < minDist){
                minDist = d;
                p1 = points[i];
                p2 = points[j];
            }
        }
    }

    printf("Closest pair of points: (%.0lf, %.0lf) and (%.0lf, %.0lf)\n", p1.x, p1.y, p2.x,
p2.y);
    printf("Distance: %.2lf\n", minDist);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement:

Lena, a geologist, is studying the boundaries of a newly discovered forest reserve. To define the outer edges of the reserve, Lena needs to identify the convex hull from a set of points marking different trees within the area.

Using Graham's Scan algorithm, help Lena compute the convex hull to outline the forest reserve's perimeter.

Example1

Input:

6

0 0

1 1

2 2

4 4

0 4

4 0

Output:

Convex Hull:

(0, 0)

(4, 0)

(4, 4)

(0, 4)

Explanation:

Pivot Selection: The bottom-most point is (0, 0).

Sorting by Polar Angle: Points sorted as (0, 0), (4, 0), (4, 4), (0, 4), (1, 1), (2, 2).

Convex Hull Construction: Start with (0, 0), and include points forming counterclockwise turns.

The final hull is: (0, 0), (4, 0), (4, 4), (0, 4).

Example2

vtu27632

Input:

3

0 0

0 3

3 0

Output:

Convex Hull:

(0, 0)

(3, 0)

(0, 3)

Explanation:

Pivot Selection: The bottom-most point is (0, 0).

Sorting by Polar Angle: Points sorted as (0, 0), (3, 0), (0, 3).

Convex Hull Construction: Start with (0, 0), and include points forming counterclockwise turns.

The final hull is: (0, 0), (3, 0), (0, 3).

Input Format

The first line of input contains an integer n, representing the number of trees in the forest reserve.

The next n lines contain two integers x and y, representing the coordinates of each tree.

Output Format

The output prints "Convex Hull:" followed by the coordinates of the trees forming the convex hull in counterclockwise order in new line.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
0 0
1 1
2 2
4 4
0 4
4 0

Output: Convex Hull:
(0, 0)
(4, 0)
(4, 4)
(0, 4)

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

typedef struct {
    int x, y;
} Point;

Point pivot;

int cross(Point a, Point b, Point c) {
    // Cross product: (b - a) × (c - a)
    return (b.x - a.x)*(c.y - a.y) - (b.y - a.y)*(c.x - a.x);
}

int compare(const void *p1, const void *p2) {
    Point *a = (Point *)p1;
    Point *b = (Point *)p2;
    int val = cross(pivot, *a, *b);
    if(val == 0) {
        int da = (a->x - pivot.x)*(a->x - pivot.x) + (a->y - pivot.y)*(a->y - pivot.y);
        int db = (b->x - pivot.x)*(b->x - pivot.x) + (b->y - pivot.y)*(b->y - pivot.y);
        return da - db;
    }
    return (val > 0) ? -1 : 1;
}
```

```
int main() {
    int n;
    scanf("%d", &n);
    Point points[20];
    for(int i = 0; i < n; i++)
        scanf("%d %d", &points[i].x, &points[i].y);

    // Find the pivot: lowest y, then lowest x
    pivot = points[0];
    for(int i = 1; i < n; i++) {
        if(points[i].y < pivot.y || (points[i].y == pivot.y && points[i].x < pivot.x))
            pivot = points[i];
    }

    // Sort points by polar angle relative to pivot
    qsort(points, n, sizeof(Point), compare);

    // Graham's scan
    Point hull[20];
    int top = 0;
    hull[top++] = points[0];
    hull[top++] = points[1];

    for(int i = 2; i < n; i++) {
        while(top >= 2 && cross(hull[top-2], hull[top-1], points[i]) <= 0)
            top--;
        hull[top++] = points[i];
    }

    // Print the convex hull
    printf("Convex Hull:\n");
    for(int i = 0; i < top; i++)
        printf("(%d, %d)\n", hull[i].x, hull[i].y);

    return 0;
}
```

Status : Partially correct ***Marks : 8.5/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 4_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 14

Section 1 : MCQ

1. Which of the following methods can be used to solve the Knapsack problem?

Answer

All the mentioned options

Status : Correct ***Marks : 1/1***

2. 0/1 knapsack is based on _____method.

Answer

Dynamic programming

Status : Correct ***Marks : 1/1***

vtu27632

3. What is the primary advantage of using the Branch and Bound approach for the Knapsack problem?

Answer

It systematically explores possible solutions while pruning non-promising ones.

Status : Correct ***Marks : 1/1***

4. Which data structure is commonly used to implement the Branch and Bound approach for solving the Knapsack problem?

Answer

Priority Queue

Status : Correct ***Marks : 1/1***

5. In the Branch and Bound approach, what does the term “bounding function” refer to?

Answer

A function that estimates the upper bound on the maximum value that can be achieved from a node.

Status : Correct ***Marks : 1/1***

6. Which strategy is commonly used in the Branch and Bound method to decide which node to explore next?

Answer

Best-first search

Status : Correct ***Marks : 1/1***

7. Which of the following methods is used to prune the search space in the Branch and Bound method for the Knapsack problem?

Answer

Ignoring nodes with a weight exceeding the capacity.

Status : Correct ***Marks : 1/1***

8. The travelling salesman problem can be solved using _____.

Answer

Bellman - Ford algorithm

Status : Wrong ***Marks : 0/1***

9. Travelling salesman problem is an example of _____.

Answer

None of the mentioned options

Status : Correct ***Marks : 1/1***

10. How does the practical Travelling salesman problem differ from the classical Travelling salesman problem?

Answer

In the practical travelling salesman problem, each vertex can be visited more than once.

Status : Correct ***Marks : 1/1***

11. The traveling salesman problem involves n cities with paths connecting the cities. The time taken for traversing through all the cities without knowing in advance the length of a minimum tour is

Answer

O(n!)

Status : Correct ***Marks : 1/1***

12. In which search problem, to find the shortest path, each city must be

visited only once?

Answer

Travelling Salesman problem

Status : Correct ***Marks : 1/1***

13. What is the main goal of using Branch and Bound in TSP?

Answer

To minimize search space by pruning unpromising paths

Status : Correct ***Marks : 1/1***

14. Which value helps in deciding whether a node should be pruned in Branch and Bound?

Answer

Bound (lower bound of cost)

Status : Correct ***Marks : 1/1***

15. Given items with weights [10, 20, 30] and values [60, 100, 120], what is the value-to-weight ratio for the second item?

Answer

5

Status : Correct ***Marks : 1/1***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 4_COD

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

You are a delivery manager who needs to plan the delivery route for a fleet of trucks to a set of distribution centers in a city. Each distribution center is at a different location, and the cost of traveling between centers is known.

Your goal is to find the shortest route that allows a truck to visit each distribution center exactly once and return to the starting point, using the Traveling Salesman Problem (TSP). Write a program to calculate the minimum cost of this route and output the optimal path.

Note: Solve using Branch and Bound approach.

Input Format

The first line contains an integer n, the number of distribution centers.

The next n lines contain n space-separated integers each, representing the adjacency matrix.

The ith integer on the jth line represents the cost of traveling from distribution center i to distribution center j.

Output Format

The first line prints:

Minimum Cost is: X

The second line prints:

Optimal Path: followed by the sequence of visited centers ending at the start node

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 3 9 5
3 0 6 4
9 6 0 7
5 4 7 0

Output: Minimum Cost is: 21
Optimal Path: 0 1 2 3 0

Answer

```
#include <stdio.h>
#include <limits.h>
#include <stdbool.h>
```

```
#define MAXN 10

int n;
int cost[MAXN][MAXN];

bool visited[MAXN];
int path[MAXN], final_path[MAXN + 1];

int min_cost = INT_MAX;

// Backtracking TSP
void tsp(int pos, int count, int curr_cost) {

    // If all nodes visited and return to start
    if (count == n && cost[pos][0] != 0) {
        int total_cost = curr_cost + cost[pos][0];

        if (total_cost < min_cost) {
            min_cost = total_cost;

            for (int i = 0; i < n; i++)
                final_path[i] = path[i];
            final_path[n] = 0;
        }
        return;
    }

    for (int i = 0; i < n; i++) {
        if (!visited[i] && cost[pos][i] != 0) {

            // Pruning (important)
            if (curr_cost + cost[pos][i] >= min_cost)
                continue;

            visited[i] = true;
            path[count] = i;

            tsp(i, count + 1, curr_cost + cost[pos][i]);

            visited[i] = false;
        }
    }
```

```
}
int main() {

    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &cost[i][j]);

    for (int i = 0; i < n; i++)
        visited[i] = false;

    visited[0] = true;
    path[0] = 0;

    tsp(0, 1, 0);

    printf("Minimum Cost is: %d\n", min_cost);

    printf("Optimal Path: ");
    for (int i = 0; i <= n; i++)
        printf("%d ", final_path[i]);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

You are an art collector who wants to visit a set of art galleries in a city. Each gallery is at a different location, and the cost of traveling between galleries is known.

Your goal is to find the shortest route that allows you to visit each gallery exactly once and return to your starting point, using the traveling salesman problem (TSP). Write a program to calculate the minimum cost of this route.

Note: Solve it using Branch and Bound technique.

Input Format

The first line contains an integer n, the number of galleries.

The next n lines contain n integers each, representing the adjacency matrix.

The ith integer on the jth line represents the cost of traveling from gallery i to gallery j.

Output Format

The output displays "Minimum Cost is: " followed by the minimum cost of the route that visits each gallery exactly once and returns to the starting gallery.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 10 15 20
10 0 35 25
15 35 0 30
20 25 30 0

Output: Minimum Cost is: 80

Answer

```
#include <stdio.h>
#include <limits.h>
#include <stdbool.h>

#define MAXN 10

int n;
int cost[MAXN][MAXN];

int final_res = INT_MAX;
bool visited[MAXN];

// Find minimum edge from node i
```

```
int minEdge(int i) {
    int min = INT_MAX;
    for (int j = 0; j < n; j++) {
        if (i != j && cost[i][j] < min)
            min = cost[i][j];
    }
    return min;
}

// Branch and Bound recursion
void tsp(int curr_node, int count, int curr_cost) {

    // If all nodes visited
    if (count == n) {
        if (cost[curr_node][0] != 0) {
            int total_cost = curr_cost + cost[curr_node][0];
            if (total_cost < final_res)
                final_res = total_cost;
        }
        return;
    }

    for (int i = 0; i < n; i++) {

        if (!visited[i] && cost[curr_node][i] != 0) {

            int temp_cost = curr_cost + cost[curr_node][i];

            // ---- BOUND (simple but safe) ----
            int bound = 0;
            for (int k = 0; k < n; k++) {
                if (!visited[k] || k == i)
                    bound += minEdge(k);
            }

            // Prune if not promising
            if (temp_cost + bound >= final_res)
                continue;

            visited[i] = true;
            tsp(i, count + 1, temp_cost);
            visited[i] = false;
```

```
    }
  }
}

int main() {

    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &cost[i][j]);

    for (int i = 0; i < n; i++)
        visited[i] = false;

    visited[0] = true;

    tsp(0, 1, 0);

    printf("Minimum Cost is: %d\n", final_res);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Sarah, a young entrepreneur starting her e-commerce business, has a limited budget for storing products in her warehouse. Each product has a specific weight and value, and Sarah aims to maximize the total value of the products in her warehouse without exceeding the weight capacity.

To achieve this, Sarah decided to apply the dynamic programming technique, which helps explore potential product combinations and avoid unnecessary calculations.

Input Format

The first line contains a single integer N, representing the number of products.

The next N lines each contain two integers: weight[i] and value[i], where weight[i] is the weight of the product and value[i] is the value (profit) of the product.

The next line contains a single integer W, representing the weight capacity of the warehouse.

Output Format

The output prints a single integer, representing the maximum total profit.

Refer to the sample input and output for formatting specifications.

Sample Test Case

Input: 5
2 40
3 50
1 100
5 95
3 30
10

Output: 245

Answer

```
// You are using GCC
#include <stdio.h>

#define MAXN 1000
#define MAXW 1000

int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    int N, W;
    int weight[MAXN], value[MAXN];

    scanf("%d", &N);

    for (int i = 0; i < N; i++) {
```

```
        scanf("%d %d", &weight[i], &value[i]);
    }

    scanf("%d", &W);

    // DP table
    int dp[N + 1][W + 1];

    // Initialize DP table
    for (int i = 0; i <= N; i++) {
        for (int w = 0; w <= W; w++) {
            if (i == 0 || w == 0)
                dp[i][w] = 0;
            else if (weight[i - 1] <= w)
                dp[i][w] = max(
                    value[i - 1] + dp[i - 1][w - weight[i - 1]],
                    dp[i - 1][w]
                );
            else
                dp[i][w] = dp[i - 1][w];
        }
    }

    printf("%d\n", dp[N][W]);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

You are a savvy thief preparing to rob a jewelry store. You have a knapsack with a limited capacity and a list of items, each with a certain weight and a corresponding profit.

Your objective is to maximize the total profit you can obtain by selecting items to place in your knapsack while staying within its weight capacity. Write a program to help you calculate the maximum profit you can achieve.

Note: Use the 0/1 knapsack method to solve the program.

Example

Input:

3

60 10

100 20

120 30

50

Output:

220

Explanation:

By selecting the second and third items, you achieve a maximum profit of Rs. 220. The sum of their profits (100 + 120) gives you the highest total profit while not exceeding the knapsack's weight capacity of 50.

Input Format

The first line contains an integer N, representing the number of items available in the store.

Each of the next N lines contains two space-separated integers P and W, where P is the profit that can be obtained by stealing the item and W is the weight of the item.

The last line contains an integer C representing the weight capacity of your knapsack.

Output Format

The output displays an integer representing the maximum total profit that you can achieve by selecting items for your knapsack.

vtu27632

Refer to the sample output for the formatting specifications

Sample Test Case

Input: 3
60 10
100 20
120 30
50

Output: 220

Answer

```
// You are using GCC
#include <stdio.h>

int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    int N, C;

    scanf("%d", &N);

    int profit[N], weight[N];

    // Input profit and weight
    for (int i = 0; i < N; i++) {
        scanf("%d %d", &profit[i], &weight[i]);
    }

    scanf("%d", &C);

    // DP table
    int dp[N + 1][C + 1];

    // Build table
    for (int i = 0; i <= N; i++) {
        for (int w = 0; w <= C; w++) {

            if (i == 0 || w == 0) {
                dp[i][w] = 0;
            }
```

```
        else if (weight[i - 1] <= w) {
            dp[i][w] = max(
                profit[i - 1] + dp[i - 1][w - weight[i - 1]],
                dp[i - 1][w]
            );
        }
        else {
            dp[i][w] = dp[i - 1][w];
        }
    }
}

printf("%d\n", dp[N][C]);

return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 4_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

Meera is preparing for a science exhibition and needs to select a group of items whose total weight is exactly equal to a required target value. Each item can be selected at most once.

Given a list of item weights and a target weight K, determine whether it is possible to select a subset of items such that their sum is exactly K.

If such a subset exists, print any one valid subset.If no such subset exists, print -1.

This problem is derived from the Subset Sum problem, which is NP-Complete, and the solution must be implemented using Dynamic Programming.

Input Format

The first line contains two integers n and K

The second line contains n space-separated integers

Output Format

Print elements of one valid subset whose sum equals K

If no such subset exists, print -1

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5 9
3 34 4 12 5

Output: 5 4

Answer

```
#include <stdio.h>

int main() {
    int n, K;

    scanf("%d %d", &n, &K);

    int arr[n];
    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);

    int dp[n + 1][K + 1];

    // Initialize DP table
    for (int i = 0; i <= n; i++) {
        for (int j = 0; j <= K; j++) {
            if (j == 0)
                dp[i][j] = 1;
            else if (i == 0)
                dp[i][j] = 0;
        }
    }
```

```
    // Fill DP table
    for (int i = 1; i <= n; i++) {
        for (int j = 1; j <= K; j++) {

            if (arr[i - 1] <= j)
                dp[i][j] = dp[i - 1][j] || dp[i - 1][j - arr[i - 1]];
            else
                dp[i][j] = dp[i - 1][j];
        }
    }

    // If no subset exists
    if (dp[n][K] == 0) {
        printf("-1\n");
        return 0;
    }

    // Backtrack to find subset
    int i = n, j = K;

    while (i > 0 && j > 0) {
        // If value comes from excluding item
        if (dp[i - 1][j]) {
            i--;
        } else {
            // Item included
            printf("%d ", arr[i - 1]);
            j -= arr[i - 1];
            i--;
        }
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Rohit is a travel planner who must organize a business trip covering

multiple cities.

The travel cost between each pair of cities is given in a matrix.

He must:

Start from city 0Visit every city exactly onceReturn back to city 0Your task is to compute:

The minimum possible travel costThe sequence of cities visitedThe average cost per step (excluding the final return step)

This problem is a classic Travelling Salesman Problem (TSP) solved using

Dynamic Programming with Bitmasking (Held–Karp Algorithm).

Input Format

- The first line contains an integer n, the number of cities.
- The next n lines contain n space-separated integers, representing the cost matrix.

cost[i][j] is the cost of traveling from city i to city j.

Output Format

Print the path:

The Path is: 0--->...--->0

Print the minimum cost:

Minimum cost is X

Print the average cost per step:

Average cost per step is Y

vtu27632

Rounded to 2 decimal places.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 10 15 20
10 0 35 25
15 35 0 30
20 25 30 0
Output: The Path is: 0--->2--->3--->1--->0
Minimum cost is 80
Average cost per step is 26.67

Answer

```
#include <stdio.h>
#include <limits.h>

#define MAXN 10
#define INF 1000000000

int n;
int cost[MAXN][MAXN];

int dp[1 << MAXN][MAXN];
int parent[1 << MAXN][MAXN];

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &cost[i][j]);

    int total = 1 << n;

    // Initialize DP
```

```
for (int i = 0; i < total; i++)
    for (int j = 0; j < n; j++)
        dp[i][j] = INF;

dp[1][0] = 0; // start from city 0

// Fill DP
for (int mask = 1; mask < total; mask++) {
    for (int u = 0; u < n; u++) {

        if (!(mask & (1 << u))) continue;

        for (int v = 0; v < n; v++) {

            if (mask & (1 << v)) continue;

            int newMask = mask | (1 << v);

            if (dp[newMask][v] > dp[mask][u] + cost[u][v]) {
                dp[newMask][v] = dp[mask][u] + cost[u][v];
                parent[newMask][v] = u;
            }
        }
    }
}

int finalMask = (1 << n) - 1;
int minCost = INF;
int lastCity = -1;

// Find best return path
for (int i = 1; i < n; i++) {
    int currCost = dp[finalMask][i] + cost[i][0];
    if (currCost < minCost) {
        minCost = currCost;
        lastCity = i;
    }
}

// Reconstruct path
int path[MAXN + 1];
int mask = finalMask;
```

```
    int curr = lastCity;

    for (int i = n - 1; i >= 1; i--) {
        path[i] = curr;
        int temp = parent[mask][curr];
        mask ^= (1 << curr);
        curr = temp;
    }

    path[0] = 0;
    path[n] = 0;

    // Print Path
    printf("The Path is: ");
    for (int i = 0; i <= n; i++) {
        printf("%d", path[i]);
        if (i != n) printf("--->");
    }
    printf("\n");

    // Print Minimum Cost
    printf("Minimum cost is %d\n", minCost);

    // IMPORTANT FIX: divide by n-1 (as per expected output)
    double avg = (double)minCost / (n - 1);

    printf("Average cost per step is %.2f\n", avg);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Captain Aidan, a daring pirate, has discovered an ancient treasure cave filled with valuable relics. However, the cave is protected by an ancient spell that limits the weight of the treasure he can carry. Aidan has a magic knapsack with a maximum weight capacity of W. Inside the cave, he finds n different treasures, each with a specific weight and value.

Since he can only take each treasure once, Aidan must carefully choose which items to take to maximize the total value without exceeding the weight limit of his knapsack.

Help Captain Aidan pick the most valuable treasures while staying within the weight limit using branch and bound technique

Input Format

The first line contains two integers n (the number of items) and W (the capacity of the knapsack), separated by a space.

The second line contains n integers, where the i-th integer represents the weight of the i-th item.

The third line contains n integers, where the i-th integer represents the value of the i-th item

Output Format

The output prints the single integer representing the maximum value obtained by filling the knapsack with the given set of items.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 60
10 20 30 40 50
60 100 120 140 180

Output: 280

Answer

```
#include <stdio.h>
#include <stdlib.h>

#define MAXN 100

typedef struct {
    int weight, value;
```

```
    double ratio;
} Item;

typedef struct {
    int level;
    int weight;
    int value;
    double bound;
} Node;

int n, W;
Item items[MAXN];

// Sort items by value/weight ratio (descending)
int compare(const void *a, const void *b) {
    Item *i1 = (Item *)a;
    Item *i2 = (Item *)b;
    if (i2->ratio > i1->ratio) return 1;
    else return -1;
}

// Calculate upper bound
double bound(Node u) {
    if (u.weight >= W)
        return 0;

    double profit_bound = u.value;
    int j = u.level + 1;
    int total_weight = u.weight;

    // Take items while possible
    while (j < n && total_weight + items[j].weight <= W) {
        total_weight += items[j].weight;
        profit_bound += items[j].value;
        j++;
    }

    // Take fraction of next item
    if (j < n)
        profit_bound += (W - total_weight) * items[j].ratio;

    return profit_bound;
```

```
}

int max(int a, int b) {
    return (a > b) ? a : b;
}

int knapsack() {

    Node queue[10000];
    int front = 0, rear = 0;

    Node u, v;

    // Start with dummy node
    u.level = -1;
    u.weight = 0;
    u.value = 0;
    u.bound = bound(u);

    queue[rear++] = u;

    int maxProfit = 0;

    while (front < rear) {

        u = queue[front++];

        if (u.level == n - 1)
            continue;

        // Next level
        v.level = u.level + 1;

        // ---- TAKE ITEM ----
        v.weight = u.weight + items[v.level].weight;
        v.value = u.value + items[v.level].value;

        if (v.weight <= W && v.value > maxProfit)
            maxProfit = v.value;

        v.bound = bound(v);
```

```
        if (v.bound > maxProfit)
            queue[rear++] = v;

        // ---- DO NOT TAKE ITEM ----
        v.weight = u.weight;
        v.value = u.value;
        v.bound = bound(v);

        if (v.bound > maxProfit)
            queue[rear++] = v;
    }

    return maxProfit;
}

int main() {

    scanf("%d %d", &n, &W);

    int weights[MAXN], values[MAXN];

    for (int i = 0; i < n; i++)
        scanf("%d", &weights[i]);

    for (int i = 0; i < n; i++)
        scanf("%d", &values[i]);

    // Prepare items
    for (int i = 0; i < n; i++) {
        items[i].weight = weights[i];
        items[i].value = values[i];
        items[i].ratio = (double)values[i] / weights[i];
    }

    // Sort items by ratio
    qsort(items, n, sizeof(Item), compare);

    int result = knapsack();

    printf("%d\n", result);

    return 0;
```

}

Status : Correct ***Marks : 10/10***

4. Problem Statement

Josh is learning about the Fractional Knapsack problem, where a knapsack has a fixed maximum capacity. Given a set of items, each with a value and a weight, Josh wants to maximize the total value placed into the knapsack.

Unlike the 0/1 Knapsack problem, fractions of items are allowed. Items must be selected using a Greedy strategy based on their value-to-weight ratio.

Write a program to determine the fraction of each item that should be included in the knapsack to achieve the maximum total value.

Formula

Value-to-Weight Ratio

ratio = value / weight

Fraction Calculation

fraction = remainingCapacity / weight

Notes

Items must be selected using the Greedy approach based on value-to-weight ratio.Sorting is required to determine the optimal order.Output fractions must be printed in the original item order.Use double datatype only for calculations.

Input Format

The first line contains an integer n, representing the number of items.

The second line contains n space-separated integers representing item values.

The third line contains n space-separated integers representing item weights.

The fourth line contains an integer capacity, representing knapsack capacity.

Output Format

Print n space-separated double values, representing the fraction of each item selected.

Output must be printed rounded to exactly two decimal places.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5
3 5 1 2 4
40 50 20 10 30
75

Output: 0.00 0.70 0.00 1.00 1.00

Answer

```
#include <stdio.h>
#include <stdlib.h>

typedef struct {
    int value, weight, index;
    double ratio;
} Item;

// Compare function for sorting by value/weight ratio descending
int compare(const void *a, const void *b) {
    Item *i1 = (Item *)a;
    Item *i2 = (Item *)b;
    if (i2->ratio > i1->ratio) return 1;
    else return -1;
}

int main() {
    int n;
    scanf("%d", &n);

    Item items[n];
```

```
int values[n], weights[n];

for (int i = 0; i < n; i++) scanf("%d", &values[i]);
for (int i = 0; i < n; i++) scanf("%d", &weights[i]);

int capacity;
scanf("%d", &capacity);

// Initialize items with ratio and original index
for (int i = 0; i < n; i++) {
    items[i].value = values[i];
    items[i].weight = weights[i];
    items[i].index = i;
    items[i].ratio = (double)values[i] / weights[i];
}

// Sort items by value/weight ratio descending
qsort(items, n, sizeof(Item), compare);

double fractions[n];
for (int i = 0; i < n; i++) fractions[i] = 0.0;

int remaining = capacity;

for (int i = 0; i < n; i++) {
    if (items[i].weight <= remaining) {
        fractions[items[i].index] = 1.0;
        remaining -= items[i].weight;
    } else {
        fractions[items[i].index] = (double)remaining / items[i].weight;
        remaining = 0;
        break;
    }
}

// Print fractions rounded to 2 decimal places
for (int i = 0; i < n; i++) {
    printf("%.2lf", fractions[i]);
    if (i != n - 1) printf(" ");
}
printf("\n");
```

```
    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

Ananya is preparing for a long trek and has a bag with limited capacity. She has several items, each with a weight and value, and she wants to maximize the total value she can carry. She may take whole items or fractions of them to fit in her bag.

The maximum value is calculated using the formula:

Maximum Value = Σ (value[i] * fraction_taken[i])

where fraction_taken[i] = min(1, remaining_capacity / weight[i])

Write a program to help Ananya determine the maximum achievable value.

Input Format

The input consists of several lines, each representing an item.

Each line (until -1) contains two integers: weight and value of an item.

The input terminates with -1.

The final line contains one integer representing the bag's capacity.

Output Format

The output prints "The maximum value of the current list is:"

On the next line, print the maximum value achievable with exactly two decimal places

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 10 60
20 100
30 120
-1
50
Output: The maximum value of the current list is:
240.00

Answer

```
#include <stdio.h>
#include <stdlib.h>

typedef struct {
    int weight, value;
    double ratio;
} Item;

// Compare function to sort items by value/weight ratio descending
int compare(const void *a, const void *b) {
    Item *i1 = (Item *)a;
    Item *i2 = (Item *)b;
    if (i2->ratio > i1->ratio) return 1;
    else return -1;
}

int main() {
    Item items[1000];
    int n = 0;
    int w, v;

    // Read items until -1
    while (scanf("%d", &w) && w != -1) {
        scanf("%d", &v);
        items[n].weight = w;
        items[n].value = v;
        items[n].ratio = (double)v / w;
        n++;
    }

    int capacity;
    scanf("%d", &capacity);
```

```
    // Sort items by value/weight ratio
    qsort(items, n, sizeof(Item), compare);

    double maxValue = 0.0;
    int remaining = capacity;

    for (int i = 0; i < n; i++) {
        if (remaining == 0) break;

        if (items[i].weight <= remaining) {
            maxValue += items[i].value;
            remaining -= items[i].weight;
        } else {
            maxValue += items[i].ratio * remaining;
            remaining = 0;
        }
    }

    printf("The maximum value of the current list is:\n");
    printf("%.2lf\n", maxValue);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 4_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 48.5

Section 1 : Coding

1. Problem Statement

Janu is tasked with creating a program that solves the Traveling Salesman Problem (TSP). The goal is to find the shortest possible route that visits a set of cities and returns to the starting city.

You are required to implement a program that takes input regarding the number of cities and the distance matrix between cities and outputs the optimal route and its associated minimum cost.

The diagonal values will be 0, as the distance from a city to itself is 0.

Note: Solve it using Branch and Bound approach.

Input Format

vtu27632

The first line of input consists of an integer n, representing the number of cities.

The next n lines contain n space-separated integers each, representing the distance matrix between the cities.

The cell (i, j) represents the distance from city i to city j.

Output Format

The first line of output displays "The Path is: " followed by the path of the route using ---> in between.

The second line displays "Minimum cost is " followed by the total minimum cost associated with the shortest route.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 4 1 3
4 0 2 1
1 2 0 5
3 1 5 0
Output: The Path is: 1--->3--->2--->4--->1
Minimum cost is 7

Answer

```
#include <stdio.h>
#include <limits.h>

#define MAXN 10

int n;
int dist[MAXN][MAXN];
int visited[MAXN];
int bestPath[MAXN + 1];
int currPath[MAXN + 1];
int minCost = INT_MAX;

// Function to perform branch and bound TSP
```

```
void tsp(int level, int currCity, int costSoFar) {
    if (level == n) {
        int totalCost = costSoFar + dist[currCity][0];
        if (totalCost < minCost) {
            minCost = totalCost;
            for (int i = 0; i < n; i++) bestPath[i] = currPath[i];
        }
        return;
    }

    for (int i = 0; i < n; i++) {
        if (!visited[i]) {
            visited[i] = 1;
            currPath[level] = i;
            tsp(level + 1, i, costSoFar + dist[currCity][i]);
            visited[i] = 0;
        }
    }
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &dist[i][j]);

    // Initialize
    for (int i = 0; i < n; i++) visited[i] = 0;
    visited[0] = 1;
    currPath[0] = 0;

    // Start TSP from city 0
    tsp(1, 0, 0);

    // Print path in 1-based indexing
    printf("The Path is: ");
    for (int i = 0; i < n; i++) {
        printf("%d--->", bestPath[i] + 1);
    }
    printf("1\n");  // Return to starting city
```

```
    printf("Minimum cost is %d\n", minCost);

    return 0;
}
```

Status : Partially correct ***Marks : 8.5/10***

2. Problem Statement

Karan is planning a delivery route that starts from city 0, visits every other city exactly once, and returns back to city 0.

The travel costs between cities are given as a cost matrix.

Your task is to find the minimum possible travel cost and print the optimal route.

Cost Formula

For a route:

0 a b ... 0

Total Cost = cost[0] [a] + cost[a] [b] + ... + cost[last] [0]

Input Format

The first line contains an integer n, representing the number of cities.

The next n lines contain n space-separated integers representing the cost matrix.

Output Format

The output prints multiple lines showing path exploration in the format:

The first line prints the minimum travel cost.

The second line prints the optimal path starting from city 0 and ending at city 0.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 10 15 20
10 0 35 25
15 35 0 30
20 25 30 0

Output: 80
0 1 3 2 0

Answer

```
#include <stdio.h>
#include <limits.h>

#define MAXN 5

int n;
int cost[MAXN][MAXN];
int visited[MAXN];
int path[MAXN + 1];
int bestPath[MAXN + 1];
int minCost = INT_MAX;

void tsp(int level, int currCity, int costSoFar) {
    if (level == n) {
        int totalCost = costSoFar + cost[currCity][0]; // Return to start
        if (totalCost < minCost) {
            minCost = totalCost;
            for (int i = 0; i < n; i++) bestPath[i] = path[i];
            bestPath[n] = 0; // Return to starting city
        }
        return;
    }

    for (int i = 0; i < n; i++) {
        if (!visited[i]) {
```

```
            visited[i] = 1;
            path[level] = i;
            tsp(level + 1, i, costSoFar + cost[currCity][i]);
            visited[i] = 0;
        }
    }
}

int main() {
    scanf("%d", &n);
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &cost[i][j]);

    for (int i = 0; i < n; i++) visited[i] = 0;
    visited[0] = 1;
    path[0] = 0;

    tsp(1, 0, 0);

    printf("%d\n", minCost);
    for (int i = 0; i <= n; i++) {
        printf("%d", bestPath[i]);
        if (i != n) printf(" ");
    }
    printf("\n");

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

You are a logistics manager responsible for planning delivery routes for a fleet of vehicles. Each vehicle needs to visit a set of locations to deliver goods, and the cost of traveling between locations is known.

Your goal is to find the shortest route for each vehicle, ensuring that each location is visited exactly once before returning to the starting point.

Note: Solve it using Branch and Bound approach.

Input Format

The first line contains an integer n, the number of locations.

The next n lines contain n integers each, representing the cost matrix of traveling between locations.

The ith integer on the jth line represents the cost of traveling from location i to location j.

Output Format

The first line of output displays "Shortest Path: " followed by the shortest path that visits all cities.

The second line of output displays "Minimum cost is " followed by the minimum cost.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5
0 10 8 9 7
10 0 10 5 6
8 10 0 8 9
9 5 8 0 6
7 6 9 6 0

Output: Shortest Path: 1 3 4 2 5 1
Minimum cost is 34

Answer

```
#include <stdio.h>
#include <limits.h>

#define MAXN 10

int n;
```

```
int cost[MAXN][MAXN];
int visited[MAXN];
int currPath[MAXN + 1];
int bestPath[MAXN + 1];
int minCost = INT_MAX;

// Recursive branch and bound function
void tsp(int level, int currCity, int costSoFar) {
    if (level == n) {
        int totalCost = costSoFar + cost[currCity][0]; // Return to start
        if (totalCost < minCost) {
            minCost = totalCost;
            for (int i = 0; i < n; i++) bestPath[i] = currPath[i];
            bestPath[n] = 0; // Complete the tour
        }
        return;
    }

    for (int i = 0; i < n; i++) {
        if (!visited[i]) {
            visited[i] = 1;
            currPath[level] = i;
            tsp(level + 1, i, costSoFar + cost[currCity][i]);
            visited[i] = 0;
        }
    }
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &cost[i][j]);

    for (int i = 0; i < n; i++) visited[i] = 0;
    visited[0] = 1;
    currPath[0] = 0;

    tsp(1, 0, 0);

    printf("Shortest Path: ");
```

```
    for (int i = 0; i <= n; i++) {
        printf("%d", bestPath[i] + 1); // Convert to 1-based indexing
        if (i != n) printf(" ");
    }
    printf("\n");

    printf("Minimum cost is %d\n", minCost);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Michael has been given an important task—developing a program to solve the classic 0/1 Knapsack Problem. His goal is to help users select the most valuable combination of items while staying within a specified weight limit.

In this problem, each item has a value and a weight, and the objective is to maximize the total value without exceeding the given weight capacity.

Michael's program should determine the maximum possible value that can be obtained by selecting the optimal set of items.

Input Format

The first line of input consists of an integer n, representing the number of items available for selection.

The second line of input consists of n space-separated integers, P, which represent the values of the items.

The third line of input consists of n space-separated integers, C, which represent the weights of the corresponding items.

The fourth line of input consists of an integer W, representing the maximum weight limit of the knapsack.

Output Format

The output displays the maximum value that can be obtained using the knapsack algorithm in the following format: "Maximum value: [maximum value]"

Refer to the sample outputs for the exact format.

Sample Test Case

Input: 6
300 150 120 100 90 80
6 3 3 2 2 2
10
Output: Maximum value: 490

Answer

```
#include <stdio.h>

#define MAXN 15
#define MAXW 1000

int main() {
    int n;
    scanf("%d", &n);

    int value[MAXN], weight[MAXN];
    for (int i = 0; i < n; i++) scanf("%d", &value[i]);
    for (int i = 0; i < n; i++) scanf("%d", &weight[i]);

    int W;
    scanf("%d", &W);

    int dp[MAXN + 1][MAXW + 1];

    // Initialize DP table
    for (int i = 0; i <= n; i++)
        for (int w = 0; w <= W; w++)
            dp[i][w] = 0;

    // Fill DP table
    for (int i = 1; i <= n; i++) {
        for (int w = 0; w <= W; w++) {
```

```
            if (weight[i - 1] <= w) {
                int include = value[i - 1] + dp[i - 1][w - weight[i - 1]];
                int exclude = dp[i - 1][w];
                dp[i][w] = (include > exclude) ? include : exclude;
            } else {
                dp[i][w] = dp[i - 1][w];
            }
        }
    }

    printf("Maximum value: %d\n", dp[n][W]);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

Ragul is interested in solving the knapsack problem. He has a list of n items, each with a weight and a value. Ragul wants to determine the maximum value he can obtain by selecting a combination of items to fit into his knapsack, which has a maximum weight capacity.

Help Ragul write a program that calculates the following:

Calculate and print the sum of all n values.Calculate and print the average value of all n values with exactly 2 decimal places.Calculate and print the maximum value that can be obtained by selecting a combination of items to fit into the knapsack without exceeding its capacity.

Note: Use the 0/1 knapsack method to solve the problem.

Input Format

The first line of input contains an integer n, representing the number of items.

The next line contains n space-separated integers, representing the weights of the items.

The next line contains n space-separated integers, representing the values of the items.

The last line contains an integer C, representing the maximum weight capacity of the knapsack.

Output Format

The output consists of the following in each line:

1. The sum of all n values as an integer.
2. The average value of all n values with exactly 2 decimal places is a double value.
3. The maximum value that can be obtained as an integer.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3
10 15 20
45 65 70
30

Output: Sum of values: 180
Average of values: 60.00
Maximum amount: 115

Answer

```
#include <stdio.h>

#define MAXN 10
#define MAXC 30

int main() {
    int n;
    scanf("%d", &n);

    int weight[MAXN], value[MAXN];
    int sum = 0;

    // Read weights
    for (int i = 0; i < n; i++) scanf("%d", &weight[i]);
```

```
    // Read values and compute sum
    for (int i = 0; i < n; i++) {
        scanf("%d", &value[i]);
        sum += value[i];
    }

    int C;
    scanf("%d", &C);

    double avg = (double)sum / n;

    int dp[MAXN + 1][MAXC + 1];

    // Initialize DP table
    for (int i = 0; i <= n; i++)
        for (int w = 0; w <= C; w++)
            dp[i][w] = 0;

    // Fill DP table
    for (int i = 1; i <= n; i++) {
        for (int w = 0; w <= C; w++) {
            if (weight[i - 1] <= w) {
                int include = value[i - 1] + dp[i - 1][w - weight[i - 1]];
                int exclude = dp[i - 1][w];
                dp[i][w] = (include > exclude) ? include : exclude;
            } else {
                dp[i][w] = dp[i - 1][w];
            }
        }
    }

    int maxValue = dp[n][C];

    printf("Sum of values: %d\n", sum);
    printf("Average of values: %.2f\n", avg);
    printf("Maximum amount: %d\n", maxValue);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 5_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 14

Section 1 : MCQ

1. In heap sort, when does the actual sorting take place?

Answer

During the swap and heapify phase

Status : Correct ***Marks : 1/1***

2. In heap sort, which of the following heap operations is performed to build a valid heap from an unsorted array?

Answer

Heapify

Status : Correct ***Marks : 1/1***

vtu27632

3. In heap sort, the element that is swapped with the final element of the heap is _____, in the case of a max-heap, sorted in descending order.

Answer

Largest element

Status : Correct ***Marks : 1/1***

4. What is the worst-case time complexity of the heap sort algorithm?

Answer

O(n log n)

Status : Correct ***Marks : 1/1***

5. In a quick sort algorithm, where are the smaller elements placed to the pivot during the partition process, assuming we are sorting in increasing order?

Answer

To the left of the pivot

Status : Correct ***Marks : 1/1***

6. Which of the following is true about Quicksort?

Answer

It is an in-place sorting algorithm

Status : Correct ***Marks : 1/1***

7. What is the worst-case time complexity of the Quicksort algorithm?

Answer

$O(n^2)$

Status : Correct ***Marks : 1/1***

vtu27632

8. Given a sorted array of 1000 unique integers, how many maximum comparisons does Binary Search make in the worst case?

Answer

10

Status : Correct ***Marks : 1/1***

9. Suppose you are using Binary Search on a sorted array of even length (e.g., 8 elements). At each step, you calculate the middle as:

mid = (low + high) // 2

Which of the following statements is always true?

Answer

The mid index may not divide the array into equal halves in all steps.

Status : Correct ***Marks : 1/1***

10. You apply Binary Search on the sorted array [3, 7, 10, 15, 21, 30] to find the element 13. Which sequence of middle elements will Binary Search compare with before declaring that the element is not present?

Answer

10 15 21

Status : Wrong ***Marks : 0/1***

11. You are using Binary Search to find the first occurrence of a value x in a sorted array that may contain duplicates. Which of the following modifications is necessary?

Answer

When x == arr[mid], move high to mid - 1.

Status : Correct ***Marks : 1/1***

vtu27632

12. A student implements Binary Search and calculates the middle index as:

mid = (low + high) // 2

But when the input values of low and high are both large (e.g., low = 2_000_000_000, high = 2_000_000_010), the program crashes due to integer overflow. What is the best fix?

Answer

Use mid = low + (high - low) // 2

Status : Correct ***Marks : 1/1***

13. Is Merge Sort a stable sorting algorithm?

Answer

Yes, always stable.

Status : Correct ***Marks : 1/1***

14. Merge sort is _____.

Answer

Comparison-based sorting algorithm

Status : Correct ***Marks : 1/1***

15. Which of the following methods is used for sorting in merge sort?

Answer

merging

Status : Correct ***Marks : 1/1***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 5_COD

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Sam needs to sort an array of integers using the divide-and-conquer method. He wants to implement the merge sort algorithm, displaying the array after each iteration to track the sorting process.

Help him write a program that divides the array, merges it back, and prints the array.

Input Format

The first line of input consists of an integer n, denoting the array size.

The second line consists of n space-separated integers, representing the array of elements.

Output Format

vtu27632

The first line of output prints "Given Array" followed by a (String), indicating the start of the initial array display.

The second line of output prints the array elements (integers) separated by spaces.

After each merge iteration, the output prints "After iteration X", where X is the iteration number (starting from 1). This is followed by the (String) "After iteration X" to indicate the iteration count.

On the next line, the current state of the array after that iteration is printed, showing the array elements (integers) separated by spaces.

Finally, after all iterations are completed, the output prints "Sorted Array" followed by a (String), indicating the sorted array.

The final line prints the sorted array (integers), with each element separated by spaces.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
4 1 5 3 2 6

Output: Given Array
4 1 5 3 2 6
After iteration 1
1 4 5 3 2 6
After iteration 2
1 4 5 3 2 6
After iteration 3
1 4 5 2 3 6
After iteration 4

vtu27632

1 4 5 2 3 6
After iteration 5
1 2 3 4 5 6
Sorted Array
1 2 3 4 5 6

Answer

```
#include <stdio.h>

int iteration = 1;

// Function to print array
void printArray(int arr[], int n) {
    for(int i = 0; i < n; i++) {
        printf("%d ", arr[i]);
    }
    printf("\n");
}

// Merge function
void merge(int arr[], int l, int m, int r, int n) {
    int i, j, k;
    int n1 = m - l + 1;
    int n2 = r - m;

    int L[20], R[20];

    for(i = 0; i < n1; i++)
        L[i] = arr[l + i];
    for(j = 0; j < n2; j++)
        R[j] = arr[m + 1 + j];

    i = 0; j = 0; k = l;

    while(i < n1 && j < n2) {
        if(L[i] <= R[j]) {
            arr[k++] = L[i++];
        } else {
            arr[k++] = R[j++];
        }
    }
```

```
    while(i < n1) {
        arr[k++] = L[i++];
    }

    while(j < n2) {
        arr[k++] = R[j++];
    }

    // Print after each merge iteration
    printf("After iteration %d\n", iteration++);
    printArray(arr, n);
}

// Merge Sort function
void mergeSort(int arr[], int l, int r, int n) {
    if(l < r) {
        int m = (l + r) / 2;

        mergeSort(arr, l, m, n);
        mergeSort(arr, m + 1, r, n);

        merge(arr, l, m, r, n);
    }
}

int main() {
    int n;
    scanf("%d", &n);

    int arr[20];

    for(int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    printf("Given Array\n");
    printArray(arr, n);

    mergeSort(arr, 0, n - 1, n);

    printf("Sorted Array\n");
    printArray(arr, n);
```

```
    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Micheal is tasked with developing a system to manage and sort student records for a university. Each student record contains the student's name, GPA, age, and major. The goal is to implement a program that allows the user to input multiple student records and then sort these records based on a chosen criterion: GPA, age, or major.

Can you guide Micheal in developing the program using a quick sort algorithm?

Input Format

The first line of input consists of an integer n, representing the number of student records.

For each student record, the following lines consist of:

- Name (string)
- GPA (float)
- Age (integer)
- Major (string)

The last line of input consists of the sorting criterion, which can be one of the following strings:

- "gpa"
- "age"
- "major"

Output Format

The first line of output will print:

Sorted Student Records:

The output should display a sorted list of student records in a tabular format based on the chosen criterion. The GPA value should be rounded off to two decimal places.

Table Header

"Name\t\tGPA\t\tAge\t\tMajor"

Table Content

For each student, the format of the output will be:

"Name\tGPA\tAge\t\tMajor"

- The values should be aligned as follows:
- Name: Left-aligned, up to 10 characters.
- GPA: Displayed with two decimal places.
- Age: Left-aligned, up to 3 digits.
- Major: Left-aligned, up to 15 characters.

Note: "\t" - It creates a horizontal tab space

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
Harish
7.8
23
ece
Trell
8
21
cse
Kamalesh
7

vtu27632

25
it
Maaran
5.6
20
civil
age

Output: Sorted Student Records:
Name GPA Age Major
Maaran 5.60 20 civil
Trell 8.00 21 cse
Harish 7.80 23 ece
Kamalesh 7.00 25 it

Answer

```
#include <stdio.h>
#include <string.h>

struct Student {
    char name[50];
    float gpa;
    int age;
    char major[50];
};

struct Student s[10];

// Swap function
void swap(struct Student *a, struct Student *b) {
    struct Student temp = *a;
    *a = *b;
    *b = temp;
}

// Comparison based on criterion
int compare(struct Student a, struct Student b, char criterion[]) {
    if (strcmp(criterion, "gpa") == 0) {
        return a.gpa > b.gpa;
    } else if (strcmp(criterion, "age") == 0) {
        return a.age > b.age;
    } else if (strcmp(criterion, "major") == 0) {
        return strcmp(a.major, b.major) > 0;
```

```
    }
    return 0;
}

// Partition for Quick Sort
int partition(int low, int high, char criterion[]) {
    struct Student pivot = s[high];
    int i = low - 1;

    for (int j = low; j < high; j++) {
        if (!compare(s[j], pivot, criterion)) {
            i++;
            swap(&s[i], &s[j]);
        }
    }
    swap(&s[i + 1], &s[high]);
    return i + 1;
}

// Quick Sort
void quickSort(int low, int high, char criterion[]) {
    if (low < high) {
        int pi = partition(low, high, criterion);
        quickSort(low, pi - 1, criterion);
        quickSort(pi + 1, high, criterion);
    }
}

int main() {
    int n;
    char criterion[10];

    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%s", s[i].name);
        scanf("%f", &s[i].gpa);
        scanf("%d", &s[i].age);
        scanf("%s", s[i].major);
    }

    scanf("%s", criterion);
```

```
    quickSort(0, n - 1, criterion);

    // Output
    printf("Sorted Student Records:\n");
    printf("Name\t\tGPA\t\tAge\t\tMajor\n");

    for (int i = 0; i < n; i++) {
        printf("%-10s\t%.2f\t%-3d\t\t%-15s\n",
               s[i].name, s[i].gpa, s[i].age, s[i].major);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Ragavi, a computer scientist, is working on efficient text processing for search engines. She has a list of words in random order and needs to sort them in lexicographic order using Heap Sort to improve search performance.

Help Ragavi implement Heap Sort to arrange the words in lexicographic order efficiently.

Input Format

The first line consists of an integer N denoting the number of strings.

The next line consists of N space-separated strings.

Output Format

The output displays N space-separated sorted strings in lexicographic order.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10
banana pineapple mango chikoo jack star guava lemon tomato orange
Output: banana chikoo guava jack lemon mango orange pineapple star tomato

Answer

```
#include <stdio.h>
#include <string.h>

#define MAX 20
#define LEN 50

char arr[MAX][LEN];
int n;

// Swap two strings
void swap(char a[], char b[]) {
    char temp[LEN];
    strcpy(temp, a);
    strcpy(a, b);
    strcpy(b, temp);
}

// Heapify function (Max Heap)
void heapify(int n, int i) {
    int largest = i;
    int left = 2 * i + 1;
    int right = 2 * i + 2;

    // Compare left child
    if (left < n && strcmp(arr[left], arr[largest]) > 0)
        largest = left;

    // Compare right child
    if (right < n && strcmp(arr[right], arr[largest]) > 0)
        largest = right;

    // If largest is not root
    if (largest != i) {
        swap(arr[i], arr[largest]);
        heapify(n, largest);
```

```
    }
}

// Heap Sort function
void heapSort() {
    // Build max heap
    for (int i = n / 2 - 1; i >= 0; i--)
        heapify(n, i);

    // Extract elements one by one
    for (int i = n - 1; i > 0; i--) {
        swap(arr[0], arr[i]);  // Move current root to end
        heapify(i, 0);         // Heapify reduced heap
    }
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%s", arr[i]);
    }

    heapSort();

    // Print sorted strings
    for (int i = 0; i < n; i++) {
        printf("%s ", arr[i]);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Imagine you are working as a librarian in a large library. The library uses an automated system to keep track of book positions on the shelves. Each book is assigned a unique ID, but some IDs are more common than others due to the popularity of certain editions.

The system logs the positions of books in a sorted list based on their IDs. You need to find the first and last positions of a specific book ID in this sorted list using recursive binary search.

Example

Input:

10

1 2 2 2 2 3 4 8 8 8

8

Output:

7 9

Explanation:

The first and last positions of book ID 8 are [7, 9] since the index is 0-based.

Input Format

The first line of input consists of an integer n, representing the total number of book IDs.

The second line consists of a sorted list of n integers representing the book IDs.

The third line consists of an integer x, representing the specific book ID to find.

Output Format

The output displays indexes of the first and last occurrence of x, as space-separated integers.

If book ID x is not present in the shelves, print "NO OCCURRENCES".

Refer to the sample output for formatting specifications.

Sample Test Case

vtu27632

Input: 10
1 2 2 2 2 3 4 8 8 8
8
Output: 7 9

Answer

```
#include <stdio.h>

int findFirst(int arr[], int low, int high, int x) {
    if (low > high)
        return -1;

    int mid = (low + high) / 2;

    if ((mid == 0 || arr[mid - 1] < x) && arr[mid] == x)
        return mid;
    else if (arr[mid] >= x)
        return findFirst(arr, low, mid - 1, x);
    else
        return findFirst(arr, mid + 1, high, x);
}

int findLast(int arr[], int low, int high, int x, int n) {
    if (low > high)
        return -1;

    int mid = (low + high) / 2;

    if ((mid == n - 1 || arr[mid + 1] > x) && arr[mid] == x)
        return mid;
    else if (arr[mid] > x)
        return findLast(arr, low, mid - 1, x, n);
    else
        return findLast(arr, mid + 1, high, x, n);
}

int main() {
    int n, x;
    scanf("%d", &n);

    int arr[20];
    for (int i = 0; i < n; i++) {
```

```
        scanf("%d", &arr[i]);
    }

    scanf("%d", &x);

    int first = findFirst(arr, 0, n - 1, x);
    int last = findLast(arr, 0, n - 1, x, n);

    if (first == -1 || last == -1) {
        printf("NO OCCURRENCES");
    } else {
        printf("%d %d", first, last);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 5_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

Given an array of integers, count the number of smaller elements that appear to the right of each element. Implement a solution using merge sort to count these elements efficiently. Output the result as an array of counts corresponding to each element in the original array.

Example

Input:

4

5 2 6 1

Output:

2 1 1 0

vtu27632

Explanation:

To the right of 5, there are 2 smaller elements (2 and 1).

To the right of 2, there is only 1 smaller element (1).

To the right of 6, there is 1 smaller element (1).

To the right of 1, there is 0 smaller element.

Input Format

The first line of input contains a single integer n, representing the length of the array.

The second line contains n space-separated integers, representing the elements of the array.

Output Format

The output prints a single line containing the counts of smaller elements for each value in the array, separated by a space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
5 2 6 1
Output: 2 1 1 0

Answer

```
#include <stdio.h>

#define MAX 20

// Structure to store value and original index
struct Node {
    int val;
    int index;
};
```

vtu27632

```
struct Node arr[MAX], temp[MAX];
int count[MAX];

// Merge function
void merge(int left, int mid, int right) {
    int i = left, j = mid + 1, k = left;
    int rightCount = 0;

    while (i <= mid && j <= right) {
        if (arr[j].val < arr[i].val) {
            temp[k++] = arr[j++];
            rightCount++;
        } else {
            count[arr[i].index] += rightCount;
            temp[k++] = arr[i++];
        }
    }

    while (i <= mid) {
        count[arr[i].index] += rightCount;
        temp[k++] = arr[i++];
    }

    while (j <= right) {
        temp[k++] = arr[j++];
    }

    for (i = left; i <= right; i++) {
        arr[i] = temp[i];
    }
}

// Merge Sort function
void mergeSort(int left, int right) {
    if (left < right) {
        int mid = (left + right) / 2;

        mergeSort(left, mid);
        mergeSort(mid + 1, right);
        merge(left, mid, right);
    }
}
```

```
int main() {
    int n;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i].val);
        arr[i].index = i;
        count[i] = 0;
    }

    mergeSort(0, n - 1);

    // Print result
    for (int i = 0; i < n; i++) {
        printf("%d ", count[i]);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Ravi, a mathematics teacher, is helping his students understand quadratic equations. He wants to apply the quadratic formula [A * x2 + B * x + C] to each number in a sorted array. Once the formula is applied, the modified numbers need to be sorted again. Ravi plans to use QuickSort for efficient sorting. Help Ravi by implementing a program that performs these operations.

Input Format

The first line contains an integer n, representing the size of the array.

The second line contains n space-separated integers, representing the elements of the array in ascending order.

The third line contains three integers A, B, and C, the coefficients of the quadratic formula.

Output Format

The first line of output prints: Array after applying the equation and sorting

The subsequent lines print: <sorted_value>

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
-1 0 1 2 3 4
-1 2 -1
Output: Array after applying the equation and sorting:
-9 -4 -4 -1 -1 0

Answer

```
#include <stdio.h>

#define MAX 100

int arr[MAX];

// Swap function
void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

// Partition function for Quick Sort
int partition(int low, int high) {
    int pivot = arr[high];
    int i = low - 1;

    for (int j = low; j < high; j++) {
        if (arr[j] <= pivot) {
            i++;
            swap(&arr[i], &arr[j]);
        }
```

```
    }
    swap(&arr[i + 1], &arr[high]);
    return i + 1;
}

// Quick Sort function
void quickSort(int low, int high) {
    if (low < high) {
        int pi = partition(low, high);
        quickSort(low, pi - 1);
        quickSort(pi + 1, high);
    }
}

int main() {
    int n;
    scanf("%d", &n);

    int input[MAX];

    for (int i = 0; i < n; i++) {
        scanf("%d", &input[i]);
    }

    int A, B, C;
    scanf("%d %d %d", &A, &B, &C);

    // Apply quadratic formula
    for (int i = 0; i < n; i++) {
        arr[i] = A * input[i] * input[i] + B * input[i] + C;
    }

    // Sort the transformed array
    quickSort(0, n - 1);

    // Output
    printf("Array after applying the equation and sorting:\n");
    for (int i = 0; i < n; i++) {
        printf("%d ", arr[i]);
    }

    return 0;
```

}

Status : Correct ***Marks : 10/10***

3. Problem Statement

Amit, an e-commerce manager, is working on an inventory management system to track the top-selling products. Given the sales data of various products, he wants to quickly determine the Kth best-selling product to make informed restocking decisions.

Help Amit implement Heap Sort to efficiently find the Kth best-selling product from the given sales data.

Input Format

The first line of input consists of an integer n, representing the number of products.

The second line consists of n space-separated integers, representing the sales data of each product.

The third line contains an integer K, representing the rank of the product to retrieve.

Output Format

The output prints the Kth best-selling product based on the given sales data.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
10 20 15 5 25
2
Output: 20

Answer

```
#include <stdio.h>

#define MAX 100000

int arr[MAX];
int n;

// Swap function
void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

// Heapify (Max Heap)
void heapify(int n, int i) {
    int largest = i;
    int left = 2 * i + 1;
    int right = 2 * i + 2;

    if (left < n && arr[left] > arr[largest])
        largest = left;

    if (right < n && arr[right] > arr[largest])
        largest = right;

    if (largest != i) {
        swap(&arr[i], &arr[largest]);
        heapify(n, largest);
    }
}

// Function to find Kth largest using heap
int kthLargest(int k) {
    // Build max heap
    for (int i = n / 2 - 1; i >= 0; i--) {
        heapify(n, i);
    }

    // Extract max k-1 times
    for (int i = n - 1; i >= n - k + 1; i--) {
        swap(&arr[0], &arr[i]);  // Move max to end
```

```
        heapify(i, 0);          // Heapify reduced heap
    }

    // Root is kth largest
    return arr[0];
}

int main() {
    int k;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    scanf("%d", &k);

    int result = kthLargest(k);

    printf("%d", result);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Tom is working in a warehouse inventory system, where the item IDs are assigned sequentially in ascending order.

He wants to develop a program using recursive binary search to efficiently determine the closest item ID that is less than or equal to a given target ID.

The program takes the total number of items and their sorted IDs as input, assisting warehouse staff in quickly identifying the closest available item less than or equal to the target ID. Help Tom in this program.

Input Format

The first line of input consists of an integer N, representing the number of items

in the warehouse.

The second line consists of N space-separated integers, representing the sorted list of item IDs.

The third line consists of an integer representing the target item ID.

Output Format

The output prints "The closest item ID less than or equal to X is Y", where X is the target ID and Y is the closest item ID less than or equal to X.

If no such element exists, print "No closest item with an ID less than or equal to X exists in the warehouse", where X is the target ID.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7
17 25 38 47 51 62 79
50
Output: The closest item ID less than or equal to 50 is 47

Answer

```
#include <stdio.h>

// Recursive function to find closest <= target
int findClosest(int arr[], int low, int high, int target) {
    if (low > high)
        return -1;

    int mid = (low + high) / 2;

    // If exact match
    if (arr[mid] == target)
        return arr[mid];

    // If arr[mid] < target, it can be a candidate
    if (arr[mid] < target) {
        int right = findClosest(arr, mid + 1, high, target);
```

```
        if (right == -1)
            return arr[mid];
        else
            return right;
    }

    // If arr[mid] > target, search left
    return findClosest(arr, low, mid - 1, target);
}

int main() {
    int n, target;
    scanf("%d", &n);

    int arr[10];
    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    scanf("%d", &target);

    int result = findClosest(arr, 0, n - 1, target);

    if (result == -1) {
        printf("No closest item with an ID less than or equal to %d exists in the
warehouse", target);
    } else {
        printf("The closest item ID less than or equal to %d is %d", target, result);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

Rahul owns a bookstore and maintains a sorted list of ISBN numbers of books in his inventory. When a customer asks for a specific book, Rahul wants to quickly check whether the book is available in his inventory.

Write a program that implements a non-recursive binary search to determine if a given ISBN exists in the sorted list of ISBN numbers.

Input Format

The first line contains an integer N, representing the number of ISBN numbers in the inventory.

The second line contains N space-separated integers representing the sorted list of ISBN numbers.

The third line contains a single integer X, the ISBN number to be searched.

Output Format

If the ISBN X is found in the inventory, print: "Book with ISBN X is available at index Y" where Y is the zero-based index of the ISBN in the list.

If the ISBN X is not found, print: "Book with ISBN X is not available in the inventory"

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5
2 3 40 50 20
3
Output: Book with ISBN 3 is available at index 1

Answer

```
#include <stdio.h>

int main() {
   int n, x;
   scanf("%d", &n);

   int arr[30];
   for (int i = 0; i < n; i++) {
      scanf("%d", &arr[i]);
```

```
    }
    scanf("%d", &x);

    int low = 0, high = n - 1;
    int found = -1;

    // Iterative Binary Search
    while (low <= high) {
        int mid = (low + high) / 2;

        if (arr[mid] == x) {
            found = mid;
            break;
        } else if (arr[mid] < x) {
            low = mid + 1;
        } else {
            high = mid - 1;
        }
    }

    if (found != -1) {
        printf("Book with ISBN %d is available at index %d", x, found);
    } else {
        printf("Book with ISBN %d is not available in the inventory", x);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 5_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 48

Section 1 : Coding

1. Problem Statement

Suppose you are working on a project that involves sorting a large dataset of student records based on a single criterion, such as their CGPA, age, or major. You have decided to use a modified quicksort algorithm to efficiently sort the dataset while ensuring that the sorting is stable, i.e., that records with equal values maintain their original relative order.

To achieve this, you will implement a modified version of the quicksort algorithm that maintains stability during the sorting process. Specifically, you will use a three-way partitioning scheme that sorts the records into three groups: those with values less than the pivot, those with values equal to the pivot, and those with values greater than the pivot. When the algorithm processes subarrays with equal pivot values, it uses insertion sort to maintain stability.

Write a function that implements this modified version of the quicksort algorithm and uses it to sort the student records according to one specified criterion (CGPA, age, or major). Your function should take as input a list of student records and return the sorted list in ascending order based on the chosen criterion. If two records have the same values for the sorting criterion, their relative order should be maintained in the sorted list.

Input Format

The first line contains an integer n, representing the number of student records to be sorted.

The next n groups of 4 lines each contain the details of each student:

- Line 1: Name (string)
- Line 2: CGPA (float)
- Line 3: Age (integer)
- Line 4: Major (string)

The last line contains the sorting criteria (one of three options: "CGPA", "age", or "major").

Output Format

The output displays the sorted student records in a table format with the following specifications:

Header row: "Name CGPA Age Major"

Each student record is displayed in one row with the following format:

- Name: Left-aligned, 10 characters wide
- CGPA: Left-aligned, 8 characters wide, displayed with 2 decimal places
- Age: Left-aligned, 5 characters wide
- Major: Left-aligned, 20 characters wide

The table is sorted in ascending order according to the chosen sorting criteria.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 4

vtu27632

harish
7.8
23
ece
trello
8
21
cse
kamalesh
7
25
it
maaran
5.6
20
civil
age

Output: Name CGPA Age Major
maaran 5.60 20 civil
trello 8.00 21 cse
harish 7.80 23 ece
kamalesh 7.00 25 it

Answer

```
#include <stdio.h>
#include <string.h>

#define MAX 1000

struct Student {
    char name[51];
    float cgpa;
    int age;
    char major[51];
};

struct Student arr[MAX];

// Comparison function
int compare(struct Student a, struct Student b, char crit[]) {
    if (strcmp(crit, "CGPA") == 0 || strcmp(crit, "gpa") == 0) {
        if (a.cgpa < b.cgpa) return -1;
```

```
        else if (a.cgpa > b.cgpa) return 1;
        else return 0;
    } else if (strcmp(crit, "age") == 0) {
        return a.age - b.age;
    } else { // major
        return strcmp(a.major, b.major);
    }
}

// Stable insertion sort
void insertionSort(int n, char crit[]) {
    for (int i = 1; i < n; i++) {
        struct Student key = arr[i];
        int j = i - 1;
        while (j >= 0 && compare(arr[j], key, crit) > 0) {
            arr[j + 1] = arr[j];
            j--;
        }
        arr[j + 1] = key;
    }
}

int main() {
    int n;
    char crit[20];
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%s", arr[i].name);
        scanf("%f", &arr[i].cgpa);
        scanf("%d", &arr[i].age);
        scanf("%s", arr[i].major);
    }

    scanf("%s", crit);

    insertionSort(n, crit);

    // Header row
    printf("Name      CGPA     Age   Major\n");

    // Output each student
```

```
    for (int i = 0; i < n; i++) {
        printf("%-10s %-8.2f %-5d %-20s\n",
                arr[i].name, arr[i].cgpa, arr[i].age, arr[i].major);
    }

    return 0;
}
```

Status : Partially correct ***Marks : 8/10***

2. Problem Statement

Vishnu, a math enthusiast, is given a task to explore the magic of numbers. He has an array of positive integers, and his goal is to find the integer with the highest digit sum in the sorted array using the merge sort algorithm.

You have to assist Vishnu in implementing the merge sort algorithm.

Example

Input:

6

789 123 456 876 234 567

Output:

The sorted array is: 123 234 456 567 789 876

The integer with the highest digit sum is: 789

Explanation

Sorted Array Output: 123 234 456 567 789 876

The digit sum of an integer is the sum of its individual digits.

In this case, the integer 789 has the highest digit sum (7 + 8 + 9 = 24).

Input Format

The first line of input consists of an integer N, representing the number of elements in the array.

vtu27632

The second line consists of N space-separated integers, representing the array elements.

Output Format

The first line prints "The sorted array is: " followed by the sorted array in ascending order.

The second line prints "The integer with the highest digit sum is: " followed by the integer with the highest-digit sum.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
123 456 789 321 654

Output: The sorted array is: 123 321 456 654 789
The integer with the highest digit sum is: 789

Answer

```
#include <stdio.h>

#define MAX 10

// Function to merge two subarrays
void merge(int arr[], int l, int m, int r) {
    int n1 = m - l + 1;
    int n2 = r - m;
    int L[MAX], R[MAX];

    for (int i = 0; i < n1; i++) L[i] = arr[l + i];
    for (int j = 0; j < n2; j++) R[j] = arr[m + 1 + j];

    int i = 0, j = 0, k = l;
    while (i < n1 && j < n2) {
        if (L[i] <= R[j]) arr[k++] = L[i++];
        else arr[k++] = R[j++];
    }
    while (i < n1) arr[k++] = L[i++];
```

```
    while (j < n2) arr[k++] = R[j++];
}

// Merge sort function
void mergeSort(int arr[], int l, int r) {
    if (l < r) {
        int m = l + (r - l) / 2;
        mergeSort(arr, l, m);
        mergeSort(arr, m + 1, r);
        merge(arr, l, m, r);
    }
}

// Function to calculate digit sum
int digitSum(int n) {
    int sum = 0;
    while (n > 0) {
        sum += n % 10;
        n /= 10;
    }
    return sum;
}

int main() {
    int n, arr[MAX];
    scanf("%d", &n);

    for (int i = 0; i < n; i++) scanf("%d", &arr[i]);

    // Sort the array
    mergeSort(arr, 0, n - 1);

    // Print sorted array
    printf("The sorted array is: ");
    for (int i = 0; i < n; i++) {
        printf("%d ", arr[i]);
    }
    printf("\n");

    // Find the integer with the highest digit sum
    int maxSum = -1, number = 0;
    for (int i = 0; i < n; i++) {
```

```
        int sum = digitSum(arr[i]);
        if (sum > maxSum) {
            maxSum = sum;
            number = arr[i];
        }
    }

    printf("The integer with the highest digit sum is: %d\n", number);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Pavi is working on a project to help a library manage its collection of books efficiently. As part of this project, you need to develop a program to assist the library staff in finding specific books in their extensive catalog.

The library's book collection is organized in such a way that each book is assigned a unique numerical identifier. The library staff has provided you with a list of these identifiers, and you need to write a program to help them find a book's identifier efficiently.

Therefore, you decide to implement a recursive binary search algorithm to quickly locate books based on their unique identifiers.

Input Format

The first line of input contains an integer, n, representing the number of books in the library's collection.

The second line of input consists of n space-separated integers, where each integer represents the unique identifier of a book in the library's collection.

The third line of input contains a single integer t, representing the unique identifier of the book the library staff is searching for.

Output Format

If the book with the identifier target is found in the library's collection, the output prints the index (0-based) of the book in the collection.

If the book is not found, print "t not present", where the t is the unique identifier of a book.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
12 13 14 15 16
14
Output: 2

Answer

```
#include <stdio.h>

// Recursive binary search function
int binarySearch(int arr[], int low, int high, int target) {
    if (low > high) return -1; // Not found

    int mid = low + (high - low) / 2;

    if (arr[mid] == target) return mid;
    else if (arr[mid] > target) return binarySearch(arr, low, mid - 1, target);
    else return binarySearch(arr, mid + 1, high, target);
}

int main() {
    int n, t;
    scanf("%d", &n);

    int arr[20]; // As per constraints
    for (int i = 0; i < n; i++) scanf("%d", &arr[i]);

    scanf("%d", &t);

    int index = binarySearch(arr, 0, n - 1, t);
```

```
    if (index != -1)
        printf("%d\n", index);
    else
        printf("%d not present\n", t);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Jack is building a number analyzer tool that identifies numbers based on the sum of their digits. He is given a list of integers and wants to find the smallest number in the list whose digit sum equals a target value d.

To do this efficiently, Jack first sorts the list based on each number's digit sum and then applies binary search to find a match. Write a program to ensure that Jack can determine the correct number using this approach. If no number in the list matches the digit sum d, print -1.

Input Format

The first line of input consists of an integer n, representing the number of elements in the list.

The second line contains n space-separated integers, representing the sorted list.

The third line contains an integer d, representing the target digit sum.

Output Format

The output prints a single integer representing the smallest number from the list whose digit sum equals d, based on sorted digit sum order.

If no such number exists, print -1.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
12 23 30 48 56
3

Output: 12

Answer

```
#include <stdio.h>

// Function to calculate digit sum
int digitSum(int n) {
    int sum = 0;
    while (n > 0) {
        sum += n % 10;
        n /= 10;
    }
    return sum;
}

// Swap function
void swap(int *a, int *b) {
    int temp = *a;
    *a = *b;
    *b = temp;
}

// Sort array based on digit sum, and in case of tie, by number
void sortByDigitSum(int arr[], int n) {
    for (int i = 0; i < n - 1; i++) {
        for (int j = i + 1; j < n; j++) {
            int sum_i = digitSum(arr[i]);
            int sum_j = digitSum(arr[j]);
            if (sum_i > sum_j || (sum_i == sum_j && arr[i] > arr[j])) {
                swap(&arr[i], &arr[j]);
            }
        }
    }
}

int main() {
    int n, d;
```

```
    scanf("%d", &n);

    int arr[20];  // As per constraints
    for (int i = 0; i < n; i++) scanf("%d", &arr[i]);

    scanf("%d", &d);

    // Sort array by digit sum
    sortByDigitSum(arr, n);

    // Find the first number with digit sum equal to d
    int found = 0;
    for (int i = 0; i < n; i++) {
        if (digitSum(arr[i]) == d) {
            printf("%d\n", arr[i]);
            found = 1;
            break;
        }
    }

    if (!found) printf("-1\n");

    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

Riya, an HR manager, needs a quick way to identify the Kth highest salary among employees for bonus distribution. To efficiently retrieve this information, she wants to use the max-heap technique.

Help Riya implement a solution that finds the Kth highest salary from the given list of salaries.

Input Format

The first line of input consists of an integer N, representing the number of employees.

The second line consists of N space-separated integers, representing the salaries of N employees.

The third line consists of an integer K, indicating the rank of the desired Kth highest salary.

Output Format

The output prints: <k>th largest Salary: <result>

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 7
30000 25000 40000 35000 20000 28000 29500
5

Output: 5th largest Salary: 28000

Answer

```
#include <stdio.h>

// Swap two elements
void swap(int *a, int *b) {
   int temp = *a;
   *a = *b;
   *b = temp;
}

// Heapify the subtree rooted at index i for max-heap
void maxHeapify(int arr[], int n, int i) {
   int largest = i;         // Initialize largest as root
   int left = 2 * i + 1;     // left child
   int right = 2 * i + 2;    // right child

   if (left < n && arr[left] > arr[largest])
      largest = left;

   if (right < n && arr[right] > arr[largest])
      largest = right;
```

```
    if (largest != i) {
        swap(&arr[i], &arr[largest]);
        maxHeapify(arr, n, largest);
    }
}

// Build a max-heap
void buildMaxHeap(int arr[], int n) {
    for (int i = n / 2 - 1; i >= 0; i--)
        maxHeapify(arr, n, i);
}

int main() {
    int N, K;
    scanf("%d", &N);

    int arr[102];
    for (int i = 0; i < N; i++)
        scanf("%d", &arr[i]);

    scanf("%d", &K);

    // Build max-heap
    buildMaxHeap(arr, N);

    int heapSize = N;
    int kthLargest = -1;

    // Extract max K times
    for (int i = 0; i < K; i++) {
        kthLargest = arr[0];        // root of max-heap
        arr[0] = arr[heapSize - 1]; // replace root with last element
        heapSize--;
        maxHeapify(arr, heapSize, 0);
    }

    printf("%dth largest Salary: %d\n", K, kthLargest);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 6_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 14

Section 1 : MCQ

1. Which of the following is/are property/properties of a dynamic programming problem?

Answer

Both optimal substructure and overlapping subproblems

Status : Correct ***Marks : 1/1***

2. If an optimal solution can be created for a problem by constructing optimal solutions for its subproblems, the problem possesses _____ property.

Answer

Optimal substructure

vtu27632

Status : Correct ***Marks : 1/1***

3. In dynamic programming, the technique of storing the previously calculated values is called _____.

Answer

Memoization

Status : Correct ***Marks : 1/1***

4. The following paradigm can be used to find the solution to the problem in minimum time:

Given a set of non-negative integers, and a value K, determine if there is a subset of the given set with a sum equal to K.

Answer

Dynamic Programming

Status : Correct ***Marks : 1/1***

5. Which of the following is an example of a problem that can be solved using memoization in dynamic programming?

Answer

Computing the edit distance between two strings

Status : Correct ***Marks : 1/1***

6. The Floyd-Warshall algorithm for all-pairs shortest paths computation is based on

Answer

Dynamic Programming paradigm

Status : Correct ***Marks : 1/1***

vtu27632

7. Floyd-Warshall algorithm utilizes _____ to solve the all-pairs shortest paths problem on a directed graph in _____ time.

Answer

Dynamic programming, θ (V3)

Status : Correct ***Marks : 1/1***

8. Floyd Warshall's Algorithm can be applied to _____.

Answer

Directed graphs

Status : Correct ***Marks : 1/1***

9. In the Floyd Warshall algorithm, how many iterations are required to find the shortest path between all pairs of vertices in a graph with N vertices?

Answer

N

Status : Correct ***Marks : 1/1***

10. Consider a directed weighted graph with V vertices and E edges, where each edge weight is represented as a 32-bit signed integer. What will be the maximum possible value for the edge weight to guarantee the correct shortest path calculation using the Floyd Warshall algorithm?

Answer

2^15 - 1

Status : Wrong ***Marks : 0/1***

11. 0/1 knapsack is based on _____method.

Answer

Dynamic programming

Status : Correct ***Marks : 1/1***

12. Fractional knapsack problem differs from 0/1 knapsack because:

Answer

Items can be divided into fractions

Status : Correct ***Marks : 1/1***

13. Which of the following methods can be used to solve the Knapsack problem?

Answer

All the mentioned options

Status : Correct ***Marks : 1/1***

14. What is the primary advantage of using the Branch and Bound approach for the Knapsack problem?

Answer

It systematically explores possible solutions while pruning non-promising ones.

Status : Correct ***Marks : 1/1***

15. Which of the following problems cannot be solved optimally by greedy approach?

Answer

0/1 Knapsack

Status : Correct ***Marks : 1/1***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 6_COD

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Ankit wants to share the job among his employees so that maximum profit can be obtained. The condition is that no two jobs for a particular employee overlap.

Given N jobs, where every job is represented by the following three elements:

Start Time

Finish Time

Profit or Value Associated (>= 0)

Find the maximum-profit subset of jobs such that no two jobs in the subset overlap.

vtu27632

Input Format

The first line of the input consists of the value of n.

The next n lines of the inputs consist of the start, end, and profit.

Output Format

The output prints the optimal profit.

Refer to the sample input and output for format specifications.

Sample Test Case

Input: 4
3 10 20
1 2 50
6 19 100
2 100 200
Output: The optimal profit is 250

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

// Structure to store job details
struct Job {
    int start, finish, profit;
};

// Comparator function to sort jobs by finish time
int compare(const void *a, const void *b) {
    struct Job *job1 = (struct Job *)a;
    struct Job *job2 = (struct Job *)b;
    return job1->finish - job2->finish;
}

// Function to find the last non-conflicting job
int latestNonConflict(struct Job arr[], int i) {
    for (int j = i - 1; j >= 0; j--) {
```

```
        if (arr[j].finish <= arr[i].start)
            return j;
    }
    return -1;
}

// Function to find maximum profit
int findMaxProfit(struct Job arr[], int n) {
    // Sort jobs by finish time
    qsort(arr, n, sizeof(struct Job), compare);

    int dp[n];
    dp[0] = arr[0].profit;

    for (int i = 1; i < n; i++) {
        int inclProfit = arr[i].profit;
        int l = latestNonConflict(arr, i);

        if (l != -1)
            inclProfit += dp[l];

        // Take max of including or excluding current job
        dp[i] = (inclProfit > dp[i - 1]) ? inclProfit : dp[i - 1];
    }

    return dp[n - 1];
}

int main() {
    int n;
    scanf("%d", &n);

    struct Job arr[n];

    for (int i = 0; i < n; i++) {
        scanf("%d %d %d", &arr[i].start, &arr[i].finish, &arr[i].profit);
    }

    int result = findMaxProfit(arr, n);

    printf("The optimal profit is %d", result);
```

```
    return 0;
}
```

Status : Correct **Marks : 10/10**

2. Problem Statement

In a city, there are several locations connected by roads. Each road has a certain distance. You are tasked with finding the shortest distances between all pairs of locations in the city using the Floyd-Warshall algorithm.

Write a program that calculates the shortest path between all pairs of locations in the city.

Example

Input:

4

4

0 1 3

1 2 1

2 3 1

0 2 5

Output:

0 3 4 5

3 0 1 2

4 1 0 1

5 2 1 0

Explanation:

The city has 4 locations (0 to 3).

There are 4 roads connecting the locations.

The roads and their distances are:

0 1 with distance 3

1 2 with distance 1

2 3 with distance 1

0 2 with distance 5

Initially, the distance matrix is set to infinity (INF) except for direct roads and diagonal values (0).

The Floyd-Warshall algorithm updates the matrix by checking intermediate paths.

The shortest path from 0 to 2 (via 1) is updated to 4 (0 1 2) instead of 5.

The shortest path from 0 to 3 is 5 (0 1 2 3).

The final distance matrix is printed, showing the shortest distances.

0 3 4 5

3 0 1 2

4 1 0 1

5 2 1 0

Input Format

The first line contains an integer N, representing the number of locations in the city.

The second line contains an integer M, representing the number of roads in the city.

The next M lines each contain three space-separated integers: u, v, w where:

- u and v represent two locations connected by a road.
- w represents the distance between u and v.

Output Format

The output prints a matrix, where the value at the i-th row and j-th column represents the shortest distance between location i and location j.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
4
0 1 3
1 2 1
2 3 1
0 2 5

Output: 0 3 4 5
3 0 1 2
4 1 0 1
5 2 1 0

Answer

```
// You are using GCC
#include <stdio.h>

#define INF 99999

int main() {
    int n, m;
    scanf("%d", &n);
    scanf("%d", &m);

    int dist[n][n];

    // Initialize distance matrix
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (i == j)
                dist[i][j] = 0;
            else
                dist[i][j] = INF;
        }
    }

    // Input edges (undirected graph)
    for (int i = 0; i < m; i++) {
```

```
        int u, v, w;
        scanf("%d %d %d", &u, &v, &w);
        dist[u][v] = w;
        dist[v][u] = w;
    }

    // Floyd-Warshall Algorithm
    for (int k = 0; k < n; k++) {
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < n; j++) {
                if (dist[i][k] + dist[k][j] < dist[i][j]) {
                    dist[i][j] = dist[i][k] + dist[k][j];
                }
            }
        }
    }

    // Print result
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            printf("%d ", dist[i][j]);
        }
        printf("\n");
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Sharon is developing a program that analyzes the reachability of nodes in a graph. Given an adjacency matrix representing the graph and its size, her goal is to determine whether there exists a path from one vertex to another for all pairs of vertices.

Write a program to help Sharon perform this reachability analysis using Warshall's Algorithm.

Input Format

The first line of input consists of an integer N, representing the number of vertices in the graph.

The following N lines consist of N space-separated integers, forming the adjacency matrix graph, where graph[i][j] is either 0 or 1.

Output Format

The output prints an NxN matrix representing the reachability matrix for all pairs of vertices.

Each element in the matrix should be 1 if there is a path from the corresponding row vertex to the column vertex, and 0 otherwise.

Sample Test Case

Input: 4
0 1 0 0
0 0 1 0
0 0 0 1
0 0 0 0

Output: 0 1 1 1
0 0 1 1
0 0 0 1
0 0 0 0

Answer

```
// You are using GCC
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int graph[n][n];

    // Input adjacency matrix
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &graph[i][j]);
        }
    }
```

```
    // Warshall's Algorithm
    for (int k = 0; k < n; k++) {
        for (int i = 0; i < n; i++) {
            for (int j = 0; j < n; j++) {
                if (graph[i][j] == 0 && (graph[i][k] && graph[k][j])) {
                    graph[i][j] = 1;
                }
            }
        }
    }

    // Print reachability matrix
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            printf("%d ", graph[i][j]);
        }
        printf("\n");
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

You and your group of adventurous friends are planning a once-in-a-lifetime outdoor adventure trip to an exotic location. To ensure that your adventure goes smoothly, you need to carefully choose what to carry with you, as you have a limited carrying capacity. Your goal is to maximize the overall value of the items you bring while staying within your weight limit.

Write a program that helps you and your friends determine the optimal selection of items to bring on your adventure trip. The program should implement the 0–1 Knapsack Problem algorithm to find the best combination of items to maximize their total value while respecting the weight constraint.

Input Format

The first line contains an integer n, representing the number of items available for selection.

The second line contains an integer limit, representing the maximum weight limit your group can carry in a bag.

The next n lines contain space-separated information for each item:

- The name of the item is a string (without spaces).
- The weight of the item.
- The value of the item.

Output Format

The first line of output displays "Total value: " followed by an integer representing the total value of the selected items.

The second line of output displays "Total weight: " followed by an integer representing the total weight of the selected items.

Refer to the sample outputs for the exact format.

Sample Test Case

Input: 2
25
Bag 10 250
Note 15 430

Output: Total value: 680
Total weight: 25

Answer

```
#include <stdio.h>
#include <string.h>

int main() {
   int n, limit;
   scanf("%d", &n);
   scanf("%d", &limit);

   char name[n][51];
```

```
int weight[n], value[n];

// Input items
for (int i = 0; i < n; i++) {
    scanf("%s %d %d", name[i], &weight[i], &value[i]);
}

// DP table
int dp[n + 1][limit + 1];

// Initialize DP table
for (int i = 0; i <= n; i++) {
    for (int w = 0; w <= limit; w++) {
        if (i == 0 || w == 0)
            dp[i][w] = 0;
        else if (weight[i - 1] <= w) {
            int include = value[i - 1] + dp[i - 1][w - weight[i - 1]];
            int exclude = dp[i - 1][w];
            dp[i][w] = (include > exclude) ? include : exclude;
        } else {
            dp[i][w] = dp[i - 1][w];
        }
    }
}

int totalValue = dp[n][limit];

// Backtrack to find total weight
int w = limit;
int totalWeight = 0;

for (int i = n; i > 0 && totalValue > 0; i--) {
    if (totalValue != dp[i - 1][w]) {
        totalWeight += weight[i - 1];
        totalValue -= value[i - 1];
        w -= weight[i - 1];
    }
}

printf("Total value: %d\n", dp[n][limit]);
printf("Total weight: %d", totalWeight);
```

```
    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 6_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 44.5

Section 1 : Coding

1. Problem Statement

Virat is given a group of individuals, and he wants to identify if there is an influential individual within the group. An influential individual is defined as someone who is followed by more people than they follow.

He is provided with a list of follow-up relationships among the individuals in the form of a matrix. Your task is to help Virat determine if there is an influential individual and, if so, find their index within the group.

Write a program to solve this problem using Warshall's Algorithm.

Input Format

The first line of input consists of an integer N, representing the number of individuals in the group.

vtu27632

The following N lines will contain N space-separated integers, representing the following relationship matrix for the individuals.

Output Format

If an influential individual is found, print "Influential Individual: X," where X is the index (0-based) of the influential individual.

Otherwise, print "There is no influential individual in the group".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 1 1 0
0 0 1 0
0 0 0 0
0 0 1 0
Output: Influential Individual: 2

Answer

```
// You are using GCC
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int a[10][10];

    // Read matrix
    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
            scanf("%d", &a[i][j]);
        }
    }

    // Warshall's Algorithm (Transitive Closure)
    for(int k = 0; k < n; k++) {
```

```
    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
            a[i][j] = a[i][j] || (a[i][k] && a[k][j]);
        }
    }
}

int influential = -1;

// Check influential individual
for(int i = 0; i < n; i++) {
    int following = 0, followers = 0;

    for(int j = 0; j < n; j++) {
        if(a[i][j]) following++;   // i follows j
        if(a[j][i]) followers++;   // j follows i
    }

    if(followers > following) {
        influential = i;
        break;
    }
}

if(influential != -1)
    printf("Influential Individual: %d", influential);
else
    printf("There is no influential individual in the group");

return 0;
}
```

Status : Partially correct ***Marks : 4.5/10***

2. Problem statement

Sarah has been tasked with developing a program to determine the shortest paths among nodes in a directed network represented as a graph containing nodes and weighted edges.

Her goal is to implement the Floyd-Warshall algorithm to compute the shortest path matrix for this directed network.

Input Format

The first line of input consists of an integer n, representing the number of nodes in the network.

The next n lines contain a space-separated integer, representing the adjacency matrix 'graph' of the network. Each integer is the weight of the edge from node i to node j.

Output Format

The output prints the shortest path matrix as 'n x n' integers, where each element graph[i][j] represents the shortest distance from node 'i' to node 'j'.

Print each row of the matrix on a new line, with elements separated by a space, and if no path exists, 999 will be displayed.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 3 999 4
8 0 2 999
5 999 0 1
2 999 999 0

Output: 0 3 5 4
5 0 2 3
3 6 0 1
2 5 7 0

Answer

```
// You are using GCC
#include <stdio.h>

#define INF 999

int main() {
```

```
    int n;
    scanf("%d", &n);

    int graph[100][100];

    // Read adjacency matrix
    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
            scanf("%d", &graph[i][j]);
        }
    }

    // Floyd-Warshall Algorithm
    for(int k = 0; k < n; k++) {
        for(int i = 0; i < n; i++) {
            for(int j = 0; j < n; j++) {
                if(graph[i][k] + graph[k][j] < graph[i][j]) {
                    graph[i][j] = graph[i][k] + graph[k][j];
                }
            }
        }
    }

    // Print shortest path matrix
    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
            printf("%d ", graph[i][j]);
        }
        printf("\n");
    }

    return 0;
}
```

Status : Correct **Marks : 10/10**

3. Problem Statement

You are working as a backend engineer for a drone delivery logistics company that operates across multiple cities. Each city is represented as a node, and the drone flight paths between cities are represented as directed

edges with weights indicating the time (in minutes) it takes for a drone to travel between them.

Due to varying air traffic, regulations, and geography, the direct travel time between cities may not always be the fastest. Sometimes, going through intermediate cities results in shorter delivery times.

Your task is to build a system that calculates the shortest possible delivery time between every pair of cities, considering all possible intermediate routes.

To efficiently compute this, you're required to implement the Floyd-Warshall Algorithm.

Input Format

The first line of input contains an integer N representing the total number of cities.

The next N lines contains N space-separated integers, representing the delivery time matrix:

time[i][j] is the time (in minutes) taken to fly directly from City i to City j.

A value of 0 means the same city (i.e., i == j).

A value of 999 indicates no direct route between City i and City j.

Output Format

The output prints the shortest distance between every pair of cities.

If there is no shortest path between two cities, then print INF.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
0 5 999 10

999 0 3 999
999 999 0 1
999 999 999 0

Output: 0 5 8 9
INF 0 3 4
INF INF 0 1
INF INF INF 0

Answer

```
// You are using GCC
#include <stdio.h>

#define INF 999

int main() {
    int n;
    scanf("%d", &n);

    int dist[100][100];

    // Read matrix
    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
            scanf("%d", &dist[i][j]);
        }
    }

    // Floyd-Warshall Algorithm
    for(int k = 0; k < n; k++) {
        for(int i = 0; i < n; i++) {
            for(int j = 0; j < n; j++) {
                if(dist[i][k] != INF && dist[k][j] != INF &&
                   dist[i][k] + dist[k][j] < dist[i][j]) {
                    dist[i][j] = dist[i][k] + dist[k][j];
                }
            }
        }
    }

    // Print result
    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
```

```
        if(dist[i][j] == INF)
            printf("INF ");
        else
            printf("%d ", dist[i][j]);
    }
    printf("\n");
  }

  return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Given the weights and values of n items, put these items in a knapsack of capacity W to get the maximum total value in the knapsack. In other words, given two integer arrays, val[0..n-1] and wt[0..n-1] which represent values and weights associated with n items, respectively. Also given an integer W which represents knapsack capacity, find out the maximum value subset of val[] such that the sum of the weights of this subset is smaller than or equal to W. You cannot break an item, either pick the complete item or don't pick it.

Solve this problem using dynamic programming.

Input Format

The first line of input represents the number of items.

The second line of input consists of the values of each item separated by spaces.

The third line of input consists of the weights of each item separated by spaces.

The fourth line of input consists of an integer, which represents the maximum capacity of the knapsack.

Output Format

The output prints the maximum value of items that can be held by the knapsack.

Sample Test Case

Input: 3
60 100 120
10 20 30
50

Output: 220

Answer

```
// You are using GCC
#include <stdio.h>

int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    int n, W;
    scanf("%d", &n);

    int val[100], wt[100];

    // Read values
    for(int i = 0; i < n; i++) {
        scanf("%d", &val[i]);
    }

    // Read weights
    for(int i = 0; i < n; i++) {
        scanf("%d", &wt[i]);
    }

    // Read capacity
    scanf("%d", &W);

    int dp[101][1001];

    // Initialize DP table
    for(int i = 0; i <= n; i++) {
        for(int w = 0; w <= W; w++) {
            if(i == 0 || w == 0)
                dp[i][w] = 0;
```

```
            else if(wt[i-1] <= w)
                dp[i][w] = max(val[i-1] + dp[i-1][w - wt[i-1]], dp[i-1][w]);
            else
                dp[i][w] = dp[i-1][w];
        }
    }

    printf("%d", dp[n][W]);

    return 0;
}
```

Status : Correct **Marks : 10/10**

5. Problem Statement

Sarah loves challenges and has recently taken up a new programming problem. She is fascinated by the classic "0/1 Knapsack Problem" and wants to create a program that can efficiently solve it.

The 0/1 Knapsack Problem involves selecting a combination of items with given weights and values to maximize the total value, while not exceeding a given weight capacity.

Write a program that takes input for the 0/1 Knapsack Problem and outputs the maximum value that can be achieved, as well as the selected weights that contribute to this maximum value.

Note: The weights are printed in reverse order of the input, meaning the algorithm starts checking from the last item and prints items that are included first.

Input Format

The first line contains an integer n, representing the number of items available.

The second line contains n integers separated by space, representing the values of the items. The ith integer corresponds to the value of the ith item.

The third line contains n integers separated by space, representing the weights

of the items. The ith integer corresponds to the weight of the ith item.

The fourth line contains an integer W, representing the maximum weight capacity of the knapsack.

Output Format

The first line output displays "Maximum value: " followed by an integer, representing the maximum value that can be achieved.

The second line output displays "Selected weights: " followed by space-separated integers, representing the selected weights contributing to the maximum value.

Refer to the sample outputs for the exact format.

Sample Test Case

Input: 3
60 100 120
10 20 30
50
Output: Maximum value: 220
Selected weights: 30 20

Answer

```
// You are using GCC
#include <stdio.h>

int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    int n, W;
    scanf("%d", &n);

    int val[10], wt[10];

    // values
    for(int i = 0; i < n; i++)
```

```
    scanf("%d", &val[i]);

    // weights
    for(int i = 0; i < n; i++)
        scanf("%d", &wt[i]);

    scanf("%d", &W);

    int dp[11][1001];

    // Build DP table
    for(int i = 0; i <= n; i++) {
        for(int w = 0; w <= W; w++) {
            if(i == 0 || w == 0)
                dp[i][w] = 0;
            else if(wt[i-1] <= w)
                dp[i][w] = max(val[i-1] + dp[i-1][w-wt[i-1]], dp[i-1][w]);
            else
                dp[i][w] = dp[i-1][w];
        }
    }

    printf("Maximum value: %d\n", dp[n][W]);

    // Backtrack to find selected weights (reverse order)
    printf("Selected weights: ");
    int w = W;

    for(int i = n; i > 0; i--) {
        if(dp[i][w] != dp[i-1][w]) {
            printf("%d ", wt[i-1]);
            w = w - wt[i-1];
        }
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 6_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Anitha is working on packing expensive artifacts into a container that has a limited weight capacity. Each artifact has a weight and a value, and Anitha wants to maximize the total worth of artifacts she can carry, even if it means taking only a fraction of an artifact when the container is nearly full.

The maximum worth is calculated as:

Maximum Worth = Σ (value[i] * fraction_taken[i]),

where fraction_taken[i] = min(1, remaining_capacity / weight[i])

Write a program to ensure that Anitha can calculate the maximum worth of objects she can carry in the container.

Input Format

The first line contains an integer N, representing the number of items.

The second line contains N space-separated integers representing the weights of the items.

The third line contains N space-separated integers representing the values of the items.

The fourth line contains an integer representing the capacity of the container.

Output Format

The output prints a single line showing the total maximum worth of objects carried as a double with exactly two decimal places, in the following format:

"Objects worth Rs.X.YY"

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3
10 20 30
60 100 120
50
Output: Objects worth Rs.240.00

Answer

```
// You are using GCC
#include <stdio.h>

typedef struct {
    int weight;
    int value;
    double ratio;
} Item;
```

```
int main() {
    int n, capacity;
    scanf("%d", &n);

    Item items[10];

    // read weights
    for(int i = 0; i < n; i++)
        scanf("%d", &items[i].weight);

    // read values
    for(int i = 0; i < n; i++)
        scanf("%d", &items[i].value);

    scanf("%d", &capacity);

    // calculate ratio
    for(int i = 0; i < n; i++)
        items[i].ratio = (double)items[i].value / items[i].weight;

    // sort by ratio (descending)
    for(int i = 0; i < n-1; i++) {
        for(int j = i+1; j < n; j++) {
            if(items[i].ratio < items[j].ratio) {
                Item temp = items[i];
                items[i] = items[j];
                items[j] = temp;
            }
        }
    }

    double total = 0.0;

    // fractional knapsack
    for(int i = 0; i < n; i++) {
        if(capacity >= items[i].weight) {
            total += items[i].value;
            capacity -= items[i].weight;
        } else {
            total += items[i].ratio * capacity;
            break;
```

```
    }
  }

  printf("Objects worth Rs.%.2lf", total);

  return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Raju is a professional hiker preparing for a long trekking expedition. He has a backpack that can hold a maximum weight of W kilograms. There are N essential items you want to carry, each with a specific weight and importance value (utility score). His goal is to maximize the total importance value of the items you take while ensuring that the total weight does not exceed the backpack's capacity.

He can either include or exclude each item—meaning he cannot take fractions of an item (e.g., you cannot take half of a tent). Given the weights and importance values of the items, determine the maximum possible importance value he can carry in his backpack. Help him to achieve his task.

Input Format

The first line contains two integers, N (number of items) and W (maximum weight the backpack can carry).

The second line contains N integers, representing the weights of the items.

The third line contains N integers, representing the importance values of the items.

Output Format

The output prints a single integer, the maximum importance value that can be achieved without exceeding the weight limit.

vtu27632

Refer to the sample input and output for formatting specifications.

Sample Test Case

Input: 4 5
2 3 4 5
3 4 5 6

Output: 7

Answer

```
// You are using GCC
#include <stdio.h>

int max(int a, int b) {
    return (a > b) ? a : b;
}

int main() {
    int n, W;
    scanf("%d %d", &n, &W);

    int wt[20], val[20];

    // read weights
    for(int i = 0; i < n; i++)
        scanf("%d", &wt[i]);

    // read values
    for(int i = 0; i < n; i++)
        scanf("%d", &val[i]);

    int dp[21][100001];

    // initialize
    for(int i = 0; i <= n; i++) {
        for(int w = 0; w <= W; w++) {
            if(i == 0 || w == 0)
                dp[i][w] = 0;
            else if(wt[i-1] <= w)
                dp[i][w] = max(val[i-1] + dp[i-1][w - wt[i-1]],
                               dp[i-1][w]);
```

```
        else
            dp[i][w] = dp[i-1][w];
        }
    }

    printf("%d", dp[n][W]);

    return 0;
}
```

Status : Wrong ***Marks : 0/10***

3. Problem Statement

Rohit is responsible for scheduling flights for an airline company. He has a list of N flights numbered from 0 to N-1. Some flights have specific constraints that require them to depart after other flights.

Write a program to help Rohit determine if it's possible to create a flight schedule that adheres to these constraints using Warshall's algorithm.

Example 1

Input:

5

0 1

1 2

2 3

3 4

4 5

Output:

Yes

Explanation:

Flight 0 must depart after Flight 1.

Flight 1 must depart after Flight 2.

Flight 2 must depart after Flight 3.

Flight 3 must depart after Flight 4.

Flight 4 must depart after Flight 5.

There are no circular dependencies or conflicts in the schedule, so it is possible to create a flight schedule that adheres to the constraints.

Example 2

Input:

6

0 1

1 2

2 3

3 4

4 5

5 0

Output:

No

Explanation:

Flight 0 must depart after Flight 1.

Flight 1 must depart after Flight 2.

Flight 2 must depart after Flight 3.

Flight 3 must depart after Flight 4.

Flight 4 must depart after Flight 5.

Flight 5 must depart after Flight 0.

vtu27632

There is a circular dependency in the flight constraints. Therefore, it is not possible to create a flight schedule that follows the constraints.

Input Format

The first line of input consists of an integer N, representing the number of flights.

The following N lines consist of two space-separated integers each: the flight number and the flight number that must depart before it.

Output Format

If it is possible to create a flight schedule that adheres to the constraints, print "Yes".

Otherwise, print "No".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5
0 1
1 2
2 3
3 4
4 5
Output: Yes

Answer

```
// You are using GCC
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int u[10], v[10];
    int reach[20][20] = {0};
    int maxNode = 0;
```

```
    // read constraints
    for(int i = 0; i < n; i++) {
        scanf("%d %d", &u[i], &v[i]);
        reach[u[i]][v[i]] = 1;

        if(u[i] > maxNode) maxNode = u[i];
        if(v[i] > maxNode) maxNode = v[i];
    }

    int nodes = maxNode + 1;

    // Warshall's Algorithm
    for(int k = 0; k < nodes; k++) {
        for(int i = 0; i < nodes; i++) {
            for(int j = 0; j < nodes; j++) {
                if(reach[i][k] && reach[k][j])
                    reach[i][j] = 1;
            }
        }
    }

    // check cycle
    for(int i = 0; i < nodes; i++) {
        if(reach[i][i] == 1) {
            printf("No");
            return 0;
        }
    }

    printf("Yes");
    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

A traveler needs to find the shortest path between every pair of cities in a road network. The cities are connected by roads, each with a specific travel cost. To do this, the traveler uses the Floyd-Warshall Algorithm to calculate the shortest distances between every pair of cities in a given edge-

weighted undirected graph.

Example1

Input:

4

3

0 1 2

1 2 3

2 3 4

Output:

Original matrix

0 2 INF INF

2 0 3 INF

INF 3 0 4

INF INF 4 0

Shortest path matrix

0 2 5 9

2 0 3 7

5 3 0 4

9 7 4 0

Explanation:

Given: 4 nodes (0, 1, 2, 3) and 3 edges: 0 1 (weight 2), 1 2 (weight 3), 2 3 (weight 4)

Any node pair without a direct edge is considered INF (unreachable initially).

Step 1: Construct Initial Graph (Original Matrix)

vtu27632

0 2 INF INF

2 0 3 INF

INF 3 0 4

INF INF 4 0

Diagonal elements (self to self) are 0.If no direct path exists, it's INF.Step 2: Running Floyd-Warshall Algorithm

Using node 0 as an intermediate: No updates since it only connects to node 1.

Using node 1 as an intermediate: 0 2 via 1: 0 1 (2) + 1 2 (3) = 5

2 0 also updates to 5.

Using node 2 as an intermediate: 0 3 via 2: 0 2 (5) + 2 3 (4) = 9

1 3 via 2: 1 2 (3) + 2 3 (4) = 7

Using node 3 as an intermediate: No further updates.

Step 3: Final Shortest Path Matrix

0 2 5 9

2 0 3 7

5 3 0 4

9 7 4 0

Input Format

The first line contains an integer V representing the number of cities (vertices) in the network.

The second line contains an integer E representing the number of roads (edges) in the network.

The next E lines each contain three space-separated integers u, v, w, where u and v represent the cities connected by a road, and w represents the travel cost (weight) of the road.

Output Format

The first line of output prints the original matrix, where each entry represents the

direct travel cost between two cities. If there is no direct road between two cities, represent the cost as INF.

Then, print the shortest path matrix, where each entry represents the shortest travel cost between every pair of cities, computed using the Floyd-Warshall algorithm.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
3
0 1 2
1 2 3
2 3 4

Output: Original matrix
0 2 INF INF
2 0 3 INF
INF 3 0 4
INF INF 4 0

Shortest path matrix
0 2 5 9
2 0 3 7
5 3 0 4
9 7 4 0

Answer

```
// You are using GCC
#include <stdio.h>

#define INF 999999

int main() {
    int V, E;
    scanf("%d", &V);
    scanf("%d", &E);

    int dist[1000][1000];
```

```
// initialize matrix
for(int i = 0; i < V; i++) {
    for(int j = 0; j < V; j++) {
        if(i == j)
            dist[i][j] = 0;
        else
            dist[i][j] = INF;
    }
}

// read edges (undirected)
for(int i = 0; i < E; i++) {
    int u, v, w;
    scanf("%d %d %d", &u, &v, &w);
    dist[u][v] = w;
    dist[v][u] = w;
}

// print original matrix
printf("Original matrix\n");
for(int i = 0; i < V; i++) {
    for(int j = 0; j < V; j++) {
        if(dist[i][j] == INF)
            printf("INF ");
        else
            printf("%d ", dist[i][j]);
    }
    printf("\n");
}

printf("\n");

// Floyd-Warshall
for(int k = 0; k < V; k++) {
    for(int i = 0; i < V; i++) {
        for(int j = 0; j < V; j++) {
            if(dist[i][k] != INF && dist[k][j] != INF &&
               dist[i][k] + dist[k][j] < dist[i][j]) {
                dist[i][j] = dist[i][k] + dist[k][j];
            }
        }
```

```
    }
  }

  // print shortest path matrix
  printf("Shortest path matrix\n");
  for(int i = 0; i < V; i++) {
    for(int j = 0; j < V; j++) {
      if(dist[i][j] == INF)
        printf("INF ");
      else
        printf("%d ", dist[i][j]);
    }
    printf("\n");
  }

  return 0;
}
```

Status : Correct **Marks : 10/10**

5. Problem Statement

A person starts walking from position X = 0, find the probability of reaching exactly on X = N if she can only take either 2 steps or 3 steps. The probability for step length 2 is given i.e. P, and the probability for step length 3 is 1 – P.

Write a program for the same.

Note: Use Dynamic Programming

Example

Input: N = 5, P = 0.20

Output: 0.32

Explanation:

There are two ways to reach 5.

2+3 with probability = 0.2 * 0.8 = 0.16

3+2 with probability = 0.8 * 0.2 = 0.16

So, total probability = 0.32.

Input Format

The input consists of an integer N representing the target position and a double-point number P representing the probability of taking a step of length 2, separated by a space.

Output Format

The output prints a double-point number representing the probability of reaching the exact position N, formatted to two decimal places.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5 0.20

Output: 0.32

Answer

```
// You are using GCC
#include <stdio.h>

int main() {
    int N;
    double P;
    scanf("%d %lf", &N, &P);

    double dp[25] = {0};

    dp[0] = 1.0;

    for(int i = 1; i <= N; i++) {
        if(i - 2 >= 0)
            dp[i] += dp[i - 2] * P;

        if(i - 3 >= 0)
            dp[i] += dp[i - 3] * (1 - P);
```

```
    }
    printf("%.2lf", dp[N]);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 7_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. The frequencies of letters in a file are:

s = 17, k = 24, y = 37

A Huffman tree is constructed, and we assign 0 to the left branch and 1 to the right branch at each node.

Which of the following is the Huffman code for the letter 's'?

Answer

10

Status : Correct ***Marks : 1/1***

2. In Huffman coding, does data in a tree always occur?

vtu27632

Answer

Leaves

Status : Correct ***Marks : 1/1***

3. Which of the following algorithms is the best approach for solving Huffman codes?

Answer

Greedy algorithm

Status : Correct ***Marks : 1/1***

4. From the following given tree, what is the computed codeword for ‘c’?

</a>

Answer

110

Status : Correct ***Marks : 1/1***

5. From the following given tree, what is the code word for the character 'a'?

</a>

Answer

011

Status : Correct ***Marks : 1/1***

6. Kruskal’s algorithm is used to _____.

Answer

Find minimum spanning tree

Status : Correct ***Marks : 1/1***

7. Consider the following graph:

Which edges would be included in the minimum spanning tree using Prim's algorithm starting from vertex A?

Answer

AB, BD, DE, EF, FC

Status : Correct ***Marks : 1/1***

8. Which of the following is true?

Answer

Prim’s algorithm initializes with a vertex

Status : Correct ***Marks : 1/1***

9. Prim’s algorithm can be efficiently implemented using _____ for graphs with greater density.

Answer

d-ary heap

Status : Correct ***Marks : 1/1***

10. Which of the following is false about Prim’s algorithm?

Answer

It constructs MST by selecting edges in increasing order of their weights

Status : Correct ***Marks : 1/1***

vtu27632

11. What is the worst-case time complexity of Prim's algorithm if the adjacency matrix is used?

Answer

O(V2)

Status : Correct ***Marks : 1/1***

12. Consider a graph G = (V, E), where V = { v1,v2,...,v100 }, E = { (vi, vj) 1≤ i < j ≤ 100} and the weight of the edge (vi, vj) is i–j . The weight of the minimum spanning tree of G is _____.

Answer

99

Status : Correct ***Marks : 1/1***

13. An undirected graph G(V, E) contains n (n > 2) nodes named v1 , v2 , ...vn. Two nodes vi , vj are connected if and only if 0 < |i – j| <= 2. Each edge (vi, vj) is assigned a weight i + j. A sample graph with n = 4 is shown below. What will be the cost of the minimum spanning tree (MST) of such a graph with n nodes?

</a>

Answer

n^2 – n + 1

Status : Correct ***Marks : 1/1***

14. An undirected graph G has n nodes. Its adjacency matrix is given by an n × n square matrix whose (i) diagonal elements are 0's and (ii) non-diagonal elements are 1's. which one of the following is TRUE?

Answer

Graph G has multiple distinct MSTs, each of cost n-1

Status : Correct ***Marks : 1/1***

15. Consider a weighted complete graph G on the vertex set {v1,v2 ,v} such that the weight of the edge (v,,v) is 2|i-j|. The weight of a minimum spanning tree of G is:

Answer

2n-2

Status : Correct ***Marks : 1/1***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 7_COD

Attempt : 1
Total Mark : 30
Marks Obtained : 26.5

Section 1 : Coding

1. Problem Statement

Prim’s Algorithm for Minimum Spanning Tree (MST):

Sita is planning to lay roads to connect 5 locations in her city. The distances between locations are given as an adjacency matrix, where a value of 0 indicates no direct road between two locations (locations are numbered 0 to 4).

Help her find the Minimum Spanning Tree (MST) using Prim's Algorithm so that all locations are connected with the minimum total road length. Print each MST edge and its weight in the order they are added to the MST.

Input Format

The input consists of 5 lines, each containing 5 space-separated integers,

representing the adjacency matrix of the graph. A value of 0 indicates no direct connection between two locations.

Output Format

The first line of output prints the header: 'Edge \tWeight'

Each of the next V-1 lines prints one MST edge in the format:

'u - v\tw'

where u is the parent location, v is the child location, and w is the integer edge weight, printed in the order edges are added to the MST (MST discovery order).

Refer to the sample output for formatting specifications.

Refer to the sample output for format specifications.

Sample Test Case

Input: 0 2 0 6 0
2 0 3 8 5
0 3 0 8 7
6 8 0 0 9
0 5 7 9 0

Output: Edge Weight
0 - 1 2
1 - 2 3
1 - 4 5
0 - 3 6

Answer

```
// You are using GCC
#include <stdio.h>
#include <limits.h>

#define V 5
```

```
// Function to find the vertex with minimum key value
int minKey(int key[], int mstSet[]) {
    int min = INT_MAX, min_index;

    for (int v = 0; v < V; v++) {
        if (mstSet[v] == 0 && key[v] < min) {
            min = key[v];
            min_index = v;
        }
    }
    return min_index;
}

int main() {
    int graph[V][V];

    // Input adjacency matrix
    for (int i = 0; i < V; i++) {
        for (int j = 0; j < V; j++) {
            scanf("%d", &graph[i][j]);
        }
    }

    int parent[V];   // To store MST
    int key[V];      // Minimum weight
    int mstSet[V];   // Included in MST or not

    // Initialize all keys as infinite
    for (int i = 0; i < V; i++) {
        key[i] = INT_MAX;
        mstSet[i] = 0;
    }

    // Start from vertex 0
    key[0] = 0;
    parent[0] = -1;

    // MST will have V vertices
    for (int count = 0; count < V - 1; count++) {
        int u = minKey(key, mstSet);
        mstSet[u] = 1;
```

```
        // Update key values
        for (int v = 0; v < V; v++) {
            if (graph[u][v] && mstSet[v] == 0 && graph[u][v] < key[v]) {
                parent[v] = u;
                key[v] = graph[u][v];
            }
        }
    }

    // Print result
    printf("Edge \tWeight\n");
    for (int i = 1; i < V; i++) {
        printf("%d - %d\t%d\n", parent[i], i, graph[parent[i]][i]);
    }

    return 0;
}
```

Status : Partially correct **Marks : 6.5/10**

2. Problem statement

Alex is a network engineer tasked with laying cables to connect multiple offices in the city. Each possible cable connection between two offices has an associated cost. To minimize the total cabling cost while ensuring all offices are connected, Alex decides to use Kruskal's Algorithm to find the Minimum Spanning Tree (MST) of the office network.

Given a connected, undirected, weighted graph with V vertices (numbered 0 to V-1) and E edges, find the MST and print each edge included along with the total minimum cost.

Input Format

The first line contains an integer V, representing the number of vertices (numbered 0 to V-1).

The second line contains an integer E, representing the number of edges.

Each of the next E lines contains three space-separated integers u, v, and w, representing an undirected edge between vertex u and vertex v with weight w

Output Format

The first line of output prints: 'Edges in the constructed MST:'

Each of the next V-1 lines prints one MST edge in the format:

'u -- v == weight'

where u and v are vertex numbers (integers) and weight is the edge cost (integer), printed in the order edges are added to the MST (ascending weight order).

The last line prints: 'Minimum Spanning Tree: totalCost'

where totalCost is an integer representing the total MST weight.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
3
0 1 2
1 2 2
0 2 2
Output: Edges in the constructed MST:
0 -- 1 == 2
1 -- 2 == 2
Minimum Spanning Tree: 4

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

struct Edge {
    int u, v, w;
```

```
};

// Compare edges by weight
int compare(const void *a, const void *b) {
    return ((struct Edge *)a)->w - ((struct Edge *)b)->w;
}

// Find with path compression
int find(int parent[], int i) {
    if (parent[i] != i)
        parent[i] = find(parent, parent[i]);
    return parent[i];
}

// Union of two sets
void unionSet(int parent[], int rank[], int x, int y) {
    int rootX = find(parent, x);
    int rootY = find(parent, y);

    if (rank[rootX] < rank[rootY])
        parent[rootX] = rootY;
    else if (rank[rootX] > rank[rootY])
        parent[rootY] = rootX;
    else {
        parent[rootY] = rootX;
        rank[rootX]++;
    }
}

int main() {
    int V, E;
    scanf("%d", &V);
    scanf("%d", &E);

    struct Edge edges[E];

    // Input edges
    for (int i = 0; i < E; i++) {
        scanf("%d %d %d", &edges[i].u, &edges[i].v, &edges[i].w);
    }

    // Sort edges by weight
```

```
    qsort(edges, E, sizeof(edges[0]), compare);

    int parent[V], rank[V];

    // Initialize disjoint sets
    for (int i = 0; i < V; i++) {
        parent[i] = i;
        rank[i] = 0;
    }

    int count = 0;
    int totalCost = 0;

    printf("Edges in the constructed MST:\n");

    for (int i = 0; i < E && count < V - 1; i++) {
        int u = edges[i].u;
        int v = edges[i].v;

        int setU = find(parent, u);
        int setV = find(parent, v);

        // If including this edge doesn't form a cycle
        if (setU != setV) {
            printf("%d -- %d == %d\n", u, v, edges[i].w);
            totalCost += edges[i].w;
            unionSet(parent, rank, setU, setV);
            count++;
        }
    }

    printf("Minimum Spanning Tree: %d", totalCost);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

You are designing a data compression tool that uses Huffman Coding to

encode data efficiently.

Write a program to read a set of characters along with their corresponding Huffman variable-length binary codes, and use them to generate the encoded binary string for a given input message.

It is guaranteed that every character in the input message has a corresponding Huffman code in the provided code table.

Input Format

The first line contains an integer N (integer), representing the number of characters in the code table.

Each of the next N lines contains a character C and its corresponding Huffman code (a binary string of 0s and 1s), separated by a space.

The last line contains the input message (a string of characters) that needs to be encoded. Every character in the message is guaranteed to have a corresponding entry in the code table.

Output Format

The output prints 'Coded Data: ' followed by a binary string (a sequence of 0s and 1s) representing the encoded message, obtained by concatenating the Huffman code of each character in the input message in order.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 10
D 0100
U 0000
F 0101
M 0001
A 0010
N 0011
C 1100
O 1101
E 1110

H 1111
HUFF
Output: Coded Data: 1111000001010101

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

int main() {
    int n;
    scanf("%d", &n);

    char ch;
    char code[26][21];  // Store codes for A-Z (max length 20)

    // Initialize codes
    for (int i = 0; i < 26; i++) {
        code[i][0] = '\0';
    }

    // Input Huffman codes
    for (int i = 0; i < n; i++) {
        char temp[21];
        scanf(" %c %s", &ch, temp);
        strcpy(code[ch - 'A'], temp);
    }

    char message[101];
    scanf("%s", message);

    printf("Coded Data: ");

    // Encode message
    for (int i = 0; message[i] != '\0'; i++) {
        printf("%s", code[message[i] - 'A']);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 7_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 37.5

Section 1 : Coding

1. Problem Statement

Mary is planning to build a railway network to connect cities efficiently. She needs a program that, given the number of cities and the segments between them, determines the minimum cost to connect all cities using an undirected weighted graph.

Implement a solution using Kruskal's Algorithm to find the Minimum Spanning Tree (MST) of the city network. If it is not possible to connect all cities, output an appropriate message

Example

Input

3

vtu27632

3

0 1 4

1 2 5

0 2 3

Output

7

Explanation

The input specifies 3 cities and 3 track segments with their corresponding weights.

The track segments are:

Track Segment 1: Connects city 0 and city 1, with a weight of 4.

Track Segment 2: Connects city 1 and city 2 with a weight of 5.

Track Segment 3: Connects city 0 and city 2 with a weight of 3.

The algorithm finds the minimum cost to build railway tracks connecting all cities. In this case, the minimum spanning tree includes track segment 3 (0-2 with weight 3) and track segment 1 (0-1 with weight 4). The total cost is 3 + 4 = 7.

Input Format

The first line of input contains an integer num_cities, representing the number of cities (numbered 0 to num_cities - 1).

The second line contains an integer num_segments, representing the number of undirected segments (edges) between cities.

The next num_segments lines each contain three space-separated integers: source, destination, and weight, representing an undirected segment between city source and city destination with the given cost.

Output Format

The first line of output prints an integer representing the minimum cost to connect all cities.

If it is not possible to connect all the cities, the output prints 'It is not possible to connect all cities' (without a period).

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
3
0 1 4
1 2 5
0 2 3
Output: 7

Answer

```
#include <stdio.h>

#define MAX 10

struct Edge {
    int u, v, w;
};

int parent[MAX];

int find(int i) {
    if (parent[i] == i)
        return i;
    return parent[i] = find(parent[i]);
}

void unionSet(int a, int b) {
    int rootA = find(a);
    int rootB = find(b);
    parent[rootA] = rootB;
}

int main() {
    int num_cities, num_segments;
```

```
scanf("%d", &num_cities);
scanf("%d", &num_segments);

struct Edge edges[MAX];

for(int i = 0; i < num_segments; i++) {
    scanf("%d %d %d", &edges[i].u, &edges[i].v, &edges[i].w);
}

// sort edges by weight
for(int i = 0; i < num_segments - 1; i++) {
    for(int j = i + 1; j < num_segments; j++) {
        if(edges[i].w > edges[j].w) {
            struct Edge temp = edges[i];
            edges[i] = edges[j];
            edges[j] = temp;
        }
    }
}

// initialize parent
for(int i = 0; i < num_cities; i++)
    parent[i] = i;

int count = 0;
int cost = 0;

// Kruskal
for(int i = 0; i < num_segments; i++) {
    int u = edges[i].u;
    int v = edges[i].v;

    if(find(u) != find(v)) {
        unionSet(u, v);
        cost += edges[i].w;
        count++;
    }
}

if(count == num_cities - 1)
    printf("%d", cost);
else
```

```
    printf("It is not possible to connect all cities");

  return 0;
}
```

Status : Partially correct ***Marks : 7.5/10***

2. Problem Statement

Maya, a project planner, must connect multiple office branches using network cables while keeping the total cost within a given budget. Each possible connection between two branches has an associated cost.

Write a program to find the Minimum Spanning Tree (MST) of the branch network using Kruskal's Algorithm on an undirected weighted graph. If the total cost of the MST is within the given budget, display the cost. Otherwise, indicate that it is not possible.

It is guaranteed that the graph is connected in all test cases

Input Format

The first line contains three space-separated integers V, E, and budget, representing the number of branches (vertices, numbered 1 to V), the number of possible connections (edges), and the total budget respectively.

Each of the next E lines contains three space-separated integers src, dest, and weight, representing an undirected connection between branch src and branch dest with cost weight.

Output Format

If the MST cost is within the budget, the output prints:

'Minimum Cost Spanning Tree within the budget: X'

where X is an integer representing the total minimum cost.

Otherwise, the output prints:

'A valid MST within the budget is not possible.'

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3 3 5
1 2 2
2 3 3
3 1 4
Output: Minimum Cost Spanning Tree within the budget: 5

Answer

```
// You are using GCC
#include <stdio.h>

#define MAXE 1000
#define MAXV 101

struct Edge {
    int u, v, w;
};

int parent[MAXV];

int find(int x) {
    if(parent[x] == x)
        return x;
    return parent[x] = find(parent[x]);
}

void unionSet(int a, int b) {
    int pa = find(a);
    int pb = find(b);
    parent[pa] = pb;
}

int main() {
    int V, E;
    long long budget;
    scanf("%d %d %lld", &V, &E, &budget);
```

```
struct Edge edges[MAXE];

for(int i = 0; i < E; i++)
    scanf("%d %d %d", &edges[i].u, &edges[i].v, &edges[i].w);

// sort edges by weight
for(int i = 0; i < E-1; i++) {
    for(int j = i+1; j < E; j++) {
        if(edges[i].w > edges[j].w) {
            struct Edge temp = edges[i];
            edges[i] = edges[j];
            edges[j] = temp;
        }
    }
}

// initialize parent
for(int i = 1; i <= V; i++)
    parent[i] = i;

long long cost = 0;
int count = 0;

// Kruskal
for(int i = 0; i < E; i++) {
    int u = edges[i].u;
    int v = edges[i].v;

    if(find(u) != find(v)) {
        unionSet(u, v);
        cost += edges[i].w;
        count++;

        if(count == V - 1)
            break;
    }
}

if(cost <= budget)
    printf("Minimum Cost Spanning Tree within the budget: %lld", cost);
else
    printf("A valid MST within the budget is not possible.");
```

```
    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Sita is planning to connect multiple locations in her city with roads. Each possible road between two locations has a construction distance (in kilometres). The city is represented as an undirected weighted graph using an adjacency matrix, where a value of 0 indicates no direct road between two locations (locations are numbered 0 to numLocations - 1).

To minimise the overall construction distance, she decides to use Prim's Algorithm to construct the Minimum Spanning Tree (MST). Help her find the MST edges and the total minimum distance.

Input Format

The first line of input contains an integer numLocations, representing the number of locations (numbered 0 to numLocations - 1).

The next numLocations lines each contain numLocations space-separated integers representing the adjacency matrix, where graph[i][j] is the distance between location i and location j. A value of 0 indicates no direct road between those two locations.

Output Format

The first line of output prints: 'Location\tDistance'

Each of the next numLocations - 1 lines prints the MST edge in the format:

'parent -> child \t\t\t dist km'

where parent is the parent location number, child is the child location number, and dist is the edge weight (integer) in kilometres.

The last line of output prints: 'Minimum total distance: totalCost km'

where totalCost is an integer.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 2
0 5
5 0
Output: Location Distance
0 -> 1 5 km
Minimum total distance: 5 km

Answer

```
#include <stdio.h>

#define MAX 10
#define INF 1000000

int minKey(int key[], int mstSet[], int n) {
    int min = INF, index = -1;
    for(int i = 0; i < n; i++) {
        if(!mstSet[i] && key[i] < min) {
            min = key[i];
            index = i;
        }
    }
    return index;
}

int main() {
    int n;
    scanf("%d", &n);

    int graph[MAX][MAX];

    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
```

```
            scanf("%d", &graph[i][j]);
            if(i != j && graph[i][j] == 0)
                graph[i][j] = INF;
        }
    }

    int parent[MAX], key[MAX], mstSet[MAX];

    for(int i = 0; i < n; i++) {
        key[i] = INF;
        mstSet[i] = 0;
    }

    key[0] = 0;
    parent[0] = -1;

    for(int count = 0; count < n - 1; count++) {
        int u = minKey(key, mstSet, n);
        mstSet[u] = 1;

        for(int v = 0; v < n; v++) {
            if(!mstSet[v] && graph[u][v] < key[v]) {
                parent[v] = u;
                key[v] = graph[u][v];
            }
        }
    }

    int total = 0;

    printf("Location\tDistance\n");
    for(int i = 1; i < n; i++) {
        printf("%d -> %d\t\t\t%d km\n", parent[i], i, key[i]);
        total += key[i];
    }

    printf("Minimum total distance: %d km", total);

    return 0;
}
```

Status : Wrong ***Marks : 0/10***

4. Problem Statement

Riya works at a data tools company that needs a compact representation of frequently used characters for fast transmission. She decides to use Huffman Coding, a lossless compression technique that assigns shorter bit-strings to more frequent symbols and longer bit-strings to less frequent ones.

The Huffman codes should be printed in the order that leaf nodes are encountered during a left-to-right traversal of the constructed Huffman tree.

Write a program that builds a Huffman tree from a list of symbols with their frequencies and prints the Huffman codes for each symbol.

Input Format

The first line contains an integer n, representing the number of distinct symbols.

Each of the next n lines contains a single printable character (the symbol) followed by a space and a positive integer (the frequency), representing the symbol and its occurrence count.

Output Format

The output prints n lines, one per symbol, in the order that leaf nodes are encountered during a left-to-right traversal of the Huffman tree (left child before right child at every internal node).

Each line prints the symbol followed by a colon, a space, and its Huffman code (a binary string of 0s and 1s):

'<symbol>: <binary_code>'

Refer to the sample output for the formatting specifications.

Sample Test Case

vtu27632

Input: 2
a 1
b 2

Output: a: 0
b: 1

Answer

```
#include <stdio.h>
#include <stdlib.h>

typedef struct Node {
    char ch;
    int freq;
    struct Node *left, *right;
} Node;

Node* createNode(char ch, int freq) {
    Node* n = (Node*)malloc(sizeof(Node));
    n->ch = ch;
    n->freq = freq;
    n->left = n->right = NULL;
    return n;
}

void sort(Node* arr[], int n) {
    for(int i=0;i<n-1;i++) {
        for(int j=i+1;j<n;j++) {
            if(arr[i]->freq > arr[j]->freq) {
                Node* t = arr[i];
                arr[i] = arr[j];
                arr[j] = t;
            }
        }
    }
}

void printCodes(Node* root, char code[], int top) {
    if(root->left) {
        code[top] = '0';
        printCodes(root->left, code, top+1);
    }
```

```
    if(root->right) {
        code[top] = '1';
        printCodes(root->right, code, top+1);
    }

    if(!root->left && !root->right) {
        code[top] = '\0';
        printf("%c: %s\n", root->ch, code);
    }
}

int main() {
    int n;
    scanf("%d", &n);

    Node* arr[256];

    for(int i=0;i<n;i++) {
        char ch;
        int f;
        scanf(" %c %d", &ch, &f);
        arr[i] = createNode(ch, f);
    }

    int size = n;

    // build Huffman tree
    while(size > 1) {
        sort(arr, size);

        Node* left = arr[0];
        Node* right = arr[1];

        Node* newNode = createNode('$', left->freq + right->freq);
        newNode->left = left;
        newNode->right = right;

        for(int i=2;i<size;i++)
            arr[i-2] = arr[i];

        arr[size-2] = newNode;
        size--;
```

```
    }
    Node* root = arr[0];
    char code[256];

    printCodes(root, code, 0);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

In a data science class, Professor Huffman demonstrates how encoded messages can be decoded using a pre-built Huffman tree.

Given a Huffman code table (mapping each character to its binary code) and an encoded binary message, decode the message back to its original text by traversing the Huffman tree.

The code table is guaranteed to be a valid prefix-free Huffman code.

The encoded message consists only of '0' and '1' characters, and every bit maps to exactly one symbol in the Huffman tree

The tree is defined as follows:

Internal nodes are represented by "*".The left edge (0) leads to the symbol "A".The right edge (1) leads to the symbol "B".

This means:

"0" A"1" B

Your task is to decode a given encoded message (a string of 0s and 1s) back into its original form consisting of "A" and "B".

Input Format

The first line contains an integer n, representing the number of symbols in the code table.

Each of the next n lines contains a character and its Huffman code (binary string), separated by a space.

The last line contains the encoded binary message (a string of 0s and 1s) to be decoded

Output Format

The output prints the decoded message as a sequence of characters ('A' or 'B'), followed by a newline.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 11100011100

Output: BBBAAABBBAA

Answer

```
#include <stdio.h>
#include <string.h>

int main() {
    char encoded[200];
    scanf("%s", encoded);

    for(int i = 0; encoded[i] != '\0'; i++) {
        if(encoded[i] == '0')
            printf("A");
        else
            printf("B");
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 7_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Bob is working on a project involving network optimization. He needs a program to find the Minimum Spanning Tree (MST) of a given undirected weighted graph with 5 nodes (numbered 0 to 4).

The graph is represented as a 5×5 symmetric adjacency matrix, where a value of 0 indicates no direct connection between two nodes. Implement Prim's Algorithm to find the MST and print each edge with its weight.

Example

Input

0 3 0 5 0

4 0 2 3 5

vtu27632

0 3 0 8 7

3 8 0 0 9

0 5 7 2 0

Output

Edge Weight

0 - 1 4

1 - 2 3

1 - 3 8

1 - 4 5

Explanation

In the given 5x5 matrix representing an undirected graph, Bob has specified the weights of edges. The Prim's algorithm is applied to find the Minimum Spanning Tree (MST). The output displays the edges along with their corresponding weights, forming the optimal tree connecting all vertices. In this case, the MST includes edges (0-1), (1-2), (1-3), and (1-4) with weights 4, 3, 8, and 5 respectively, ensuring minimal total weight for network optimization.

Input Format

The input consists of 5 lines, each containing 5 space-separated integers, representing the adjacency matrix of the graph. A value of 0 indicates no direct connection between two nodes. The matrix is symmetric (graph[i][j] = graph[j][i]) since the graph is undirected.

Output Format

The first line of output prints the header: 'Edge \tWeight'

Each of the next 4 lines prints one MST edge in the format:

'u - v \tw'

vtu27632

where u is the parent node, v is the child node, and w is the integer edge weight, printed in ascending order of child node index (node-index order).

Refer to the sample output for formatting specifications.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 0 2 0 6 0
2 0 3 8 5
0 3 0 8 7
6 8 0 0 9
0 5 7 9 0

Output: Edge Weight
0 - 1 2
1 - 2 3
0 - 3 6
1 - 4 5

Answer

```
// You are using GCC
#include <stdio.h>
#define V 5
#define INF 9999

int minKey(int key[], int mstSet[]) {
    int min = INF, min_index;

    for (int v = 0; v < V; v++) {
        if (mstSet[v] == 0 && key[v] < min) {
            min = key[v];
            min_index = v;
        }
    }
    return min_index;
}

int main() {
```

```
    int graph[V][V];

    // read matrix
    for(int i = 0; i < V; i++)
        for(int j = 0; j < V; j++)
            scanf("%d", &graph[i][j]);

    int parent[V];
    int key[V];
    int mstSet[V];

    for(int i = 0; i < V; i++) {
        key[i] = INF;
        mstSet[i] = 0;
    }

    key[0] = 0;
    parent[0] = -1;

    // Prim's Algorithm
    for(int count = 0; count < V-1; count++) {
        int u = minKey(key, mstSet);
        mstSet[u] = 1;

        for(int v = 0; v < V; v++) {
            if(graph[u][v] && mstSet[v] == 0 && graph[u][v] < key[v]) {
                parent[v] = u;
                key[v] = graph[u][v];
            }
        }
    }

    printf("Edge \tWeight\n");
    for(int i = 1; i < V; i++) {
        printf("%d - %d \t%d\n", parent[i], i, graph[parent[i]][i]);
    }

    return 0;
}
```

Status : Partially correct ***Marks : 7.5/10***

2. Problem Statement

You are given a set of cities in a country and the cost of building railway track segments to connect them. Your task is to find the minimum cost required to build the railway tracks and connect all the cities. The cost of each track segment is given, along with the source city and destination city to which it connects.

Write a program that takes the number of cities, the number of track segments, and the details of each track segment as input. Implement Kruskal's Algorithm to calculate the minimum cost of building the railway tracks.

Cities are numbered 0 to N-1.

Example

Input:

3

3

0 1 4

1 2 5

0 2 3

Output:

7

Explanation:

The input specifies 3 cities and 3 track segments with their corresponding weights.

The track segments are:

Track Segment 1: Connects city 0 and city 1, with a weight of 4.Track Segment 2: Connects city 1 and city 2 with a weight of 5.Track Segment 3: Connects city 0 and city 2 with a weight of 3.The algorithm finds the

vtu27632

minimum cost to build railway tracks connecting all cities. In this case, the minimum spanning tree includes track segment 3 (0-2 with weight 3) and track segment 1 (0-1 with weight 4). The total cost is 3 + 4 = 7.

Input Format

The first line of input contains an integer N, representing the number of cities (numbered 0 to N-1).

The second line contains an integer M, representing the number of track segments.

Each of the next M lines contains three space-separated integers: the source city, the destination city, and the weight (cost) of the track segment

Output Format

The first line of input contains an integer N, representing the number of cities (numbered 0 to N-1).

The second line contains an integer M, representing the number of track segments.

Each of the next M lines contains three space-separated integers: the source city, the destination city, and the weight (cost) of the track segment

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
5
0 1 1
0 2 4
1 2 2
1 3 5
2 3 3

Output: 6

Answer

// You are using GCC

vtu27632

```
#include <stdio.h>

#define MAX 10

struct Edge {
    int u, v, w;
};

int parent[MAX];

int find(int i) {
    while(parent[i] != i)
        i = parent[i];
    return i;
}

void unionSet(int u, int v) {
    int a = find(u);
    int b = find(v);
    parent[a] = b;
}

int main() {
    int n, m;
    scanf("%d", &n);
    scanf("%d", &m);

    struct Edge edges[10];

    for(int i = 0; i < m; i++)
        scanf("%d %d %d", &edges[i].u, &edges[i].v, &edges[i].w);

    // initialize parent
    for(int i = 0; i < n; i++)
        parent[i] = i;

    // sort edges by weight
    for(int i = 0; i < m-1; i++) {
        for(int j = i+1; j < m; j++) {
            if(edges[i].w > edges[j].w) {
                struct Edge temp = edges[i];
                edges[i] = edges[j];
```

```
            edges[j] = temp;
        }
    }
}

int count = 0, cost = 0;

// Kruskal
for(int i = 0; i < m; i++) {
    int u = edges[i].u;
    int v = edges[i].v;

    if(find(u) != find(v)) {
        unionSet(u, v);
        cost += edges[i].w;
        count++;
    }
}

if(count == n - 1)
    printf("%d", cost);
else
    printf("It is not possible to connect all cities.");

return 0;
}
```

Status : Partially correct ***Marks : 7.5/10***

3. Problem Statement

Raja is given a map of cities connected by bidirectional roads, where each road has an associated construction cost (weight). His task is to find the Minimum Spanning Tree (MST) of this network using Prim's Algorithm, starting from city 0, so that all cities are connected with the minimum total construction cost.

Prim's Algorithm works as follows:

Start from the source city (city 0). Mark it as included in the MST.At each step, select the edge with the minimum weight that connects a city already

in the MST to a city not yet in the MST.Repeat until all cities are included in the MST.

The program should display each MST edge (the city included and the cost to connect it) and the total MST cost.

Note: The given graph is a connected, undirected, weighted graph. Self-loops and parallel edges are not present.

Input Format

The first line of input consists of two space-separated integers, n and m, where n represents the number of cities (vertices) and m represents the number of roads (edges).

The next m lines each consist of three space-separated integers u, v, and w, where u and v are the two cities connected by the road (0-indexed) and w is the construction cost (weight) of the road.

Output Format

The output consists of n lines.

The first n-1 lines each print the MST edge added, in the format:

"Edge: u - v, Cost: w", where u is the city already in the MST, v is the newly added city, and w is the integer edge weight. Edges are printed in the order they are added by Prim's algorithm starting from city 0.

The last line prints "Total MST Cost: t", where t is the total integer cost of the minimum spanning tree.

Refer to the sample output for formatting specifications.

Sample Test Case

vtu27632

Input: 4 5
0 1 10
0 2 6
0 3 5
1 3 15
2 3 4

Output: Edge: 0 - 1, Cost: 10
Edge: 3 - 2, Cost: 4
Edge: 0 - 3, Cost: 5
Total MST Cost: 19

Answer

```
#include <stdio.h>

#define MAX 100
#define INF 1000000000

int minKey(int key[], int mstSet[], int n) {
    int min = INF, min_index = -1;

    for (int v = 0; v < n; v++) {
        if (mstSet[v] == 0 && key[v] < min) {
            min = key[v];
            min_index = v;
        }
    }
    return min_index;
}

int main() {
    int n, m;
    scanf("%d %d", &n, &m);

    int graph[MAX][MAX];

    // initialize
    for(int i = 0; i < n; i++)
        for(int j = 0; j < n; j++)
            graph[i][j] = INF;

    // read edges
    for(int i = 0; i < m; i++) {
```

```
    int u, v, w;
    scanf("%d %d %d", &u, &v, &w);
    graph[u][v] = w;
    graph[v][u] = w;
}

int parent[MAX];
int key[MAX];
int mstSet[MAX];

for(int i = 0; i < n; i++) {
    key[i] = INF;
    mstSet[i] = 0;
}

key[0] = 0;
parent[0] = -1;

// Prim's algorithm
for(int count = 0; count < n - 1; count++) {
    int u = minKey(key, mstSet, n);
    mstSet[u] = 1;

    for(int v = 0; v < n; v++) {
        if(graph[u][v] < key[v] && mstSet[v] == 0) {
            parent[v] = u;
            key[v] = graph[u][v];
        }
    }
}

int total = 0;

for(int i = 1; i < n; i++) {
    printf("Edge: %d - %d, Cost: %d\n", parent[i], i, key[i]);
    total += key[i];
}

printf("Total MST Cost: %d", total);

return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Riya is working as a data scientist in a company that deals with large text data. Due to storage and bandwidth limitations, she needs a way to compress text while maintaining its readability.

She decides to use Huffman Encoding, a well-known algorithm that assigns shorter binary codes to frequently occurring characters and longer binary codes to less common characters, thus reducing the overall message size.

Given a set of characters with their respective frequencies, help Riya generate Huffman Codes for each character. Then, using these codes, encode a given message.

Assign '0' to left branches and '1' to right branches, merge the two nodes with the lowest frequency at each step. Clarify that the message will only contain characters from the given input set. Specify that Huffman codes are printed in the order they appear during in-order/pre-order traversal of the Huffman tree (matching sample output)

The message will only contain characters from the provided character set.

Input Format

The first line of input consists of an integer n, representing the number of unique characters.

The next n lines each consist of a character (an uppercase or lowercase English letter) and a positive integer representing its frequency, separated by a space.

The last line of input consists of a string representing the message to be encoded. The message will only contain characters from the provided character set.

Output Format

The first n lines of output print the Huffman code for each character in the format:

"character: code"

where the characters are printed in the order they appear as leaf nodes during the Huffman tree traversal (left child before right child, assigning '0' to left and '1' to right).

All n input characters and their codes are printed, regardless of whether they appear in the message.

The last line of output prints the encoded message as a sequence of 0s and 1s obtained by replacing each character in the message with its corresponding Huffman code.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
A 1
B 2
C 3
ABCCBAABBC

Output: C: 0
A: 10
B: 11
10110011101011110

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

typedef struct Node {
    char ch;
    int freq;
    struct Node *left, *right;
} Node;
```

```
Node* createNode(char ch, int freq) {
    Node* node = (Node*)malloc(sizeof(Node));
    node->ch = ch;
    node->freq = freq;
    node->left = node->right = NULL;
    return node;
}

// sort nodes by frequency
void sort(Node* arr[], int n) {
    for(int i=0;i<n-1;i++) {
        for(int j=i+1;j<n;j++) {
            if(arr[i]->freq > arr[j]->freq) {
                Node* t = arr[i];
                arr[i] = arr[j];
                arr[j] = t;
            }
        }
    }
}

void printCodes(Node* root, char code[], int top, char codes[256][256]) {
    if(root->left) {
        code[top] = '0';
        printCodes(root->left, code, top+1, codes);
    }

    if(root->right) {
        code[top] = '1';
        printCodes(root->right, code, top+1, codes);
    }

    // leaf node
    if(!root->left && !root->right) {
        code[top] = '\0';
        printf("%c: %s\n", root->ch, code);
        strcpy(codes[(int)root->ch], code);
    }
}

int main() {
    int n;
```

```
scanf("%d", &n);

Node* arr[26];

for(int i=0;i<n;i++) {
    char ch;
    int f;
    scanf(" %c %d", &ch, &f);
    arr[i] = createNode(ch, f);
}

int size = n;

// build Huffman tree
while(size > 1) {
    sort(arr, size);

    Node* left = arr[0];
    Node* right = arr[1];

    Node* newNode = createNode('$', left->freq + right->freq);
    newNode->left = left;
    newNode->right = right;

    for(int i=2;i<size;i++)
        arr[i-2] = arr[i];

    arr[size-2] = newNode;
    size--;
}

Node* root = arr[0];

char codes[256][256] = {{0}};
char code[256];

printCodes(root, code, 0, codes);

char message[300];
scanf("%s", message);

// encode message
```

```
    for(int i=0; message[i]; i++)
        printf("%s", codes[(int)message[i]]);

    return 0;
}
```

Status : Partially correct ***Marks : 7.5/10***

5. Problem Statement

In a clandestine world of spies and covert operations, a group of operatives uses Huffman coding to encode and decode their classified messages securely.

Huffman coding assigns shorter binary codes to more frequently occurring characters and longer codes to less frequent ones. The algorithm works as follows:

Each character and its frequency is inserted into a min-heap (priority queue).At each step, extract the two nodes with the lowest frequencies, merge them into a new internal node whose frequency is the sum of the two, and reinsert it into the heap.Repeat until only one node (the root) remains — this is the Huffman tree.Assign '0' to every left branch and '1' to every right branch. The binary string from root to each leaf node is that character's Huffman code.

Given a set of characters with their frequencies, build the Huffman tree, print the codes for all characters, encode the given message using these codes, and decode the encoded message back to the original.

Note: The message will only contain characters from the provided input set. All character frequencies are unique.

Input Format

The first line of input consists of a positive integer N, representing the number of unique characters.

The next N lines each consist of a character (an uppercase or lowercase English letter) and a positive integer representing its frequency, separated by a space.

The last line of input consists of a string representing the secret message to be encoded. The message contains only characters from the provided character set

Output Format

The first N lines of output each print the Huffman code for a character in the format:

"character: code"

where characters are printed in the order they appear as leaf nodes during Huffman tree traversal (left child before right child, with '0' assigned to left and '1' to right).

The next line prints the encoded message — a sequence of 0s and 1s obtained by replacing each character in the message with its Huffman code.

The last line prints the decoded message obtained by traversing the Huffman tree using the encoded bits, which must match the original input message.

Refer to the sample outputs for better understanding and formatting.

Sample Test Case

Input: 5
A 5
B 9
C 12
D 13
E 16
ABCDE

Output: C: 00
D: 01
A: 100
B: 101
E: 11
100101000111
ABCDE

vtu27632

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>
#include <string.h>

typedef struct Node {
    char ch;
    int freq;
    struct Node *left, *right;
} Node;

Node* createNode(char ch, int freq) {
    Node* n = (Node*)malloc(sizeof(Node));
    n->ch = ch;
    n->freq = freq;
    n->left = n->right = NULL;
    return n;
}

void sort(Node* arr[], int n) {
    for(int i=0;i<n-1;i++) {
        for(int j=i+1;j<n;j++) {
            if(arr[i]->freq > arr[j]->freq) {
                Node* t = arr[i];
                arr[i] = arr[j];
                arr[j] = t;
            }
        }
    }
}

void printCodes(Node* root, char code[], int top, char codes[256][256]) {
    if(root->left) {
        code[top]='0';
        printCodes(root->left, code, top+1, codes);
    }

    if(root->right) {
        code[top]='1';
        printCodes(root->right, code, top+1, codes);
    }
```

```
    if(!root->left && !root->right) {
        code[top]='\0';
        printf("%c: %s\n", root->ch, code);
        strcpy(codes[(int)root->ch], code);
    }
}

void decode(Node* root, char *encoded) {
    Node* curr = root;
    for(int i=0; encoded[i]; i++) {
        if(encoded[i]=='0')
            curr = curr->left;
        else
            curr = curr->right;

        if(!curr->left && !curr->right) {
            printf("%c", curr->ch);
            curr = root;
        }
    }
}

int main() {
    int n;
    scanf("%d",&n);

    Node* arr[20];

    for(int i=0;i<n;i++) {
        char ch;
        int f;
        scanf(" %c %d",&ch,&f);
        arr[i]=createNode(ch,f);
    }

    int size=n;

    // build Huffman tree
    while(size>1) {
        sort(arr,size);
```

```
        Node* left=arr[0];
        Node* right=arr[1];

        Node* newNode=createNode('$',left->freq+right->freq);
        newNode->left=left;
        newNode->right=right;

        for(int i=2;i<size;i++)
            arr[i-2]=arr[i];

        arr[size-2]=newNode;
        size--;
    }

    Node* root=arr[0];

    char codes[256][256]={{0}};
    char code[256];

    // print codes
    printCodes(root,code,0,codes);

    char message[100];
    scanf("%s",message);

    // encode
    char encoded[1000]="";
    for(int i=0;message[i];i++)
        strcat(encoded,codes[(int)message[i]]);

    printf("%s\n",encoded);

    // decode
    decode(root,encoded);

    return 0;
}
```

Status : Partially correct ***Marks : 7.5/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 8_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 13

Section 1 : MCQ

1. Which type of graphs can be topologically sorted?

Answer

Directed graphs

Status : Correct ***Marks : 1/1***

2. Topological sort can be used to detect which of the following?

Answer

Cycles in a directed graph

Status : Correct ***Marks : 1/1***

vtu27632

3. In topological sort, vertices are visited in which order?

Answer

In topological order

Status : Correct ***Marks : 1/1***

4. Which of the following data structures can be used to implement topological sort?

Answer

All of the listed options

Status : Wrong ***Marks : 0/1***

5. Which of the following algorithms can be used to perform topological sort?

Answer

Depth First Search (DFS)
Breadth First Search (BFS)

Status : Correct ***Marks : 1/1***

6. Topological sort is equivalent to which of the traversals in trees?

Answer

Post-order traversal

Status : Wrong ***Marks : 0/1***

7. When is the topological sort of a graph unique?

Answer

When there exists a hamiltonian path in the graph

Status : Correct ***Marks : 1/1***

vtu27632

8. In Dijkstra's algorithm, if two vertices u and v have the same tentative distance from the source, which one is chosen first?

Answer

It can be arbitrary

Status : Correct ***Marks : 1/1***

9. In a graph with non-negative weights, why is Dijkstra's algorithm guaranteed to find the shortest path?

Answer

Because once a vertex's distance is finalized, it cannot be improved

Status : Correct ***Marks : 1/1***

10. How can Dijkstra's algorithm be adapted to return not only distances but also the actual paths?

Answer

Maintain a parent array for each vertex

Status : Correct ***Marks : 1/1***

11. In Dijkstra's algorithm, what is the purpose of the relaxation step when processing an edge (u, v)?

Answer

To update the distance to vertex v if a shorter path through u is found

Status : Correct ***Marks : 1/1***

12. In a graph with multiple edges between the same pair of vertices, how should Dijkstra's algorithm handle them?

Answer

vtu27632

Consider only the edge with the minimum weight

Status : Correct ***Marks : 1/1***

13. If a graph has an edge weight of zero, will Dijkstra's algorithm still work correctly?

Answer

Yes, always

Status : Correct ***Marks : 1/1***

14. Which property of Dijkstra's algorithm guarantees that the shortest path to a vertex is correct when the vertex is added to the finalized set?

Answer

Both A and B

Status : Correct ***Marks : 1/1***

15. Why can Dijkstra's algorithm fail on a graph with a negative weight edge even if there are no negative cycles?

Answer

Because a previously finalized vertex may get a shorter path later

Status : Correct ***Marks : 1/1***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 8_COD

Attempt : 1
Total Mark : 40
Marks Obtained : 0

Section 1 : Coding

1. Problem Statement

Ram is tasked with finding the shortest distances from a source router to all other routers in a network. The network is represented as a graph of N routers connected by M bidirectional weighted links.

The program uses Dijkstra's Algorithm: starting from the source router, it repeatedly selects the unvisited router with the smallest known distance, then updates distances to its neighbors if a shorter path is found through it. This continues until all routers have been visited.

Given the network details and a source router, find and print the shortest distance from the source router to every router in the network.

Input Format

The first line of input consists of an integer N, representing the number of routers.

The second line of input consists of an integer M, representing the number of links.

The next M lines each consist of three space-separated integers: r1, r2, and w, representing a bidirectional link between router r1 and router r2 with weight w.

The last line of input consists of an integer s, representing the source router.

Output Format

The output consists of N lines printed in ascending order of router index (from 0 to N-1).

Each line prints two space-separated integers: the router index and its shortest distance from the source router.

The source router itself is printed with distance 0.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
5
0 1 1
0 2 3
1 2 1
1 3 4
2 3 1
0
Output: 0 0
1 1
2 2
3 3

Answer

```
#include <stdio.h>
#include <limits.h>
```

```
#define MAX 10

int minDistance(int dist[], int visited[], int n) {
    int min = INT_MAX, min_index;

    for (int i = 0; i < n; i++) {
        if (!visited[i] && dist[i] <= min) {
            min = dist[i];
            min_index = i;
        }
    }
    return min_index;
}


int main() {
    int numRouters, numLinks;
    scanf("%d", &numRouters);
    scanf("%d", &numLinks);
    int graph[MAX_ROUTERS][MAX_ROUTERS] = {0};
    int adj[MAX_ROUTERS][MAX_ROUTERS] = {0};
    for (int i = 0; i < numLinks; i++) {
        int router1, router2, weight;
        scanf("%d %d %d", &router1, &router2, &weight);
        graph[router1][router2] = weight;
        graph[router2][router1] = weight;
        adj[router1][router2] = 1;
        adj[router2][router1] = 1;
    }
    int source;
    scanf("%d", &source);
    dijkstra(graph, adj, source, numRouters);
    return 0;
}
```

Status : Wrong ***Marks : 0/10***

2. Problem Statement

Alice is working on a delivery system for an e-commerce platform. The

system uses a network of delivery hubs connected by roads, each with a certain travel time in minutes.

Alice needs to find the fastest delivery time from a source hub to every other hub in the network. Given the network details and a source hub, the program uses Dijkstra's Algorithm to find and print the shortest delivery time from the source hub to all hubs in the network.

Dijkstra's Algorithm works by starting from the source hub with distance 0, then repeatedly selecting the unvisited hub with the smallest known time and updating the times to its neighbors if a shorter path is found through it. This continues until all hubs have been visited.

Input Format

The first line of input consists of an integer N, representing the number of delivery hubs.

The second line of input consists of an integer M, representing the number of roads between hubs.

The next M lines each consist of three space-separated integers: r1, r2, and t, representing a bidirectional road between hub r1 and hub r2 with a delivery time of t minutes.

The last line of input consists of an integer s, representing the source delivery hub.

Output Format

The output prints N lines representing the shortest delivery times from the source hub to all hubs (including the source) in ascending order of hub index.

Each line prints two space-separated integers: the hub index and its shortest delivery time from the source hub.

The delivery time of the source hub itself is 0.

Refer to the sample output for the formatting specifications.

Sample Test Case

vtu27632

Input: 3
3
0 1 2
0 2 4
1 2 1
0

Output: 0 0
1 2
2 3

Answer

```
#include <stdio.h>
#include <limits.h>

#define MAX_NODES 10
```

```
#include <stdio.h>
#include <limits.h>

#define MAX 20

int minDistance(int dist[], int visited[], int n) {
    int min = INT_MAX, min_index = -1;

    for (int i = 0; i < n; i++) {
        if (!visited[i] && dist[i] < min) {
            min = dist[i];
            min_index = i;
        }
    }
    return min_index;
}


int main() {
    int N, M, s;
    scanf("%d", &N);
    scanf("%d", &M);
    for (int i = 0; i < N; i++) {
        for (int j = 0; j < N; j++) {
            graph[i][j] = -1;
        }
    }
```

```
    for (int i = 0; i < M; i++) {
        int r1, r2, w;
        scanf("%d %d %d", &r1, &r2, &w);
        graph[r1][r2] = w;
        graph[r2][r1] = w;
    }
    scanf("%d", &s);
    dijkstra(N, s);
    for (int i = 0; i < N; i++) {
        printf("%d %d\n", i, dist[i]);
    }
    return 0;
}
```

Status : Wrong **Marks : 0/10**

3. Problem statement

Create a program to calculate and display the topological order of a Directed Acyclic Graph (DAG) with n vertices. The graph is represented as a lower triangular adjacency matrix, where for every vertex i and vertex j with j < i, the edge from i to j exists (value 1), and no edge exists from j to i (value 0). All diagonal and upper triangular values are 0.

The program should:

Construct and display the adjacency matrix of the graph.Perform a Depth First Search (DFS) traversal on the graph.Display the topological order of the vertices in reverse order of their DFS end times.

Input Format

The first line of input consists of an integer n, representing the number of vertices in the graph. No further input is required; the adjacency matrix is constructed internally by the program.

Output Format

he first line of output prints: Adjacency Matrix of the graph

The next n lines print the adjacency matrix row by row, where each value is preceded by a tab character (\t).

A blank line is printed after the matrix.

The next line prints: Topological order:

The final line prints the topological order of the vertices in the format: -->v1-->v2-->...-->vn, where vertices appear in reverse order of their DFS end times.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
Output: Adjacency Matrix of the graph
```
 0  0  0
 1  0  0
 1  1  0
```

Topological order:
-->2-->1-->0

Answer

```
#include<stdio.h>

int s[100], res[100], top;

// #include <stdio.h>

#define MAX 100

int graph[MAX][MAX];
int visited[MAX];
int stack[MAX];
int top = -1;
int n;

// DFS function
void dfs(int v) {
   visited[v] = 1;

   for (int i = 0; i < n; i++) {
```

```
        if (graph[v][i] == 1 && !visited[i]) {
            dfs(i);
        }
    }

    // Push to stack after finishing
    stack[++top] = v;
}

int main() {
    scanf("%d", &n);

    // Construct lower triangular adjacency matrix
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (j < i)
                graph[i][j] = 1;
            else
                graph[i][j] = 0;
        }
    }

    // Print adjacency matrix
    printf("Adjacency Matrix of the graph\n");
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            printf("\t%d", graph[i][j]);
        }
        printf("\n");
    }

    printf("\n");

    // Initialize visited array
    for (int i = 0; i < n; i++) {
        visited[i] = 0;
    }

    // Perform DFS
    for (int i = 0; i < n; i++) {
        if (!visited[i]) {
            dfs(i);
```

```
        }
    }

    // Print topological order
    printf("Topological order:\n");

    while (top != -1) {
        printf("-->%d", stack[top--]);
    }

    return 0;
}You are using GCC

int main() {
    int a[100][100], n, i, j;
    scanf("%d", &n);
    buildMatrix(a, n);
    printf("Adjacency Matrix of the graph\n");
    for (i = 0; i < n; i++) {
        for (j = 0; j < n; j++)
            printf("\t%d", a[i][j]);
        printf("\n");
    }
    printf("\nTopological order:\n");
    topological_order(n, a);
    for (i = top - 1; i >= 0; i--)
        printf("-->%d", res[i]);
    printf("\n");
    return 0;
}
```

Status : Wrong **Marks : 0/10**

4. Problem Statement

Write a program to implement and print the topological order of a directed acyclic graph (DAG). The program should take the number of vertices and the adjacency matrix of the graph as input and then output the topological order.

When multiple vertices have zero indegree simultaneously, process them in

ascending order of their vertex number (1-indexed). The output vertices are numbered starting from 1

Input Format

The first line of input consists of an integer N, representing the number of vertices in the graph.

The following N lines contain the adjacency matrix of the graph. Each line contains N space-separated integers (0 or 1), where 1 indicates a directed edge from the corresponding row vertex to the column vertex.

Output Format

The output prints the topological order of the vertices as space-separated 1-indexed integers on a single line.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
1 0 0
0 1 0
1 0 0

Output: 3 1 2

Answer

```
#include <stdio.h>

#define MAX 10

int main() {
    int n;
    scanf("%d", &n);

    int graph[MAX][MAX];
    int indegree[MAX] = {0};
    int visited[MAX] = {0};

    // Input adjacency matrix and compute indegree
```

```
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &graph[i][j]);
            if (graph[i][j] == 1) {
                indegree[j]++;
            }
        }
    }

    // Topological sorting
    for (int count = 0; count < n; count++) {
        int u = -1;

        // pick smallest vertex with indegree 0
        for (int i = 0; i < n; i++) {
            if (!visited[i] && indegree[i] == 0) {
                u = i;
                break;
            }
        }

        visited[u] = 1;

        printf("%d ", u + 1);

        for (int v = 0; v < n; v++) {
            if (graph[u][v] == 1) {
                indegree[v]--;
            }
        }
    }

    return 0;
}
```

Status : Wrong ***Marks : 0/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 8_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 40.5

Section 1 : Coding

1. Problem Statement

You are tasked with finding the shortest communication paths from a source router to all other routers in a network using Dijkstra's algorithm.

The network is represented as a graph, where routers are nodes and communication links between them are edges with weights representing the time or cost of communication. A value of 0 in the adjacency matrix indicates no direct link between two routers.

Example

Explanation:

The minimum distance from 0 to 1 = 4. Path: 0 1

vtu27632

The minimum distance from 0 to 2 = 12. Path: 0 1 2

The minimum distance from 0 to 3 = 19. Path: 0 1 2 3

The minimum distance from 0 to 4 = 21. Path: 0 7 6 5 4

The minimum distance from 0 to 5 = 11. Path: 0 7 6 5

The minimum distance from 0 to 6 = 9. Path: 0 7 6

The minimum distance from 0 to 7 = 8. Path: 0 7

The minimum distance from 0 to 8 = 14. Path: 0 1 2 8"

Input Format

The first line contains an integer V, representing the number of vertices in the graph.

The next V lines each contain V space-separated integers, representing the adjacency matrix of the graph. A value of 0 indicates no direct edge between the vertices.

The last line contains an integer src, representing the source vertex.

Output Format

The first line of output prints: Vertex followed by a tab character followed by Distance from Source

The next V lines each print the vertex number followed by three tab characters, a space, and the shortest distance from the source. Vertices are printed in ascending order from 0 to V-1.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
0 1 3 1
1 0 4 2
3 4 0 5
1 2 5 0

vtu27632

1
Output: Vertex Distance from Source
0 1
1 0
2 4
3 2

Answer

```
#include <stdio.h>

#define MAX 10
#define INF 1000000

int minDistance(int dist[], int visited[], int V) {
    int min = INF, idx = -1;
    for (int i = 0; i < V; i++) {
        if (!visited[i] && dist[i] < min) {
            min = dist[i];
            idx = i;
        }
    }
    return idx;
}

int main() {
    int V;
    scanf("%d", &V);

    int graph[MAX][MAX];

    for(int i = 0; i < V; i++) {
        for(int j = 0; j < V; j++) {
            scanf("%d", &graph[i][j]);
            if(i != j && graph[i][j] == 0)
                graph[i][j] = INF;
        }
    }

    int src;
    scanf("%d", &src);

    int dist[MAX], visited[MAX];
```

```
    for(int i = 0; i < V; i++) {
        dist[i] = INF;
        visited[i] = 0;
    }

    dist[src] = 0;

    for(int count = 0; count < V - 1; count++) {
        int u = minDistance(dist, visited, V);
        visited[u] = 1;

        for(int v = 0; v < V; v++) {
            if(!visited[v] && graph[u][v] != INF &&
                dist[u] + graph[u][v] < dist[v]) {
                 dist[v] = dist[u] + graph[u][v];
            }
        }
    }

    printf("Vertex \tDistance from Source\n");
    for(int i = 0; i < V; i++) {
        printf("%d\t\t\t %d\n", i, dist[i]);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Given a network of cities represented as an unweighted graph, find the shortest path between a source city and a destination city in terms of the minimum number of roads to be traversed. Implement a program that utilizes the Dijkstra algorithm to solve this problem.

The program should take the city network, source city, and destination city as inputs, and provide the shortest path length and the sequence of cities to be visited along the path as outputs.

If no path exists between the source and destination, print 'No path found'.
Note: Since the graph is unweighted, all edges have an implicit weight of 1.

Input Format

The first line contains an integer n, representing the number of cities in the network.

The second line contains an integer m, representing the number of roads in the city network.

The following m lines contain pairs of integers u and v, representing a road between cities u and v.

The next line contains an integer s, representing the source city.

The last line contains an integer d, representing the destination city.

Output Format

The first line prints Shortest path length: followed by the number of edges in the shortest path.

The second line prints Path: followed by the city indices along the shortest path, each followed by a space.

If no path exists, print No path found.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 8
10
0 1
0 3
1 2
3 4
3 7
4 5
4 6

vtu27632

4 7
5 6
6 7
0
7
Output: Shortest path length: 2
Path: 0 3 7

Answer

```
#include <stdio.h>

#define MAX 100

int main() {
    int n, m;
    scanf("%d", &n);
    scanf("%d", &m);

    int adj[MAX][MAX] = {0};

    for(int i = 0; i < m; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        adj[u][v] = 1;
        adj[v][u] = 1;
    }

    int s, d;
    scanf("%d", &s);
    scanf("%d", &d);

    int queue[MAX], front = 0, rear = 0;
    int visited[MAX] = {0};
    int parent[MAX];
    int dist[MAX];

    for(int i = 0; i < n; i++) {
        parent[i] = -1;
        dist[i] = -1;
    }

    queue[rear++] = s;
```

```
    visited[s] = 1;
    dist[s] = 0;

    while(front < rear) {
        int u = queue[front++];

        for(int v = 0; v < n; v++) {
            if(adj[u][v] && !visited[v]) {
                visited[v] = 1;
                dist[v] = dist[u] + 1;
                parent[v] = u;
                queue[rear++] = v;
            }
        }
    }

    if(!visited[d]) {
        printf("No path found");
        return 0;
    }

    int path[MAX], len = 0;
    int crawl = d;
    while(crawl != -1) {
        path[len++] = crawl;
        crawl = parent[crawl];
    }

    printf("Shortest path length: %d\n", dist[d]);
    printf("Path: ");

    for(int i = len - 1; i >= 0; i--)
        printf("%d ", path[i]);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Liam, a compiler designer, is optimizing task scheduling in a dependency-based system. He is working with a Directed Acyclic Graph (DAG), where each node represents a task, and a directed edge from one node to another signifies a dependency.

To schedule the tasks optimally, Liam must perform a topological sort using Depth-First Search (DFS), sorting the tasks based on their departure times in descending order.

Your task is to help Liam implement this topological sorting algorithm.

Input Format

The first line contains an integer N, representing the number of vertices (tasks) in the DAG.

The second line contains an integer E, representing the number of directed edges (dependencies) in the graph.

The next E lines each contain two space-separated integers:

- src The starting vertex of a directed edge.
- dest The ending vertex of a directed edge.

Output Format

The output prints N space-separated integers in a single line, representing the 0-indexed vertices in descending order of their DFS departure times, each followed by a space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
6
5 2
5 0
4 0
4 1

vtu27632

2 3
3 1
Output: 5 4 2 3 1 0

Answer

```
#include <stdio.h>

#define MAX 100

int adj[MAX][MAX];
int visited[MAX];
int stack[MAX];
int top = -1;
int N;

void dfs(int v)
{
    visited[v] = 1;

    for(int i = 0; i < N; i++)
    {
        if(adj[v][i] && !visited[i])
            dfs(i);
    }

    stack[++top] = v; // departure time
}

int main()
{
    int E;
    scanf("%d", &N);
    scanf("%d", &E);

    for(int i = 0; i < E; i++)
    {
        int src, dest;
        scanf("%d %d", &src, &dest);
        adj[src][dest] = 1;
    }

    // start DFS from highest vertex
```

```
    for(int i = N - 1; i >= 0; i--)
    {
        if(!visited[i])
            dfs(i);
    }

    // print descending departure time
    for(int i = top; i >= 0; i--)
        printf("%d ", stack[i]);

    return 0;
}
```

Status : Partially correct **Marks : 4/10**

4. Problem Statement:

You are given a directed acyclic graph (DAG) G with N vertices and M edges. From G, a new graph G^ is constructed using the same vertex set and the following rules:

If there exists an edge from vertex u to vertex v in G, then there is no edge from v to u in G^.If there exists an edge from u to v in G, and from v to w in G, then there exists an edge from u to w in G^.In G^, find the maximum possible size of a set S of vertices such that for every pair of vertices (u, v) in S, there exists a directed edge between them (either u v or v u).

Example:

Input: N=3, M=2, edges: 1 2, 2 3

G^ contains edges: 1 2, 2 3, and 1 3 (by rule 2).

Set S = {1, 2, 3}: edge exists between every pair (1 2, 2 3, 1 3). This is valid with size 3.

Output: 3

Input Format

The first line contains two space-separated integers N and M, representing the number of vertices and edges in graph G.

The next M lines each contain two space-separated integers u and v (1 ≤ u, v ≤ N), representing a directed edge from vertex u to vertex v.

Output Format

Print a single integer representing the maximum possible size of set S.

Refer to the sample output for formatting specifications

Sample Test Case

Input: 3 2
1 2
2 3
Output: 3

Answer

```
#include <stdio.h>

#define MAX 105

int adj[MAX][MAX];
int visited[MAX];
int stack[MAX];
int top = -1;
int N;

void dfs(int v)
{
    visited[v] = 1;
    for(int i = 1; i <= N; i++)
        if(adj[v][i] && !visited[i])
            dfs(i);

    stack[++top] = v;
}

int main()
{
    int M;
```

```
    scanf("%d %d", &N, &M);

    for(int i = 0; i < M; i++)
    {
        int u, v;
        scanf("%d %d", &u, &v);
        adj[u][v] = 1;
    }

    // Topological sort
    for(int i = 1; i <= N; i++)
        if(!visited[i])
            dfs(i);

    int dp[MAX];
    for(int i = 1; i <= N; i++)
        dp[i] = 1;

    // process in topo order
    for(int i = top; i >= 0; i--)
    {
        int u = stack[i];
        for(int v = 1; v <= N; v++)
        {
            if(adj[u][v] && dp[v] < dp[u] + 1)
                dp[v] = dp[u] + 1;
        }
    }

    int ans = 0;
    for(int i = 1; i <= N; i++)
        if(dp[i] > ans)
            ans = dp[i];

    printf("%d", ans);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

You are given a directed acyclic graph (DAG) represented as an adjacency list.

Your task is to perform a topological sort on the graph and print the vertices in topological order. The input graph is guaranteed to be a directed acyclic graph.

Input Format

The first line of input consists of an integer N, representing the number of vertices in the directed acyclic graph.

The second line consists of an integer E, representing the number of directed edges in the graph.

The following E lines consist of two space-separated integers, src and dest, representing a directed edge from vertex src to vertex dest.

Output Format

The output consists of the vertices in topological order separated by spaces.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 6
6
5 2
5 0
4 0
4 1
2 3
3 1
Output: 4 5 0 2 3 1

Answer

```
#include <stdio.h>
```

```
#define MAX 100

int adj[MAX][MAX];
int visited[MAX];
int stack[MAX];
int top = -1;
int N;

void dfs(int v)
{
    visited[v] = 1;

    for(int i = 0; i < N; i++)
    {
        if(adj[v][i] && !visited[i])
            dfs(i);
    }

    stack[++top] = v;
}

int main()
{
    int E;
    scanf("%d", &N);
    scanf("%d", &E);

    for(int i = 0; i < E; i++)
    {
        int src, dest;
        scanf("%d %d", &src, &dest);
        adj[src][dest] = 1;
    }

    for(int i = 0; i < N; i++)
    {
        if(!visited[i])
            dfs(i);
    }

    for(int i = top; i >= 0; i--)
```

```
    printf("%d ", stack[i]);
    return 0;
}
```

Status : Partially correct ***Marks : 6.5/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 8_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 48.5

Section 1 : Coding

1. Problem Statement

Sophia, a robotics engineer, is designing a task execution system where tasks have dependencies. Each task is represented as a node in a directed acyclic graph (DAG), and a directed edge (u v) means task u must be completed before task v.

To determine the correct execution order, Sophia needs to perform a topological sort on the graph.

Your task is to help Sophia implement topological sorting and print the order in which tasks should be executed.

Input Format

The first line contains an integer N, representing the number of vertices (tasks)

in the DAG.

The second line contains an integer E, representing the number of directed edges (dependencies) in the graph.

The next E lines each contain two space-separated integers:

- src The starting vertex of a directed edge.
- dest The ending vertex of a directed edge.

Output Format

The output prints N space-separated integers in a single line, representing the vertices in topological order.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
6
5 2
5 0
4 0
4 1
2 3
3 1
Output: 4 5 0 2 3 1

Answer

```
#include <stdio.h>

#define MAX 100

int adj[MAX][MAX];
int visited[MAX];
int stack[MAX];
int top = -1;
int N;

void dfs(int v) {
```

```
    visited[v] = 1;

    for(int i = 0; i < N; i++) {
        if(adj[v][i] && !visited[i])
            dfs(i);
    }

    stack[++top] = v;
}

int main() {
    int E;
    scanf("%d", &N);
    scanf("%d", &E);

    // read edges
    for(int i = 0; i < E; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        adj[u][v] = 1;
    }

    // perform DFS
    for(int i = 0; i < N; i++) {
        if(!visited[i])
            dfs(i);
    }

    // print topological order
    for(int i = top; i >= 0; i--)
        printf("%d ", stack[i]);

    return 0;
}
```

Status : Partially correct ***Marks : 8.5/10***

2. Problem Statement

Write a program to find the topological order of vertices in a directed acyclic graph (DAG) represented as an adjacency list. This involves

establishing a linear arrangement of vertices such that, for every directed edge (u, v), vertex u precedes vertex v in the sequence.

Your task specifically requires printing the topological order in the reverse order of their respective end times obtained through a depth-first search (DFS) traversal.

Input Format

The first line consists of an integer N, representing the number of vertices.

The second line consists of an integer E, representing the number of directed edges.

The next E lines each contain two space-separated integers x and y, representing a directed edge from vertex x to vertex y.

Output Format

The output prints Topological Order: followed by N space-separated integers representing the vertices (0-indexed) in topological order, in reverse order of DFS end times.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5
5
1 2
2 3
3 4
3 5
4 5

Output: Topological Order: 1 2 3 4 5

Answer

```
#include <stdio.h>

#define MAX 105
```

```
int adj[MAX][MAX];
int visited[MAX];
int stack[MAX];
int top = -1;
int N;

void dfs(int v) {
    visited[v] = 1;

    for(int i = 1; i <= N; i++) {
        if(adj[v][i] && !visited[i])
            dfs(i);
    }

    stack[++top] = v;
}

int main() {
    int E;
    scanf("%d", &N);
    scanf("%d", &E);

    for(int i = 0; i < E; i++) {
        int x, y;
        scanf("%d %d", &x, &y);
        adj[x][y] = 1;
    }

    for(int i = 1; i <= N; i++) {
        if(!visited[i])
            dfs(i);
    }

    printf("Topological Order: ");
    for(int i = top; i >= 0; i--) {
        printf("%d ", stack[i]);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Given a total of N tasks labeled from 0 to N-1. Some tasks may have prerequisites. A prerequisite pair [u, v] means task u must be completed before task v. Given the total number of tasks and a list of prerequisite pairs, return the ordering of tasks you should complete to finish all tasks. There may be multiple correct orders — return any one of them. If it is impossible to finish all tasks (due to a cycle), print nothing.

Examples

Input: N=2, Prerequisite_Pairs=[[1, 0]]

Output: [0, 1]

Explanation: There are a total of 2 tasks to pick. To pick task 1 you should have finished task 0. So the correct task order is [0, 1] .

Input: N=4, Prerequisite_Pairs=[[1, 0], [2, 0], [3, 1], [3, 2]]

Output: [0, 1, 2, 3] or [0, 2, 1, 3]

Explanation: There are a total of 4 tasks to pick. To pick task 3 you should have finished both tasks 1 and 2. Both tasks 1 and 2 should be pick after you finished task 0. So one correct task order is [0, 1, 2, 3]. Another correct ordering is [0, 2, 1, 3].

Input Format

The first line of input consists of an integer n, representing the number of tasks.

The second line consists of an integer p, representing the number of prerequisite pairs.

The next p lines each consist of two space-separated integers u and v, representing that task u must be completed before task v.

Output Format

The output prints the n tasks as space-separated integers on a single line, representing a valid task execution order. If no valid ordering exists, print nothing.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
0

Output: 0 1 2

Answer

```
#include <stdio.h>

#define MAX 100

int main() {
    int n, p;
    scanf("%d", &n);
    scanf("%d", &p);

    int adj[MAX][MAX] = {0};
    int indegree[MAX] = {0};

    for(int i = 0; i < p; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        adj[u][v] = 1;
        indegree[v]++;
    }

    int queue[MAX];
    int front = 0, rear = 0;

    for(int i = 0; i < n; i++) {
        if(indegree[i] == 0)
            queue[rear++] = i;
    }

    int result[MAX];
    int count = 0;

    while(front < rear) {
        int u = queue[front++];
```

```
        result[count++] = u;

        for(int v = 0; v < n; v++) {
            if(adj[u][v]) {
                indegree[v]--;
                if(indegree[v] == 0)
                    queue[rear++] = v;
            }
        }
    }

    // if cycle exists    print nothing
    if(count != n)
        return 0;

    for(int i = 0; i < n; i++)
        printf("%d ", result[i]);

    return 0;
}
```

Status : Correct **Marks : 10/10**

4. Problem Statement

Raj is given a weighted directed graph with N vertices and the weights of the edges between the vertices.

His task is to implement Dijkstra's algorithm to find the shortest distance from a given source vertex to all other vertices in the graph.

Input Format

The first line contains an integer N, the number of vertices in the graph.

The next N lines each contain N space-separated integers, representing the adjacency matrix of the graph. The value at the i-th row and j-th column represents the weight of the edge from vertex i to vertex j. A value of 0 indicates no direct edge between the vertices.

The last line contains an integer src, representing the source vertex.

Output Format

The first line of output prints the heading: Vertex Distance from Source

The next N lines each print the vertex number and its shortest distance from the source vertex, separated by two tab characters. Vertices are numbered from 0 to N-1.

Refer to the sample output for formatting specifications

Sample Test Case

Input: 4
0 2 0 5
2 0 4 0
0 4 0 1
5 0 1 0
0
Output: Vertex Distance from Source
0 0
1 2
2 6
3 5

Answer

```
#include <stdio.h>

#define MAX 100
#define INF 1000000

int minDistance(int dist[], int visited[], int n) {
    int min = INF, index = -1;
    for(int i = 0; i < n; i++) {
        if(!visited[i] && dist[i] < min) {
            min = dist[i];
            index = i;
        }
    }
    return index;
}
```

```
int main() {
    int n;
    scanf("%d", &n);

    int graph[MAX][MAX];

    for(int i = 0; i < n; i++) {
        for(int j = 0; j < n; j++) {
            scanf("%d", &graph[i][j]);
            if(i != j && graph[i][j] == 0)
                graph[i][j] = INF;
        }
    }

    int src;
    scanf("%d", &src);

    int dist[MAX], visited[MAX];

    for(int i = 0; i < n; i++) {
        dist[i] = INF;
        visited[i] = 0;
    }

    dist[src] = 0;

    for(int count = 0; count < n - 1; count++) {
        int u = minDistance(dist, visited, n);
        visited[u] = 1;

        for(int v = 0; v < n; v++) {
            if(!visited[v] && graph[u][v] != INF &&
               dist[u] + graph[u][v] < dist[v]) {
                dist[v] = dist[u] + graph[u][v];
            }
        }
    }

    printf("Vertex Distance from Source\n");
    for(int i = 0; i < n; i++) {
        printf("%d\t\t%d\n", i, dist[i]);
```

```
    }
    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

Anu is given a weighted, directed, and connected graph with V vertices and E edges represented as an adjacency list. They are also given a source vertex S.

The task is to find the shortest distance from the source vertex S to all other vertices in the graph using Dijkstra's algorithm.

Input Format

The first line contains an integer V representing the number of vertices in the graph.

The second line contains an integer E representing the number of edges in the graph.

The next E lines contain three integers each: from, to, and weight, denoting an edge between vertices from and to with the given weight.

The last line contains an integer S representing the source vertex.

Output Format

The output prints a single line in the format:

Shortest distances from vertex S to all other vertices: d0 d1 d2 ... dV-1

where S is the source vertex number and d0, d1, ..., dV-1 are the shortest distances from S to vertices 0 through V-1 respectively, each followed by a space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2
1
0 1 9
0
Output: Shortest distances from vertex 0 to all other vertices: 0 9

Answer

```
#include <stdio.h>

#define MAX 100
#define INF 1000000

int minDistance(int dist[], int visited[], int V) {
    int min = INF, idx = -1;
    for (int i = 0; i < V; i++) {
        if (!visited[i] && dist[i] < min) {
            min = dist[i];
            idx = i;
        }
    }
    return idx;
}

int main() {
    int V, E;
    scanf("%d", &V);
    scanf("%d", &E);

    int graph[MAX][MAX];

    for(int i=0;i<V;i++)
        for(int j=0;j<V;j++)
            graph[i][j] = INF;

    for (int i = 0; i < E; i++) {
        int from, to, weight;
        scanf("%d %d %d", &from, &to, &weight);
        graph[from][to] = weight;
        graph[to][from] = weight;   // undirected
```

```
    }
    int S;
    scanf("%d", &S);

    int dist[MAX], visited[MAX];

    for (int i = 0; i < V; i++) {
        dist[i] = INF;
        visited[i] = 0;
    }

    dist[S] = 0;

    for (int i = 0; i < V - 1; i++) {
        int u = minDistance(dist, visited, V);
        visited[u] = 1;

        for (int v = 0; v < V; v++) {
            if (!visited[v] && graph[u][v] != INF &&
                dist[u] + graph[u][v] < dist[v]) {
                dist[v] = dist[u] + graph[u][v];
            }
        }
    }

    printf("Shortest distances from vertex %d to all other vertices: ", S);
    for (int i = 0; i < V; i++)
        printf("%d ", dist[i]);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 9_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 14

Section 1 : MCQ

1. The problem of finding a path in a graph that visits every vertex exactly once is called?

Answer

Hamiltonian path problem

Status : Correct ***Marks : 1/1***

2. In the Hamiltonian Cycle problem, if a graph contains a Hamiltonian cycle, it is called a

Answer

Hamiltonian graph

Status : Correct ***Marks : 1/1***

vtu27632

3. What is the primary difficulty in finding a Hamiltonian Path in a general graph?

Answer

It is an NP-complete problem.

Status : Correct ***Marks : 1/1***

4. Which of the following statements is true regarding the backtracking algorithm for the Hamiltonian Cycle problem?

Answer

It explores different paths in the graph to find a Hamiltonian cycle.

Status : Correct ***Marks : 1/1***

5. Which algorithmic paradigm is commonly used to solve the Hamiltonian Cycle problem?

Answer

Backtracking

Status : Correct ***Marks : 1/1***

6. The following paradigm can be used to find the solution to the problem in minimum time: Given a set of non-negative integers, and a value K, determine if there is a subset of the given set with a sum equal to K:

Answer

Dynamic Programming

Status : Correct ***Marks : 1/1***

7. What is a subset sum problem?

Answer

vtu27632

Checking for the presence of a subset that has the sum of elements equal to a given number and printing true or false based on the result

Status : Correct ***Marks : 1/1***

8. Which of the following is not true about the subset sum problem?

Answer

the dynamic programming solution has a time complexity of O(n log n)

Status : Correct ***Marks : 1/1***

9. What is the worst case time complexity of dynamic programming solution of the subset sum problem(sum=given subset sum)?

Answer

O(sum*n)

Status : Correct ***Marks : 1/1***

10. Placing N-queens so that no two queens attack each other is called _____.

Answer

N-queen’s problem

Status : Correct ***Marks : 1/1***

11. Where is the n-queens problem implemented?

Answer

Chess

Status : Correct ***Marks : 1/1***

12. Which of the following methods can be used to solve N-Queen's problem?

Answer

Backtracking

Status : Correct ***Marks : 1/1***

13. Which one of the following is an application of the backtracking algorithm?

Answer

Crossword

Status : Correct ***Marks : 1/1***

14. For N Queens problem, the time complexity is

Answer

O(N!)

Status : Correct ***Marks : 1/1***

15. How many unique solutions are there to the 4 Queens problem, where solutions that are reflections or rotations of each other are considered the same?

Answer

1

Status : Wrong ***Marks : 0/1***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 9_COD

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Bob has a task to find a Hamiltonian cycle in a given undirected simple graph (no self-loops) represented as an adjacency matrix, where a value of 1 indicates an edge exists between two vertices and a value of 0 indicates no edge. A Hamiltonian cycle is a cycle that visits every vertex exactly once and returns to the starting vertex. Bob needs to write a program that will determine if such a cycle exists and, if so, print the cycle starting and ending at vertex 0. If no cycle is found, the program should output "No solution".

Your task is to help Bob implement this.

Input Format

The first line contains an integer V, representing the number of vertices.

The following V lines each contain V space-separated integers (0 or 1), representing the adjacency matrix. The matrix is symmetric (undirected graph) and has zeros on the diagonal (no self-loops)

Output Format

If a Hamiltonian cycle is found, the first line prints "Solution found" and the second line prints the cycle as a series of space-separated integers, representing the vertices starting and ending at vertex 0.

If no Hamiltonian cycle is found, print "No solution".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 8
0 1 0 1 1 0 0 0
1 0 1 0 0 1 0 0
0 1 0 1 0 0 1 0
1 0 1 0 0 0 0 1
1 0 0 0 0 1 0 1
0 1 0 0 1 0 1 0
0 0 1 0 0 1 0 1
0 0 0 1 1 0 1 0
Output: Solution found
0 1 2 3 7 6 5 4 0

Answer

```
// You are using GCC
#include <stdio.h>

#define MAX 10

int graph[MAX][MAX];
int path[MAX];
int visited[MAX];
int V;

// Check if vertex can be added
```

```
int isSafe(int v, int pos) {
    if (graph[path[pos - 1]][v] == 0)
        return 0;

    if (visited[v])
        return 0;

    return 1;
}

// Backtracking function
int hamiltonian(int pos) {
    if (pos == V) {
        // Check last to first edge
        if (graph[path[pos - 1]][path[0]] == 1)
            return 1;
        else
            return 0;
    }

    for (int v = 1; v < V; v++) {
        if (isSafe(v, pos)) {
            path[pos] = v;
            visited[v] = 1;

            if (hamiltonian(pos + 1))
                return 1;

            visited[v] = 0;
        }
    }

    return 0;
}

int main() {
    scanf("%d", &V);

    for (int i = 0; i < V; i++) {
        for (int j = 0; j < V; j++) {
            scanf("%d", &graph[i][j]);
        }
```

```
    }

    // Initialize
    for (int i = 0; i < V; i++)
        visited[i] = 0;

    // Start from vertex 0
    path[0] = 0;
    visited[0] = 1;

    if (hamiltonian(1)) {
        printf("Solution found\n");

        for (int i = 0; i < V; i++) {
            printf("%d ", path[i]);
        }

        printf("0");
    } else {
        printf("No solution");
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Given an undirected complete graph with N vertices (N ≥ 3), find the number of distinct Hamiltonian cycles in the graph using backtracking. A Hamiltonian cycle is a cycle that visits each vertex exactly once and returns to the starting vertex.

Two Hamiltonian cycles are considered identical if one can be obtained from the other by rotation (changing the starting vertex) or reversal (traversing in the opposite direction).

Example:

For N=4, the vertices are 0, 1, 2, 3. The 3 distinct Hamiltonian cycles are:

0 1 2 3 00 1 3 2 00 2 1 3 0

Output: 3

Input Format

The input consists of a single integer N, representing the number of vertices in the complete graph.

Output Format

Print a single integer on its own line representing the number of distinct Hamiltonian cycles in the complete graph with N vertices.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6

Output: 60

Answer

```
// You are using GCC
#include <stdio.h>

// factorial using recursion (backtracking style)
long long fact(int n) {
    if (n == 0 || n == 1)
        return 1;
    return n * fact(n - 1);
}

int main() {
    int n;
    scanf("%d", &n);

    long long result = fact(n - 1) / 2;

    printf("%lld", result);
```

```
    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

A college is organizing an event and has collected donations from N sponsors. Each sponsor contributes a fixed amount. The event coordinator wants to know all possible groups of sponsors whose donation sum matches exactly the required event budget S.

Write a program using Backtracking to find all subsets of sponsor contributions whose sum is exactly equal to S.

A subset may contain any number of sponsors, but each sponsor amount can be used only once.

Formula:

A subset is valid if: a1 + a2 + ... + ak = S

Input Format

The first line contains an integer N, representing the number of sponsors.

The second line contains N space-separated integers in ascending order, representing the donation amounts.

The third line contains an integer S, representing the required budget.

Output Format

Print all subsets whose sum is exactly S, one subset per line. Within each subset, print the elements in the order they appear in the input, each followed by a space. Subsets are printed in the order they are discovered during backtracking (subsets starting with smaller elements appear first).

If no subset exists, print: No subset found

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
10 20 30 40
50

Output: 10 40
20 30

Answer

```
// You are using GCC
#include <stdio.h>

#define MAX 20

int arr[MAX];
int subset[MAX];
int n, S;
int found = 0;

void printSubset(int size) {
    for (int i = 0; i < size; i++) {
        printf("%d ", subset[i]);
    }
    printf("\n");
}

void backtrack(int index, int currentSum, int size) {
    // valid solution
    if (currentSum == S) {
        printSubset(size);
        found = 1;
        return;
    }

    // stop if exceeded or end reached
    if (index == n || currentSum > S)
        return;
```

```
    // include current element
    subset[size] = arr[index];
    backtrack(index + 1, currentSum + arr[index], size + 1);

    // exclude current element
    backtrack(index + 1, currentSum, size);
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    scanf("%d", &S);

    backtrack(0, 0, 0);

    if (!found) {
        printf("No subset found");
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Emily is working on arranging queens on a chessboard where one queen must already be fixed at a given position. She wants to find all possible configurations of placing N queens such that no two queens attack each other, with the condition that the queen at the specified position cannot be moved.

A queen can attack any cell in its row, column, or diagonal. Row and column indices are 0-based.

Write a program to ensure that the chessboard solutions are displayed correctly, or state "No solution" if none exist.

Input Format

The first line contains an integer N representing the size of the chessboard.

The second line contains an integer i, representing the row index of the fixed queen.

The third line contains an integer j, representing the column index of the fixed queen.

Output Format

The first line of output consists of a single floating-point number representing the maximum total value, formatted to two decimal places.

The next n lines each consist of a single floating-point number representing the fraction x of each item selected, formatted to two decimal places. x represents the fraction of the i-th item taken (1.00 means the item is fully taken, a value between 0.00 and 1.00 means a fraction is taken). The fractions should be printed in the same order as the input items.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
0
1
Output: . Q . .
. . . Q
Q . . .
. . Q .

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

#define MAX 10
```

```
int n;
int board[MAX][MAX];
int col[MAX];
int d1[2 * MAX];
int d2[2 * MAX];

int fixed_i, fixed_j;
int found = 0;

// print board
void printBoard() {
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (board[i][j])
                printf("Q ");
            else
                printf(". ");
        }
        printf("\n");
    }
    printf("\n");
}

// backtracking
void solve(int row) {
    if (row == n) {
        found = 1;
        printBoard();
        return;
    }

    // fixed queen row
    if (row == fixed_i) {
        solve(row + 1);
        return;
    }

    for (int j = 0; j < n; j++) {
        if (!col[j] && !d1[row - j + n] && !d2[row + j]) {

            board[row][j] = 1;
            col[j] = d1[row - j + n] = d2[row + j] = 1;
```

```
            solve(row + 1);

            board[row][j] = 0;
            col[j] = d1[row - j + n] = d2[row + j] = 0;
        }
    }
}

int main() {
    scanf("%d", &n);
    scanf("%d", &fixed_i);
    scanf("%d", &fixed_j);

    // initialize
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            board[i][j] = 0;

    for (int i = 0; i < MAX; i++) {
        col[i] = 0;
        d1[i] = 0;
        d2[i] = 0;
    }

    // place fixed queen
    board[fixed_i][fixed_j] = 1;
    col[fixed_j] = 1;
    d1[fixed_i - fixed_j + n] = 1;
    d2[fixed_i + fixed_j] = 1;

    solve(0);

    if (!found)
        printf("No solution");

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 9_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Given an adjacency matrix adj[][] of an undirected graph consisting of N vertices, find a Hamiltonian Path in the graph if one exists. If found, print the path as a sequence of vertex indices separated by ->. Otherwise, print No Hamiltonian Path found.

A Hamiltonian path visits each and every vertex of the graph exactly once. The adjacency matrix is symmetric with zeros on the diagonal (no self-loops).

Write a program using Backtracking to find the Hamiltonian Path.

Examples:

Input: adj[][] = {{0, 1, 1, 1, 0}, {1, 0, 1, 0, 1}, {1, 1, 0, 1, 1}, {1, 0, 1, 0, 0}}

Output: Yes

Explanation:

There exists a Hamiltonian Path for the given graph, as shown in the image below:

Input: adj[][] = {{0, 1, 0, 0}, {1, 0, 1, 1}, {0, 1, 0, 0}, {0, 1, 0, 0}}

Output: No

Input Format

The first line contains an integer N, representing the number of vertices in the graph.

The next N lines each contain N space-separated integers (0 or 1), representing the adjacency matrix of the graph.

Output Format

If a Hamiltonian path exists, print the vertices of the path separated by -> on a single line.

If no Hamiltonian path exists, print: No Hamiltonian Path found

Refer to the sample output for formatting specifications.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5
0 1 1 1 0
1 0 1 0 1
1 1 0 1 1
1 0 1 0 0
0 1 1 0 0
Output: 0 -> 1 -> 4 -> 2 -> 3

Answer

```
#include <stdio.h>
```

```
int n;
int graph[10][10];
int path[10];
int visited[10];

int isSafe(int v, int pos) {
    if (graph[path[pos - 1]][v] == 0)
        return 0;

    if (visited[v])
        return 0;

    return 1;
}

int solve(int pos) {
    if (pos == n)
        return 1;

    for (int v = 0; v < n; v++) {
        if (isSafe(v, pos)) {
            path[pos] = v;
            visited[v] = 1;

            if (solve(pos + 1))
                return 1;

            visited[v] = 0;
        }
    }
    return 0;
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &graph[i][j]);

    for (int start = 0; start < n; start++) {
```

```
        for (int i = 0; i < n; i++)
            visited[i] = 0;

        path[0] = start;
        visited[start] = 1;

        if (solve(1)) {
            for (int i = 0; i < n; i++) {
                printf("%d", path[i]);
                if (i != n - 1)
                    printf(" -> ");
            }
            return 0;
        }
    }

    printf("No Hamiltonian Path found");
    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

You are given an undirected graph with N vertices. Implement a function longest_hamiltonian_cycle to find the longest Hamiltonian cycle in the graph. A Hamiltonian cycle is a cycle that visits every vertex exactly once, except for the starting and ending vertices, which are the same.

Input Format

The first line of input consists of an integer N representing the number of vertices in the graph.

The next N lines each contain N space-separated integers, representing the adjacency matrix of the graph. The value at graph[i][j] is 1 if there is an edge between vertex i and vertex j, and 0 otherwise.

Output Format

If a Hamiltonian cycle exists, print "Longest Hamiltonian Cycle:" followed by the vertices of the longest cycle found in order within square bracket separated by a comma.

If no Hamiltonian cycle exists, print "No Hamiltonian Cycle found".

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 1 1 0
1 0 1 1
1 1 0 1
0 1 1 0
Output: Longest Hamiltonian Cycle: [0, 1, 3, 2]

Answer

```
#include <stdio.h>

int n;
int graph[10][10];
int path[10];
int visited[10];

int solve(int pos) {
    if (pos == n) {
        if (graph[path[pos - 1]][path[0]] == 1)
            return 1;
        return 0;
    }

    for (int v = 1; v < n; v++) {
        if (!visited[v] && graph[path[pos - 1]][v]) {
            visited[v] = 1;
            path[pos] = v;

            if (solve(pos + 1))
                return 1;

            visited[v] = 0;
        }
    }
```

```
    return 0;
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &graph[i][j]);

    for (int i = 0; i < n; i++)
        visited[i] = 0;

    path[0] = 0;
    visited[0] = 1;

    if (solve(1)) {
        printf("Longest Hamiltonian Cycle: [");
        for (int i = 0; i < n; i++) {
            printf("%d", path[i]);
            if (i != n - 1)
                printf(", ");
        }
        printf("]");
    } else {
        printf("No Hamiltonian Cycle found");
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Nira is studying the N-Queens problem and needs to write a program to solve it. The program should find a valid arrangement of N queens on an N×N chessboard, ensuring that no two queens can attack each other.

Two queens attack each other if they are in the same row, the same column, or the same diagonal. Once a solution is found, display the board

with queens placed correctly. A solution is guaranteed to exist for all valid values of N.

Write a program using Backtracking to solve the N-Queens problem.

Example

Input:

4 // Value of N

Output:

0 0 1 0

1 0 0 0

0 0 0 1

0 1 0 0

Explanation: The output represents a valid arrangement of queens on the 4x4 chessboard, where 1 indicates the position of a queen and 0 indicates an empty cell.

In the first row, a queen is placed in the third column.In the second row, a queen is placed in the first column.In the third row, a queen is placed in the fourth column.In the fourth row, a queen is placed in the second column.This arrangement of queens on the board ensures that no two queens threaten each other.

Input Format

The input consists of a single integer N, representing the size of the chessboard (N×N).

Output Format

Print the N×N board as N rows of N space-separated integers. Each integer is followed by a space (including the last integer on each row). Print 1 where a queen is placed and 0 for an empty cell. Print any one valid solution.

vtu27632

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4

Output: 0 0 1 0
1 0 0 0
0 0 0 1
0 1 0 0

Answer

```
#include <stdio.h>

int n;
int board[25][25];
int col[25], d1[50], d2[50];

int solve(int r) {
    if (r == n) return 1;

    for (int c = 0; c < n; c++) {
        if (!col[c] && !d1[r - c + n] && !d2[r + c]) {
            board[r][c] = 1;
            col[c] = d1[r - c + n] = d2[r + c] = 1;

            if (solve(r + 1))
                return 1;

            board[r][c] = 0;
            col[c] = d1[r - c + n] = d2[r + c] = 0;
        }
    }
    return 0;
}

int main() {
    scanf("%d", &n);

    solve(0);

    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++)
            printf("%d ", board[i][j]);
```

```
    printf("\n");
  }

  return 0;
}
```

Status : Wrong ***Marks : 0/10***

4. Problem Statement

In chess, a knight moves in an "L" shape: two squares in one direction and one square perpendicular to it. From position (0, 0) on an infinite chessboard, a knight can move to one of the following eight positions in a single step:

(1, 2), (−1, 2), (1, −2), (−1, −2), (2, 1), (−2, 1), (2, −1), (−2, −1).

Given a target position (x, y) where both x and y are positive integers, find the minimum number of steps needed for the knight to travel from (0, 0) to (x, y) using BFS (Breadth-First Search).

Beginning from location (0,0), what is the minimum number of steps needed for a knight to get to some other arbitrary location (x,y)?

Input Format

The first line contains two space-separated integers x and y, representing the target position of the knight on the chessboard.

Output Format

Print a single integer representing the minimum number of steps needed for the knight to move from (0, 0) to (x, y).

Refer to the sample output for formatting specifications

Sample Test Case

Input: 1 2

Output: 1

Answer

```
#include <stdio.h>

int main() {
    int x, y;
    scanf("%d %d", &x, &y);

    int dx[8] = {1,-1,1,-1,2,-2,2,-2};
    int dy[8] = {2,2,-2,-2,1,1,-1,-1};

    int visited[20][20] = {0};
    int qx[400], qy[400], dist[400];

    int front = 0, rear = 0;

    qx[rear] = 0;
    qy[rear] = 0;
    dist[rear] = 0;
    rear++;

    visited[0][0] = 1;

    while(front < rear) {
        int cx = qx[front];
        int cy = qy[front];
        int cd = dist[front];
        front++;

        if(cx == x && cy == y) {
            printf("%d", cd);
            return 0;
        }

        for(int i = 0; i < 8; i++) {
            int nx = cx + dx[i];
            int ny = cy + dy[i];

            if(nx >= -8 && nx <= 8 && ny >= -8 && ny <= 8) {
                int ix = nx + 8;
                int iy = ny + 8;
```

```
            if(!visited[ix][iy]) {
                visited[ix][iy] = 1;
                qx[rear] = nx;
                qy[rear] = ny;
                dist[rear] = cd + 1;
                rear++;
            }
        }
    }
  }

  return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

A customer is shopping in a supermarket and has selected N items, each with a fixed price.

The customer has a discount coupon that can be applied only if the total price of some selected items is exactly equal to a target amount S.

Write a program using Backtracking to find all distinct subsets of item prices whose sum is exactly equal to S.

Each item price can be used only once. If the input contains duplicate prices, the output must not contain repeated subsets.

Formula: A subset is valid if: p1 + p2 + ... + pk = S

Print each valid subset with its elements in ascending order. Print subsets in the order they are discovered by the backtracking algorithm (which processes the sorted array from left to right).

Input Format

The first line contains an integer N representing the number of items.

The second line contains N space-separated integers representing item prices.

The prices may include duplicate values.

The third line contains an integer S representing the target bill amount.

Output Format

Print each distinct valid subset on a separate line. Within each subset, print elements in ascending order, each followed by a space (including the last element).

Print subsets in the order they are found during backtracking on the sorted input.

If no valid subset exists, print: No subset found

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
5 5 10 15 20
25

Output: 5 5 15
5 20
10 15

Answer

```
#include <stdio.h>
#include <stdlib.h>

int n, target;
int arr[25], subset[25];
int found = 0;

int cmp(const void *a, const void *b) {
    return (*(int*)a - *(int*)b);
}

void backtrack(int start, int sum, int size) {
    if (sum == target) {
        for (int i = 0; i < size; i++)
            printf("%d ", subset[i]);
```

```
        printf("\n");
        found = 1;
        return;
    }

    for (int i = start; i < n; i++) {

        if (i > start && arr[i] == arr[i - 1])
            continue;

        if (sum + arr[i] > target)
            break;

        subset[size] = arr[i];
        backtrack(i + 1, sum + arr[i], size + 1);
    }
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);

    scanf("%d", &target);

    qsort(arr, n, sizeof(int), cmp);

    backtrack(0, 0, 0);

    if (!found)
        printf("No subset found");

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 9_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 41

Section 1 : Coding

1. Problem Statement

Diya is given a weighted, undirected graph with N vertices. She wants to find the minimum weight Hamiltonian cycle in the graph, if one exists. A Hamiltonian cycle is a cycle that visits every vertex exactly once, except for the starting and ending vertices, which are the same. The weight of a Hamiltonian cycle is the sum of the weights of all edges in the cycle:

W = w(v , v) + w(v , v) + ... + w(v , v)

Write a program using Backtracking to find the minimum weight Hamiltonian cycle.

Example: For a graph with 4 vertices and the adjacency matrix:

0 10 15 20

10 0 35 25

15 35 0 30

20 25 30 0

The algorithm explores all Hamiltonian cycles starting from vertex 0. Among all valid cycles, 0 1 3 2 0 has the minimum weight: 10 + 25 + 30 + 15 = 80.

Input Format

The first line contains an integer N representing the number of vertices in the graph.

The next N lines each contain N space-separated integers representing the adjacency matrix of the weighted graph. The value at graph[i][j] is the weight of the edge between vertices i and j. A value of 0 means no edge exists. The matrix is symmetric (graph[i][j] == graph[j][i]) and the diagonal is always 0 (graph[i][i] == 0).

Output Format

If a minimum weight Hamiltonian cycle exists, print Minimum Weight Hamiltonian Cycle: on the first line, then print the vertices of the cycle in square brackets separated by a comma and a space, including the starting vertex at both the beginning and the end of the cycle. On the next line, print Total Weight: followed by a space and the integer total weight.

If no Hamiltonian cycle exists, print No Hamiltonian Cycle found with minimum weight.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
0 10 15 20
10 0 35 25
15 35 0 30
20 25 30 0

Output: Minimum Weight Hamiltonian Cycle:
[0, 1, 3, 2, 0]
Total Weight: 80

Answer

```
#include <stdio.h>

#define MAX 10
#define INF 1000000

int n;
int graph[MAX][MAX];

int path[MAX], bestPath[MAX];
int visited[MAX];
int minCost = INF;

void tsp(int pos, int count, int cost)
{
    if (count == n && graph[pos][0] > 0)
    {
        int total = cost + graph[pos][0];
        if (total < minCost)
        {
            minCost = total;
            for (int i = 0; i < n; i++)
                bestPath[i] = path[i];
        }
        return;
    }

    for (int i = 0; i < n; i++)
    {
        if (!visited[i] && graph[pos][i] > 0)
        {
            visited[i] = 1;
            path[count] = i;

            tsp(i, count + 1, cost + graph[pos][i]);

            visited[i] = 0;
        }
```

```
    }
}

int main()
{
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &graph[i][j]);

    for (int i = 0; i < n; i++)
        visited[i] = 0;

    path[0] = 0;
    visited[0] = 1;

    tsp(0, 1, 0);

    if (minCost == INF)
    {
        printf("No Hamiltonian Cycle found with minimum weight.");
        return 0;
    }

    printf("Minimum Weight Hamiltonian Cycle:\n[");
    for (int i = 0; i < n; i++)
        printf("%d, ", bestPath[i]);

    printf("0]\n");
    printf("Total Weight: %d", minCost);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Alice is tasked with determining whether a given graph contains a Hamiltonian Cycle and, if it does, listing all such cycles. A Hamiltonian

Cycle in a graph is a cycle that visits each vertex exactly once and returns to the starting vertex.

Write a program using Backtracking that takes a graph represented by an adjacency matrix and finds all Hamiltonian Cycles starting from the first vertex (vertex 0), if any exist.

Input Format

The first line contains an integer N representing the number of vertices in the graph.

The next N lines each contain a single string — the name of each vertex (no surrounding spaces).

The following N lines each contain N space-separated integers (0 or 1) representing the adjacency matrix. A value of 1 at position [i][j] means an edge exists between vertex i and vertex j; 0 means no edge.

Output Format

For each Hamiltonian Cycle found, print a line in the format: ['v0', 'v1', ..., 'vn', 'v0'] where vertex names are enclosed in single quotes, separated by a comma and a space, with the starting vertex repeated at the end. Print cycles in the order they are discovered by the backtracking algorithm.

If no Hamiltonian Cycle exists, print: No Hamiltonian Cycle

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 8
a
b
c
d
e

vtu27632

f
g
h
0 1 0 0 0 0 0 1
1 0 1 0 0 0 0 0
0 1 0 1 0 0 0 1
0 0 1 0 1 0 1 0
0 0 0 1 0 1 0 0
0 0 0 0 1 0 1 0
0 0 0 1 0 1 0 1
1 0 1 0 0 0 1 0

Output: ['a', 'b ', 'c ', 'd ', 'e ', 'f ', 'g ', 'h', 'a']
['a', 'h', 'g ', 'f ', 'e ', 'd ', 'c ', 'b ', 'a']

Answer

```
#include <stdio.h>
#include <string.h>

int n;
char names[10][20];
int graph[10][10];
int path[10];
int used[10];
int found = 0;

void printCycle() {
    printf("[");
    for (int i = 0; i < n; i++) {
        printf("'%s', ", names[path[i]]);
    }
    printf("'%s']\n", names[path[0]]);
}

int isSafe(int v, int pos) {
    if (graph[path[pos - 1]][v] == 0)
        return 0;

    for (int i = 0; i < pos; i++)
        if (path[i] == v)
            return 0;

    return 1;
```

```
}

void hamiltonian(int pos) {
    if (pos == n) {
        if (graph[path[pos - 1]][path[0]] == 1) {
            printCycle();
            found = 1;
        }
        return;
    }

    for (int v = 1; v < n; v++) {
        if (isSafe(v, pos)) {
            path[pos] = v;
            hamiltonian(pos + 1);
        }
    }
}

int main() {
    scanf("%d", &n);
    getchar();

    for (int i = 0; i < n; i++) {
        fgets(names[i], sizeof(names[i]), stdin);
        names[i][strcspn(names[i], "\n")] = 0;
    }

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &graph[i][j]);

    path[0] = 0;

    hamiltonian(1);

    if (!found)
        printf("No Hamiltonian Cycle");

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

A company has N employees, and each employee can contribute a fixed number of training hours.

The manager wants to form groups of employees such that the total training hours of a selected group is exactly equal to the required training goal S.

Write a program using Backtracking to find all distinct subsets of employee training hours whose sum is exactly equal to S.

Each employee's training hours can be used only once.

If the input contains duplicate hour values, the output must not contain repeated subsets.

Condition

A subset is valid if:

h1 + h2 + ... + hk = S

Input Format

The first line contains an integer N representing the number of employees.

The second line contains N space-separated integers representing the training hours of each employee. The input may contain duplicate values.

The third line contains an integer S representing the required training goal.

Output Format

Print each distinct valid subset on a separate line. Within each subset, print elements in ascending order, each followed by a space (including the last element). Print subsets in the order they are found during backtracking on the sorted input.

If no valid subset exists, print: No subset found

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
2 2 3 5 6 8
10

Output: 2 2 6
2 3 5
2 8

Answer

```
#include <stdio.h>
#include <stdlib.h>

int n, target;
int arr[25], subset[25];
int found = 0;

int compare(const void *a, const void *b) {
    return (*(int*)a - *(int*)b);
}

void backtrack(int start, int sum, int size) {
    if (sum == target) {
        for (int i = 0; i < size; i++)
            printf("%d ", subset[i]);
        printf("\n");
        found = 1;
        return;
    }

    for (int i = start; i < n; i++) {
        if (i > start && arr[i] == arr[i - 1])
            continue;

        if (sum + arr[i] > target)
            break;

        subset[size] = arr[i];
        backtrack(i + 1, sum + arr[i], size + 1);
    }
```

```
}
int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        scanf("%d", &arr[i]);

    scanf("%d", &target);

    qsort(arr, n, sizeof(int), compare);

    backtrack(0, 0, 0);

    if (!found)
        printf("No subset found");

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Nikila is exploring the N Queens Problem. This classic problem involves placing N queens on an N×N chessboard such that no two queens threaten each other. In chess, queens can move horizontally, vertically, and diagonally, so the challenge is to arrange the queens to ensure they do not share the same row, column, or diagonal.

Write a program using Backtracking to find and print all valid solutions to the N Queens Problem.

Input Format

The input consists of a single integer N representing both the size of the chessboard (N×N) and the number of queens to be placed.

Output Format

Print all valid solutions in the order they are found by the backtracking algorithm. Each solution is represented as an N×N matrix where 1 indicates the position of

a queen and 0 represents an empty cell. Each value is followed by a space. Each row is printed on a new line. Print a blank line after each solution including the last one. If no valid solution exists, print nothing.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4

Output: 0 0 1 0
1 0 0 0
0 0 0 1
0 1 0 0

0 1 0 0
0 0 0 1
1 0 0 0
0 0 1 0

Answer

```
#include <stdio.h>

int n;
int board[10][10];

int isSafe(int row, int col) {
    int i, j;

    for (i = 0; i < row; i++)
        if (board[i][col])
            return 0;

    for (i = row - 1, j = col - 1; i >= 0 && j >= 0; i--, j--)
        if (board[i][j])
            return 0;

    for (i = row - 1, j = col + 1; i >= 0 && j < n; i--, j++)
        if (board[i][j])
            return 0;
```

```
    return 1;
}

void printSolution() {
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            printf("%d ", board[i][j]);
        }
        printf("\n");
    }
    printf("\n");
}

void solve(int row) {
    if (row == n) {
        printSolution();
        return;
    }

    for (int col = 0; col < n; col++) {
        if (isSafe(row, col)) {
            board[row][col] = 1;
            solve(row + 1);
            board[row][col] = 0;
        }
    }
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            board[i][j] = 0;

    solve(0);

    return 0;
}
```

Status : Partially correct ***Marks : 1/10***

5. Problem Statement

Sarah wants to verify whether a given arrangement of queens on a 4×4 chessboard constitutes a valid solution to the 4 Queens Problem. The objective is to position four queens on the board in a way that prevents any queen from threatening another, considering horizontal, vertical, and diagonal movements.

To determine the validity of the solution, Sarah needs to ensure that there are exactly four queens on the board, each row and column contains only one queen, and no two queens share the same diagonal.

Your task is to assist Sarah by implementing a program that checks these criteria for the given chessboard arrangement.

Input Format

The input consists of 4 lines, each containing 4 space-separated integers representing one row of the chessboard. Each integer is either 1 (queen present) or 0 (empty cell).

Output Format

Print a single line indicating whether the placement is valid, checking conditions in the following priority order:

1. If the total number of queens is not exactly 4: False - Invalid number of queens: X where X is the count of queens on the board.
2. If a row does not contain exactly one queen: False - Row Y has Z queens where Y is the 0-based row index and Z is the number of queens in that row.
3. If a column does not contain exactly one queen: False - Column Y has Z queens where Y is the 0-based column index and Z is the number of queens in that column.
4. If a main diagonal (top-left to bottom-right) contains more than one queen: False - Main diagonal (d=X) has Y queens where X is the diagonal identifier computed as column - row (range −3 to 3) and Y is the number of queens on that diagonal.
5. If an anti-diagonal (top-right to bottom-left) contains more than one queen: False - Anti-diagonal (d=X) has Y queens where X is the diagonal identifier computed as column + row (range 0 to 6) and Y is the number of queens on that diagonal.
6. If all conditions are satisfied: True - Valid 4 Queens solution: All conditions satisfied

vtu27632

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 0 1 0 0
0 0 0 1
1 0 0 0
0 0 1 0
Output: True - Valid 4 Queens solution: All conditions satisfied

Answer

```
// You are using GCC
#include <stdio.h>

int main() {
    int a[4][4];
    int i, j;

    for(i = 0; i < 4; i++)
        for(j = 0; j < 4; j++)
            scanf("%d", &a[i][j]);

    int total = 0;
    for(i = 0; i < 4; i++)
        for(j = 0; j < 4; j++)
            total += a[i][j];

    if(total != 4) {
        printf("False - Invalid number of queens: %d", total);
        return 0;
    }

    // row check
    for(i = 0; i < 4; i++) {
        int count = 0;
        for(j = 0; j < 4; j++)
            count += a[i][j];

        if(count != 1) {
```

```
        printf("False - Row %d has %d queens", i, count);
        return 0;
    }
}

// column check
for(j = 0; j < 4; j++) {
    int count = 0;
    for(i = 0; i < 4; i++)
        count += a[i][j];

    if(count != 1) {
        printf("False - Column %d has %d queens", j, count);
        return 0;
    }
}

// main diagonal (col - row)
for(int d = -3; d <= 3; d++) {
    int count = 0;
    for(i = 0; i < 4; i++) {
        for(j = 0; j < 4; j++) {
            if(j - i == d && a[i][j] == 1)
                count++;
        }
    }
    if(count > 1) {
        printf("False - Main diagonal (d=%d) has %d queens", d, count);
        return 0;
    }
}

// anti diagonal (col + row)
for(int d = 0; d <= 6; d++) {
    int count = 0;
    for(i = 0; i < 4; i++) {
        for(j = 0; j < 4; j++) {
            if(i + j == d && a[i][j] == 1)
                count++;
        }
    }
    if(count > 1) {
```

```
        printf("False - Anti-diagonal (d=%d) has %d queens", d, count);
        return 0;
    }
  }

  printf("True - Valid 4 Queens solution: All conditions satisfied");

  return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 10_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 14

Section 1 : MCQ

1. Which of the following methods is commonly used to solve assignment problems?

Answer

Hungarian method

Status : Correct ***Marks : 1/1***

2. The application of assignment problems is to obtain _____

Answer

Minimum cost or maximum profit

Status : Correct ***Marks : 1/1***

vtu27632

3. The assignment problem is said to be balanced if _____.

Answer

the number of rows is equal to the number of columns

Status : Correct ***Marks : 1/1***

4. The minimum number of lines covering all zeros in a reduced cost matrix of order n can be _____.

Answer

at the most n

Status : Correct ***Marks : 1/1***

5. The assignment problem _____.

Answer

All of the mentioned options

Status : Correct ***Marks : 1/1***

6. You are given a knapsack that can carry a maximum weight of 60. There are 4 items with weights of {20, 30, 40, and 70} and values {70, 80, 90, and 200}.

What is the maximum value of the items you can carry in the knapsack?

Answer

160

Status : Correct ***Marks : 1/1***

7. What is the objective of the knapsack problem?

Answer

vtu27632

To Get Maximum Total Value In The Knapsack

Status : Correct ***Marks : 1/1***

8. Which of the following methods is used to prune the search space in the Branch and Bound method for the Knapsack problem?

Answer

Ignoring nodes with a weight exceeding the capacity.

Status : Correct ***Marks : 1/1***

9. What is the key difference between Backtracking and Branch and Bound in solving the Knapsack problem?

Answer

Backtracking does not use any bounding function, while Branch and Bound does.

Status : Correct ***Marks : 1/1***

10. What is the primary advantage of using the Branch and Bound approach for the Knapsack problem?

Answer

It systematically explores possible solutions while pruning non-promising ones.

Status : Correct ***Marks : 1/1***

11. The travelling salesman problem can be solved using _____.

Answer

a minimum spanning tree

Status : Correct ***Marks : 1/1***

12. In a traveling salesman problem, the elements of diagonal from left-top to right-bottom are_____.

vtu27632

Answer

all infinity

Status : Correct ***Marks : 1/1***

13. Which type of graph is used to model the TSP problem?

Answer

Directed Weighted Graph

Status : Wrong ***Marks : 0/1***

14. What is the main goal of using Branch and Bound in TSP?

Answer

To minimize search space by pruning unpromising paths

Status : Correct ***Marks : 1/1***

15. Which value helps in deciding whether a node should be pruned in Branch and Bound?

Answer

Bound (lower bound of cost)

Status : Correct ***Marks : 1/1***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 10_COD

Attempt : 1
Total Mark : 30
Marks Obtained : 22

Section 1 : Coding

1. Problem Statement

Riya, the manager of a software development company, needs to assign three developers to three different projects.

Each developer has a different cost (in terms of time and resource usage) for completing each project. Riya wants to assign exactly one developer to each project such that the total development cost is minimized.

To solve this efficiently, she decides to use the Branch and Bound technique for the Assignment Problem.

Your task is to help Riya determine the minimum total cost of assigning developers to projects.

Input Format

vtu27632

The input consists of three lines with three space-separated integers each, representing a 3×3 cost matrix.

Each cell (i, j) represents the cost of assigning the ith developer to the jth project.

Output Format

The output should display the minimum total cost of the assignment in the following exact format: "Minimum total cost: X" , Where X is the minimum total cost obtained after assigning each worker to exactly one task.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 10 12 19
10 5 7
15 14 13

Output: Minimum total cost: 28

Answer

```
// You are using GCC
#include <stdio.h>
#include <limits.h>

#define N 3

int cost[N][N];
int visited[N];
int minCost = INT_MAX;

// Backtracking function
void solve(int worker, int currentCost) {
    if (worker == N) {
        if (currentCost < minCost)
            minCost = currentCost;
        return;
    }

    for (int job = 0; job < N; job++) {
        if (!visited[job]) {
```

```
            visited[job] = 1;

            int newCost = currentCost + cost[worker][job];

            // pruning (branch and bound)
            if (newCost < minCost) {
                solve(worker + 1, newCost);
            }

            visited[job] = 0;
        }
    }
}

int main() {
    // Input cost matrix
    for (int i = 0; i < N; i++) {
        for (int j = 0; j < N; j++) {
            scanf("%d", &cost[i][j]);
        }
    }

    for (int i = 0; i < N; i++)
        visited[i] = 0;

    solve(0, 0);

    printf("Minimum total cost: %d", minCost);

    return 0;
}
```

Status : Correct **Marks : 10/10**

2. Problem Statement

Arjun is the manager of a disaster relief center responsible for sending essential supplies to a flood-affected area using a single rescue truck. The truck has a limited carrying capacity, so Arjun must carefully select which supply packages to load.

Each package has a specific weight and an importance score representing how critical it is for the affected people. Arjun wants to maximize the total importance score of the packages loaded onto the truck without exceeding its weight capacity.

To solve this efficiently, Arjun uses the Branch and Bound technique, which systematically explores possible combinations of packages while pruning choices that cannot produce better results.

Your task is to help Arjun determine the maximum total importance score that can be transported.

Input Format

The first line contains an integer N, representing the number of available packages.

The next N lines each contain two integers: weight[i] value[i]

- weight[i] – weight of the package
- value[i] – importance score of the package

The last line contains an integer W, representing the maximum capacity of the rescue truck.

Output Format

The output prints a single integer representing the maximum total importance score that can be carried without exceeding the truck's weight capacity.

Refer to the sample input and output for formatting specifications.

Sample Test Case

Input: 5
2 40
3 50
1 100
5 95
3 30

vtu27632

10
Output: 245

Answer

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

typedef struct {
    int weight;
    int value;
    float ratio;
} Item;

int n, W;
Item items[1000];
int maxProfit = 0;

// sort by value/weight ratio (descending)
int compare(const void *a, const void *b) {
    Item *i1 = (Item *)a;
    Item *i2 = (Item *)b;

    if (i2->ratio > i1->ratio) return 1;
    else return -1;
}

// bound function (fractional knapsack idea)
float bound(int index, int currentWeight, int currentValue) {
    float profit = currentValue;
    int totalWeight = currentWeight;

    for (int i = index; i < n; i++) {
        if (totalWeight + items[i].weight <= W) {
            totalWeight += items[i].weight;
            profit += items[i].value;
        } else {
            profit += (W - totalWeight) * items[i].ratio;
            break;
        }
    }
    return profit;
```

```
}

// branch and bound recursion
void knapsack(int index, int currentWeight, int currentValue) {
    if (index == n) {
        if (currentValue > maxProfit)
            maxProfit = currentValue;
        return;
    }

    // include item
    if (currentWeight + items[index].weight <= W) {
        knapsack(index + 1,
                 currentWeight + items[index].weight,
                 currentValue + items[index].value);
    }

    // exclude item only if promising
    if (bound(index + 1, currentWeight, currentValue) > maxProfit) {
        knapsack(index + 1, currentWeight, currentValue);
    }
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d %d", &items[i].weight, &items[i].value);
        items[i].ratio = (float)items[i].value / items[i].weight;
    }

    scanf("%d", &W);

    qsort(items, n, sizeof(Item), compare);

    knapsack(0, 0, 0);

    printf("%d", maxProfit);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

You are an art collector who wants to visit a set of art galleries in a city. Each gallery is at a different location, and the cost of traveling between galleries is known.

Your goal is to find the shortest route that allows you to visit each gallery exactly once and return to your starting point, using the traveling salesman problem (TSP). Write a program to calculate the minimum cost of this route.

Note: Solve it using Branch and Bound technique.

Input Format

The first line contains an integer n, the number of galleries.

The next n lines contain n integers each, representing the adjacency matrix.

The ith integer on the jth line represents the cost of traveling from gallery i to gallery j.

Output Format

The output displays "Minimum Cost is: " followed by the minimum cost of the route that visits each gallery exactly once and returns to the starting gallery.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 10 15 20
10 0 35 25
15 35 0 30
20 25 30 0
Output: Minimum Cost is: 80

Answer

```
// You are using GCC
#include <stdio.h>
#include <limits.h>

#define MAX 10

int n;
int cost[MAX][MAX];
int visited[MAX];
int minCost = INT_MAX;

// function to find minimum edge from a node
int firstMin(int i) {
    int min = INT_MAX;
    for (int j = 0; j < n; j++) {
        if (cost[i][j] && cost[i][j] < min)
            min = cost[i][j];
    }
    return min;
}

// second minimum edge from a node
int secondMin(int i) {
    int first = INT_MAX, second = INT_MAX;

    for (int j = 0; j < n; j++) {
        if (i == j || cost[i][j] == 0)
            continue;

        if (cost[i][j] <= first) {
            second = first;
            first = cost[i][j];
        } else if (cost[i][j] <= second) {
            second = cost[i][j];
        }
    }
    return second;
}

// Branch and Bound recursive function
void tsp(int currBound, int currWeight, int level, int currPath[]) {
```

```
    if (level == n) {
        if (cost[currPath[level - 1]][currPath[0]] != 0) {
            int total = currWeight + cost[currPath[level - 1]][currPath[0]];
            if (total < minCost)
                minCost = total;
        }
        return;
    }

    for (int i = 0; i < n; i++) {
        if (cost[currPath[level - 1]][i] && !visited[i]) {

            int temp = currBound;
            currWeight += cost[currPath[level - 1]][i];

            if (level == 1)
                currBound -= (firstMin(currPath[level - 1]) + firstMin(i)) / 2;
            else
                currBound -= (secondMin(currPath[level - 1]) + firstMin(i)) / 2;

            if (currBound + currWeight < minCost) {
                currPath[level] = i;
                visited[i] = 1;

                tsp(currBound, currWeight, level + 1, currPath);
            }

            currWeight -= cost[currPath[level - 1]][i];
            currBound = temp;

            for (int j = 0; j < n; j++)
                visited[j] = 0;

            for (int j = 0; j < level; j++)
                visited[currPath[j]] = 1;
        }
    }
}

int main() {
    scanf("%d", &n);
```

```
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &cost[i][j]);
        }
    }

    int currPath[MAX];

    for (int i = 0; i < n; i++)
        visited[i] = 0;

    int currBound = 0;

    for (int i = 0; i < n; i++)
        currBound += (firstMin(i) + secondMin(i));

    currBound = (currBound & 1) ? currBound / 2 + 1 : currBound / 2;

    visited[0] = 1;
    currPath[0] = 0;

    tsp(currBound, 0, 1, currPath);

    printf("Minimum Cost is: %d", minCost);

    return 0;
}
```

Status : Partially correct ***Marks : 2/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 10_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Meera, the director of a national disaster response team, must deploy three specialized rescue units to three critical disaster sites. Each rescue unit has a different response time (in minutes) to reach each site due to distance, terrain, and accessibility constraints.

However, Meera has an additional operational rule:

Rescue Unit 1 cannot be assigned to Site 3 due to equipment limitations.Rescue Unit 2 must not be assigned to Site 1 because of route restrictions.

Meera decides to use the Branch and Bound technique to explore only valid and efficient assignments while respecting all constraints.

Your task is to determine the total response time of the best valid

deployment plan that satisfies all given restrictions.

Input Format

The input consists of three lines with three space-separated integers each, representing a 3 × 3 response time matrix.

Each cell (i, j) represents the response time (in minutes) if the ith rescue unit is deployed to the jth disaster site.

Output Format

The output should display the total response time in the following exact format: "Total Response Time: X" ,where X is the total response time of the best valid deployment plan.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 12 25 40
30 14 28
16 18 11
Output: Total Response Time: 37

Answer

```
#include <stdio.h>
#include <limits.h>

#define N 3

int cost[N][N];
int assigned[N];
int bestAssign[N];

int bestCost = INT_MAX;

int isValid(int unit, int site) {
    if (unit == 0 && site == 2) return 0; // Unit 1 -> Site 3 forbidden
    if (unit == 1 && site == 0) return 0; // Unit 2 -> Site 1 forbidden
    return 1;
```

```
}

void copySol(int curr[]) {
    for (int i = 0; i < N; i++)
        bestAssign[i] = curr[i];
}

void solve(int unit, int currCost, int currAssign[]) {
    if (unit == N) {
        if (currCost < bestCost) {
            bestCost = currCost;
            copySol(currAssign);
        }
        return;
    }

    for (int site = 0; site < N; site++) {
        if (!assigned[site] && isValid(unit, site)) {
            assigned[site] = 1;
            currAssign[unit] = site;

            solve(unit + 1, currCost + cost[unit][site], currAssign);

            assigned[site] = 0;
        }
    }
}

int main() {
    for (int i = 0; i < N; i++)
        for (int j = 0; j < N; j++)
            scanf("%d", &cost[i][j]);

    int currAssign[N];

    for (int i = 0; i < N; i++) {
        assigned[i] = 0;
        currAssign[i] = -1;
    }

    solve(0, 0, currAssign);
```

```
    printf("Total Response Time: %d", bestCost);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Captain Aidan, a daring pirate, has discovered an ancient treasure cave filled with valuable relics. However, the cave is protected by an ancient spell that limits the weight of the treasure he can carry. Aidan has a magic knapsack with a maximum weight capacity of W. Inside the cave, he finds n different treasures, each with a specific weight and value.

Since he can only take each treasure once, Aidan must carefully choose which items to take to maximize the total value without exceeding the weight limit of his knapsack.

Help Captain Aidan pick the most valuable treasures while staying within the weight limit using branch and bound technique

Input Format

The first line contains two integers n (the number of items) and W (the capacity of the knapsack), separated by a space.

The second line contains n integers, where the i-th integer represents the weight of the i-th item.

The third line contains n integers, where the i-th integer represents the value of the i-th item

Output Format

The output prints the single integer representing the maximum value obtained by filling the knapsack with the given set of items.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 60
10 20 30 40 50
60 100 120 140 180

Output: 280

Answer

```
#include <stdio.h>
#include <stdlib.h>

typedef struct {
    int w, v;
    double ratio;
} Item;

int n, W;
Item items[105];

int bestValue = 0;

int cmp(const void *a, const void *b) {
    Item *x = (Item *)a;
    Item *y = (Item *)b;
    if (y->ratio > x->ratio) return 1;
    return -1;
}

double bound(int idx, int currW, int currV) {
    double res = currV;
    int totalW = currW;

    for (int i = idx; i < n; i++) {
        if (totalW + items[i].w <= W) {
            totalW += items[i].w;
            res += items[i].v;
        } else {
            int remain = W - totalW;
            res += items[i].ratio * remain;
            break;
        }
```

```
    }
    return res;
}

void dfs(int idx, int currW, int currV) {
    if (currW > W) return;

    if (idx == n) {
        if (currV > bestValue)
            bestValue = currV;
        return;
    }

    // include item
    if (currW + items[idx].w <= W)
        dfs(idx + 1, currW + items[idx].w, currV + items[idx].v);

    // exclude item with pruning
    if (bound(idx + 1, currW, currV) > bestValue)
        dfs(idx + 1, currW, currV);
}

int main() {
    scanf("%d %d", &n, &W);

    int w[105], v[105];

    for (int i = 0; i < n; i++)
        scanf("%d", &w[i]);

    for (int i = 0; i < n; i++)
        scanf("%d", &v[i]);

    for (int i = 0; i < n; i++) {
        items[i].w = w[i];
        items[i].v = v[i];
        items[i].ratio = (double)v[i] / w[i];
    }

    qsort(items, n, sizeof(Item), cmp);

    dfs(0, 0, 0);
```

```
    printf("%d", bestValue);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Commander Vikram is preparing a spacecraft for an interplanetary research mission. The spacecraft has a limited cargo capacity, so he must carefully decide which scientific equipment modules to load.

Each module has a scientific importance value and a specific weight. Commander Vikram wants to load the spacecraft in such a way that the total scientific value of the selected modules is maximized without exceeding the cargo weight limit.

To solve this efficiently, he uses the Branch and Bound technique applied to the 0/1 Knapsack problem, which explores possible combinations of equipment and eliminates options that cannot lead to better solutions.

Your task is to help Commander Vikram determine the maximum achievable value and the selected module weights that should be loaded into the spacecraft.

Note: The weights must be printed in reverse order of the input, meaning the algorithm starts evaluating items from the last item and prints the selected weights first.

Input Format

The first line contains an integer n, representing the number of equipment modules available.

The second line contains n space-separated integers val[i], representing the scientific value of each module.

The third line contains n space-separated integers wt[i], representing the weight

of each module.

The fourth line contains an integer W, representing the maximum cargo capacity of the spacecraft.

Output Format

The first line output displays "Maximum value: " followed by an integer, representing the maximum value that can be achieved.

The second line output displays "Selected weights: " followed by space-separated integers, printed in reverse order of the input.

Refer to the sample outputs for the exact format.

Sample Test Case

Input: 3
60 100 120
10 20 30
50
Output: Maximum value: 220
Selected weights: 30 20

Answer

```
#include <stdio.h>

int n, W;
int val[105], wt[105];
int best = 0;

void dfs(int i, int curW, int curV) {
    if (curW > W) return;

    if (i == n) {
        if (curV > best)
            best = curV;
        return;
    }

    // take
```

```
    dfs(i + 1, curW + wt[i], curV + val[i]);

    // not take
    dfs(i + 1, curW, curV);
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        scanf("%d", &val[i]);

    for (int i = 0; i < n; i++)
        scanf("%d", &wt[i]);

    scanf("%d", &W);

    dfs(0, 0, 0);

    printf("%d", best);

    return 0;
}
```

Status : Wrong ***Marks : 0/10***

4. Problem Statement

You are tasked with solving the Travelling Salesman Problem (TSP) for a given set of cities.

Given the distances between pairs of cities, your goal is to find the shortest route that visits each city exactly once and returns to the starting city.

Note: Solve it using Branch and Bound approach.

Input Format

The first line of input contains an integer n, representing the number of cities.

The following n lines each contain n space-separated integers, representing the

distances between pairs of cities.

The distance between city i and city j is given at the ith row and jth column of the matrix.

Output Format

The first line displays "The Path is: " followed by the sequence of cities visited in the shortest path,

separated by "--->".

The second line displays "Minimum cost is X", where X is the minimum cost of the shortest path found.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 4 1 3
4 0 2 1
1 2 0 5
3 1 5 0
Output: The Path is: 1--->3--->2--->4--->1
Minimum cost is 7

Answer

```
#include <stdio.h>

#define MAX 15
#define INF 999999

int n;
int cost[MAX][MAX];
int visited[MAX];

int bestCost = INF;
int bestPath[MAX];
int currPath[MAX];
```

```
void copyPath() {
    for (int i = 0; i < n; i++)
        bestPath[i] = currPath[i];
}

void tsp(int level, int currCost, int lastCity) {
    if (level == n) {
        if (cost[lastCity][0] != 0) {
            int total = currCost + cost[lastCity][0];
            if (total < bestCost) {
                bestCost = total;
                copyPath();
            }
        }
        return;
    }

    for (int i = 0; i < n; i++) {
        if (!visited[i] && cost[lastCity][i] != 0) {
            visited[i] = 1;
            currPath[level] = i + 1;

            tsp(level + 1, currCost + cost[lastCity][i], i);

            visited[i] = 0;
        }
    }
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &cost[i][j]);

    for (int i = 0; i < n; i++)
        visited[i] = 0;

    visited[0] = 1;
    currPath[0] = 1;
```

```
    tsp(1, 0, 0);

    printf("The Path is: ");
    for (int i = 0; i < n; i++)
        printf("%d--->", bestPath[i]);
    printf("1\n");

    printf("Minimum cost is %d", bestCost);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

You are a logistics manager responsible for planning delivery routes for a fleet of vehicles. Each vehicle needs to visit a set of locations to deliver goods, and the cost of traveling between locations is known.

Your goal is to find the shortest route for each vehicle, ensuring that each location is visited exactly once before returning to the starting point.

Note: Solve it using Branch and Bound approach.

Input Format

The first line contains an integer n, the number of locations.

The next n lines contain n integers each, representing the cost matrix of traveling between locations.

The ith integer on the jth line represents the cost of traveling from location i to location j.

Output Format

The first line of output displays "Shortest Path: " followed by the shortest path that visits all cities.

The second line of output displays "Minimum cost is " followed by the minimum cost.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5
0 10 8 9 7
10 0 10 5 6
8 10 0 8 9
9 5 8 0 6
7 6 9 6 0

Output: Shortest Path: 1 3 4 2 5 1
Minimum cost is 34

Answer

```
#include <stdio.h>

#define MAX 15
#define INF 999999

int n;
int cost[MAX][MAX];
int visited[MAX];

int bestCost = INF;
int bestPath[MAX];
int currPath[MAX];

void copyPath() {
    for (int i = 0; i < n; i++)
        bestPath[i] = currPath[i];
}

void tsp(int level, int currCost, int last) {
    if (level == n) {
        if (cost[last][0] != 0) {
            int total = currCost + cost[last][0];
            if (total < bestCost) {
                bestCost = total;
                copyPath();
```

```
        }
    }
    return;
}

for (int i = 0; i < n; i++) {
    if (!visited[i] && cost[last][i] != 0) {
        visited[i] = 1;
        currPath[level] = i + 1;

        tsp(level + 1, currCost + cost[last][i], i);

        visited[i] = 0;
    }
}
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &cost[i][j]);

    for (int i = 0; i < n; i++)
        visited[i] = 0;

    visited[0] = 1;
    currPath[0] = 1;

    tsp(1, 0, 0);

    printf("Shortest Path: ");
    for (int i = 0; i < n; i++)
        printf("%d ", bestPath[i]);
    printf("1\n");

    printf("Minimum cost is %d", bestCost);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 10_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Arun, the operations manager of a logistics company, needs to assign three delivery drivers to three delivery zones.

Each driver requires a different amount of fuel (in liters) to complete deliveries in each zone due to varying distances and traffic conditions. Arun wants to assign exactly one driver to each zone such that the total fuel consumption is minimized.

To efficiently explore possible assignments and avoid unnecessary computations, Arun decides to use the Branch and Bound technique.

Your task is to help Arun determine the optimal assignment of drivers to zones that results in the least total fuel consumption.

Input Format

The input consists of three lines with three space-separated integers each, representing a 3 × 3 matrix.

Each cell (i, j) represents the fuel required (in liters) if the ith driver is assigned to the jth zone.

Output Format

The output should display the optimal assignment in the following format:

Optimal Assignment:

Driver 1 -> Zone X

Driver 2 -> Zone Y

Driver 3 -> Zone Z

Where:

Each driver is assigned to exactly one zone.

Each zone is assigned to exactly one driver.

The assignment must produce the least total fuel consumption.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 8 6 10
9 7 4
3 12 5
Output: Optimal Assignment:
Driver 1 -> Zone 2
Driver 2 -> Zone 3
Driver 3 -> Zone 1

Answer

vtu27632

```
#include <stdio.h>
#include <limits.h>

#define N 3

int cost[N][N];
int assigned[N];
int bestCost = INT_MAX;
int bestAssign[N];

void copySolution() {
    for (int i = 0; i < N; i++) {
        bestAssign[i] = assigned[i];
    }
}

void branchAndBound(int driver, int currentCost) {
    if (driver == N) {
        if (currentCost < bestCost) {
            bestCost = currentCost;
            copySolution();
        }
        return;
    }

    for (int zone = 0; zone < N; zone++) {
        if (!assigned[zone]) {
            assigned[zone] = 1;
            branchAndBound(driver + 1, currentCost + cost[driver][zone]);
            assigned[zone] = 0;
        }
    }
}

int main() {
    for (int i = 0; i < N; i++) {
        for (int j = 0; j < N; j++) {
            scanf("%d", &cost[i][j]);
        }
    }

    for (int i = 0; i < N; i++) {
```

```
        assigned[i] = 0;
    }

    branchAndBound(0, 0);

    printf("Optimal Assignment:\n");
    for (int i = 0; i < N; i++) {
        printf("Driver %d -> Zone %d\n", i + 1, bestAssign[i] + 1);
    }

    return 0;
}
```

Status : Wrong ***Marks : 0/10***

2. Problem Statement

Captain Arvind has discovered a hidden island filled with valuable treasures. Before leaving the island, he must load the treasures onto his small ship. However, the ship has a strict weight capacity, so he cannot carry everything he finds.

Each treasure chest has a specific value and weight. Captain Arvind wants to select the best combination of treasure chests to load onto the ship so that the total value of the treasures is maximized without exceeding the ship's weight limit.

To solve this efficiently, Captain Arvind decides to use the Branch and Bound technique applied to the 0/1 Knapsack problem, which systematically explores possible combinations and eliminates choices that cannot produce better results.

Your task is to help Captain Arvind determine the maximum total treasure value he can carry on his ship.

Input Format

The first line contains an integer n, representing the total number of treasure chests.

The next n lines contain two space-separated integers: val[i] w[i]

where

- val[i] represents the value of the i-th treasure chest
- w[i] represents the weight of the i-th treasure chest

The last line contains an integer W, representing the maximum weight capacity of the ship.

Output Format

The output prints "Optimal Total Value: X" , where X is the maximum value that Captain Arvind can obtain using the Branch and Bound approach for the 0/1 Knapsack problem.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3
60 10
100 20
120 30
50
Output: Optimal Total Value: 220

Answer

```
#include <stdio.h>
#include <stdlib.h>

typedef struct {
    int value;
    int weight;
    double ratio;
} Item;

int n, W;
Item items[20];

int bestValue = 0;
```

```
int compare(const void *a, const void *b) {
    Item *x = (Item *)a;
    Item *y = (Item *)b;
    if (y->ratio > x->ratio) return 1;
    return -1;
}

double bound(int idx, int currW, int currV) {
    double result = currV;
    int totalW = currW;

    for (int i = idx; i < n; i++) {
        if (totalW + items[i].weight <= W) {
            totalW += items[i].weight;
            result += items[i].value;
        } else {
            int remain = W - totalW;
            result += items[i].ratio * remain;
            break;
        }
    }
    return result;
}

void knapsack(int idx, int currW, int currV) {
    if (idx == n) {
        if (currV > bestValue)
            bestValue = currV;
        return;
    }

    if (currW + items[idx].weight <= W) {
        knapsack(idx + 1, currW + items[idx].weight,
                 currV + items[idx].value);
    }

    if (bound(idx + 1, currW, currV) > bestValue) {
        knapsack(idx + 1, currW, currV);
    }
}
```

```
int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d %d", &items[i].value, &items[i].weight);
        items[i].ratio = (double)items[i].value / items[i].weight;
    }

    scanf("%d", &W);

    qsort(items, n, sizeof(Item), compare);

    knapsack(0, 0, 0);

    printf("Optimal Total Value: %d", bestValue);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Dr. Aarav is a field scientist preparing for an important research expedition to a remote mountain region. Since the research base is located in a difficult-to-reach area, he can only carry a limited amount of equipment in his field backpack.

Each piece of equipment has a scientific importance value and a specific weight. Dr. Aarav wants to choose the best combination of equipment so that the total scientific value is maximized without exceeding the backpack's weight capacity.

To solve this efficiently, Dr. Aarav applies the Branch and Bound technique using the 0/1 Knapsack algorithm, which systematically explores possible selections and eliminates combinations that cannot yield better results.

Your task is to help Dr. Aarav determine which equipment weights should be selected to achieve the maximum total value.

Note: The weights must be printed in the same order as they appear in the input.

Input Format

The first line of input contains an integer n, representing the number of available equipment items.

The second line contains n space-separated integers val[i], representing the scientific value of each item.

The third line contains n space-separated integers w[i], representing the weight of each item.

The fourth line contains an integer W, representing the maximum carrying capacity of the backpack.

Output Format

The output displays the "Specified weights: <weights>", where <weights> are the weights of the selected equipment items that maximize the total value using the Branch and Bound approach for the 0/1 Knapsack problem.

Refer to the sample outputs for the exact format.

Sample Test Case

Input: 4
10 20 30 40
1 2 3 4
8
Output: Specified weights: 1 3 4

Answer

```
#include <stdio.h>
#include <stdlib.h>

typedef struct {
  int val;
  int wt;
```

```
    int idx;
    double ratio;
} Item;

int n, W;
Item items[15];

int bestValue = 0;
int bestTaken[15];
int currTaken[15];

double bound(int i, int currW, int currV) {
    double res = currV;
    int totalW = currW;

    for (int j = i; j < n; j++) {
        if (totalW + items[j].wt <= W) {
            totalW += items[j].wt;
            res += items[j].val;
        } else {
            int rem = W - totalW;
            res += items[j].ratio * rem;
            break;
        }
    }
    return res;
}

void dfs(int i, int currW, int currV) {
    if (currW > W) return;

    if (i == n) {
        if (currV > bestValue) {
            bestValue = currV;
            for (int k = 0; k < n; k++)
                bestTaken[k] = currTaken[k];
        }
        return;
    }

    // include item
    currTaken[items[i].idx] = 1;
```

```
    dfs(i + 1, currW + items[i].wt, currV + items[i].val);
    currTaken[items[i].idx] = 0;

    // exclude item
    if (bound(i + 1, currW, currV) > bestValue) {
        dfs(i + 1, currW, currV);
    }
}

int cmp(const void *a, const void *b) {
    Item *x = (Item *)a;
    Item *y = (Item *)b;
    return (y->ratio > x->ratio) - (y->ratio < x->ratio);
}

int main() {
    scanf("%d", &n);

    int val[15], wt[15];

    for (int i = 0; i < n; i++)
        scanf("%d", &val[i]);

    for (int i = 0; i < n; i++)
        scanf("%d", &wt[i]);

    scanf("%d", &W);

    for (int i = 0; i < n; i++) {
        items[i].val = val[i];
        items[i].wt = wt[i];
        items[i].idx = i;
        items[i].ratio = (double)val[i] / wt[i];
        currTaken[i] = 0;
        bestTaken[i] = 0;
    }

    qsort(items, n, sizeof(Item), cmp);

    dfs(0, 0, 0);

    printf("Specified weights: ");
```

```
    for (int i = 0; i < n; i++) {
        if (bestTaken[i]) {
            printf("%d ", wt[i]);
        }
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Janu is tasked with creating a program that solves the Traveling Salesman Problem (TSP). The goal is to find the shortest possible route that visits a set of cities and returns to the starting city.

You are required to implement a program that takes input regarding the number of cities and the distance matrix between cities and outputs the optimal route and its associated minimum cost.

The diagonal values will be 0, as the distance from a city to itself is 0.

Note: Solve it using Branch and Bound approach.

Input Format

The first line of input consists of an integer n, representing the number of cities.

The next n lines contain n space-separated integers each, representing the distance matrix between the cities.

The cell (i, j) represents the distance from city i to city j.

Output Format

The first line of output displays "The Path is: " followed by the path of the route using ---> in between.

The second line displays "Minimum cost is " followed by the total minimum cost associated with the shortest route.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 4 1 3
4 0 2 1
1 2 0 5
3 1 5 0

Output: The Path is: 1--->3--->2--->4--->1
Minimum cost is 7

Answer

```
#include <stdio.h>
#include <limits.h>

#define MAX 10

int n;
int cost[MAX][MAX];

int bestCost = INT_MAX;

int finalPath[MAX + 1];
int currPath[MAX + 1];

int visited[MAX];

int firstMin(int i) {
    int min = INT_MAX;
    for (int j = 0; j < n; j++) {
        if (cost[i][j] && cost[i][j] < min)
            min = cost[i][j];
    }
    return min;
}

int secondMin(int i) {
    int first = INT_MAX, second = INT_MAX;
```

```
    for (int j = 0; j < n; j++) {
        if (i == j || cost[i][j] == 0) continue;

        if (cost[i][j] <= first) {
            second = first;
            first = cost[i][j];
        } else if (cost[i][j] <= second && cost[i][j] != first) {
            second = cost[i][j];
        }
    }
    return second;
}

void TSPRec(int level, int currCost, int bound) {
    if (level == n) {
        if (cost[currPath[level - 1]][currPath[0]] != 0) {
            int totalCost = currCost + cost[currPath[level - 1]][currPath[0]];

            if (totalCost < bestCost) {
                bestCost = totalCost;
                for (int i = 0; i < n; i++)
                    finalPath[i] = currPath[i];
                finalPath[n] = currPath[0];
            }
        }
        return;
    }

    for (int i = 0; i < n; i++) {
        if (cost[currPath[level - 1]][i] != 0 && !visited[i]) {
            int tempBound = bound;

            currCost += cost[currPath[level - 1]][i];

            if (level == 1)
                tempBound -= (firstMin(currPath[level - 1]) + firstMin(i)) / 2;
            else
                tempBound -= (secondMin(currPath[level - 1]) + firstMin(i)) / 2;

            if (tempBound + currCost < bestCost) {
                currPath[level] = i;
                visited[i] = 1;
```

```
            TSPRec(level + 1, currCost, tempBound);

            visited[i] = 0;
        }

        currCost -= cost[currPath[level - 1]][i];
    }
  }
}

void TSP() {
  int bound = 0;

  for (int i = 0; i < n; i++)
    bound += (firstMin(i) + secondMin(i));

  bound = (bound & 1) ? bound / 2 + 1 : bound / 2;

  visited[0] = 1;
  currPath[0] = 0;

  TSPRec(1, 0, bound);
}

int main() {
  scanf("%d", &n);

  for (int i = 0; i < n; i++)
    for (int j = 0; j < n; j++)
      scanf("%d", &cost[i][j]);

  TSP();

  printf("The Path is: ");
  for (int i = 0; i <= n; i++) {
    printf("%d", finalPath[i] + 1);
    if (i < n) printf("--->");
  }

  printf("\nMinimum cost is %d", bestCost);
```

```
    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

A traveling salesman is tasked with finding the shortest route to visit a set of cities and return to the starting city. The goal is to minimize the total distance traveled by the salesman while visiting each city exactly once.

Input Format

The first line contains an integer n, the number of cities.

The next n lines contain n space-separated integers each, representing the distances between cities.

The ith line represents the distances from city i to all other cities.

The last line contains an integer s, representing the starting city.

Output Format

The first line of output displays "Shortest Path: " followed by the shortest path taken by the salesman, represented as a list of city indices within square brackets.

The second line of output displays "Minimum Cost: " followed by the minimum cost (total distance) of the shortest path.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
0 10 15 20
10 0 35 25
15 35 0 30
20 25 30 0

0
Output: Shortest Path: [0, 1, 3, 2, 0]
Minimum Cost: 80

Answer

```
#include <stdio.h>
#include <limits.h>

#define MAX 10

int n, start;
int cost[MAX][MAX];

int visited[MAX];
int path[MAX], bestPath[MAX];

int bestCost = INT_MAX;

void copyPath() {
    for (int i = 0; i < n; i++)
        bestPath[i] = path[i];
}

void tsp(int level, int currCost) {
    if (level == n) {
        if (cost[path[level - 1]][start] != 0) {
            int total = currCost + cost[path[level - 1]][start];

            if (total < bestCost) {
                bestCost = total;
                copyPath();
            }
        }
        return;
    }

    for (int i = 0; i < n; i++) {
        if (!visited[i] && cost[path[level - 1]][i] != 0) {
            visited[i] = 1;
            path[level] = i;

            tsp(level + 1, currCost + cost[path[level - 1]][i]);
```

```
            visited[i] = 0;
        }
    }
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            scanf("%d", &cost[i][j]);

    scanf("%d", &start);

    visited[start] = 1;
    path[0] = start;

    tsp(1, 0);

    printf("Shortest Path: [");
    for (int i = 0; i < n; i++) {
        printf("%d, ", bestPath[i]);
    }
    printf("%d]\n", start);

    printf("Minimum Cost: %d", bestCost);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 11_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : Coding

1. _____ is a matching with the largest number of edges.

Answer

Maximum bipartite matching

Status : Correct ***Marks : 1/1***

2. How many colors are used in a bipartite graph?

Answer

2

Status : Correct ***Marks : 1/1***

vtu27632

3. What is the simplest method to prove that a graph is bipartite?

Answer

It does not have a cycle of an odd length

Status : Correct ***Marks : 1/1***

4. A matching that matches all the vertices of a graph is called?

Answer

Perfect matching

Status : Correct ***Marks : 1/1***

5. In a bipartite graph G=(V,U,E), the matching of a free vertex in V to a free vertex in U called?

Answer

Augmenting

Status : Correct ***Marks : 1/1***

6. There are four students in a class namely A, B, C and D. A tells that a triangle is a bipartite graph. B tells pentagon is a bipartite graph. C tells square is a bipartite graph. D tells heptagon is a bipartite graph. Who among the following is correct?

Answer

C

Status : Correct ***Marks : 1/1***

7. Which of the following is not a property of the bipartite graph?

Answer

Asymmetric spectrum

vtu27632

Status : Correct ***Marks : 1/1***

8. The maximum number of edges in a bipartite graph with 14 vertices is _____.

Answer

49

Status : Correct ***Marks : 1/1***

9. What does the Halting Problem attempt to determine?

Answer

Whether a program will eventually stop running or continue forever

Status : Correct ***Marks : 1/1***

10. The Halting Problem was introduced by which computer scientist?

Answer

Alan Turing

Status : Correct ***Marks : 1/1***

11. Why is the Halting Problem considered unsolvable?

Answer

Because no algorithm can determine for every program whether it halts or runs forever

Status : Correct ***Marks : 1/1***

12. In computation theory, what does an undecidable problem mean?

Answer

A problem that cannot be solved by any algorithm for all inputs

vtu27632

Status : Correct ***Marks : 1/1***

13. In the context of the Halting Problem, what does the term halting refer to?

Answer

A program stopping its execution after completing its task

Status : Correct ***Marks : 1/1***

14. What is the main implication of the Halting Problem for computer science?

Answer

Some computational problems cannot be solved by any algorithm

Status : Correct ***Marks : 1/1***

15. The Halting Problem generally takes which of the following as input?

Answer

A program and its input data

Status : Correct ***Marks : 1/1***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 11_COD

Attempt : 1
Total Mark : 30
Marks Obtained : 29

Section 1 : Coding

1. Problem Statement

Alice needs to assign works to employees in a company. Each employee can be assigned at most one work, and each work can be assigned to at most one employee. Her goal is to maximize the number of employees who are assigned works, ensuring that each work is assigned to exactly one employee and each employee is assigned at most one work.

Help Alice to complete the task.

Input Format

The first line consists of an integer N, representing the number of connections between employees and works.

The next N lines consists of two space-separated integers X and Y, representing a connection where X is the index of an employee (0-based indexing), and Y is

the index of a work (0-based indexing), indicating that employee X can perform work Y.

Output Format

The first line of the output displays "Maximum number of employees that could get works are: a", where a is an integer representing the maximum number of employees that could be assigned works according to the given conditions.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 9
0 0
0 1
0 2
1 0
2 1
3 4
4 3
4 4
5 5
Output: Maximum number of employees that could get works are: 6

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

#define MAX 100

int adj[MAX][MAX];
int match[MAX];
int visited[MAX];
int N;
int empCount = 0;

// DFS to find augmenting path
int bpm(int u) {
    for (int v = 0; v < N; v++) {
```

```
        if (adj[u][v] && !visited[v]) {
            visited[v] = 1;

            if (match[v] == -1 || bpm(match[v])) {
                match[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

int main() {
    scanf("%d", &N);

    // initialize adjacency matrix
    for (int i = 0; i < N; i++)
        for (int j = 0; j < N; j++)
            adj[i][j] = 0;

    int x, y;

    // input edges
    for (int i = 0; i < N; i++) {
        scanf("%d %d", &x, &y);
        adj[x][y] = 1;
    }

    // initialize match array
    for (int i = 0; i < N; i++)
        match[i] = -1;

    // try matching each employee
    for (int u = 0; u < N; u++) {
        memset(visited, 0, sizeof(visited));

        if (bpm(u))
            empCount++;
    }

    printf("Maximum number of employees that could get works are: %d",
empCount);
```

```
return 0;
}
```

Status : Partially correct ***Marks : 9/10***

2. Problem Statement

Given an undirected bipartite graph with X vertices on the left side and Y vertices on the right side, the graph may contain multiple edges between the same pair of vertices.

Your task is to determine the minimum vertex cover for this graph.

A vertex cover of a graph is a set of vertices such that every edge in the graph is incident to at least one vertex in the set.

Input Format

The first line contains two space-separated integers X and Y, representing the number of vertices in the left set and right set, respectively.

The second line contains an integer e, representing the number of edges in the bipartite graph.

The next e lines each contain two space-separated integers u and v, representing an edge between: vertex u in the left set and vertex v in the right set

Output Format

The output prints the vertices in the minimum vertex cover, separated by a space.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4 4
4

0 1
0 2
1 3
2 3

Output: 0 3

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

#define MAX 105

int X, Y;
int adj[MAX][MAX];

int matchR[MAX];
int visR[MAX];
int visL[MAX];

// DFS for matching
int bpm(int u) {
    for (int v = 0; v < Y; v++) {
        if (adj[u][v] && !visR[v]) {
            visR[v] = 1;

            if (matchR[v] == -1 || bpm(matchR[v])) {
                matchR[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

// DFS for alternating path (for vertex cover)
void dfs(int u) {
    visL[u] = 1;

    for (int v = 0; v < Y; v++) {
        if (adj[u][v] && !visR[v]) {
            visR[v] = 1;
```

```
            if (matchR[v] != -1 && !visL[matchR[v]]) {
                dfs(matchR[v]);
            }
        }
    }
}

int main() {
    scanf("%d %d", &X, &Y);

    int e;
    scanf("%d", &e);

    memset(adj, 0, sizeof(adj));

    for (int i = 0; i < e; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        adj[u][v] = 1;
    }

    // initialize matching
    for (int i = 0; i < Y; i++)
        matchR[i] = -1;

    // maximum matching
    for (int i = 0; i < X; i++) {
        memset(visR, 0, sizeof(visR));
        bpm(i);
    }

    // reset visited
    memset(visL, 0, sizeof(visL));
    memset(visR, 0, sizeof(visR));

    // start DFS from unmatched left vertices
    for (int i = 0; i < X; i++) {
        int matched = 0;
        for (int j = 0; j < Y; j++) {
            if (matchR[j] == i) {
                matched = 1;
```

```
            break;
        }
    }
    if (!matched && !visL[i]) {
        dfs(i);
    }
}

// minimum vertex cover:
// Left side not visited + Right side visited
for (int i = 0; i < X; i++) {
    if (!visL[i])
        printf("%d ", i);
}

for (int j = 0; j < Y; j++) {
    if (visR[j])
        printf("%d ", j);
}

return 0;
}
```

Status : Correct **Marks : 10/10**

3. Problem Statement

You are given an undirected graph with 'num_vertices' vertices and 'num_edges' edges. Your task is to determine whether the given graph is bipartite or not. A graph is bipartite if it can be divided into two disjoint sets of vertices such that each edge connects a vertex from one set to a vertex from the other set.

Input Format

The first line contains two integers separated by a space: 'num_vertices' and 'num_edges'. These represent the number of vertices and edges in the graph, respectively.

The next 'num_edges' lines each contain two integers 'u' and 'v' separated by a space, representing an edge between vertex 'u' and vertex 'v'.

Output Format

The output displays a single line indicating whether the given graph is bipartite or not.

If the graph is bipartite, print "The graph is bipartite."

If the graph is not bipartite, print "The graph is not bipartite."

Sample Test Case

Input: 4 4
0 1
1 2
2 3
3 0
Output: The graph is bipartite.

Answer

```
// You are using GCC
#include <stdio.h>

#define MAX 105

int graph[MAX][MAX];
int color[MAX];
int n, m;

// BFS function using simple queue
int bfsCheck(int start) {
    int queue[MAX];
    int front = 0, rear = 0;

    queue[rear++] = start;
    color[start] = 1;

    while (front < rear) {
        int u = queue[front++];

        for (int v = 0; v < n; v++) {
            if (graph[u][v]) {

                if (color[v] == -1) {
```

```
                color[v] = 1 - color[u];
                queue[rear++] = v;
            }
            else if (color[v] == color[u]) {
                return 0; // not bipartite
            }
        }
    }
}

    return 1;
}

int main() {
    scanf("%d %d", &n, &m);

    // initialize
    for (int i = 0; i < n; i++) {
        color[i] = -1;
        for (int j = 0; j < n; j++) {
            graph[i][j] = 0;
        }
    }

    // input edges
    for (int i = 0; i < m; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        graph[u][v] = 1;
        graph[v][u] = 1;
    }

    // check all components
    for (int i = 0; i < n; i++) {
        if (color[i] == -1) {
            if (!bfsCheck(i)) {
                printf("The graph is not bipartite.");
                return 0;
            }
        }
    }
```

```
    printf("The graph is bipartite.");

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 11_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 40.5

Section 1 : Coding

1. Problem Statement:

John is developing a recommendation system for a social networking platform. The system suggests potential friends to users based on their interests and mutual connections. To enhance the user experience, you want to ensure that the recommendation algorithm considers the removal of certain users from the network due to various reasons such as account deletion or user activity.

However, he still wants to maintain effective friend suggestions even after removing these users. John plan to integrate a functionality that calculates the maximum matching in the bipartite graph representing the user network after removing specific users and their connections.

Help him to achieve the task.

vtu27632

Input Format

Enter the number of vertices in partition

Enter the number of vertices in partition

Enter the adjacency matrix representation of the bipartite graph

Enter the vertex to remove

Output Format

Maximum matching after removing vertex

Sample Test Case

Input: 3
2
0 1
1 0
0 0
1
Output: Maximum matching after removing vertex 1: 1

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

#define MAX 15

int n, m;
int graph[MAX][MAX];
int match[MAX];
int vis[MAX];

int dfs(int u) {
    for (int v = 1; v <= m; v++) {
        if (graph[u][v] && !vis[v]) {
            vis[v] = 1;

            if (match[v] == 0 || dfs(match[v])) {
                match[v] = u;
                return 1;
```

```
        }
    }
    }
    return 0;
}

int maxMatching() {
    memset(match, 0, sizeof(match));
    int res = 0;

    for (int i = 1; i <= n; i++) {
        memset(vis, 0, sizeof(vis));
        if (dfs(i)) res++;
    }
    return res;
}

int main() {
    scanf("%d", &n);
    scanf("%d", &m);

    int e = n * m;  // adjacency matrix input
    for (int i = 1; i <= n; i++) {
        for (int j = 1; j <= m; j++) {
            scanf("%d", &graph[i][j]);
        }
    }

    int removed;
    scanf("%d", &removed);

    // Remove vertex (disable all its edges)
    for (int j = 1; j <= m; j++) {
        graph[removed][j] = 0;
    }

    int ans = maxMatching();

    printf("Maximum matching after removing vertex %d: %d", removed, ans);

    return 0;
}
```

Status : Partially correct ***Marks : 4/10***

2. Problem Statement

Charlie is working on optimizing the hiring process for interns at a tech startup. There are 4 open positions and 4 applicants, each having different skill sets.

Charlie wants to design a system that matches applicants to positions based on their suitability. The suitability is represented using a binary matrix, where:

1 indicates the applicant is suitable for the position.0 indicates the applicant is not suitable for the position.

Each applicant can be assigned to only one position, and each position can accept only one applicant.

The goal is to determine the maximum number of positions that can be filled by assigning suitable applicants.

Input Format

The input consists of 4 lines.

Each line contains 4 space-separated integers (0 or 1).

Each row represents an applicant.

Each column represents a job position.

Output Format

The output prints the result in the following format: "The job can hire up to X applicants" where X represents the maximum number of applicants that can be assigned to positions.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1 1 0 0
1 0 0 0
0 0 1 1
0 0 0 1

Output: The job can hire up to 4 applicants

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

#define N 5

int graph[N][N];
int match[N];
int vis[N];

int dfs(int u) {
    for (int v = 1; v <= 4; v++) {
        if (graph[u][v] && !vis[v]) {
            vis[v] = 1;

            if (match[v] == 0 || dfs(match[v])) {
                match[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

int maxMatching() {
    memset(match, 0, sizeof(match));
    int result = 0;

    for (int i = 1; i <= 4; i++) {
        memset(vis, 0, sizeof(vis));
        if (dfs(i)) result++;
    }
    return result;
```

```
}

int main() {
    // 4x4 input
    for (int i = 1; i <= 4; i++) {
        for (int j = 1; j <= 4; j++) {
            scanf("%d", &graph[i][j]);
        }
    }

    int ans = maxMatching();

    printf("The job can hire up to %d applicants", ans);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Emily is working on a project that involves managing relationships between two sets of entities, set U and set V. She wants to determine the maximum matching in a bipartite graph to optimize connections without overlap.

Emily also needs the ability to remove a specific connection (edge) between two entities in order to analyze different scenarios and measure the impact on the size of the maximum matching.

Your task is to compute the size of the maximum matching before and after removing a given edge.

Note: Vertices in set U are numbered from 1 to n, and vertices in set V are numbered from 1 to m.

Input Format

The first line contains an integer n, representing the number of vertices in set U.

The second line contains an integer m, representing the number of vertices in set V.

The third line contains an integer e, representing the number of edges.

The next e lines each contain two integers u and v, representing an edge between vertex u (from set U) and vertex v (from set V).

The last line contains two integers u and v, representing the edge that must be removed.

Output Format

The first line displays: "Size of maximum matching before edge removal: X"

The second line displays: "Size of maximum matching after edge removal: Y"

Refer to the sample output for the formatting specifications

Sample Test Case

Input: 3
3
3
0 1
0 2
1 2
1 2
Output: Size of maximum matching before edge removal: 1
Size of maximum matching after edge removal: 0

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

#define MAX 105

int n, m;
int graph[MAX][MAX];
int match[MAX];
```

```
int vis[MAX];

int dfs(int u) {
    for (int v = 1; v <= m; v++) {
        if (graph[u][v] && !vis[v]) {
            vis[v] = 1;

            if (match[v] == 0 || dfs(match[v])) {
                match[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

int maxMatching() {
    memset(match, 0, sizeof(match));
    int res = 0;

    for (int i = 1; i <= n; i++) {
        memset(vis, 0, sizeof(vis));
        if (dfs(i)) res++;
    }
    return res;
}

int main() {
    scanf("%d", &n);
    scanf("%d", &m);

    int e;
    scanf("%d", &e);

    memset(graph, 0, sizeof(graph));

    for (int i = 0; i < e; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        graph[u][v] = 1;
    }
```

```
    int ru, rv;
    scanf("%d %d", &ru, &rv);

    // remove edge
    graph[ru][rv] = 0;

    int before = maxMatching();

    // restore edge
    graph[ru][rv] = 1;

    int after = maxMatching();

    printf("Size of maximum matching before edge removal: %d\n", before);
    printf("Size of maximum matching after edge removal: %d", after);

    return 0;
}
```

Status : Partially correct ***Marks : 6.5/10***

4. Problem Statement

In a computer lab, Alex is experimenting with task scheduling on a cluster of processors. The lab has 7 tasks that need to be executed and 5 processors available.

Each task can run only on certain processors due to compatibility constraints. These compatibilities are represented using a binary matrix, where:

1 indicates the task can run on that processor.0 indicates the task cannot run on that processor.

Each processor can execute only one task at a time, and each task can be assigned to only one processor. Alex wants to determine the maximum number of tasks that can be executed simultaneously.

Write a program to compute the maximum number of compatible task–processor assignments.

Input Format

The input consists of 7 lines.

Each line contains 5 space-separated integers (0 or 1).

Each row represents a task.

Each column represents a processor.

Output Format

The output prints the result in the format: "The processors can run a maximum of x tasks at one time." , where x is the maximum number of tasks that can be executed simultaneously.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1 1 0 0 0
0 1 0 0 0
0 0 1 1 0
0 0 0 1 1
1 0 0 0 0
0 0 1 0 0
0 0 0 0 1
Output: The processors can run a maximum of 5 tasks at one time.

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

#define T 7
#define P 5

int graph[T + 1][P + 1];
int match[P + 1];
int vis[P + 1];
```

```
int dfs(int u) {
    for (int v = 1; v <= P; v++) {
        if (graph[u][v] && !vis[v]) {
            vis[v] = 1;

            if (match[v] == 0 || dfs(match[v])) {
                match[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

int maxMatching() {
    memset(match, 0, sizeof(match));
    int res = 0;

    for (int i = 1; i <= T; i++) {
        memset(vis, 0, sizeof(vis));
        if (dfs(i)) res++;
    }
    return res;
}

int main() {
    // input 7 x 5 matrix
    for (int i = 1; i <= T; i++) {
        for (int j = 1; j <= P; j++) {
            scanf("%d", &graph[i][j]);
        }
    }

    int ans = maxMatching();

    printf("The processors can run a maximum of %d tasks at one time.", ans);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

Alex is working on a project that involves pairing students from two different classes for a team project. The project's success depends on maximizing the number of compatible pairs between these two groups. Each student from one group can be paired with a student from the other group, but no student can belong to more than one pair.

Alex represents the compatibility between students using a binary adjacency matrix, where:

1 indicates that the students are compatible.0 indicates that the students are not compatible.

Write a program to determine the maximum number of compatible student pairs that can be formed.

Input Format

The first line contains two integers n and m, representing the number of students in the first group and second group, respectively.

The next n lines each contain m space-separated integers, representing the adjacency matrix of student compatibility.

Output Format

The output prints a single line in the following format: "Maximum Bipartite Matching: X" , where X is the maximum number of compatible student pairs.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4 3
1 1 0
1 0 1
0 1 0
1 0 0
Output: Maximum Bipartite Matching: 3

vtu27632

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

#define MAXN 105
#define MAXM 105

int n, m;
int graph[MAXN][MAXM];
int match[MAXM];
int vis[MAXM];

int dfs(int u) {
    for (int v = 1; v <= m; v++) {
        if (graph[u][v] && !vis[v]) {
            vis[v] = 1;

            if (match[v] == 0 || dfs(match[v])) {
                match[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

int maxMatching() {
    memset(match, 0, sizeof(match));
    int result = 0;

    for (int i = 1; i <= n; i++) {
        memset(vis, 0, sizeof(vis));
        if (dfs(i)) result++;
    }
    return result;
}

int main() {
    scanf("%d %d", &n, &m);

    for (int i = 1; i <= n; i++) {
```

```
        for (int j = 1; j <= m; j++) {
            scanf("%d", &graph[i][j]);
        }
    }

    int ans = maxMatching();

    printf("Maximum Bipartite Matching: %d", ans);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 11_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 24

Section 1 : Coding

1. Problem Statement

You are given a bipartite graph represented using an edge list. The graph contains two sets of nodes tasks and processors. Each edge connects a task node to a processor node, indicating that the processor can execute that task.

Your goal is to determine the maximum matching in the bipartite graph. A matching is a set of edges such that:

Each task is assigned to at most one processor.Each processor is assigned to at most one task.

Write a program to compute the maximum number of task–processor assignments possible.

Input Format

The first line contains an integer T, representing the number of tasks.

The second line contains an integer P, representing the number of processors.

The third line contains an integer E, representing the number of edges in the bipartite graph.

The next E lines each contain two space-separated integers task and processor where this indicates that the given task can be assigned to the specified processor.

Output Format

The output prints the result in the following format: "The maximum matching is: X", where X is the maximum number of matches that can be made in the bipartite graph.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
3
5
1 1
2 2
4 3
3 3
4 1
Output: The maximum matching is: 3

Answer

```
#include <stdio.h>
#include <string.h>

#define MAX 15

int T, P, E;
int graph[MAX][MAX];
int match[MAX];
int visited[MAX];
```

```
int dfs(int u) {
    for (int v = 1; v <= P; v++) {
        if (graph[u][v] && !visited[v]) {
            visited[v] = 1;

            if (match[v] == 0 || dfs(match[v])) {
                match[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

int main() {
    scanf("%d", &T);
    scanf("%d", &P);
    scanf("%d", &E);

    memset(graph, 0, sizeof(graph));
    memset(match, 0, sizeof(match));

    for (int i = 0; i < E; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        graph[u][v] = 1;
    }

    int result = 0;

    for (int i = 1; i <= T; i++) {
        memset(visited, 0, sizeof(visited));
        if (dfs(i))
            result++;
    }

    printf("The maximum matching is: %d", result);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Irfan is working on a project that involves managing relationships between two sets of entities, set U and set V. He wants to determine the maximum matching in a bipartite graph to optimize connections without overlap.Irfan also wants to explore different scenarios by adding a new connection (edge) between two entities and observing how it affects the maximum matching.

Your task is to compute the size of the maximum matching before and after adding a specified edge.

Note: Vertices in set U are numbered from 0 to n-1, and vertices in set V are numbered from 1 to m.

Input Format

The first line contains an integer n, representing the number of vertices in set U.

The second line contains an integer m, representing the number of vertices in set V.

The third line contains an integer e, representing the number of edges.

The next e lines each contain two integers u and v, representing an edge between vertex u from set U and vertex v from set V.

The last line contains two integers u and v, representing the edge to be added.

Output Format

The output prints the results in the following format:

Size of maximum matching before adding edges: X

Size of maximum matching after adding edges: Y

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3
4
3
0 1
0 2
1 1
1 2

Output: Size of maximum matching before adding edges: 1
Size of maximum matching after adding edges: 1

Answer

```
#include <stdio.h>
#include <string.h>

#define MAX 105

int n, m, e;
int graph[MAX][MAX];
int match[MAX];
int vis[MAX];

int dfs(int u) {
   for (int v = 1; v <= m; v++) {
      if (graph[u][v] && !vis[v]) {
         vis[v] = 1;

         if (match[v] == -1 || dfs(match[v])) {
            match[v] = u;
            return 1;
         }
      }
   }
   return 0;
}

int maxMatching() {
   for (int i = 0; i <= m; i++)
      match[i] = -1;
```

```
    int result = 0;

    for (int u = 0; u < n; u++) {
        for (int i = 0; i <= m; i++)
            vis[i] = 0;

        if (dfs(u))
            result++;
    }

    return result;
}

int main() {
    scanf("%d", &n);
    scanf("%d", &m);
    scanf("%d", &e);

    memset(graph, 0, sizeof(graph));

    for (int i = 0; i < e; i++) {
        int u, v;
        scanf("%d %d", &u, &v);

        // ensure valid range only
        if (u >= 0 && u < n && v >= 1 && v <= m)
            graph[u][v] = 1;
    }

    int u, v;
    scanf("%d %d", &u, &v);

    int before = maxMatching();

    if (u >= 0 && u < n && v >= 1 && v <= m)
        graph[u][v] = 1;

    int after = maxMatching();

    printf("Size of maximum matching before adding edges: %d\n", before);
    printf("Size of maximum matching after adding edges: %d", after);
```

```
    return 0;
}
```

Status : Partially correct ***Marks : 2.5/10***

3. Problem Statement

Jack wants to create a program to manage a bipartite graph, which contains two sets of vertices.He needs the program to:

Initialize the graph with a specific size,Add edges between the two sets of vertices, andFind pairings where each vertex from the first set is matched with at most one vertex from the second set, and no two vertices from the first set are matched with the same vertex from the second set.

The goal is to determine the maximum matching pairs in the bipartite graph.

Input Format

The first line contains an integer m, representing the number of vertices in the first set.

The second line contains an integer n, representing the number of vertices in the second set.

The third line contains an integer e, representing the number of edges in the graph.

The next e lines each contain two integers u and v, representing an edge between vertex u in the first set and vertex v in the second set.

Output Format

The output prints the maximum matching pairs in increasing order of u, where each pair is printed in the format: (u, v)

If there are no matching pairs, print: "No matching found"

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
3
5
1 1
2 2
4 3
3 3
4 1

Output: (1, 1)
(2, 2)
(3, 3)

Answer

```
#include <stdio.h>
#include <string.h>

#define MAX 15

int m, n, e;
int graph[MAX][MAX];
int match[MAX];
int vis[MAX];

int dfs(int u) {
    for (int v = 1; v <= n; v++) {
        if (graph[u][v] && !vis[v]) {
            vis[v] = 1;

            if (match[v] == 0 || dfs(match[v])) {
                match[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

int main() {
    scanf("%d", &m);
```

```
    scanf("%d", &n);
    scanf("%d", &e);

    memset(graph, 0, sizeof(graph));
    memset(match, 0, sizeof(match));

    for (int i = 0; i < e; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        graph[u][v] = 1;
    }

    for (int u = 1; u <= m; u++) {
        memset(vis, 0, sizeof(vis));
        dfs(u);
    }

    int found = 0;

    for (int v = 1; v <= n; v++) {
        if (match[v] != 0) {
            printf("(%d, %d)\n", match[v], v);
            found = 1;
        }
    }

    if (!found)
        printf("No matching found");

    return 0;
}
```

Status : Partially correct ***Marks : 1.5/10***

4. Problem Statement

Alex needs to pair students from two different classes for a project, aiming to maximize the number of compatible pairs. Each student can be paired with only one student from the other class. The compatibility between students is represented as a binary adjacency matrix.

Alex wants to write a program to find the maximum number of compatible student pairs that can be formed.

Input Format

The first line contains an integer n, representing the number of students in each group.

The second line contains an integer m, representing the number of students in the second group.

The next n lines contain m space-separated integers each, representing the adjacency matrix of student compatibility.

Output Format

The single line containing the phrase "Maximum Bipartite Matching: x" where x is an integer representing the maximum number of compatible pairs that can be formed.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 4
3
1 1 0
1 0 1
0 1 0
1 0 0
Output: Maximum Bipartite Matching: 3

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

#define MAX 105

int n, m;
```

```
int graph[MAX][MAX];
int match[MAX];
int vis[MAX];

int dfs(int u) {
    for (int v = 1; v <= m; v++) {
        if (graph[u][v] && !vis[v]) {
            vis[v] = 1;

            if (match[v] == 0 || dfs(match[v])) {
                match[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

int main() {
    scanf("%d", &n);
    scanf("%d", &m);

    memset(graph, 0, sizeof(graph));
    memset(match, 0, sizeof(match));

    for (int i = 1; i <= n; i++) {
        for (int j = 1; j <= m; j++) {
            scanf("%d", &graph[i][j]);
        }
    }

    int result = 0;

    for (int i = 1; i <= n; i++) {
        memset(vis, 0, sizeof(vis));
        if (dfs(i))
            result++;
    }

    printf("Maximum Bipartite Matching: %d", result);

    return 0;
```

}

Status : Correct ***Marks : 10/10***

5. Problem Statement:

John is developing a recommendation system for a social networking platform. The system suggests potential friends to users based on their interests and mutual connections. To enhance the user experience, you want to ensure that the recommendation algorithm considers the removal of certain users from the network due to various reasons such as account deletion or user activity.

However, he still wants to maintain effective friend suggestions even after removing these users. John plan to integrate a functionality that calculates the maximum matching in the bipartite graph representing the user network after removing specific users and their connections.

Help him to achieve the task.

Input Format

Enter the number of vertices in partition

Enter the number of vertices in partition

Enter the adjacency matrix representation of the bipartite graph

Enter the vertex to remove

Output Format

Maximum matching after removing vertex

Sample Test Case

Input: 3
2
0 1
1 0
0 0
1

vtu27632

Output: Maximum matching after removing vertex 1: 1

Answer

```
// You are using GCC
#include <stdio.h>
#include <string.h>

#define MAX 105

int n, m;
int graph[MAX][MAX];
int match[MAX];
int vis[MAX];

int dfs(int u) {
    for (int v = 1; v <= m; v++) {
        if (graph[u][v] && !vis[v]) {
            vis[v] = 1;

            if (match[v] == 0 || dfs(match[v])) {
                match[v] = u;
                return 1;
            }
        }
    }
    return 0;
}

int maxMatching() {
    memset(match, 0, sizeof(match));
    int result = 0;

    for (int i = 1; i <= n; i++) {
        memset(vis, 0, sizeof(vis));
        if (dfs(i)) result++;
    }
    return result;
}

int main() {
    scanf("%d", &n);
    scanf("%d", &m);
```

```
    int e;
    scanf("%d", &e);

    memset(graph, 0, sizeof(graph));

    for (int i = 0; i < e; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        graph[u][v] = 1;
    }

    int removed;
    scanf("%d", &removed);

    // remove vertex
    for (int i = 1; i <= m; i++) graph[removed][i] = 0;

    int ans = maxMatching();

    printf("Maximum matching after removing vertex %d: %d", removed, ans);

    return 0;
}
```

Status : Wrong ***Marks : 0/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 12_MCQ

Attempt : 1
Total Mark : 15
Marks Obtained : 15

Section 1 : MCQ

1. How many conditions have to be met if an NP-complete problem is polynomially reducible?

Answer

2

Status : Correct ***Marks : 1/1***

2. _____ is the class of decision problems that can be solved by non-deterministic polynomial algorithms.

Answer

NP

Status : Correct ***Marks : 1/1***

vtu27632

3. To which of the following classes does a CNF-satisfiability problem belong?

Answer

NP complete

Status : Correct ***Marks : 1/1***

4. For problems X and Y, Y is NP-complete and X reduces to Y in polynomial time. Which of the following is TRUE?

Answer

X is in NP, but not necessarily NP-complete

Status : Correct ***Marks : 1/1***

5. A problem in NP is NP-complete if

Answer

The 3-SAT problem can be reduced to it in polynomial time

Status : Correct ***Marks : 1/1***

6. Which class contains problems that can be solved in polynomial time using a deterministic machine?

Answer

P

Status : Correct ***Marks : 1/1***

7. What is the key property of problems in NP?

Answer

Their solutions can be verified in polynomial time

Status : Correct ***Marks : 1/1***

vtu27632

8. What does it mean if a problem is in both NP and NP-Complete?

Answer

It is the hardest among NP problems

Status : Correct ***Marks : 1/1***

9. If P = NP is ever proven, what would it imply?

Answer

All problems in NP can be solved in polynomial time

Status : Correct ***Marks : 1/1***

10. What is the class NP named after?

Answer

Nondeterministic Polynomial time

Status : Correct ***Marks : 1/1***

11. Which complexity class includes problems that are at least as hard as the hardest problems in NP?

Answer

NP-hard

Status : Correct ***Marks : 1/1***

12. What is the defining property of NP-hard problems?

Answer

They are at least as hard as the hardest problems in NP.

Status : Correct ***Marks : 1/1***

vtu27632

13. In computational complexity theory, what does "NP" stand for?

Answer

Non-Deterministic Polynomial Time

Status : Correct ***Marks : 1/1***

14. What is the main characteristic that distinguishes NP-complete problems from NP-hard problems?

Answer

NP-complete problems are the hardest problems in NP.

Status : Correct ***Marks : 1/1***

15. The concept of "polynomial-time reduction" is commonly used to establish which of the following relationships between problems?

Answer

NP-hardness

Status : Correct ***Marks : 1/1***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 12_COD

Attempt : 1
Total Mark : 30
Marks Obtained : 30

Section 1 : Coding

1. Problem Statement

Raj is developing financial software that must identify all non-empty subsets of a given list of expenses whose total sum equals a specified target value.

Each expense can either be included or excluded from a subset. The same expense cannot be used more than once in a subset.

Your task is to print all such valid subsets. If no valid non-empty subset exists whose sum equals the target value, print:

No subset matches the target sum

This problem demonstrates how the number of possible subsets increases exponentially when using brute-force approaches.

vtu27632

Formula

Subset Sum = sum of selected elements in the subset

A subset is considered valid if:

sum(subset elements) = target

Input Format

The first line contains an integer n, representing the number of expenses.

The second line contains n space-separated integers representing the expense values.

The third line contains an integer t, representing the target sum.

Output Format

Print each valid non-empty subset whose elements sum to t, one subset per line.

Elements of a subset must be printed as space-separated integers.

If no such subset exists, print:

No subset matches the target sum

Refer to the sample output for formatting.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3
1 2 3
3
Output: 1 2
3

vtu27632

Answer

```
// You are using GCC
#include <stdio.h>

#define MAX 20

int arr[MAX];
int subset[MAX];
int n, target;
int found = 0;

void printSubset(int size) {
    for (int i = 0; i < size; i++) {
        printf("%d ", subset[i]);
    }
    printf("\n");
}

void backtrack(int index, int currentSum, int size) {
    if (index == n) {
        if (currentSum == target && size > 0) {
            printSubset(size);
            found = 1;
        }
        return;
    }

    // include current element
    subset[size] = arr[index];
    backtrack(index + 1, currentSum + arr[index], size + 1);

    // exclude current element
    backtrack(index + 1, currentSum, size);
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }
```

```
    scanf("%d", &target);

    backtrack(0, 0, 0);

    if (!found) {
        printf("No subset matches the target sum");
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Sanjana is a cybersecurity analyst responsible for securing communication in a corporate network. The network consists of multiple computers (nodes) connected by communication links (edges).

To ensure secure communication, Sanjana wants to select a group of computers such that every pair of selected computers is directly connected to each other. This ensures a fully trusted group where all members can communicate securely without intermediaries. Such a group is called a clique.

Sanjana is given a list of connections in the network, and she needs to determine whether there exists a clique of size k.

Input Format

The first line contains two integers n and m, representing the number of computers (nodes) and connections (edges).

The next m lines each contain two integers u and v, representing a connection between nodes u and v.

The last line contains an integer k, representing the required clique size.

Output Format

If a clique of size k exists, the output prints: "Clique Found: v1 v2 v3 ..."

Otherwise, the output prints: "No clique of given size exists"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 6
0 1
0 2
1 2
1 3
2 3
3 4
3
Output: Clique Found: 0 1 2

Answer

```
// You are using GCC
#include <stdio.h>

#define MAX 20

int graph[MAX][MAX];
int n, m, k;

int subset[MAX];
int found = 0;

int isClique(int size) {
    for (int i = 0; i < size; i++) {
        for (int j = i + 1; j < size; j++) {
            if (!graph[subset[i]][subset[j]]) {
                return 0;
            }
        }
    }
    return 1;
}
```

```
void printSubset() {
    printf("Clique Found: ");
    for (int i = 0; i < k; i++) {
        printf("%d ", subset[i]);
    }
}

void backtrack(int start, int depth) {
    if (depth == k) {
        if (isClique(k)) {
            printSubset();
            found = 1;
        }
        return;
    }

    for (int i = start; i < n; i++) {
        subset[depth] = i;
        backtrack(i + 1, depth + 1);
        if (found) return;
    }
}

int main() {
    scanf("%d %d", &n, &m);

    // initialize graph
    for (int i = 0; i < n; i++)
        for (int j = 0; j < n; j++)
            graph[i][j] = 0;

    // input edges
    for (int i = 0; i < m; i++) {
        int u, v;
        scanf("%d %d", &u, &v);
        graph[u][v] = 1;
        graph[v][u] = 1;
    }

    scanf("%d", &k);

    backtrack(0, 0);
```

```
    if (!found) {
        printf("No clique of given size exists");
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Rehan, a logistics manager, is packing valuable items into two separate containers. Each item has a specific value, and he wants both containers to carry the same total value to ensure balance and fairness. He needs to decide if it's possible to divide the items this way and print one such valid division if it exists.

This problem is based on a classic NP-complete problem known as the Partition Problem, where finding a solution may require checking all combinations in the worst case.

Help him write a program to solve this problem.

Input Format

The first line of input consists of an integer n, representing the number of items.

The second line contains n space-separated integers, where each integer represents the value of an item.

Output Format

If a valid equal partition exists, print:

- Subset 1: x1 x2 x3 ...
- Subset 2: y1 y2 y3 ...

If no such partition exists, it prints "No valid equal partition exists."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
1 5 11 5

Output: Subset 1: 1 5 5
Subset 2: 11

Answer

```
// You are using GCC
#include <stdio.h>

#define MAX 16

int arr[MAX];
int subset[MAX];
int used[MAX];
int n;
int target;
int found = 0;

void printResult() {
    int sum1 = 0, sum2 = 0;

    printf("Subset 1: ");
    for (int i = 0; i < n; i++) {
        if (used[i]) {
            printf("%d ", arr[i]);
            sum1 += arr[i];
        }
    }

    printf("\nSubset 2: ");
    for (int i = 0; i < n; i++) {
        if (!used[i]) {
            printf("%d ", arr[i]);
            sum2 += arr[i];
        }
    }
}
```

```
void backtrack(int index, int currentSum) {
    if (found) return;

    if (currentSum == target) {
        found = 1;
        printResult();
        return;
    }

    if (index == n || currentSum > target) return;

    // include
    used[index] = 1;
    backtrack(index + 1, currentSum + arr[index]);

    // exclude
    used[index] = 0;
    backtrack(index + 1, currentSum);
}

int main() {
    scanf("%d", &n);

    int sum = 0;

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
        sum += arr[i];
    }

    if (sum % 2 != 0) {
        printf("No valid equal partition exists.");
        return 0;
    }

    target = sum / 2;

    backtrack(0, 0);

    if (!found) {
        printf("No valid equal partition exists.");
```

```
    }
    return 0;
}
```

Status : Correct ***Marks : 10/10***

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 12_CY

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

You are given a graph, and your task is to find the minimum vertex cover for the given graph. A vertex cover is a subset of vertices in the graph such that every edge in the graph is incident to at least one vertex in the cover.

Input Format

The first line contains an integer 'vertices' representing the number of vertices in the graph.

The second line contains an integer 'edges' representing the number of edges in the graph.

The following 'edges' lines each contain two integers 'u' and 'v' representing an edge between vertices 'u' and 'v'.

Output Format

The output prints the minimum vertex cover for the given graph, where each vertex in the cover is separated by a space.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 7
6
0 1
0 2
1 3
3 4
4 5
5 6

Output: 0 1 3 4 5 6

Answer

```
// You are using GCC
#include <stdio.h>

int adj[105][105];
int vis[105];
int n, e;

int main() {
    scanf("%d", &n);
    scanf("%d", &e);

    int u, v;

    for (int i = 0; i < e; i++) {
        scanf("%d %d", &u, &v);
        adj[u][v] = 1;
        adj[v][u] = 1;
    }

    int cover[105];
```

```
    int csz = 0;

    for (int i = 0; i < n; i++) vis[i] = 0;

    for (int i = 0; i < n; i++) {
        for (int j = i + 1; j < n; j++) {
            if (adj[i][j]) {
                if (!vis[i] && !vis[j]) {
                    cover[csz++] = i;
                    cover[csz++] = j;
                    vis[i] = vis[j] = 1;
                }
            }
        }
    }

    for (int i = 0; i < csz; i++) {
        printf("%d ", cover[i]);
    }

    return 0;
}
```

Status : Correct **Marks : 10/10**

2. Problem Statement

A financial analyst is studying the daily profit and loss values of a company over a period of time. Each day's profit or loss is recorded as an integer in an array, where positive values indicate profit and negative values indicate loss.

The analyst wants to identify a continuous period of days during which the company achieved the maximum total profit. This period must consist of consecutive days only, and at least one day must be selected.

Given an array of integers representing daily profit and loss values, determine the maximum possible sum of any contiguous subarray.

To solve this efficiently, you must use a linear-time algorithm.

Input Format

The first line contains an integer n, representing the number of days.

The second line contains n space-separated integers representing daily profit or loss values.

Output Format

Print a single integer representing the maximum sum of a contiguous subarray.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 9
-2 1 -3 4 -1 2 1 -5 4

Output: 6

Answer

```
// You are using GCC
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int arr[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    int maxSum = arr[0];
    int currentSum = arr[0];

    for (int i = 1; i < n; i++) {
        if (currentSum + arr[i] > arr[i])
            currentSum = currentSum + arr[i];
        else
            currentSum = arr[i];
```

```
    if (currentSum > maxSum)
        maxSum = currentSum;
  }

  printf("%d", maxSum);

  return 0;
}
```

Status : Correct **Marks : 10/10**

3. Problem Statement

Given an array of integers, determine whether there exists a majority element in the array.

A majority element is defined as an element that appears more than n/2 times in the array.

Your task is to implement a function majorityElement() that takes the input array and returns the majority element if it exists. If no such element exists, return -1.

Formula

An element is considered a majority element if:

frequency(element) > n/2

where n is the total number of elements in the array.

Input Format

The first line of input contains an integer n, representing the number of elements in the array.

The second line contains n space-separated integers a1 a2 a3 ... an representing the array elements.

Output Format

Print the majority element if it exists. Otherwise, print -1.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 9
3 3 4 2 4 4 2 4 4

Output: 4

Answer

```
// You are using GCC
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int arr[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    // Step 1: Find candidate
    int candidate = arr[0];
    int count = 1;

    for (int i = 1; i < n; i++) {
        if (arr[i] == candidate)
            count++;
        else
            count--;

        if (count == 0) {
            candidate = arr[i];
            count = 1;
        }
```

```
    }

    // Step 2: Verify candidate
    count = 0;
    for (int i = 0; i < n; i++) {
        if (arr[i] == candidate)
            count++;
    }

    if (count > n / 2)
        printf("%d", candidate);
    else
        printf("-1");

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Aarav is analyzing temperature fluctuations recorded over several days. The temperature changes are stored in an array of integers. He wants to identify a contiguous period of days such that the product of the temperature changes during that period is maximized.

Given an array of integers, determine the maximum product that can be obtained from any contiguous subarray containing at least one element.

Your task is to compute this value efficiently.

Formula

To correctly handle both positive and negative values, track both the maximum and minimum product ending at each index.

If the current element is negative, swap the previous maximum and minimum values before updating.

At each index i:

currentMax = max(arr[i], arr[i] × currentMax)

currentMin = min(arr[i], arr[i] × currentMin)

The final answer is the maximum value obtained among all currentMax values.

Input Format

The first line contains an integer n, representing the number of days.

The second line contains n space-separated integers representing the temperature change factors.

Output Format

The first line contains an integer n, representing the number of days.

The second line contains n space-separated integers representing the temperature change factors.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 6
2 3 -2 4 -1 5
Output: 240

Answer

```
// You are using GCC
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    int arr[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
```

```
    }
    int maxProd = arr[0];
    int currMax = arr[0];
    int currMin = arr[0];

    for (int i = 1; i < n; i++) {
        int temp = currMax;

        if (arr[i] < 0) {
            int t = currMax;
            currMax = currMin;
            currMin = t;
        }

        if (arr[i] > currMax * arr[i])
            currMax = arr[i];
        else
            currMax = currMax * arr[i];

        if (arr[i] < currMin * arr[i])
            currMin = arr[i];
        else
            currMin = currMin * arr[i];

        if (currMax > maxProd)
            maxProd = currMax;
    }

    printf("%d", maxProd);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

5. Problem Statement

Sidhant is a logistics manager responsible for planning delivery routes for a fleet of trucks. He has a list of cities, and the distances between every pair of cities are given in the form of a matrix.

Each truck must start from a central warehouse (city 0), visit every other city exactly once, and return back to the warehouse. The goal is to minimize the total travel distance.

Sidhant needs to determine the minimum distance required to complete the route and also print the optimal path taken.

Input Format

The first line contains an integer n, representing the number of cities.

The next n lines contain n space-separated integers, representing the distance matrix.

Output Format

The first line of output prints the minimum travel distance.

In the next line, print the optimal path starting and ending at city 0.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
0 10 15 20
10 0 35 25
15 35 0 30
20 25 30 0

Output: 80
0 1 3 2 0

Answer

```
// You are using GCC
#include <stdio.h>
#include <limits.h>

#define MAX 16

int n;
```

```
int dist[MAX][MAX];
int dp[1 << MAX][MAX];
int parent[1 << MAX][MAX];

int min(int a, int b) {
    return a < b ? a : b;
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            scanf("%d", &dist[i][j]);
        }
    }

    int maxMask = 1 << n;

    for (int mask = 0; mask < maxMask; mask++) {
        for (int i = 0; i < n; i++) {
            dp[mask][i] = INT_MAX;
            parent[mask][i] = -1;
        }
    }

    dp[1][0] = 0;

    for (int mask = 1; mask < maxMask; mask++) {
        for (int u = 0; u < n; u++) {
            if (!(mask & (1 << u))) continue;
            if (dp[mask][u] == INT_MAX) continue;

            for (int v = 0; v < n; v++) {
                if (mask & (1 << v)) continue;

                int newMask = mask | (1 << v);
                int newCost = dp[mask][u] + dist[u][v];

                if (newCost < dp[newMask][v]) {
                    dp[newMask][v] = newCost;
                    parent[newMask][v] = u;
```

```
            }
        }
    }
}

int full = (1 << n) - 1;
int bestCost = INT_MAX;
int last = -1;

for (int i = 1; i < n; i++) {
    if (dp[full][i] != INT_MAX && dist[i][0] != 0) {
        int cost = dp[full][i] + dist[i][0];
        if (cost < bestCost) {
            bestCost = cost;
            last = i;
        }
    }
}

printf("%d\n", bestCost);

int path[MAX], idx = 0;
int mask = full;

path[idx++] = 0;

int cur = last;
for (int i = n - 1; i >= 1; i--) {
    path[idx++] = cur;
    int p = parent[mask][cur];
    mask ^= (1 << cur);
    cur = p;
}

path[idx++] = 0;

for (int i = 0; i < idx; i++) {
    printf("%d", path[i]);
    if (i != idx - 1) printf(" ");
}

return 0;
```

}

Status : Correct ***Marks : 10/10***

vtu27632

Vel Tech Group of Institutions

Name: EDUMUDI NANDINI CHOWDARY 27632
Email: vtu27632@veltech.edu.in
Roll no: vtu27632
Phone: null
Branch: VTU
Department: Others
Batch: 2027
Degree: Others - Demo

Scan to verify results

2028_NeoColab_Design and Analysis of AlgorithmsS1L10

VTU_DAA_Week 12_PAH

Attempt : 1
Total Mark : 50
Marks Obtained : 50

Section 1 : Coding

1. Problem Statement

Meera is preparing for a science exhibition and needs to select a group of items such that their total weight is exactly equal to a given target weight. Each item has a known weight, and every item can be selected at most once.

Given a list of item weights and a target weight k, determine whether there exists a subset of items whose total weight is exactly k.

If such a subset exists, print any one valid subset.

If no such subset exists, print -1.

The solution must be implemented using Dynamic Programming.

vtu27632

Formula

Let

dp[i][j] = true

if a subset of the first i items can form a sum j.

Transition:

If arr[i-1] > j

dp[i][j] = dp[i-1][j]

Else

dp[i][j] = dp[i-1][j] OR dp[i-1][j - arr[i-1]]

Input Format

The first line contains two integers n and k, where n is the number of items and k is the target weight.

The second line contains n space-separated integers representing item weights.

Output Format

If a valid subset exists, print the elements of one such subset in a single line separated by spaces.

If no subset exists, print -1.

Refer to the sample output for formatting specifications.

Sample Test Case

vtu27632

Input: 5 9
3 34 4 12 5
Output: 5 4

Answer

```
// You are using GCC
#include <stdio.h>

int dp[105][1005];
int arr[105];

int main() {
    int n, k;
    scanf("%d %d", &n, &k);

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    // DP initialization
    dp[0][0] = 1;

    for (int i = 1; i <= n; i++) {
        for (int j = 0; j <= k; j++) {
            dp[i][j] = dp[i - 1][j];

            if (j >= arr[i - 1] && dp[i - 1][j - arr[i - 1]]) {
                dp[i][j] = 1;
            }
        }
    }

    if (!dp[n][k]) {
        printf("-1");
        return 0;
    }

    // reconstruct subset
    int i = n, j = k;
    int result[105], idx = 0;

    while (i > 0 && j > 0) {
```

```
        if (dp[i - 1][j]) {
            i--;
        } else {
            result[idx++] = arr[i - 1];
            j -= arr[i - 1];
            i--;
        }
    }

    // print subset
    for (int t = 0; t < idx; t++) {
        printf("%d ", result[t]);
    }

    return 0;
}
```

Status : Correct ***Marks : 10/10***

2. Problem Statement

Ramya is working as a logistics coordinator for a delivery company. Every day, she receives a list of delivery locations arranged along a straight highway. Each location has a certain delivery priority value (which may be positive or negative depending on profit or loss).

Ramya wants to choose a continuous sequence of delivery locations such that the total delivery priority is maximized, ensuring maximum profit for that day.

Since the company handles a large number of deliveries, Ramya needs an efficient solution that runs in polynomial time.

Input Format

The first line contains an integer n, representing the number of delivery locations.

The second line contains n space-separated integers, representing the priority values.

Output Format

The output prints a single integer representing the maximum total priority of any contiguous sequence of locations.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 8
-2 3 5 -1 4 -5 2 6

Output: 14

Answer

```
// You are using GCC
#include <stdio.h>

int main() {
    int n;
    scanf("%d", &n);

    long long arr[n];

    for (int i = 0; i < n; i++) {
        scanf("%lld", &arr[i]);
    }

    long long current = arr[0];
    long long max = arr[0];

    for (int i = 1; i < n; i++) {
        if (current + arr[i] > arr[i])
            current = current + arr[i];
        else
            current = arr[i];

        if (current > max)
            max = current;
    }

    printf("%lld", max);
```

```
    return 0;
}
```

Status : Correct ***Marks : 10/10***

3. Problem Statement

Ragav is managing a chain of warehouses located along a long highway. Each warehouse is positioned at a specific coordinate on the road.

To improve efficiency, Ragav wants to choose a central hub location such that the total travel distance from all warehouses to this hub is minimized.

He can place the hub at any one of the existing warehouse locations.

Since the number of warehouses can be very large, Ragav needs an efficient algorithm that runs in polynomial time to compute the optimal location.

Input Format

The first line contains an integer n, representing the number of warehouses.

The second line contains n space-separated integers, representing the positions of warehouses on the highway.

Output Format

The output prints a single integer representing the minimum total distance from all warehouses to the chosen hub.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
1 2 3 6 10
Output: 13

Answer

vtu27632

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>

int cmp(const void *a, const void *b) {
    long long x = *(long long*)a;
    long long y = *(long long*)b;
    if (x < y) return -1;
    if (x > y) return 1;
    return 0;
}

int main() {
    int n;
    scanf("%d", &n);

    long long arr[n];

    for (int i = 0; i < n; i++) {
        scanf("%lld", &arr[i]);
    }

    qsort(arr, n, sizeof(long long), cmp);

    long long median = arr[n / 2];

    long long sum = 0;
    for (int i = 0; i < n; i++) {
        sum += llabs(arr[i] - median);
    }

    printf("%lld", sum);

    return 0;
}
```

Status : Correct ***Marks : 10/10***

4. Problem Statement

Peter is a project manager in a software company. He has a list of

employees, and each employee has a certain skill contribution value (which can be positive or negative depending on their impact on the project).

Peter wants to form a team such that the total skill contribution is exactly equal to a given target value. Each employee can be selected at most once, and the team must contain at least one employee.

Since the number of possible teams grows rapidly with the number of employees, Peter needs to determine whether such a team exists.

Input Format

The first line contains an integer n, representing the number of employees.

The second line contains n space-separated integers, representing the skill contribution of each employee.

The third line contains an integer target, representing the required total skill.

Output Format

If a valid team exists, the output prints: "Team Found: x1 x2 x3 ..."

If no such team exists, the output prints: "No valid team found"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
3 7 -2 5 1
6
Output: Team Found: 3 -2 5

Answer

```
// You are using GCC
#include <stdio.h>

int n, target;
```

```
int arr[25];
int path[25];
int found = 0;

void dfs(int idx, int sum, int count) {
    if (found) return;

    if (sum == target && count > 0) {
        printf("Team Found: ");
        for (int i = 0; i < count; i++) {
            printf("%d ", path[i]);
        }
        found = 1;
        return;
    }

    if (idx == n) return;

    // include
    path[count] = arr[idx];
    dfs(idx + 1, sum + arr[idx], count + 1);

    // exclude
    dfs(idx + 1, sum, count);
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d", &arr[i]);
    }

    scanf("%d", &target);

    dfs(0, 0, 0);

    if (!found) {
        printf("No valid team found");
    }

    return 0;
```

}

Status : Correct ***Marks : 10/10***

5. Problem Statement

Viyana is an event coordinator organizing multiple sessions for a tech conference. Each session has a start time and an end time.

Due to limited resources, Viyana wants to select a group of sessions such that:

No two selected sessions overlap in time.The total number of selected sessions is maximized.

However, to make the event more impactful, each session also has a priority score, and Viyana wants to maximize the total priority score instead of just the count.

Your task is to help Viyana select the optimal set of non-overlapping sessions that yields the maximum total priority score.

Input Format

The first line contains an integer n, representing the number of sessions.

The next n lines each contain three integers:start time, end time and priority score.

Output Format

The first line of output prints the maximum total priority score.

In the next line, print the selected sessions (indices starting from 1) in ascending order.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 4
1 3 5
2 5 6
4 6 5
6 7 4

Output: 14
1 3 4

Answer

```
// You are using GCC
#include <stdio.h>

int n;
int s[25], e[25], p[25];

int bestSum = 0;
int bestMask = 0;

int overlap(int mask) {
    int lastEnd = -1;

    for (int i = 0; i < n; i++) {
        if (mask & (1 << i)) {
            if (s[i] < lastEnd) return 1;
            lastEnd = e[i];
        }
    }
    return 0;
}

int main() {
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d %d %d", &s[i], &e[i], &p[i]);
    }

    for (int mask = 0; mask < (1 << n); mask++) {
        int valid = 1;
```

```
        int sum = 0;

        int lastEnd = -1;

        for (int i = 0; i < n; i++) {
            if (mask & (1 << i)) {
                if (s[i] < lastEnd) {
                    valid = 0;
                    break;
                }
                lastEnd = e[i];
                sum += p[i];
            }
        }

        if (valid && sum > bestSum) {
            bestSum = sum;
            bestMask = mask;
        }
    }

    printf("%d\n", bestSum);

    int first = 1;
    for (int i = 0; i < n; i++) {
        if (bestMask & (1 << i)) {
            if (!first) printf(" ");
            printf("%d", i + 1);
            first = 0;
        }
    }
    printf(" ");

    return 0;
}
```

Status : Correct ***Marks : 10/10***