

Model Checking Real-Time Systems

Vincent Trélat

Technical University of Munich

December 12, 2022

1. Timed Automata

1.1 Preliminaries

1.2 Timed Automata

1.3 Regions and zones

1.4 Extensions

2. Model Checking Real-Time Systems

2.1 TLTL

2.2 Timed Games

3. Language-Theoretic Properties

4. References

1. Timed Automata

- 1.1 Preliminaries
- 1.2 Timed Automata
- 1.3 Regions and zones
- 1.4 Extensions

2. Model Checking Real-Time Systems

- 2.1 TLTL
- 2.2 Timed Games

3. Language-Theoretic Properties

4. References

Set of *time values*: $\mathbb{R}_{\geq 0}$

Timed words over $\Sigma \times \mathbb{R}_{\geq 0}$

Set of *valuations* over a set of clocks C : $\mathbb{R}_{\geq 0}^C$

Constraints over C : $\varphi ::= x \odot k \mid \varphi \wedge \varphi$ where $x \in C$, $k \in \mathbb{Z}$ and $\odot \in \{<, \leq, =, \geq, >\}$

Set of valuations *satisfying* φ : $\llbracket \varphi \rrbracket_C = \{v \in \mathbb{R}_{\geq 0}^C \mid v \models \varphi\}$


Definition 1

A *Timed Automaton* (TA) \mathcal{A} is the tuple $(L, \ell_0, C, \Sigma, I, E)$ where:

- L is a finite set of *locations* with initial location $\ell_0 \in L$
- C is a finite set of *clocks*
- Σ is a finite set of *actions*
- $I: L \rightarrow \Phi(C)$ is an *invariant mapping*
- $E \subseteq L \times \Phi(C) \times \Sigma \times 2^C \times L$ is a set of edges.

Edges are denoted by $\ell \xrightarrow{\varphi, a, r} \ell'$.

Example of a TA with 3 locations, 2 clocks and 2 actions (letters):



References