



# Formal verification in Isabelle / HOL of an algorithm for computing SCCs

Vincent Trélat

École Nationale Supérieure des Mines de Nancy  
Département Informatique

January 14, 2022

## ① Introduction

Definition


Motivation


## ② Example of the proof process


## ③ A sequential set-based SCC algorithm

Description of the algorithm

Implementation in Isabelle








## Definition 1

Let  $\mathcal{G} := (\mathcal{V}, \mathcal{E})$  be a **directed graph** and  $\mathcal{C} \subseteq \mathcal{V}$ .  $\mathcal{C}$  is a SCC of  $\mathcal{G}$  if:

$$\forall x, y \in \mathcal{C}, (x \Rightarrow y) \wedge (y \Rightarrow x)$$



## Definition 1

Let  $\mathcal{G} := (\mathcal{V}, \mathcal{E})$  be a **directed graph** and  $\mathcal{C} \subseteq \mathcal{V}$ .  $\mathcal{C}$  is a SCC of  $\mathcal{G}$  if:

$$\forall x, y \in \mathcal{C}, (x \Rightarrow y) \wedge (y \Rightarrow x)$$

## ① Introduction

Definition


**Motivation**

## ② Example of the proof process

## ③ A sequential set-based SCC algorithm


Description of the algorithm

Implementation in Isabelle



- Networks: connection and data sharing
- Model checking: counter-examples finding





- Networks: connection and data sharing
- Model checking: counter-examples finding

Efficient algorithms (ex: Tarjan)

- Formal verification of correctness is worthwhile
- Parallelization is another challenge

## Isabelle / HOL

- Generic proof assistant
- Formalisation of mathematical proofs
- Higher-Order Logic theorem proving environment
- Powerful proof tools and language (Isar)
- Mutual induction, recursion and datatypes, complex pattern matching

## ① Introduction

Definition

Motivation

## ② Example of the proof process

## ③ A sequential set-based SCC algorithm

Description of the algorithm

Implementation in Isabelle

## (Type definition)

```
datatype 'a list = Empty | Cons 'a "'a list"
```

- Generic / polymorphic and static type
- Implicit constructor definition
- Recursive structure giving an induction principle for that type

## (Function definition)

```
fun concat :: 'a list  $\Rightarrow$  'a list  $\Rightarrow$  'a list where  
  concat Empty xs = xs  
| concat (Cons x xs) ys = Cons x (concat xs ys)
```

```
fun rev :: 'a list  $\Rightarrow$  'a list where  
  rev Empty = Empty  
| rev (Cons x xs) = concat (rev xs) (Cons x Empty)
```

(Theorem statement)

```
theorem rev_rev : rev (rev xs) = xs
```

(Theorem statement)

```
theorem rev_rev : rev (rev xs) = xs  
  apply (induction xs)  
  apply auto
```

## (Theorem statement)

```
theorem rev_rev : rev (rev xs) = xs
  apply (induction xs)
  apply auto
```

## (Subgoal)

```
∧ x1 x.
  rev (rev x) = x ⇒
  rev (concat (rev x) (Cons x1 Empty)) = Cons x1 x
```



## (Adding a first lemma)

```
lemma rev_concat: rev (concat xs ys) = concat(rev ys) (rev xs)
  apply (induction xs)
  apply auto
```

## (Adding a first lemma)

```
lemma rev_concat: rev (concat xs ys) = concat (rev ys) (rev xs)
  apply (induction xs)
  apply auto
```

## (Subgoals)

1.  $\text{rev } \text{ys} = \text{concat } (\text{rev } \text{ys}) \text{ Empty}$
2.  $\bigwedge x1 \text{ xs.}$   
 $\text{rev } (\text{concat } \text{xs } \text{ys}) = \text{concat } (\text{rev } \text{ys}) (\text{rev } \text{xs}) \implies$   
 $\text{rev } (\text{concat } (\text{Cons } x1 \text{ xs}) \text{ys}) = \text{concat } (\text{rev } \text{ys}) (\text{rev } (\text{Cons } x1 \text{ xs}))$

### (Adding a second lemma)

```
lemma concat_empty:  concat xs Empty = xs
  apply (induction xs)
  apply auto
```

### (Adding a third lemma: associative property)

```
lemma concat_assoc:  concat (concat xs ys) zs = concat xs
(concat ys zs)
  apply (induction xs)
  apply auto
```

```
theorem rev_rev: rev (rev xs) = xs
  apply (induction xs)
  apply auto
```

No subgoals!

## ① Introduction

Definition

Motivation

## ② Example of the proof process

## ③ A sequential set-based SCC algorithm

Description of the algorithm


Implementation in Isabelle

**Data:** A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

```

1 Initialize an empty set DEAD;
2 Initialize an empty set VISITED;
3 Initialize an empty stack R;
4 setBased( $v_0$ );
5 function setBased:  $v \in \mathcal{V} \rightarrow \text{None}$ 
6     VISITED := VISITED  $\cup \{v\}$ ;
7     R.push( $v$ );
8     foreach  $w \in \text{POST}(v)$  do
9         if  $w \in \text{DEAD}$  then
10             continue;
11         else if  $w \notin \text{VISITED}$  then
12             setBased( $w$ );
13         else
14             while  $\mathcal{S}(v) \neq \mathcal{S}(w)$  do
15                  $r := \text{R.pop}()$ ;
16                 UNITE( $\mathcal{S}, r, \text{R.top}()$ );
17     if  $v = \text{R.top}()$  then
18         report SCC  $\mathcal{S}(v)$ ;
19         DEAD := DEAD  $\cup \mathcal{S}(v)$ ;
20         R.pop();

```



$R = []$   
 $VISITED = \{\}$   
 $DEAD = \{\}$

$\mathcal{S} = \{A\} \cup \{B\} \cup \{C\} \cup \{D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$

Data: A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

Initialize an empty set  $DEAD$ ;

2 Initialize an empty set  $VISITED$ ;

3 Initialize an empty stack  $R$ ;

4  $setBased(v_0)$ ;

5 **function**  $setBased: v \in \mathcal{V} \rightarrow None$

6      $VISITED := VISITED \cup \{v\}$ ;

7      $R.push(v)$ ;

8     **foreach**  $w \in POST(v)$  **do**

9         **if**  $w \in DEAD$  **then**

10             continue;

11         **else if**  $w \notin VISITED$  **then**

12              $setBased(w)$ ;

13         **else**

14             **while**  $S(v) \neq S(w)$  **do**

15                  $r := R.pop()$ ;


16                  $UNITE(S, r, R.top())$ ;

17             **if**  $v = R.top()$  **then**

18                 **report SCC**  $S(v)$ ;

19                  $DEAD := DEAD \cup S(v)$ ;

20                  $R.pop()$ ;



$R = [H]$

$VISITED = \{H\}$

$DEAD = \{\}$

$S = \{A\} \cup \{B\} \cup \{C\} \cup \{D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$

Data: A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

Initialize an empty set  $DEAD$ ;

Initialize an empty set  $VISITED$ ;

Initialize an empty stack  $R$ ;

$setBased(v_0)$ ;

**function**  $setBased: v \in \mathcal{V} \rightarrow None$

$VISITED := VISITED \cup \{v\}$ ;

$R.push(v)$ ;

**foreach**  $w \in POST(v)$  **do**

**if**  $w \in DEAD$  **then**

            continue;

**else if**  $w \notin VISITED$  **then**

$setBased(w)$ ;

**else**

**while**  $S(v) \neq S(w)$  **do**

$r := R.pop()$ ;

$UNITE(S, r, R.top())$ ;

**while**  $S(v) \neq S(w)$  **do**

$r := R.pop()$ ;


$UNITE(S, r, R.top())$ ;

**if**  $v = R.top()$  **then**

**report** SCC  $S(v)$ ;

$DEAD := DEAD \cup S(v)$ ;

$R.pop()$ ;



$R = [H, E]$

$VISITED = \{H, E\}$

$DEAD = \{\}$

$S = \{A\} \cup \{B\} \cup \{C\} \cup \{D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$



---

Data: A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

Initialize an empty set DEAD;

2 Initialize an empty set VISITED;

3 Initialize an empty stack R;

4  $\text{setBased}(v_0)$ ;

5 **function**  $\text{setBased}: v \in \mathcal{V} \rightarrow \text{None}$

6     VISITED := VISITED  $\cup \{v\}$ ;

7     R.push( $v$ );

8     **foreach**  $w \in \text{POST}(v)$  **do**

9         **if**  $w \in \text{DEAD}$  **then**

10             continue;

11         **else if**  $w \notin \text{VISITED}$  **then**

12              $\text{setBased}(w)$ ;

13         **else**

14             **while**  $\mathcal{S}(v) \neq \mathcal{S}(w)$  **do**

15                  $r := \text{R.pop}()$ ;

16                 UNITE( $\mathcal{S}, r, \text{R.top}()$ );


17         **if**  $v = \text{R.top}()$  **then**

18             **report** SCC  $\mathcal{S}(v)$ ;

19             DEAD := DEAD  $\cup \mathcal{S}(v)$ ;

20             R.pop();

---



$R = [H, E, A]$

$\text{VISITED} = \{H, E, A\}$

$\text{DEAD} = \{\}$

$\mathcal{S} = \{A\} \cup \{B\} \cup \{C\} \cup \{D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$

Data: A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

Initialize an empty set DEAD;

2 Initialize an empty set VISITED;

3 Initialize an empty stack R;

4  $\text{setBased}(v_0)$ ;

5 **function**  $\text{setBased}: v \in \mathcal{V} \rightarrow \text{None}$

6     VISITED := VISITED  $\cup \{v\}$ ;

7     R.push( $v$ );

8     **foreach**  $w \in \text{POST}(v)$  **do**

9         **if**  $w \in \text{DEAD}$  **then**

10             continue;

11         **else if**  $w \notin \text{VISITED}$  **then**

12              $\text{setBased}(w)$ ;

13         **else**

14             **while**  $\mathcal{S}(v) \neq \mathcal{S}(w)$  **do**

15                  $r := \text{R.pop}()$ ;


16                  $\text{UNITE}(\mathcal{S}, r, \text{R.top}())$ ;

17         **if**  $v = \text{R.top}()$  **then**

18             **report SCC**  $\mathcal{S}(v)$ ;

19              $\text{DEAD} := \text{DEAD} \cup \mathcal{S}(v)$ ;

20              $\text{R.pop}()$ ;



$R = [H, E, A, B]$

$\text{VISITED} = \{H, E, A, B\}$

$\text{DEAD} = \{\}$

$\mathcal{S} = \{A\} \cup \{B\} \cup \{C\} \cup \{D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$

Data: A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

Initialize an empty set DEAD;

2 Initialize an empty set VISITED;

3 Initialize an empty stack R;

4  $\text{setBased}(v_0)$ ;

5 **function**  $\text{setBased}: v \in \mathcal{V} \rightarrow \text{None}$

6     VISITED := VISITED  $\cup \{v\}$ ;

7     R.push( $v$ );

8     **foreach**  $w \in \text{POST}(v)$  **do**

9         **if**  $w \in \text{DEAD}$  **then**

10             continue;

11         **else if**  $w \notin \text{VISITED}$  **then**

12              $\text{setBased}(w)$ ;

13         **else**

14             **while**  $\mathcal{S}(v) \neq \mathcal{S}(w)$  **do**

15                  $r := \text{R.pop}()$ ;


16                  $\text{UNITE}(\mathcal{S}, r, \text{R.top}())$ ;

17         **if**  $v = \text{R.top}()$  **then**

18             **report** SCC  $\mathcal{S}(v)$ ;

19              $\text{DEAD} := \text{DEAD} \cup \mathcal{S}(v)$ ;

20              $\text{R.pop}()$ ;



$R = [H, E, A, B, C]$

$\text{VISITED} = \{H, E, A, B, C\}$

$\text{DEAD} = \{\}$

$\mathcal{S} = \{A\} \cup \{B\} \cup \{C\} \cup \{D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$

---

Data: A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

Initialize an empty set DEAD;

2 Initialize an empty set VISITED;

3 Initialize an empty stack R;

4  $\text{setBased}(v_0)$ ;

5 **function**  $\text{setBased}: v \in \mathcal{V} \rightarrow \text{None}$

6     VISITED := VISITED  $\cup \{v\}$ ;

7     R.push( $v$ );

8     **foreach**  $w \in \text{POST}(v)$  **do**

9         **if**  $w \in \text{DEAD}$  **then**

10             continue;

11         **else if**  $w \notin \text{VISITED}$  **then**

12              $\text{setBased}(w)$ ;

13         **else**

14             **while**  $\mathcal{S}(v) \neq \mathcal{S}(w)$  **do**

15                  $r := \text{R.pop}()$ ;


16                  $\text{UNITE}(\mathcal{S}, r, \text{R.top}())$ ;

17             **if**  $v = \text{R.top}()$  **then**

18                 **report** SCC  $\mathcal{S}(v)$ ;

19                  $\text{DEAD} := \text{DEAD} \cup \mathcal{S}(v)$ ;

20                  $\text{R.pop}()$ ;



$R = [H, E, A, B, C, D]$

$\text{VISITED} = \{H, E, A, B, C, D\}$

$\text{DEAD} = \{\}$

$\mathcal{S} = \{A\} \cup \{B\} \cup \{C\} \cup \{D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$

Data: A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

Initialize an empty set DEAD;

Initialize an empty set VISITED;

Initialize an empty stack R;

setBased( $v_0$ ):

function setBased:  $v \in \mathcal{V} \rightarrow \text{None}$

VISITED := VISITED  $\cup \{v\}$ ;

R.push( $v$ );

foreach  $w \in \text{POST}(v)$  do

if  $w \in \text{DEAD}$  then

continue;

else if  $w \notin \text{VISITED}$  then

setBased( $w$ );

else

while  $\mathcal{S}(v) \neq \mathcal{S}(w)$  do

$r := \text{R.pop}()$ ;


UNITE( $\mathcal{S}, r, \text{R.top}()$ );

if  $v = \text{R.top}()$  then

report SCC  $\mathcal{S}(v)$ ;

DEAD := DEAD  $\cup \mathcal{S}(v)$ ;

R.pop();



$R = [H, E]$

$\text{VISITED} = \{H, E, A, B, C, D\}$

$\text{DEAD} = \{A, B, C, D\}$

$S = \{A, B, C, D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$

---

Data: A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

Initialize an empty set DEAD;

2 Initialize an empty set VISITED;

3 Initialize an empty stack R;

4  $\text{setBased}(v_0)$ ;

5 **function**  $\text{setBased}: v \in \mathcal{V} \rightarrow \text{None}$

6     VISITED := VISITED  $\cup \{v\}$ ;

7     R.push( $v$ );

8     **foreach**  $w \in \text{POST}(v)$  **do**

9         **if**  $w \in \text{DEAD}$  **then**

10             continue;

11         **else if**  $w \notin \text{VISITED}$  **then**

12              $\text{setBased}(w)$ ;

13         **else**

14             **while**  $\mathcal{S}(v) \neq \mathcal{S}(w)$  **do**

15                  $r := \text{R.pop}()$ ;

16                  $\text{UNITE}(\mathcal{S}, r, \text{R.top}())$ ;


17             **if**  $v = \text{R.top}()$  **then**

18                 **report** SCC  $\mathcal{S}(v)$ ;

19                 DEAD := DEAD  $\cup \mathcal{S}(v)$ ;

20                 R.pop();

---




$R = [H, E, F]$

$\text{VISITED} = \{H, E, A, B, C, D, F\}$

$\text{DEAD} = \{A, B, C, D\}$

$S = \{A, B, C, D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$

		R.pop();
--	--	----------


$$S = \{A, B, C, D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$$

---

Data: A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

Initialize an empty set DEAD;

2 Initialize an empty set VISITED;

3 Initialize an empty stack R;

4  $\text{setBased}(v_0)$ ;

5 **function**  $\text{setBased}: v \in \mathcal{V} \rightarrow \text{None}$

6     VISITED := VISITED  $\cup \{v\}$ ;

7     R.push( $v$ );

8     **foreach**  $w \in \text{POST}(v)$  **do**

9         **if**  $w \in \text{DEAD}$  **then**

10             continue;

11         **else if**  $w \notin \text{VISITED}$  **then**

12              $\text{setBased}(w)$ ;

13         **else**

14             **while**  $\mathcal{S}(v) \neq \mathcal{S}(w)$  **do**

15                  $r := \text{R.pop}()$ ;

16                  $\text{UNITE}(\mathcal{S}, r, \text{R.top}())$ ;


17         **if**  $v = \text{R.top}()$  **then**

18             **report SCC**  $\mathcal{S}(v)$ ;

19              $\text{DEAD} := \text{DEAD} \cup \mathcal{S}(v)$ ;

20              $\text{R.pop}()$ ;

---



$R = [H, E, F]$

$\text{VISITED} = \{H, E, A, B, C, D, F, G\}$

$\text{DEAD} = \{A, B, C, D, G\}$

$\mathcal{S} = \{A, B, C, D\} \cup \{E\} \cup \{F\} \cup \{G\} \cup \{H\}$




**Data:** A graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ , a starting node  $v_0$ ;

```

1 Initialize an empty set DEAD;
2 Initialize an empty set VISITED;
3 Initialize an empty stack R;
4 setBased( $v_0$ );
5 function setBased:  $v \in \mathcal{V} \rightarrow \text{None}$ 
6     VISITED := VISITED  $\cup \{v\}$ ;
7     R.push( $v$ );
8     foreach  $w \in \text{POST}(v)$  do
9         if  $w \in \text{DEAD}$  then
10              $\quad$  continue;
11         else if  $w \notin \text{VISITED}$  then
12              $\quad$  setBased( $w$ );
13         else
14             while  $\mathcal{S}(v) \neq \mathcal{S}(w)$  do
15                  $\quad r := \text{R.pop}()$ ;
16                  $\quad \text{UNITE}(\mathcal{S}, r, \text{R.top}());$ 
17 if  $v = \text{R.top}()$  then
18     report SCC  $\mathcal{S}(v)$ ;
19     DEAD := DEAD  $\cup \mathcal{S}(v)$ ;
20     R.pop();

```



$$R = []$$

$$\text{VISITED} = \{H, E, A, B, C, D, F, G\}$$

$$\text{DEAD} = \{A, B, C, D, G, E, F, H\}$$

$$\mathcal{S} = \{A, B, C, D\} \cup \{E, F, H\} \cup \{G\}$$

## ① Introduction

Definition

Motivation

## ② Example of the proof process

## ③ A sequential set-based SCC algorithm

Description of the algorithm

Implementation in Isabelle

## (Finite directed graphs)

```
locale graph =  
  fixes vertices :: "'v set"  
  and successors :: "'v ⇒ 'v set"  
  assumes vfin: "finite vertices"  
  and sclosed: " $\forall x \in \text{vertices}. \text{successors } x \subseteq \text{vertices}$ "
```

```
abbreviation edge where  
"edge x y  $\equiv$  y  $\in$  successors x"
```

```
inductive reachable where  
  reachable_refl[iff]: "reachable x x"  
| reachable_succ[elim]:  
  "[edge x y; reachable y z]  $\implies$  reachable x z"
```

## (Finite directed graphs)

```

locale graph =
  fixes vertices :: "'v set"
  and successors :: "'v ⇒ 'v set"
  assumes vfin: "finite vertices"
  and sclosed: "∀ x ∈ vertices. successors x ⊆ vertices"

```

```

abbreviation edge where
  "edge x y ≡ y ∈ successors x"

```

```

inductive reachable where
  reachable_refl[iff]: "reachable x x"
| reachable_succ[elim]:
  "[[edge x y; reachable y z]] ⇒ reachable x z"

```

(SCC)

definition is\_subscs where

"is\_subscs S  $\equiv$   $\forall x \in S. \forall y \in S. \text{reachable } x \ y$ "

(Maximal SCC)

definition is\_scc where

"is\_scc S  $\equiv S \neq \{\}$

$\wedge$  is\_subscs S

$\wedge (\forall S'. S \subseteq S' \wedge \text{is_subscs } S' \longrightarrow S' = S)"$

## Proof process

## (Well-formed environment)

**definition** wf\_env **where**

"wf\_env e  $\equiv$ "

distinct (stack e)

$\wedge$  set (stack e)  $\subseteq$  visited e

$\wedge$  explored e  $\subseteq$  visited e

$\wedge$  explored e  $\cap$  set (stack e) =  $\{\}$

$\wedge$  ( $\forall v\ w. w \in \mathcal{S}\ e\ v \longleftrightarrow \mathcal{S}\ e\ v = \mathcal{S}\ e\ w$ )

$\wedge$  ( $\forall v \in \text{set}(\text{stack } e). \forall w \in \text{set}(\text{stack } e). v \neq w \longrightarrow$   
 $\mathcal{S}\ e\ v \cap \mathcal{S}\ e\ w = \{\}$ )

$\wedge$  ( $\forall v. v \notin \text{visited } e \longrightarrow \mathcal{S}\ e\ v = \{v\}$ )

$\wedge \bigcup \{\mathcal{S}\ e\ v \mid v. v \in \text{set}(\text{stack } e)\} = \text{visited } e - \text{explored } e$

```
definition pre_dfs where
  "pre_dfs v e  $\equiv$  wf_env e  $\wedge$  v  $\notin$  visited e"
definition post_dfs where "post_dfs v e  $\equiv$  wf_env e"
```

```
definition pre_dfss where "pre_dfs v vs e  $\equiv$  wf_env e"
definition post_dfss where "post_dfs v vs e  $\equiv$  wf_env e"
```



```
lemma pre_dfs_pre_dfss:  
  assumes "pre_dfs v e"  
  shows "pre_dfss v (successors v) (e(|visited:=visited e ∪ {v},  
stack:= v # stack e|))"
```

```
lemma pre_dfss_pre_dfs:  
  assumes "pre_dfss v vs e" and "w ∉ visited e"  
  shows "pre_dfs w e"
```

```
lemma pre_dfs_implies_post_dfs:...
```

```
lemma pre_dfss_implies_post_dfss:...
```

## Possible prospects

- Finish the entire proof (with termination and functions domains)
- Parallel algorithm for computing SCC
  - The algorithm is already written<sup>1</sup>
  - A consistent work on the structure of the parallel workers is already in progress

---

<sup>1</sup>V. Bloemen, 2019. *Strong Connectivity and Shortest Paths for Checking Models* 