

RA disp

Generated by Doxygen 1.9.5

1 Introduction	1
1.1 Hosted codes	1
2 File Index	3
2.1 File List	3
3 File Documentation	5
3.1 dada2spec.c File Reference	5
3.1.1 Detailed Description	5
3.2 pipe_spec_plplot.c File Reference	6
3.2.1 Detailed Description	6

Chapter 1

Introduction

This repo hosts some tools for radio astronomy signal processing. This includes both stand-alone tools as well as codes to explore concepts. There is no guarantee that the codes will work, and everything here is experimental !

1.1 Hosted codes

As of now, the only code is a `dada2spec` tool which is under development.

Chapter 2

File Index

2.1 File List

Here is a list of all documented files with brief descriptions:

dada2spec.c	Reads a psrdada file and generates spectra out of them. The number of FFT bins and required time averaging can be specified	5
pipe_spec_plplot.c	This is a sample code	6

Chapter 3

File Documentation

3.1 dada2spec.c File Reference

Reads a psrdada file and generates spectra out of them. The number of FFT bins and required time averaging can be specified.

```
#include <stdio.h>
#include <stddef.h>
#include <unistd.h>
#include <stdlib.h>
#include <string.h>
#include <stdbool.h>
#include <signal.h>
```

Functions

- void **interrupt_handler** (int dummy)
- int **findinheader** (const char *hdr_buf, const char *hdr_name, double *val)
- void **print_acq_usage** (char *const argv[])
- int **main** (int argc, char *argv[])

3.1.1 Detailed Description

Reads a psrdada file and generates spectra out of them. The number of FFT bins and required time averaging can be specified.

Author

Jishnu N. Thekkepattu (j.thekkepattu@curtin.edu.au)

Version

0.1

Date

2023-02-08

3.2 pipe_spec_plplot.c File Reference

This is a sample code.

```
#include <stdio.h>
#include <math.h>
#include <unistd.h>
#include <plplot/plplotP.h>
#include <fftw3.h>
```

Macros

- `#define NFFT 4096`

Functions

- void **linspace** (double *arra, double low_value, double high_value, int N_points)
- double **array_min** (double *in_array, int N_points)
- double **array_max** (double *in_array, int N_points)
- int **main** ()

3.2.1 Detailed Description

This is a sample code.

Author

Jishnu N. Thekkepattu (j.thekkeppattu@curtin.edu.au)

Version

0.1

Date

2023-02-08