

Visualizing Dynamic Programming On Tree Decompositions

Martin Röbbke
Fakultät Informatik
Technische Universität Dresden
Germany




- ▶ **WHAT is the motivation**
- ▶ **WHO benefits from visualization?**
- ▶ **CHALLENGES and solutions**
- ▶ **WHAT could be used otherwise?**
- ▶ **OUTLOOK and ideas**

Motivation

- ▶ **DP-on-TD-algorithms can solve various combinatorial problems like model counting**
- ▶ **Efficient (if the treewidth is small)**
- ▶ **Competitive with other modern solvers**
- ▶ **But tedious and hard to implement if done efficiently**
- ▶ **Often bugs in the implementation**
- ▶ **DP for Model Counting is extremely space demanding (much more than SAT)**

Ideas

- ▶ Inspect intermediate data during solving process
- ▶ Represent the input, tree decomposition and created solutions
- ▶ Lightweight but customizable output format



Contribution

This thesis created tdvisu as a tool that

- ▶ **integrates into existing implementations**
- ▶ **statically exports data from runs**
- ▶ **compiles simple DOT files and SVG graphics**

For further research it provides


- ▶ **starting point for more complex investigations of**
 - ▷ **bug spotting**
 - ▷ **and fixing by using visualizations**

Background

The algorithms of interest solve problems of:

- ▶ **NP-complete**
- ▶ **#P-complete problems** - instead of **one** solution we want to **count all** solutions



Example of two snapshots of getting a minimal vertex cover via DP:



Tree Decomposition

Gives the DP algorithm a partial ordering for sub-problems.

1. Each vertex must occur in some bag
2. For each edge, there is a bag containing both endpoints
3. Subgraph of bags containing a given vertex must be connected



Width of a TD is: size of largest bag - 1
width = 3

Graphs for Boolean Formulas

► Example set of CNF-clauses:

$\{c_1 = \{v_1, v_3, \neg v_4\}, c_2 = \{\neg v_1, v_6\}, c_3 = \{\neg v_2, \neg v_3, \neg v_4\}, c_4 = \{\neg v_2, v_6\}, c_5 = \{\neg v_3, \neg v_4\}, c_6 = \{\neg v_3, v_5\}, c_7 = \{\neg v_5, \neg v_6\}, c_8 = \{v_5, v_7\}\}$





Figure: The primal (left), incidence (middle) and dual (right) graph

gpusat2 - Solving #SAT on GPU



► Customized tree decompositions

Images: Markus Zisser. *Solving the #SAT problem on the GPU with dynamic programming and OpenCL*. Technische Universität Wien, 2018.

Database templates in Python Generating SQL queries

1. Create graph representation
2. Decompose graph
3. Solve sub-problems
4. Combine rows

```

- #εTab#:          SELECT 1 AS cnt
- #intrTab#:       SELECT 1 AS val UNION ALL 0
- #localProbFilter#: (l1,1 OR ... OR l1,k1) AND ... AND (ln,1 OR ... OR ln,kn)
- #aggrExp#:       SUM(cnt) AS cnt
- #extProj#:       τ1.cnt * ... * τℓ.cnt AS cnt

```

(a) Problem #SAT

```

- #εTab#:          SELECT 0 AS card
- #intrTab#:       SELECT 1 AS val UNION ALL 0
- #localProbFilter#: ([u1] OR [v1]) AND ... AND ([un] OR [vn])
- #aggrExp#:       MIN(card) AS card
- #extProj#:       τ1.card + ... + τℓ.card - (Σi=1ℓ |χ(ti) ∩ {a1}| - 1) *
                  τ1. [a1] - ... - (Σi=1ℓ |χ(ti) ∩ {ak}| - 1) * τ1. [ak]

```


(b) Problem MinVC

- ▶ SAT and #SAT
- ▶ #o-Coloring
- ▶ Vertex cover


...

“Exploiting Database Management Systems and Treewidth for Counting”,
Johannes Fichte et al. doi: 10.1007/978-3-030-39197-3_10.

Running tdvisu



TDVisu producing flexible and further processable formats



Capabilities and Limitations

Integration of solvers via [TDVisu.schema.json](#) ¹

Capabilities:

- ▶ **Extracting basic (extendable) information (TD, solution nodes, order+time of processing...) from gpusat + dpdb**
- ▶ **Constructing and enriching the with solver information**
- ▶ **Adding multiple graphs for e.g. problems on Boolean formulas**
- ▶ **Providing a discrete timeline**
- ▶ **Parameters to control the layout and coloring of the data**

Limitations:

- ▶ **Can not further animate for example the origin of solutions**
- ▶ **Maneuvering in very large graphs is not very ergonomic with static content**
- ▶ **In the optimal case, a comprehensive test suite should be run prior to this.**

raw.githubusercontent.com/VaeterchenFrost/tdvisu/master/TDVisu.schema.json

Visualization in Action

MinVC example size 90 (expected 82)

Debugging with Visualization

1. Inspect visualization
2. Verify findings in solver (in this case dpdb)

public.p3_td_node_59/pgsql@PostgreSQL 12


Query Editor Query History

```
1 SELECT * FROM public.p3_td_node_59
2
```

Data Output Explain Messages Notifications

	v16 boolean	v23 boolean	v40 boolean	v41 boolean	v52 boolean	v55 boolean	v60 boolean	v61 boolean	v66 boolean	v84 boolean	v99 boolean	v100 boolean	size integer
1	[null]	[null]	[null]	[null]	[null]	[null]	[null]	[null]	[null]	[null]	[null]	[null]	8

3. Cross reference with standalone tree-decomposition



4. Fix the root cause

Related Work on the Algorithms


- ▶ Fichte, Johannes & Hecher, Markus & Morak, Michael & Woltran, Stefan. (2018). Exploiting Treewidth for Projected Model Counting and Its Limits. 10.1007/978-3-319-94144-8_11.
- ▶ Hecher, Markus. (2020). Treewidth-aware Reductions of Normal ASP to SAT - Is Normal ASP Harder than SAT after All?. 485-495. 10.24963/kr.2020/49.
- ▶ Hecher M., Thier P., Woltran S. (2020) Taming High Treewidth with Abstraction, Nested Dynamic Programming, and Database Technology. In: Pulina L., Seidl M. (eds) Theory and Applications of Satisfiability Testing - SAT 2020. SAT 2020. Lecture Notes in Computer Science, vol 12178. Springer, Cham. https://doi.org/10.1007/978-3-030-51825-7_25

Related Work on Visualizations

- ▶ Marie-Christin Harre, Jan Jelschen, and Andreas Winter. “ELVIZ: A querybased approach to model visualization”. In: Lecture Notes in Informatics (LNI), Proceedings - Series of the Gesellschaft für Informatik (GI) (Jan. 2014), pp. 105–120.
- ▶ Stephan Diehl. Software Visualization. Visualizing the Structure, Behaviour, and Evolution of Software. English. Springer, 2007. 199 pp. isbn: 978-3540465041.
- ▶ Jason Daida et al. “Visualizing Tree Structures in Genetic Programming”. In: Genetic Programming and Evolvable Machines 6 (Mar. 2005). doi: 10.1007/s10710-005-7621-2.



LaBRI
université
BORDEAUX



Gephi.org¹ Tulip²



³ Vis.js



Sigma.js



vasturiano/3d-force-graph⁴

With the diverse / large node labels and special layout the creation of a lightweight and customizable exchange format took precedence over the integration into special layout software.

<https://gephi.org/> - Tool for data analysts and scientists keen to explore and understand graphs.

<https://tulip.labri.fr/TulipDrupal/> - Better Visualization Through Research.

<https://neo4j.com/developer/tools-graph-visualization/>

<https://github.com/vasturiano/3d-force-graph>

Outlook

Static → Dynamic

Interesting Questions :



- ▶ **Cross reference the creation of rows in parent nodes**
- ▶ **Enriching the visualization with more data for each node**
- ▶ **For more advanced debugging tasks you may also need to revise the approach**
- ▶ **Utilizing graph databases for debugging**

Final slide

Bibliography


See the citations in the thesis.

MinVC for example graph




Visualization

Manually for one run




"Exploiting Database Management Systems and Treewidth for Counting",
Johannes Fichte et al. doi: 10.1007/978-3-030-39197-3_10.

"Solving #SAT on the GPU with Dynamic Programming and OpenCL",
Diploma Markus Zisser 2018 Technische Universität Wien, p.33



Benchmark

Performance of all three programs on #SAT instances:



ELVIZ - Query based approach to software visualization




Figure: Overview of the ELVIZ-approach⁵

Fig 1 in: Marie-Christin Harre, J. Jelschen, A. Winter. "ELVIZ: A querybased approach to model visualization". In: Lecture Notes in Informatics (LNI), Proceedings - Series of the Gesellschaft für Informatik (GI) (Jan. 2014), pp. 105–120.

