

Visualizing Dynamic Programming On Tree Decompositions


Martin Rübke

Fakultät Informatik

Technische Universität Dresden

Germany

- ▶ **REWORK AFTER CHAPTERS**
- ▶ **WHAT was the motivation**
- ▶ **WHAT could be used otherwise?**
- ▶ **WHO benefits from visualization?**
- ▶ **METHODOLOGY challenges and solutions**
- ▶ **WHAT could be developed next?**



"Logic is everywhere ..."

Motivation

- ▶ DP-on-TD-algorithms can solve Model Counting and various combinatorial problems
- ▶ Implementations of those are competing with modern solvers
- ▶ **But:** those are fairly hard to implement efficiently
- ▶ Practical debug output quickly becomes very large (GB)
- ▶ Finding the cause of the problem is a time consuming challenge

Background

The algorithms of interest solve problems of:

- ▶ **combinatorics (NP-problems)**
- ▶ **model-counting (#P-problems)**

Recent promising results for Projected Model Counting by Markus Hecher¹.

¹Hecher M., Thier P., Woltran S. (2020) Taming High Treewidth with Abstraction, Nested Dynamic Programming, and Database Technology. In: Pulina L., Seidl M. (eds) Theory and Applications of Satisfiability Testing - SAT 2020. SAT 2020. Lecture Notes in Computer Science, vol 12178. Springer, Cham. https://doi.org/10.1007/978-3-030-51825-7_25

Tree Decompositions

A tree decomposition is a tree obtained from an arbitrary graph s.t.

1. **Each vertex must occur in some bag**
2. **For each edge, there is a bag containing both endpoints**
3. **Connected: Subgraph “restricted” to any vertex must be connected**

Graphic

Graphs for Boolean Formulas


► Example set of CNF-clauses:

$\{c_1 = \{v_1, v_3, \neg v_4\}, c_2 = \{\neg v_1, v_6\}, c_3 = \{\neg v_2, \neg v_3, \neg v_4\}, c_4 = \{\neg v_2, v_6\}, c_5 = \{\neg v_3, \neg v_4\}, c_6 = \{\neg v_3, v_5\}, c_7 = \{\neg v_5, \neg v_6\}, c_8 = \{v_5, v_7\}\}$




Figure: The primal (left), incidence (middle) and dual (right) graph

gpusat2 - Solving on GPU



- Customized tree decompositions
- Adapted memory-management
- Improved precision handling



¹text

Using databases for intermediate results

1. Create graph representation
2. Decompose graph
3. Solve sub-problems
4. Combine rows

Generator SQL Qs = \mathcal{J} Datenbank Templating in Python

```
- #εTab#:      SELECT 1 AS cnt
- #intrTab#:   SELECT 1 AS val UNION ALL 0
- #localProbFilter#: (l1,1 OR ... OR l1,k1) AND ... AND (ln,1 OR ... OR ln,kn)
- #aggrExp#:   SUM(cnt) AS cnt
- #extProj#:   τ1.cnt * ... * τℓ.cnt AS cnt
```

(a) Problem #SAT

```
- #εTab#:      SELECT 1 AS cnt
- #intrTab#:   SELECT 1 AS val UNION ALL ... UNION ALL 0
- #localProbFilter#: NOT ([u1] = [v1]) AND ... AND NOT ([un] = [vn])
- #aggrExp#:   SUM(cnt) AS cnt
- #extProj#:   τ1.cnt * ... * τℓ.cnt AS cnt
```

► SAT

► #SAT

► Vertex cover

(b) Problem #o-Col

```
- #εTab#:      SELECT 0 AS card
- #intrTab#:   SELECT 1 AS val UNION ALL 0
- #localProbFilter#: ([u1] OR [v1]) AND ... AND ([un] OR [vn])
- #aggrExp#:   MIN(card) AS card
- #extProj#:   τ1.card + ... + τℓ.card - (Σi=1ℓ |χ(ti) ∩ {ai}| - 1) *
               τ1. [a1] - ... - (Σi=1ℓ |χ(ti) ∩ {ak}| - 1) * τ1. [ak]
```

(c) Problem MinVC

github: https://github.com/hmarkus/dp_on_dbs

Challenge1

Generisches Datenformat /Strings Visu
=¿ Anwendungen

Challenge2

=¿ Wie robust ist die Datenverarbeitung in der Visu =¿ Was Gedanken bei der Visu waren

Challenge3



© Gephi.org - a tool for data analysts and scientists keen to explore and understand graphs.²



LaBRI
université
BORDEAUX



Tulip - Better Visualization Through Research.³



⁴ Vis.js



Sigma.js



vasturiano/3d-force-graph⁵

=₂ Related Work Schluss / Wiss Arbeiten -₂ Nicht speziell Angeschaut / Format aus Solvern extrahiert - kann trotzdem sehr generisch sein (dpdb speziell)

²<https://gephi.org/>

³<https://tulip.labri.fr/TulipDrupal/>

⁴<https://neo4j.com/developer/tools-graph-visualization/>

Visualization

Manually for gpusat




Figure: Handcrafted #SAT example-run from Markus Zisser⁶

=_i Dynamic programming Grafiken / Verlaufsschema Kurz erklären -_i Beweise dazu sind aufwändig und recht speziell / _____

⁶"Solving #SAT on the GPU with Dynamic Programming and OpenCL".

Outlook

for relevant problems the static graph visualization will become to complicated.

<https://data-science-blog.com/blog/2015/07/20/3d-visualisierung-von-graphen/>


=¿ Automatische Methoden werden häufig schwerer als gedacht.

Für tiefere Debugging Tasks müsste evtl auch der Ansatz erneuert werden

=¿ Was wären weitere Fragestellungen was man ansehen möchte

Benchmark

Performance of all three programs on #SAT instances:



Visualization

Manually for dpdb




Figure: Handcrafted #SAT example-run from dpdb⁷

⁷"Exploiting Database Management Systems and Treewidth for Counting",
Fichte, Hecher, Thier, Woltran

Bibliography

