

Visualizing Dynamic Programming On Tree Decompositions

Martin Röbke Fakultät Informatik Technische Universität Dresden Germany

- ▶ WHAT is the motivation
- WHO benefits from visualization?
- CHALLENGES and solutions
- WHAT could be used otherwise?
- OUTLOOK and ideas



Motivation

- DP-on-TD-algorithms can solve Model Counting and various combinatorial problems and are provable efficient at it
- Implementations of those are competing with modern solvers
- But: those are fairly tedious to implement efficiently
- Model counting is extremely space intensive (much more than SAT)
- Often bugs in the implementation



Contribution

This thesis created tovisu as a tool that

- integrates into existing implementations
- statically exports data from runs
- compiles simple DOT files and SVG graphics

For further research it provides

- starting point for more complex investigations of
 - bug spotting
 - and fixing by using visualizations



Background

The algorithms of interest solve problems of:

- combinatorics (NP-problems)
- ▶ model-counting (#P-problems) Instead of one solution we want to count all solutions




Background

The algorithms of interest solve problems of:

- combinatorics (NP-problems)
- ▶ model-counting (#P-problems) Instead of one solution we want to count all solutions

Example of two snapshots of getting a minimal vertex cover via DP:






Background

The algorithms of interest solve problems of:

- combinatorics (NP-problems)
- ▶ model-counting (#P-problems) Instead of one solution we want to count all solutions

Example of two snapshots of getting a minimal vertex cover via DP:





Gives the DP algorithm a partial ordering for sub-problems.

1. Each vertex must occur in some bag



Gives the DP algorithm a partial ordering for sub-problems.

- 1. Each vertex must occur in some bag
- 2. For each edge, there is a bag containing both endpoints




Gives the DP algorithm a partial ordering for sub-problems.

- 1. Each vertex must occur in some bag
- 2. For each edge, there is a bag containing both endpoints
- 3. Subgraph "restricted" to any vertex must be connected



Gives the DP algorithm a partial ordering for sub-problems.

- 1. Each vertex must occur in some bag
- 2. For each edge, there is a bag containing both endpoints
- 3. Subgraph "restricted" to any vertex must be connected



Width of a TD is: size of largest bag -1 width = 3



Graphs for Boolean Formulas


► Example set of CNF-clauses:

$$\{c1 = \{v1, v3, \neg v4\}, c2 = \{\neg v1, v6\}, c3 = \{\neg v2, \neg v3, \neg v4\}, c4 = \{\neg v2, v6\}, c5 = \{\neg v3, \neg v4\}, c6 = \{\neg v3, v5\}, c7 = \{\neg v5, \neg v6\}, c8 = \{v5, v7\}\}$$



Figure: The primal (left), incidence (middle) and dual (right) graph

gpusat2 - Solving #SAT on GPU



- Customized tree decompositions
- Adapted memory-management
- Improved precision handling

⁰Images: Markus Zisser. *Solving the #SAT problem on the GPU with dynamic programming and OpenCL*. Technische Universität Wien, 2018.



dpdb

Database templates in Python Generating SQL queries

- Create graph representation
- 2. Decompose graph
- 3. Solve sub-problems
- 4. Combine rows

(a) Problem #SAT

```
- #-Tab#: SELECT 0 AS card
- ##ortab#: SELECT 1 AS val WINDA ALL 0
- ##oraPob#iter#: ([n] 0.8 [n]) AND ... AND ([n] 0.8 [n])
- ##oraPob#iter#: ([n] 0.8 [n]) AND ... AND ([n] 0.8 [n])
- ##oraPob#: 71, card + ... + 72, card - Cf_{in}[\(\chi(n)\) ([n]) 1 0 7], [n]
- #. - Cf_{in}[\(\chi(n)\) ([n]) 1 0 7], [n]
```

(b) Problem MinVC

- SAT and #SAT
- #o-Coloring
- Vertex cover

. . .

⁰ "Exploiting Database Management Systems and Treewidth for Counting", Johannes Fichte et al. doi: 10.1007/978-3-030-39197-3 10.







TDVisu producing flexible and further processable formats






TDVisu producing flexible and further processable formats





TDVisu producing flexible and further processable formats





Capabilities and Limitations

Integration of solvers via TDVisu.schema.json 1

Capabilities:

- Extracting basic (extendable) information (TD, solution nodes, order+time of processing...) from gpusat + dpdb
- Constructing and enriching the tree decomposition with solver information
- Adding the incidence graph for problems on Boolean formulas, from which primal and dual graphs can be derived
- Providing a discrete timeline over the solving process
- Parameters to control the quantity, coloring and, to a limited extent, the layout
 of the data

Limitations:

- Can not further animate for example the origin of solutions
- Maneuvering in very large graphs is not very ergonomic with static content

¹raw.githubusercontent.com/VaeterchenFrost/tdvisu/master/TDVisu.schema.json



MinVC example size 90 (expected 82)



1. Inspect visualization



- 1. Inspect visualization
- 2. Verify findings in solver (in this case dpdb)

- 1. Inspect visualization
- 2. Verify findings in solver (in this case dpdb)



- 1. Inspect visualization
- 2. Verify findings in solver (in this case dpdb)



3. Cross reference with standalone tree-decomposition

- 1. Inspect visualization
- 2. Verify findings in solver (in this case dpdb)



3. Cross reference with standalone tree-decomposition



- 1. Inspect visualization
- 2. Verify findings in solver (in this case dpdb)



3. Cross reference with standalone tree-decomposition



4. Fix the root cause



Related Work on the Algorithms

- Fichte, Johannes & Hecher, Markus & Morak, Michael & Woltran, Stefan. (2018). Exploiting Treewidth for Projected Model Counting and Its Limits. 10.1007/978-3-319-94144-8 11.
- ▶ Hecher, Markus. (2020). Treewidth-aware Reductions of Normal ASP to SAT Is Normal ASP Harder than SAT after All?. 485-495. 10.24963/kr.2020/49.
- Hecher M., Thier P., Woltran S. (2020)
 Taming High Treewidth with Abstraction, Nested Dynamic Programming, and Database Technology. In: Pulina L., Seidl M. (eds) Theory and Applications of Satisfiability Testing SAT 2020. SAT 2020. Lecture Notes in Computer Science, vol 12178. Springer, Cham. https://doi.org/10.1007/978-3-030-51825-7_25



Related Work on Visualizations

- Marie-Christin Harre, Jan Jelschen, and Andreas Winter. "ELVIZ: A querybased approach to model visualization". In: Lecture Notes in Informatics (LNI), Proceedings Series of the Gesellschaft fur Informatik (GI) (Jan. 2014), pp. 105–120.
- Stephan Diehl. Software Visualization. Visualizing the Structure, Behaviour, and Evolution of Software. English. Springer, 2007. 199 pp. isbn: 978-3540465041.
- Jason Daida et al. "Visualizing Tree Structures in Genetic Programming". In: Genetic Programming and Evolvable Machines 6 (Mar. 2005). doi: 10. 1007/s10710-005-7621-2.









Gephi.org² Tulip ³



4 Vis.js



Sigma.js



vasturiano/3d-force-graph 5

With the diverse / large node labels and special layout the creation of a lightweight and customizable exchange format took precedence over the integration into special layout software.

²https://gephi.org/ - Tool for data analysts and scientists keen to explore and understand graphs.

³tulip.labri.fr/TulipDrupal/ - Better Visualization Through Research.

⁴https://neo4j.com/developer/tools-graph-visualization/

⁵https://github.com/vasturiano/3d-force-graph



Outlook

Static → Dynamic

Interesting Questions:

- Utilizing graph databases for visualization and queries for debugging
- Enrich the visualization with debugging info for each node
- Cross reference the creation of rows in parent nodes
- ▶ For more advanced debugging tasks you may also need to revise the approach




Final slide



Bibliography

See the citations in the thesis.


MinVC for example graph






Visualization

Manually for one run






⁵"Exploiting Database Management Systems and Treewidth for Counting", Johannes Fichte et al. doi: 10.1007/978-3-030-39197-3.10.


⁵"Solving #SAT on the GPU with Dynamic Programming and OpenCL", Diploma Markus Zisser 2018 Technische Universität Wien, p.33





Benchmark

Performance of all three programs on #SAT instances:





ELVIZ - Query based approach to software visualization




Figure: Overview of the ELVIZ-approach⁶

⁶Fig 1 in: Marie-Christin Harre, J. Jelschen, A. Winter. "ELVIZ: A querybased approach to model visualization". In: Lecture Notes in Informatics (LNI), Proceedings - Series of the Gesellschaft fur Informatik (GI) (Jan. 2014), pp. 105–120.