


Spring Security Custom Tables



Default Spring Security Database Schema

Default Spring Security Database Schema



Custom Tables

Custom Tables


- What if we have our own custom tables?

Custom Tables

- What if we have our own custom tables?
- Our own custom column names?

Custom Tables

- What if we have our own custom tables?
- Our own custom column names?



For Security Schema Customization

- Tell Spring how to query your custom tables
- Provide query to find user by user name
- Provide query to find authorities / roles by user name

Development Process

Step-By-Step

Development Process

Step-By-Step

1. Create our custom tables with SQL

Development Process

Step-By-Step

1. Create our custom tables with SQL
2. Update JDBC properties file to point to new database schema

Development Process

Step-By-Step

1. Create our custom tables with SQL
2. Update JDBC properties file to point to new database schema
3. Update Spring Security Configuration

Development Process

Step-By-Step


1. Create our custom tables with SQL
2. Update JDBC properties file to point to new database schema
3. Update Spring Security Configuration
 - Provide query to find user by user name

Development Process

Step-By-Step

1. Create our custom tables with SQL
2. Update JDBC properties file to point to new database schema
3. Update Spring Security Configuration
 - Provide query to find user by user name
 - Provide query to find authorities / roles by user name

Step 1: Create our custom tables with SQL



Step 2: Update JDBC properties file to point to new database schema


File: src/main/resources/persistence-mysql.properties

```
#  
# JDBC connection properties  
#  
jdbc.driver=com.mysql.jdbc.Driver  
jdbc.url=jdbc:mysql://localhost:3306/spring_security_demo_bcrypt_custom?useSSL=false  
jdbc.user=springstudent  
jdbc.password=springstudent  
  
#  
# Connection pool properties  
#  
connection.pool.initialPoolSize=5  
connection.pool.minPoolSize=5  
connection.pool.maxPoolSize=20  
connection.pool.maxIdleTime=3000
```


Step 2: Update JDBC properties file to point to new database schema

File: src/main/resources/persistence-mysql.properties

```
#  
# JDBC connection properties  
#  
jdbc.driver=com.mysql.jdbc.Driver  
jdbc.url=jdbc:mysql://localhost:3306/spring_security_demo_bcrypt_custom?useSSL=false  
jdbc.user=springstudent  
jdbc.password=springstudent  
  
#  
# Connection pool properties  
#  
connection.pool.initialPoolSize=5  
connection.pool.minPoolSize=5  
connection.pool.maxPoolSize=20  
connection.pool.maxIdleTime=3000
```



Step 3: Update Spring Security Configuration

```
@Configuration
@EnableWebSecurity
public class DemoSecurityConfig extends WebSecurityConfigurerAdapter {

    @Autowired
    private DataSource securityDataSource;

    @Override
    protected void configure(AuthenticationManagerBuilder auth) throws Exception {

        auth.jdbcAuthentication().dataSource(securityDataSource)

            .usersByUsernameQuery("select user_id, pw, active from members where user_id=?")

            .authoritiesByUsernameQuery("select user_id, role from roles where user_id=?");

    }

    ...

}
```


Step 3: Update Spring Security Configuration

```
@Configuration
@EnableWebSecurity
public class DemoSecurityConfig extends WebSecurityConfigurerAdapter {

    @Autowired
    private DataSource securityDataSource;

    @Override
    protected void configure(AuthenticationManagerBuilder auth) throws Exception {

        auth.jdbcAuthentication().dataSource(securityDataSource)


            .usersByUsernameQuery("select user_id, pw, active from members where user_id=?")

            .authoritiesByUsernameQuery("select user_id, role from roles where user_id=?");

    }

    ...

}
```



Step 3: Update Spring Security Configuration

```
@Configuration
@EnableWebSecurity
public class DemoSecurityConfig extends WebSecurityConfigurerAdapter {

    @Autowired
    private DataSource securityDataSource;

    @Override
    protected void configure(AuthenticationManagerBuilder auth) throws Exception {

        auth.jdbcAuthentication().dataSource(securityDataSource)


            .usersByUsernameQuery("select user_id, pw, active from members where user_id=?")

            .authoritiesByUsernameQuery("select user_id, role from roles where user_id=?");

    }

    ...

}
```



How to find users

Step 3: Update Spring Security Configuration

```
@Configuration
@EnableWebSecurity
public class DemoSecurityConfig extends WebSecurityConfigurerAdapter {

    @Autowired
    private DataSource securityDataSource;

    @Override
    protected void configure(AuthenticationManagerBuilder auth) throws Exception {

        auth.jdbcAuthentication().dataSource(securityDataSource)


            .usersByUsernameQuery("select user_id, pw, active from members where user_id=?")

            .authoritiesByUsernameQuery("select user_id, role from roles where user_id=?");

    }

    ...

}
```



How to find users

Step 3: Update Spring Security Configuration

```
@Configuration
@EnableWebSecurity
public class DemoSecurityConfig extends WebSecurityConfigurerAdapter {

    @Autowired
    private DataSource securityDataSource;

    @Override
    protected void configure(AuthenticationManagerBuilder auth) throws Exception {

        auth.jdbcAuthentication().dataSource(securityDataSource)


            .usersByUsernameQuery("select user_id, pw, active from members where user_id=?")

            .authoritiesByUsernameQuery("select user_id, role from roles where user_id=?");

    }

    ...

}
```



How to find users

Question mark “?”
Parameter value will be the
user name from login form

Step 3: Update Spring Security Configuration

```
@Configuration
@EnableWebSecurity
public class DemoSecurityConfig extends WebSecurityConfigurerAdapter {

    @Autowired
    private DataSource securityDataSource;

    @Override
    protected void configure(AuthenticationManagerBuilder auth) throws Exception {

        auth.jdbcAuthentication().dataSource(securityDataSource)


            .usersByUsernameQuery("select user_id, pw, active from members where user_id=?")

            .authoritiesByUsernameQuery("select user_id, role from roles where user_id=?");

    }

    ...

}
```



How to find roles

Step 3: Update Spring Security Configuration

```
@Configuration
@EnableWebSecurity
public class DemoSecurityConfig extends WebSecurityConfigurerAdapter {

    @Autowired
    private DataSource securityDataSource;

    @Override
    protected void configure(AuthenticationManagerBuilder auth) throws Exception {

        auth.jdbcAuthentication().dataSource(securityDataSource)


            .usersByUsernameQuery("select user_id, pw, active from members where user_id=?")

            .authoritiesByUsernameQuery("select user_id, role from roles where user_id=?");

    }

    ...

}
```



How to find roles

Step 3: Update Spring Security Configuration

```
@Configuration
@EnableWebSecurity
public class DemoSecurityConfig extends WebSecurityConfigurerAdapter {

    @Autowired
    private DataSource securityDataSource;

    @Override
    protected void configure(AuthenticationManagerBuilder auth) throws Exception {

        auth.jdbcAuthentication().dataSource(securityDataSource)


            .usersByUsernameQuery("select user_id, pw, active from members where user_id=?")

            .authoritiesByUsernameQuery("select user_id, role from roles where user_id=?");

    }

    ...

}
```



How to find roles

Question mark "?"
Parameter value will be the
user name from login form