

PART-B

Program 14

Write a program for error detecting code using CRC-CCITT (16-bits).

Code :

```
def xor(a, b):
    # XOR operation between two binary strings
    result = []
    for i in range(1, len(b)):
        result.append('0' if a[i] == b[i] else '1')
    return ''.join(result)

def mod2div(dividend, divisor): #
    Performs Modulo-2 division
    pick = len(divisor)
    tmp = dividend[:pick]

    while pick < len(dividend):
        if tmp[0] == '1':
            tmp = xor(divisor, tmp) + dividend[pick]
        else:
            tmp = xor('0' * pick, tmp) + dividend[pick]
        pick += 1

    # For the last set of bits
    if tmp[0] == '1':
        tmp = xor(divisor, tmp)
    else:
        tmp = xor('0' * pick, tmp)

    return tmp

def encode_data(data, key): #
    Encode data with CRC
    l_key = len(key)
    padded_data = data + '0' * (l_key - 1)
    remainder = mod2div(padded_data, key)
    codeword = data + remainder
    return codeword, remainder

def check_data(received_data, key): #
    Check received data for errors
    remainder = mod2div(received_data, key)
    return '0' * (len(key) - 1) == remainder

# Main program
```

```

if __name__ == "__main__":
    print("Error Detection using CRC-CCITT (8-bits)")

# Transmitter
data = input("Enter data to be transmitted: ").strip()
key = input("Enter the Generating polynomial: ").strip()

print("\n----- ")
padded_data = data + '0' * (len(key) - 1)
print("Data padded with n-1 zeros:", padded_data)

encoded_data, crc = encode_data(data, key)
print("CRC or Check value is:", crc)
print("Final data to be sent:", encoded_data)
print("----- ")

# Receiver
received_data = input("\nEnter the received data: ").strip()
print("\n----- ")
print("Data received:", received_data)

if check_data(received_data, key):
    print("No error detected")
else:
    print("Error detected")
print("----- ")

```

Output

```
Enter data to be transmitted: 1001100
Enter the Generating polynomial: 100001011

-----
Data padded with n-1 zeros: 100110000000000
CRC or Check value is: 0100010
Final data to be sent: 10011000100010
-----

Enter the received data: 10011000100011

-----
Data received: 10011000100011
Error detected
```

```
Error Detection using CRC-CCITT (8-bits)
Enter data to be transmitted: 1001100
cell output actions Generating polynomial: 100001011

-----
Data padded with n-1 zeros: 100110000000000
CRC or Check value is: 10100010
Final data to be sent: 100110010100010
-----

Enter the received data: 100110010100010

-----
Data received: 100110010100010
No error detected
-----
```

2. Aim: Implementation of CRC

Code:

```
def xor(a, b):
```

```
    result = []
```

```
    for i in range(1, len(b)):
```

```
        if a[i] == b[i]:
```

```
            result.append('0')
```

```
        else:
```

```
            result.append('1')
```

```
    return ''.join(result)
```

```
def modDiv(dividend, divisor):
```

```
    pick = len(divisor)
```

```
    temp = dividend[0: pick]
```

```
    while pick < len(dividend):
```

```
        if temp[0] == '1':
```

```
            temp = xor(divisor, temp) + dividend[pick]
```

```
        else:
```

```
            temp = xor('0' * pick, temp) + dividend[pick]
```

```
        pick += 1
```

```
    if temp[0] == '1':
```

```
        temp = xor(divisor, temp)
```

```
    else:
```

```
        temp = xor('0' * pick, temp)
```

```
    checksum = temp
```

```
    return checksum
```

```
def encodeData(data, key):
```

```
    l = len(key)
```

```
    append_data = data + '0' * (l - key[-1])
```

```
    remainder = modDiv(append_data, key)
```

```
    codeword = data + remainder
```

```
print("Remainder", remainder)
print("Encoded Data (Data + Remainder) :", encoded_data)
```

data = "100100"

key = "1101"

encode_data(data, key)

Output :

Sender side -----

Remainder : 001

Encode Data (Data + Remainder) : 10010001

Receiver side

Correct message received.

for
02/04/25

Program 15

Write a program for congestion control using Leaky bucket algorithm.

Code :

```
# Getting user inputs
storage = int(input("Enter initial packets in the bucket: "))
no_of_queries = int(input("Enter total no. of times bucket content is checked: ")) bucket_size
= int(input("Enter total no. of packets that can be accommodated in the bucket: "))
input_pkt_size = int(input("Enter no. of packets that enters the bucket at a time: "))
output_pkt_size = int(input("Enter no. of packets that exits the bucket at a time: "))

for i in range(no_of_queries): # space left
    size_left = bucket_size - storage
    if input_pkt_size <= size_left: #
        update storage
        storage += input_pkt_size
    else:
        print("Packet loss =", input_pkt_size)

print(f"Buffer size = {storage} out of bucket size = {bucket_size}")

# as packets are sent out into the network, the size of the storage decreases storage
-= output_pkt_size
```

Output

```
Enter initial packets in the bucket: 0
Enter total no. of times bucket content is checked: 4
Enter total no. of packets that can be accommodated in the bucket: 10
Enter no. of packets that enters the bucket at a time: 4
Enter no. of packets that exits the bucket at a time: 1
Buffer size = 4 out of bucket size = 10
Buffer size = 7 out of bucket size = 10
Buffer size = 10 out of bucket size = 10
Packet loss = 4
Buffer size = 9 out of bucket size = 10
```

Cycle 2

1. Aim: Implementation of Leaky Bucket Algorithm:

Code:

```
#include <stdio.h>
int main() {
    int incoming, outgoing, bucket_size, n, store = 0;
    printf("Enter bucket size, outgoing rate and no. of input");
    scanf("%d %d %d", &bucket_size, &outgoing, &n);
    while(n >= 0) {
        printf("Enter the incoming packet size:");
        scanf("%d", &incoming);
        printf("Incoming packet size %d\n", incoming);
        if (incoming <= (bucket_size - store)) {
            store += incoming;
            printf("Bucket buffer size %d out of %d\n",
                store, bucket_size);
        } else {
            printf("Dropped %d no. of packets\n", incoming -
                (bucket_size - store));
            printf("Bucket buffer size %d out of %d\n", store,
                bucket_size);
            store = bucket_size;
        }
        store = store - outgoing;
        printf("After outgoing %d bytes left out of %d in
            buffer\n", store, bucket_size);
        n--;
    }
}
```


Output:

Enter bucket size, outgoing rate & no of inputs : 100 20 3

Enter the incoming packet size : 30

Incoming packet size 30

Bucket buffer size 30 out of 100

After outgoing 10 bytes left out of 100 in buffer

Enter incoming packet size : 50

Incoming packet size 50

Bucket buffer size 60 out of 100

After outgoing 40 bytes left out of 100 in buffer

Enter the incoming packet size : 80

Incoming packet size 80

Dropped 20 no of packets

Bucket buffer size 40 out of 100

After outgoing 80 bytes left out of 100 in buffer.

~~Ans~~
02/01/25

Program 16

Using TCP/IP sockets, write a client-server program to make the client send the file name and the server to send back the contents of the requested file if present.

Code:

Client.py

```
from socket import *
serverName = "127.0.0.1" # Server address (localhost)
serverPort = 12000 # Port number where the server listens

# Create TCP socket
clientSocket = socket(AF_INET, SOCK_STREAM)
clientSocket.connect((serverName, serverPort)) # Connect to server

# Ask user for file name to request
sentence = input("Enter file name: ")

# Send file name to server
clientSocket.send(sentence.encode())

# Receive file contents from server
filecontents = clientSocket.recv(1024).decode()
print('From Server:', filecontents)

# Close the connection
clientSocket.close()
```

Server.py

```
from socket import *
serverName = "127.0.0.1" # Server address (localhost)
serverPort = 12000 # Port number to listen on

# Create TCP socket
serverSocket = socket(AF_INET, SOCK_STREAM)
serverSocket.bind((serverName, serverPort)) # Bind socket to the address and port
serverSocket.listen(1) # Listen for 1 connection
print("The server is ready to receive")

while True:
    # Accept a connection
    connectionSocket, addr = serverSocket.accept()

    # Receive the file name from the client
    sentence = connectionSocket.recv(1024).decode()

    # Try opening the file try:
```


```

file = open(sentence, "r") # Open file in read mode
    fileContents = file.read(1024) # Read file content (up to 1024 bytes)
    file.close()
except FileNotFoundError:
    # Send error message if file not found
    connectionSocket.send("File not found".encode())

# Close the connection
connectionSocket.close()

```

Output



```

PROBLEMS  TERMINAL  OUTPUT  DEBUG CONSOLE  PORTS  SEARCH ERROR  COMMENTS
(base) PS D:\BMSCE\Fifth SEM CSE\CN\Lab - 15(24.12.24)> py Client.py
Enter file name: TCP.txt
From Server: This is a test file.

Using TCP/IP sockets, write a client-server program to make client sending
the
file name and the server to send back the contents of the requested file if
present.

(base) PS D:\BMSCE\Fifth SEM CSE\CN\Lab - 15(24.12.24)> py Client.py
Enter file name: testfile.txt
From Server: File not found
(base) PS D:\BMSCE\Fifth SEM CSE\CN\Lab - 15(24.12.24)> 

```

```

(base) PS D:\BMSCE\Fifth SEM CSE\CN\Lab - 15(24.12.24)> py Server.py
The server is ready to receive

```

3- Aim: Implementation of TCP/IP

Code:

Client.py

```
from socket import *
Server Name = "127.0.0.1"
Server Port = 12000
Client Socket = socket(AF_INET, SOCK_STREAM)
Client Socket = connect((Server Name, Server Port))
sentence = input("Enter the name")
Client Socket.send(sentence.encode())
file contents = Client Socket.recv(6024).decode()
print("from server", file contents)
Client Socket.close()
```

Server.py

```
from socket import *
Server Name = "127.0.0.1"
Server Port = 12000
Server Socket = socket(AF_INET, SOCK_STREAM)
Server Socket.bind((Server Name, Server Port))
Server Socket.listen(1)
print("The server is ready to receive")
while 1:
    connection Socket, add = Server Socket.accept()
    sentence = connection Socket.recv(1024).decode()
    file = open(sentence, "r")
    l = file.read(1024)
    connection Socket.send(l.encode())
```

file.close()
connectionSocket.close()

Output:

Sender side
Sender is ready to receive
Client side
Enter file Name: hello.txt
from server: Hello World.

~~02/01/25~~

Program 17

Using UDP sockets, write a client-server program to make the client send the file name and the server to send back the contents of the requested file if present.

Code:

ClientUDP.py

```
from socket import *

serverName = "127.0.0.1"
serverPort = 12000
clientSocket = socket(AF_INET, SOCK_DGRAM)

sentence = input("Enter file name: ")
clientSocket.sendto(sentence.encode(), (serverName, serverPort))

filecontents, serverAddress = clientSocket.recvfrom(2048)
print('From Server:', filecontents.decode())

clientSocket.close()
```

ServerUDP.py

```
from socket import *

serverPort = 12000
serverSocket = socket(AF_INET, SOCK_DGRAM)
serverSocket.bind(("127.0.0.1", serverPort))

print("The server is ready to receive")

while True:
    sentence, clientAddress = serverSocket.recvfrom(2048)
```

try:

with open(sentence.decode(), "r") as file:

l = file.read(2048)


serverSocket.sendto(l.encode(), clientAddress)

print(f'Sent back to client: {l}')

except FileNotFoundError:

serverSocket.sendto("File not found.".encode(), clientAddress)

Output



```
PROBLEMS  TERMINAL  OUTPUT  DEBUG CONSOLE  PORTS  SEARCH ERROR  COMMENTS  pwsh + v [ ] [ ] ...

(base) PS D:\BMSCE\Fifth SEM CSE\CN\Lab - 15(24.12.24)> py ClientUDP.py
Enter file name: UDP.txt
From Server: This is a test file.

Using UDP sockets, write a client-server program to make client sending
the file
name and the server to send back the contents of the requested file if p
resent.
(base) PS D:\BMSCE\Fifth SEM CSE\CN\Lab - 15(24.12.24)> py ClientUDP.py
Enter file name: testfile.txt
From Server: File not found
(base) PS D:\BMSCE\Fifth SEM CSE\CN\Lab - 15(24.12.24)>

(base) PS D:\BMSCE\Fifth SEM CSE\CN\Lab - 15(24.12.24)> py ServerUDP.py
The server is ready to receive
[ ]
```

4. Aim: Implement UDP

Code:

Client UDP.py

```
from socket import *
serverName = "127.0.0.1"
serverPort = 12000
clientSocket = socket(AF_INET, SOCK_DGRAM)
sentence = input("Enter file name")
clientSocket.sendto(bytes(sentence, "utf-8"), (serverName, serverPort))
fileContents, serverAddress = clientSocket.recvfrom(2048)
print("from server:", fileContents)
clientSocket.close()
```

Server UDP.py

Server

```
from socket import *
serverPort = 12000
serverSocket = socket(AF_INET, SOCK_DGRAM)
serverSocket.bind(("127.0.0.1", serverPort))
print("The server is ready to receive")
while True:
    sentence, clientAddress = serverSocket.recvfrom(2048)
    file = open(sentence, "r")
    l = file.read(2048)
    serverSocket.sendto(bytes(l, "utf-8"), clientAddress)
    print("sent back to client", l)
file.close()
```


Output:

Server side . . .

The server is ready to receive

sent back to client : hello world

Client side ---

Enter file name : hello.txt

from server : hello world

Athi
22/10/20