

Lab (Option B: JavaScript): Using GitHub Actions - Part 2



Estimated time needed: 30 minutes

In this lab, you will build the Continuous Integration pipeline by setting up the steps under job in your workflow. Please ensure you complete setting up the workflow, before starting this lab.

You will add the following steps to the job in this lab:

- Check out the code
- Install dependencies
- Lint code with ESLint
- Run unit tests with Jest

Learning objectives

After completing this lab, you will be able to:

- Explain components of a job in a GitHub Actions workflow
- Use predefined GitHub actions
- Run multiline inline code in a step
- Explore action logs in the GitHub UI

Prerequisites

- It is highly recommended that you complete the lab titled "Using GitHub Actions - Setting up workflow." If you have not finished the lab, please finish that before starting this lab.
- A basic understanding of YAML.
- A GitHub account.
- An intermediate-level knowledge of CLIs.

Pre-work

1. Generate a personal access token on [GitHub Settings](#), if you already don't have one.
2. Open a terminal window by using the menu in the editor: Terminal > New Terminal.

First, let's run the following commands to install GitHub CLI.

```
sudo apt update
sudo apt install gh
```

3. Run the following command to authenticate with GitHub in the terminal with the personal access token.

```
gh auth login
```

You will be taken through a guided experience, as shown here:

```
What account do you want to log into? GitHub.com
What is your preferred protocol for Git operations? HTTPS
Authenticate Git with your GitHub credentials. Yes
How would you like to authenticate GitHub CLI? Paste an authentication token.
Paste your authentication token: *****
You will be logged into GitHub as your account user.
```

4. Clone your copy of the forked [GitHub repository](#). This creates the `ttwt-jhxyb-ci-cd-pipeline_js` subdirectory under `/home/project` directory.

If you already have cloned this repository under /home/project, you can skip this step.

5. If you don't have .github/workflows/workflow.yml in ttwst-jhxyb-ci-cd-pipeline_js directory, create workflow.yml file in the /home/project/ttwst-jhxyb-ci-cd-pipeline_js/.github/workflows directory with the following code:

```
name: CI workflow
on:
  push:
    branches: [ "main" ]
  pull_request:
    branches: [ "main" ]
jobs:
  build:
    runs-on: ubuntu-latest
    container: node:20-alpine
```

Step 1: Add the checkout step

You will now add your first step to the job. The first task is to check out the code from the repository. You will use the predefined actions/checkout@v3 action to do this. You can learn more about this action on the [GitHub page](#).

Your task

1. Add the steps: section at the end of the build job in the workflow file.
 - Click here for a hint.
2. Add the checkout step as the first step. Give it the name: Check out and call the action actions/checkout@v3 by using the uses: keyword.
 - Click here for a hint.

Double-check that your work matches the solution below.

Solution

- Click here for the answer.
-

Step 2: Install dependencies

Now that you have checked out the code, the next step is to install the dependencies. This application uses npm, the Node.js package manager, to install all the dependencies from the package.json file. The node:20-alpine container you are using already has the npm package manager installed.

The commands that you will use in this step are:

```
npm ci
```

This command installs all the dependencies listed in the package.json and package-lock.json files. The ci command, which stands for "clean install," is specifically designed for CI/CD pipelines. Unlike npm install, it does not modify the package-lock.json file and installs exactly what's specified there

Your task

1. Add a new named step after the checkout step. Name this step Install dependencies.
 - Click here for a hint.
2. Next, you want to run the command to install the dependencies. You can run this using the run: keyword
 - Click here for a hint.

Double-check that your work matches the solution below.

Solution

- Click here for the answer.

Step 3: Lint with ESLint

It is always a good idea to add quality checks to your CI pipeline. This is especially true if you are working on an open source project with many different contributors. This makes sure that everyone who contributes is following the same style guidelines.

The next step is to use ESLint to lint the source code. Linting is checking your code for syntactical and stylistic issues. Some examples are spacing, using spaces or tabs for indentation, locating uninitialized or undefined variables, and missing brackets. The `eslint` library should be installed as a development dependency in the `package.json` file.

The ESLint command will analyze your JavaScript code according to the rules defined in your `.eslintrc.*` configuration file.

```
npm run lint
```

This command runs the `lint` script defined in your `package.json` file, which typically executes `eslint` on your source code.

Your task

1. Add a new named step after the `Install dependencies` step. Call this step `Lint with ESLint`.

► [Click here for a hint.](#)

2. Next, you want to run the ESLint command to lint your code.

```
npm run lint
```

You can run inline commands using the `run` keyword with the pipe `|` operator.

► [Click here for a hint.](#)

Double-check that your work matches the solution below.

Solution

► [Click here for the answer.](#)

Step 4: Test code coverage with Jest

You will use Jest in this step to unit test the source code. Jest is a delightful JavaScript testing framework with a focus on simplicity. It works with projects using Babel, TypeScript, Node, React, Angular, Vue, and more.

Jest is configured via the `jest.config.js` file or in `package.json` to automatically collect code coverage information. At the end of the test run, you should see a percentage of coverage report.

Your task

1. Add a new named step after the `Lint with ESLint` step. Call this step `Run unit tests with Jest`.

► [Click here for a hint.](#)

2. Next, you want to run the Jest command to test your code and report on code coverage.

```
npm test -- --coverage
```

This command runs Jest with the coverage flag enabled, which generates a code coverage report.

► [Click here for a hint.](#)

Double-check that your work matches the solution below.

Solution

► [Click here for the answer.](#)

Step 5: Push code to GitHub

To test the workflow and the CI pipeline, you need to commit the changes and push your branch back to the GitHub repository. As described earlier, each new push to the main branch should trigger the workflow.

Your task

1. Configure the Git account with your email and name using the `git config --global user.email` and `git config --global user.name` commands.

► [Click here for a hint.](#)

2. The next step is to stage all the changes you made in the previous exercises and push them to your forked repo on GitHub.

► [Click here for a hint.](#)

Your output should look similar to the image below:

Solution

```
theia@theia-harshsingh15:/home/project/ttwst-jhxyb-ci-cd-pipeline_js$
theia@theia-harshsingh15:/home/project/ttwst-jhxyb-ci-cd-pipeline_js$
E"
[main a911dec] COMMIT MESSAGE
1 file changed, 15 insertions(+), 2 deletions(-)
theia@theia-harshsingh15:/home/project/ttwst-jhxyb-ci-cd-pipeline_js$
Username for 'https://github.com': harsh-skillup
Password for 'https://harsh-skillup@github.com':
Enumerating objects: 9, done.
Counting objects: 100% (9/9), done.
Delta compression using up to 8 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (5/5), 600 bytes | 600.00 KiB/s, done.
Total 5 (delta 1), reused 0 (delta 0), pack-reused 0
remote: Resolving deltas: 100% (1/1), completed with 1 local object.
To https://github.com/harsh-skillup/ttwst-jhxyb-ci-cd-pipeline_js.git
7e13dae..a911dec main -> main
theia@theia-harshsingh15:/home/project/ttwst-jhxyb-ci-cd-pipeline_js$
```

Step 6: Run the workflow

You can run the workflow now. Open the **Actions** tab in the forked repository in your GitHub account. Click the **CI workflow** action. Pushing changes in the previous step should have triggered a build action and it should be visible in the Actions tab.

Actions

New workflow

All workflows

CI workflow

Management

Caches

Attestations

Runners

Usage metrics

Performance metrics

All workflows

Showing runs from all workflows

2 workflow runs

✓

COMMIT MESSAGE

CI workflow #6: Commit [72c889d](#) pushed by harsh-skillup

main

✗

COMMIT MESSAGE

CI workflow #1: Commit [5b4291d](#) pushed by harsh-skillup

main

Click the most recent workflow run to open the details page. You should see your workflow completed successfully:

The screenshot shows the GitHub Actions interface for a workflow named "ttwst-jhxyb-ci-cd-pipeline_js" by user "harsh-skillup". The top navigation bar includes links for Code, Pull requests, Actions (highlighted), Projects, Wiki, and a shield icon. Below the navigation bar, the workflow is identified as "CI workflow". The main heading is "COMMIT MESSAGE #6", preceded by a green checkmark icon. On the left sidebar, there are sections for "Summary" (with a house icon), "Jobs" (containing a green checkmark and the job name "build"), "Run details", "Usage" (with a clock icon), and "Workflow file" (with a code icon). On the right side, there are two panels. The top panel shows the trigger "Triggered via push 3 minutes" and the user "harsh-skillup pushed". The bottom panel is titled "workflow.yml" with the trigger "on: push" and contains a job summary for "build" with a green checkmark icon.

You can now click the `build` job to see the logs for each step:

harsh-skillup / ttwst-jhxyb-ci-cd-pipeline_js

<> Code

Pull requests

Actions

Projects

Wiki

< CI workflow

COMMIT MESSAGE #6

Summary

Jobs

build

Run details

Usage

Workflow file

build

succeeded 4 minutes ago in

> Set up job

> Initialize contain

> Checkout

> Install depende

> Lint with ESLint

> Run unit tests w

> Post Checkout

> Stop containers

> Complete job

about:blank

7/12

Spend some time here to expand each section:

Summary

Jobs

 build

Run details

Usage

 Workflow file

build

succeeded 6 minutes ago in

Run unit tests w

64 ✓ should

```
65 GET /count
```

66 ✓ should

67 ✓ should

68 PUT /count

69 ✓ should

70 ✓ should

71 DELETE /co

72 ✓ should

73

74 _____

75 File

76 -----

77 All files

78 service

79 app.js

```
80 routes.js
```

81 service/commo

82 errorHandler

83 logger.js

```
84 status.js
```

85

86 Test Suites: 3

87 Tests: 2

88 Snapshots: 0

89 Time: 1

```
90 Ran all test s
```

> Post Checkout

> ☒ Stop containers

> Complete job

If the workflow completes, you will see the Complete job step at the end of the build job logs.

harsh-skillup / ttwst-jhxyb-ci-cd-pipeline_js

<> Code

Pull requests

Actions

Projects

Wiki

← CI workflow

✓

COMMIT MESSAGE #6

🏠 Summary

Jobs

✓

build

Run details

Usage

Workflow file

build

succeeded 6 minutes ago in

>

✓

 Set up job

>

✓

 Initialize contain

>

✓

 Checkout

>

✓

 Install depende

>

✓

 Lint with ESLint

>

✓

 Run unit tests w

>

✓

 Post Checkout

>

✓

 Stop containers

✓

 Complete job

1 Cleaning up or

about:blank

11/12

Conclusion

Congratulations! You are now able to use GitHub Actions to create workflows for the CI pipeline.

In this lab, you added the steps to your Continuous Integration pipeline for your application. As a result, your application is automatically built and tested when you commit your code to the GitHub repository.

Next steps

Try to set up a GitHub action for your own project that checks out the code, runs unit tests, and performs linting on every push request to the default branch.

Author(s)

Tapas Mandal

Other Contributor(s)

Captain Fedora
John Rofrano

© IBM Corporation. All rights reserved.