

The Hidden Costs and Challenges of Renewable Energy

Solar, Wind, and Hydropower - A Realistic Look at the Invisible Price Tag

Vahid Nezamivand Chegane

Independent Researcher | Founder, AquaNexus Project

vahidmaykoltarh@yahoo.com | ORCID: 0009-0003-6477-091X

Original Scientific Synthesis - 4 September 2026

Abstract.

Solar, wind, and hydropower are widely promoted as cornerstones of the global energy transition. However, a rigorous scientific examination reveals that these renewable sources, despite their well-known benefits, carry significant hidden costs and disadvantages that are frequently overlooked in policy and investment decisions. This paper systematically analyzes the technical, economic, environmental, and social challenges of each source. Key issues include: intermittency and dependence on weather conditions; vast land requirements; negative impacts on wildlife and biodiversity; waste management challenges for solar panels, wind turbine blades, and dam reservoirs; greenhouse gas emissions from hydropower reservoirs (particularly methane); displacement of human populations; reliance on critical minerals such as lithium and cobalt; and the high costs of energy storage. The paper concludes that a successful and sustainable energy transition requires a diversified portfolio, with geothermal energy serving as a reliable, firm power source that overcomes many inherent limitations of solar, wind, and hydro.

Keywords: Solar Energy; Wind Energy; Hydropower; Renewable Energy Disadvantages; Environmental Impact; Energy Storage; Critical Minerals; Energy Transition; Intermittency; Sustainability; Baseload Power; Geothermal Energy

1. Introduction: Beyond the Green Marketing

Renewable energy sources have been promoted as the ultimate solution to the global energy crisis and climate change. Governments and corporations have invested hundreds of billions of dollars in solar, wind, and hydropower technologies over the past two decades. However, a balanced scientific assessment reveals that these energy sources carry significant, often overlooked, hidden costs and disadvantages that can challenge their long-term sustainability if deployed without careful system design and realistic planning.

The purpose of this paper is not to undermine renewable energy, but to provide a realistic, evidence-based analysis of their challenges, enabling policymakers, investors, and engineers to make more informed decisions. The analysis focuses on three dominant renewable technologies - solar photovoltaics (PV), onshore wind, and large-scale hydropower - and contrasts them with geothermal energy as a firm, low-carbon alternative capable of providing high-capacity-factor power.

Throughout this article, quantitative claims are supported by recent, peer-reviewed literature and authoritative reports from the IPCC, IEA, IRENA, NREL, World Bank, and leading scientific journals.

2. Disadvantages of Solar Energy

2.1. Intermittency and Dependence on Sunlight

Solar PV generation is intrinsically variable, driven by diurnal cycles, weather, and seasonal changes:

- Night and day: Solar panels do not generate power at night, requiring complementary generation or storage for 24/7 supply.
- Cloud cover and rain: Output can drop by 50-90% on heavily overcast days, depending on panel technology and location.
- Seasonal variation: In mid- to high-latitude regions, winter output may be 30-60% lower than summer peaks.
- Capacity factor: Utility-scale solar PV typically achieves capacity factors of 20-25% globally, with site-specific ranges from ~15% to ~30% [IEA 2026; IRENA 2025; NREL 2025].

Implication: Solar energy cannot, on its own, meet baseload demand. Without cost-effective storage or firm complementary generation, it is an inherently variable power source.

2.2. Land Requirements

Utility-scale solar farms require substantial land areas, which can compete with agriculture, conservation, and other land uses:

- Typical land use for ground-mounted solar PV is 1.5-2.5 hectares per MW for fixed-tilt systems, and 2.2-2.8 ha/MW for single-axis tracking systems [NREL 2025; SurgePV 2026].
- A 100 MW solar farm thus requires roughly 150-280 hectares, depending on technology and layout.
- By comparison, geothermal power plants typically require less than 1-2 ha/MW of direct footprint, though access roads and drilling pads add to the total area [Geothermal Insider 2026].

Implication: In densely populated or agriculturally valuable regions, large solar deployments face significant land-use trade-offs.




Figure 1. Direct land footprint comparison across renewable energy technologies (hectares per 100 MW).

2.3. Solar Panel Waste and Recycling

Solar panels have finite lifespans, typically 25-30 years, after which they become waste streams containing glass, aluminum, silicon, copper, silver, and in some technologies, toxic elements such as cadmium and lead:

- IRENA and IEA-PVPS project cumulative end-of-life PV waste to reach approximately 78 million tonnes by 2050 under baseline scenarios, with annual waste flows exceeding 25 million tonnes per year around mid-century under ambitious decarbonization pathways [IRENA 2026; Solar Now 2026; IndexBox 2026].
- Current recycling rates remain low globally; in many regions, less than 10% of decommissioned panels are formally recycled, with the rest landfilled or informally processed [Reuters 2026; VaHorizon 2026].
- Advanced recycling technologies in Europe and China can recover more than 90% of panel mass (glass, aluminum, copper, silicon, silver), but economic viability remains challenging without policy support or extended producer responsibility schemes [OEnergetice 2026; Canal Solar 2026].

Implication: Solar panel waste represents a growing environmental and logistical challenge, requiring scaled recycling infrastructure and sound policy frameworks.

2.4. Dependence on Critical Minerals and Materials

Solar PV manufacturing depends on several materials with supply, cost, and environmental implications:

- Silicon: The primary semiconductor material; production is energy-intensive and concentrated in a few countries.
- Silver: Used in electrical contacts; demand from PV competes with other industrial uses, raising concerns about long-term scarcity and price volatility.
- Indium, tellurium, gallium: Used in thin-film technologies (CIGS, CdTe); these elements are relatively scarce and geologically concentrated.
- Aluminum, copper, glass: Required in large quantities; their production has non-trivial carbon and

environmental footprints.

Implication: Rapid PV scale-up intensifies demand for specific minerals and metals, with associated supply chain and environmental risks [IEA 2026; UNEP 2025].

2.5. Water Consumption in Production and Operation

Although solar PV consumes little water during operation, water use occurs in manufacturing and, in some regions, during panel cleaning:

- Silicon and module production: Involves water-intensive industrial processes, particularly in polysilicon refining and wafer manufacturing.
- Panel cleaning: In arid and semi-arid regions with high dust loads, regular cleaning can require significant volumes of water, potentially competing with agricultural and domestic needs.

Implication: In water-stressed regions, large solar deployments must account for life-cycle water use, particularly for cleaning and cooling in associated infrastructure.

3. Disadvantages of Wind Energy

3.1. Intermittency and Dependence on Wind

Wind power is highly variable in time and space, with output dependent on local and regional wind regimes:

- Calm periods: Turbines produce zero power when wind speeds fall below cut-in thresholds.
- High variability: Output can fluctuate from 0% to 100% of rated capacity over hours to days.
- Forecast uncertainty: Wind forecasts beyond 24-48 hours carry significant uncertainty, complicating long-lead scheduling.
- Capacity factor: Modern onshore wind farms typically achieve capacity factors of 30-40%, with offshore sites often higher (40-50%) but at greater cost [IEA 2026; NREL 2025; DataDeep 2026].

Implication: Like solar, wind cannot provide firm baseload power without substantial storage, overbuilding, or complementary firm generation.




Figure 2. Conceptual illustration of variable power output from solar and wind versus firm, stable output from geothermal energy over a 48-hour period.

3.2. Impacts on Wildlife: Birds and Bats

Wind turbines interact with flying wildlife, causing collisions and potentially affecting populations, particularly for sensitive species:

- Bird fatalities: Peer-reviewed syntheses estimate median fatality rates of ~2-6 birds per MW per year for onshore wind, with substantial site-to-site variation [REWI 2025; AWWIC 2025].
- Bat fatalities: Median estimates are ~3-7 bats per MW per year, with some projects in migratory corridors reporting much higher rates [AWWIC 2026; Tethys 2026].
- Endangered species: Raptors (e.g., golden eagles, hawks) and certain bat species are of particular concern in some regions.
- Migration disruption: Poorly sited wind farms can intersect key migratory routes, amplifying impacts.

Implication: Careful siting, monitoring, and mitigation (e.g., curtailment during peak migration, deterrent technologies) are essential to minimize biodiversity impacts.

3.3. Noise, Infrasound, and Social Acceptance

Wind turbines generate audible noise and low-frequency sound, which can affect nearby residents:

- Turbine noise: Typical sound levels are 40-50 dB at 300-500 m, depending on turbine size and atmospheric conditions.
- Infrasound: Low-frequency sound (less than 20 Hz) is present but generally below perceptual thresholds at typical setback distances; health impacts remain debated and appear to be small for most people, though some individuals report sensitivity.
- Property values: Some studies report modest reductions (less than 10%) in property values very close to large wind farms, though results vary by context and market.

Implication: Social license for wind projects depends on transparent planning, adequate setbacks, and community engagement.

3.4. Wind Turbine Blade Waste

Wind turbine blades are made primarily of fiber-reinforced composites (glass or carbon fiber in epoxy resin), which are difficult to recycle:

- Material: Blades consist of 60-70% glass fiber, ~30% thermoset resin, and minor additives; thermoset resins cannot be remelted like conventional plastics.
- Waste projections: Global cumulative blade waste is projected to reach ~43 million tonnes by 2050, with annual flows of several million tonnes in mid-century [Nature Wind 2025; IEA Wind 2026; Gadget Review 2025].
- Current disposal: In many jurisdictions, the majority of decommissioned blades are landfilled or co-processed in cement kilns, as high-value recycling remains limited and costly [MDPI 2025; Anovip 2026].
- Recycling technologies: Mechanical grinding, pyrolysis, and solvolysis can recover fibers and resins to varying degrees, but economic viability and material quality remain challenges.

Implication: Wind blade waste represents a significant, growing end-of-life challenge requiring policy incentives and technological innovation.

3.5. Radar and Communication Interference

Large wind turbines can interfere with radar and communication systems:

- Radar disruption: Rotating blades can create clutter and false targets on aviation, weather, and military radars.
- Mitigation: Requires careful siting, radar upgrades, or operational constraints near sensitive installations.

Implication: Wind farm development near airports, defense sites, or meteorological networks requires coordinated planning and technical mitigation.

4. Disadvantages of Hydropower

4.1. Alteration of River Ecosystems

Large dams fundamentally change river hydrology, sediment transport, temperature regimes, and ecological connectivity:

- Flow alteration: Dams regulate natural flow variability, affecting downstream habitats, floodplain dynamics, and riparian ecosystems.
- Sediment trapping: Reservoirs trap sediments that would otherwise replenish deltas and coastal zones, contributing to downstream erosion and delta subsidence.
- Temperature changes: Deep reservoir releases can be colder or warmer than natural river temperatures, affecting aquatic species.

Implication: Hydropower projects must be evaluated in the context of whole-basin ecological and geomorphological impacts.

4.2. Biodiversity Loss and Species Extinction

Dams are among the most significant drivers of freshwater biodiversity loss:

- Migratory fish: Dams block migration routes for salmon, eels, sturgeon, and other species, contributing to population declines and local extinctions.
- Aquatic communities: Altered flow and habitat reduce diversity of fish, invertebrates, and aquatic plants.
- Terrestrial impacts: Reservoir inundation destroys forests, wetlands, and other habitats, displacing terrestrial wildlife.

Implication: Hydropower expansion must weigh biodiversity costs against climate and energy benefits, particularly in biodiversity-rich basins.

4.3. Greenhouse Gas Emissions from Reservoirs

Contrary to the common perception of hydropower as zero-emission, reservoirs can emit significant greenhouse gases, especially in tropical regions:

- Methane (CH₄): Anaerobic decomposition of organic matter in reservoir sediments produces methane, a potent greenhouse gas.
- Emission ranges: Life-cycle assessments report hydropower emissions from less than 1 to more than 400 gCO₂e/kWh, with median values around 20-30 gCO₂e/kWh, but tropical reservoirs can exceed 100-400 gCO₂e/kWh in extreme cases [Nature Comm 2025; Nature Geo 2025; MDPI 2026; Solartech 2025].
- Key drivers: Shallow, warm, nutrient-rich reservoirs in tropical zones with high pre-impoundment biomass tend to have the highest emissions.

Implication: Hydropower is not uniformly low-carbon; reservoir GHG emissions must be assessed site-by-site, particularly in the tropics.




Figure 3. Schematic illustration of methane (CH₄) emissions from hydropower reservoirs due to anaerobic decomposition of organic matter in sediment layers.

4.4. Displacement of Human Populations

Large dams have displaced tens of millions of people worldwide, often with inadequate compensation and lasting social impacts:

- Scale: Estimates suggest 40-80 million people have been displaced by large dams globally over the past century [World Bank 2025; Scribd Dams 2026].
- Social impacts: Displacement disrupts livelihoods, cultural ties, and community structures; indigenous peoples are often disproportionately affected.
- Examples: The Three Gorges Dam (China) displaced more than 1 million people; the Rogun project (Tajikistan) is expected to resettle ~60,000 people [Rights in Dev 2025].

Implication: Social safeguards, fair compensation, and participatory planning are critical for any new large-dam projects.

4.5. Vulnerability to Climate Change and Drought

Hydropower output is sensitive to changes in precipitation, snowmelt, and drought frequency:

- Drought risk: Prolonged droughts can reduce reservoir inflows and generation by 30-50% or more in severe cases (e.g., Brazil 2021, parts of the western U.S. in recent years).
- Climate change: Altered hydrological regimes and increased variability may reduce the reliability of hydropower in some regions.

Implication: Hydropower cannot be assumed fully climate-resilient; portfolio diversification and adaptive management are essential.

4.6. Sedimentation and Reduced Dam Lifespan

Reservoir sedimentation gradually reduces storage capacity and can shorten dam lifespans:

- Sediment accumulation: Many reservoirs lose 0.5-2% of storage capacity per decade, with higher rates in sediment-rich rivers.
- Lifespan: Typical economic lifespans are 50-100 years, but heavy sedimentation can reduce this substantially without costly dredging or sediment management.
- Examples: The Aswan High Dam and several large Chinese reservoirs face significant

sedimentation challenges.

Implication: Long-term hydropower planning must include sediment management strategies and realistic lifespan assumptions.

4.7. High Construction Costs and Geological Risks

Large hydropower projects involve high capital costs, long construction times, and geological uncertainties:

- Capital cost: Multi-billion-dollar investments are common for major dams, with construction periods of 5-15 years.
- Geological risks: Seismic activity, foundation issues, and water leakage can increase costs and risks.
- Cost overruns: Many large dams experience significant budget and schedule overruns.

Implication: Hydropower projects require rigorous risk assessment, transparent cost-benefit analysis, and strong governance.

4.8. Dam Failure and Catastrophic Risk

Although rare, dam failures can cause catastrophic loss of life and property:

- Historical disasters: The 1975 Banqiao Dam failure in China is estimated to have caused 170,000-230,000 deaths, making it the deadliest dam failure on record [Banqiao 2026; SMS 2026].
- Other incidents: The 1963 Vajont Dam disaster in Italy caused ~2,000 deaths due to a landslide-induced wave, not structural failure per se.
- Climate stress: More extreme precipitation events may increase stress on aging dam infrastructure.

Implication: Robust design, monitoring, and emergency preparedness are essential to manage low-probability, high-consequence risks.

5. Common Challenges Across Solar, Wind, and Hydropower

5.1. Intermittency and the Need for Storage

Solar and wind are variable renewable energy (VRE) sources, while hydropower can be more flexible but is still climate-dependent:

- Capacity factors (typical ranges):
- Solar PV: 20-25%
- Onshore wind: 30-40%
- Hydropower: 35-50% (highly site-dependent)
- Geothermal: 65-90%, depending on resource and plant design [Geothermal Insider 2026; Lazard 2025].
- Storage requirement: High shares of solar and wind require substantial investment in batteries, pumped hydro, or other storage to maintain reliability, increasing system costs.

Implication: System-level planning must account for the cost and scalability of storage and firm capacity.

5.2. Grid Infrastructure and Smart Grids

Integrating large shares of variable renewables requires upgraded transmission and digital grid infrastructure:

- Transmission: Remote solar and wind resources often require long-distance transmission lines to load centers.
- Smart grids: Advanced monitoring, control, and demand-response capabilities are needed to manage variability and maintain stability.
- System cost: When storage, transmission, and grid upgrades are included, the true system cost of high-VRE scenarios can be 1.5-3 times higher than simple levelized cost estimates suggest.

Implication: Policymakers must consider full system costs, not just technology-level levelized costs.

5.3. Dependence on Critical Minerals

The energy transition relies heavily on specific minerals for batteries, electronics, and generators:

- Lithium, cobalt, nickel: Essential for lithium-ion batteries used in stationary storage and electric vehicles; extraction has environmental and social impacts, particularly in the Democratic Republic of Congo (cobalt) and sensitive ecosystems (lithium brines).
- Rare earth elements: Neodymium and dysprosium are used in high-performance wind turbine generators.
- Supply risks: Geopolitical concentration of production and processing creates supply chain vulnerabilities [IEA 2026; UNEP 2025].

Implication: Diversification of supply, recycling, and material-efficient designs are strategic priorities.




Figure 4. Illustrative supply risk index (1-10 scale) for critical minerals essential to renewable energy technologies and energy storage systems.

5.4. Life-Cycle Carbon Footprint

All energy technologies have life-cycle greenhouse gas emissions from manufacturing, construction, operation, and decommissioning:

- Median life-cycle emissions (gCO₂e/kWh):
- Solar PV: ~20-50
- Onshore wind: ~10-15
- Hydropower: ~20-30 (median; tropical reservoirs can be much higher)
- Geothermal: ~30-45 (median; site-dependent, with some plants lower or higher) [IPCC 2022; MDPI 2026; Solartech 2025].

Implication: While all these options are far lower-carbon than fossil fuels, their life-cycle emissions are non-zero and must be considered in net-zero strategies.

5.5. Land Use and Land-Use Change

Different technologies have markedly different land footprints:

- Direct land use (approximate, per 100 MW):
- Solar PV: 150-280 ha
- Onshore wind: 500-1,000 ha (though much land can remain in agricultural use between turbines)
- Hydropower: 50-100 ha for plant infrastructure, plus large flooded areas (often thousands of hectares)
- Geothermal: less than 10-20 ha for plant and wells, with minimal surface disturbance beyond access roads [NREL 2025; Geothermal Insider 2026].

Implication: Land-use efficiency is an important criterion, particularly in ecologically sensitive or densely populated regions.

6. Comprehensive Comparison: Solar, Wind, Hydropower, and Geothermal

	Metric	Solar PV	Onshore Wind	Hydropower	Geothermal
	Capacity factor (%)	20-25	30-40	35-50	65-90
	Firm baseload capability	No	No	Partial	Yes
	Weather dependence	Very high	High	High	Low
	Direct land use (ha/100 MW)	150-280	500-1,000*	50-100**	<10-20
	Wildlife impact	Moderate	Moderate-High	High	Low
	Waste generation (end-of-life)	High (panels)	High (blades)	Low-Moderate	Low
	Human displacement risk	Low	Low	High	Very low
	Storage need for 24/7 supply	Very high	Very high	Moderate	Low
Median	life-cycle GHG (gCO ₂ e/kWh)	20-50	10-15	20-30***	30-45

* Much land between turbines can remain in agricultural use.

** Excluding large flooded reservoir areas, which can be orders of magnitude larger.

*** Median global value; tropical reservoirs can be much higher.

7. Conclusion

Solar, wind, and hydropower will play important roles in the global energy transition, but they cannot, on their own, meet global energy needs in a reliable, low-cost, and environmentally sustainable manner. Their disadvantages - intermittency, land use, wildlife impacts, waste, displacement, mineral dependence, and, in the case of some hydropower projects, significant greenhouse gas emissions - demand a realistic, system-level assessment.

A sustainable energy system requires a diversified portfolio that combines variable renewables with firm, low-carbon resources. Geothermal energy, with its high capacity factor (65-90%), low land footprint, minimal wildlife impact, low waste generation, and ability to provide 24/7 power without large-scale storage, is uniquely positioned to serve as a backbone of a clean, reliable energy system - particularly in geologically favorable regions.

Future work should focus on: (i) improving life-cycle data and transparency for all renewable technologies; (ii) developing cost-effective recycling and circular economy solutions for solar panels and wind blades; (iii) refining reservoir greenhouse gas assessment tools to guide low-carbon hydropower development; and (iv) accelerating the deployment of firm, low-carbon resources such as geothermal, advanced nuclear, and long-duration storage to complement solar and wind.

References (Selected)

- IPCC (2022). Climate Change 2022: Mitigation of Climate Change.
- IEA (2026). World Energy Outlook 2026.
- IRENA (2025, 2026). Renewable Power Generation Costs; PV Waste Reports.
- NREL (2025). Land Use and Environmental Impacts of Solar and Wind.
- UNEP (2025). Critical Minerals and the Energy Transition.
- REWI (2025). Wind Energy Interactions with Wildlife.
- AWWIC (2025, 2026). Bird and Bat Fatality Data Summaries.
- Nature Communications / Geoscience (2025). Reservoir GHG Emissions.
- World Bank (2025). Hydropower Social Impacts.
- Geothermal Insider (2026). Geothermal Energy Facts.
- Lazard (2025). Levelized Cost of Energy+ v18.0.