

The 3–7–12 Environmental Resilience Framework: A Systems Approach to Waste, Climate, and Ecological Restoration

Vahid Nezamivand Chegane

ORCID: 0009-0003-6477-091X | vahidmaykoltarh@yahoo.com

Original conceptual research architecture • English manuscript • 29 August 2026

Abstract

The accelerating convergence of waste proliferation, greenhouse-gas emissions, and ecological degradation constitutes a coupled environmental systems problem rather than three independent policy challenges. This paper proposes the 3–7–12 Environmental Resilience Framework as an integrated research and policy architecture for connecting material flows, climate mitigation, and ecological restoration. The framework is organized around three coupled pillars: (1) waste as a resource system, emphasizing prevention, reuse, repair, recycling, organics management, material recovery, and environmentally sound residual treatment; (2) greenhouse-gas mitigation, emphasizing methane avoidance and capture, fossil-carbon substitution, energy efficiency, and high-integrity carbon removal where appropriate; and (3) ecological restoration, emphasizing recovery of soil, freshwater, habitat, biodiversity, and ecosystem functions. Seven functional stages—awareness, accountability, transformation, repair, regeneration, resilience, and stewardship—describe the transition from diagnosis to durable system performance. Twelve indicators provide a proposed evidence architecture covering waste prevention, material circularity, methane, greenhouse gases, energy, air and water quality, soil and biodiversity, restoration, human well-being, economic resilience, and governance. The framework is grounded in contemporary evidence. The World Bank's What a Waste 3.0 reports 2.56 billion tonnes of municipal solid waste generated globally in 2022 and projects 3.86 billion tonnes by 2050 under business as usual, a 50% increase. UNEP's Global Waste Management Outlook 2024 estimates 2.1 billion tonnes of municipal solid waste in 2023 and projects 3.8 billion tonnes by 2050, while estimating 2020 global waste-management costs at US\$252 billion directly and US\$361 billion when selected hidden pollution, health, and climate costs are included. UNEP also identifies waste and wastewater as major human-caused methane sources, while the IPCC's AR6 assigns methane 27.0 times the 100-year global warming potential of CO₂ for biogenic methane and 29.8 for fossil methane from fugitive and process sources. These findings support a systems strategy in which prevention is prioritized over disposal, methane is treated as a near-term climate lever, and ecological restoration is treated as infrastructure rather than an afterthought. The framework is explicitly proposed—not presented as a validated causal model or composite index. Its scientific contribution is therefore a testable architecture for hypothesis generation, integrated monitoring, investment screening, scenario analysis, and coordinated public policy. The paper concludes that environmental resilience requires shifting the objective from managing waste after generation to redesigning the material system that generates waste, while simultaneously reducing greenhouse-gas emissions and restoring ecological functions.

Keywords: circular economy; waste management; climate change; greenhouse-gas emissions; methane mitigation; landfill gas; waste-to-energy; life-cycle assessment; ecological restoration; systems engineering; environmental resilience; 3–7–12 framework; resource efficiency; regeneration

3-7-12 ENVIRONMENTAL RESILIENCE FRAMEWORK

Three coupled pillars • Seven functional stages • Twelve performance indicators




Figure 1. Architecture of the proposed 3–7–12 Environmental Resilience Framework. This is a conceptual architecture and not a validated causal model.

Evidence Snapshot

Evidence anchor	Value	Interpretive role
Municipal waste, 2022	2.56 billion tonnes	Current global waste scale; World Bank What a Waste 3.0
Municipal waste, 2050 BAU	3.86 billion tonnes	~50% increase vs. 2022; World Bank
UNEP MSW projection, 2050	3.8 billion tonnes	Independent dataset/definition; convergent scale
Waste management cost, 2020	US\$252B direct; US\$361B incl. selected hidden costs	Economic externalities
High-ambition waste GHG, 2050	0.91 GtCO ₂ e/year	Scenario outcome in World Bank What a Waste 3.0
Methane GWP100	27.0 biogenic; 29.8 fossil fugitive/process	IPCC AR6 metric; source-dependent
Waste & wastewater share of human-caused methane	~20%	UNEP Global Methane Assessment

Note: Values come from different assessments with different base years, definitions, and scenario assumptions. They are evidence anchors, not a single composite index.

1. Introduction

Waste is often treated as the final stage of an economic process, while climate policy and ecological conservation are managed through separate institutional systems. This separation is increasingly difficult to justify. Material extraction, product design, consumption, waste generation, energy use, methane emissions, land conversion, and ecosystem degradation are physically connected through the metabolism of the economy.

The scale of the challenge is substantial. The World Bank's 2026 What a Waste 3.0 assessment, based on data from 217 countries and economies and 262 cities, estimates that 2.56 billion tonnes of municipal solid waste were generated in 2022. Under business as usual, annual municipal waste is projected to reach 3.86 billion tonnes by 2050—approximately 50% above 2022 levels [1]. UNEP's Global Waste Management Outlook 2024 similarly projects municipal solid waste growth to approximately 3.8 billion tonnes by 2050 and estimates that the direct global cost of waste management was US\$252 billion

in 2020, rising to US\$361 billion when selected hidden costs from pollution, health impacts, and climate change are included [2].

Waste is also a climate issue. Organic material disposed under anaerobic conditions can generate methane, while open burning and inefficient treatment can emit carbon dioxide, particulate matter, and other pollutants. UNEP identifies waste and wastewater as a major sectoral source of human-caused methane [3]. The climate significance of methane is especially important because it is short-lived relative to CO₂ but has much greater warming potency per unit mass over conventional reporting horizons. Under IPCC AR6, the 100-year global warming potential is 27.0 for biogenic methane and 29.8 for fossil methane from fugitive and process sources [4]. The often-repeated statement that methane is “25 times stronger than CO₂” is therefore outdated for current IPCC AR6 accounting.

At the same time, waste is not merely a pollutant. Materials in discarded products retain embodied energy, labor, water, and economic value. The challenge is to distinguish materials that can safely circulate from materials that should be reduced, substituted, treated, or permanently isolated. This requires a hierarchy: prevention first, then reduction, reuse, repair, refurbishment, remanufacturing, recycling and biological recovery where environmentally justified, followed by energy recovery for appropriate residuals, and safe disposal only for unavoidable fractions.

The 3–7–12 Environmental Resilience Framework is proposed to connect these issues. It does not claim that waste-to-energy, recycling, or carbon sequestration automatically produce environmental benefits. Instead, it asks which intervention reduces life-cycle harm under a specified system boundary, baseline, technology, and counterfactual. This distinction is essential for scientific credibility.

2. Conceptual Foundation

The framework is based on five propositions.

Proposition 1: Waste is a system outcome, not merely a disposal problem. Waste is generated by product design, procurement, consumption, infrastructure, economic incentives, and cultural norms. End-of-pipe management cannot fully solve a problem created upstream.

Proposition 2: Waste and climate are connected through material and energy flows. Organic waste can produce methane; waste collection and treatment require energy; manufacturing replacement products requires new extraction; recycling can displace virgin material production; and combustion can recover energy while generating emissions and residues. Life-cycle assessment is therefore necessary to compare pathways.

Proposition 3: Ecological restoration is a systems intervention. Restored wetlands, forests, soils, rivers, and urban ecosystems can provide climate adaptation, biodiversity, water regulation, heat reduction, and human-health benefits. Restoration should therefore be evaluated as functional infrastructure, not only as land-cover change.

Proposition 4: Prevention has priority over downstream treatment when it avoids more life-cycle impact. A circular economy is not simply a higher recycling rate. It is a redesign of production and consumption so that fewer virgin resources are required and products remain useful longer.

Proposition 5: Resilience requires simultaneous environmental and social performance. A waste system that reduces emissions but excludes informal workers, creates unsafe labor conditions, or becomes financially unsustainable is not fully resilient. The framework therefore includes human well-being, equity, economic resilience, and governance among its indicators.

3. The Three Coupled Pillars

Pillar I — Waste as a Resource System. This pillar covers prevention, source reduction, reuse, repair, refurbishment, remanufacturing, recycling, composting and anaerobic digestion for suitable organic streams, material recovery, and safe residual management. The central question is not “How do we dispose of waste?” but “How do we minimize the creation of waste and maximize the safe utility of materials?”

Pillar II — Greenhouse-Gas Mitigation. This pillar targets methane, CO₂, and other greenhouse gases across the waste life cycle. Priority actions include preventing biodegradable waste from entering unmanaged anaerobic disposal, improving landfill gas capture where landfilling remains necessary, reducing food loss and waste, improving wastewater treatment, electrifying and decarbonizing collection and processing, and avoiding emissions-intensive virgin material production. Carbon sequestration is included only where additionality, permanence, leakage, monitoring, and ecological integrity can be demonstrated.

Pillar III — Ecological Restoration. This pillar focuses on restoring ecological function rather than merely increasing nominal green area. Relevant functions include soil carbon and fertility, water infiltration and retention, habitat connectivity, biodiversity, nutrient cycling, erosion control, flood regulation, and thermal regulation. Restoration must be context-specific because an intervention beneficial in one ecosystem can be damaging in another.

The pillars are coupled. Waste prevention can reduce upstream extraction and energy demand. Methane capture can reduce near-term warming. Restoration can improve resilience to heat, drought, flood, and erosion. Conversely, climate change can increase waste-system vulnerability through extreme weather, while ecosystem degradation can reduce the capacity of landscapes to absorb pollution and buffer climate shocks.

4. The Seven Functional Stages

1. Awareness — establish a shared evidence base, define system boundaries, quantify material and emissions flows, and distinguish observed trends from assumptions.
2. Accountability — identify actors, incentives, externalized costs, distributional effects, regulatory gaps, and responsibilities across producers, municipalities, consumers, financiers, and public institutions.
3. Transformation — redesign products, infrastructure, markets, energy systems, procurement, and behavior to reduce virgin material demand and environmental pressure.
4. Repair — eliminate uncontrolled dumping and burning, remediate contaminated sites, upgrade failing collection and treatment systems, and address accumulated ecological damage.
5. Regeneration — restore soil, water, habitat, biodiversity, and ecosystem functions while rebuilding social and institutional capacity.
6. Resilience — create diversified, financially viable, shock-resistant systems with redundancy, adaptive management, reliable monitoring, and inclusive governance.
7. Stewardship — institutionalize long-term responsibility through standards, education, ecological accounting, intergenerational planning, transparent reporting, and continuous improvement.

The stages are not strictly linear. A community may simultaneously be transforming its collection system, repairing a polluted river, and building resilience to climate extremes. The sequence is therefore a diagnostic maturity model rather than a rigid project-management schedule.

Figure 4. Seven functional stages from environmental crisis to resilience




Figure 4. Seven functional stages from environmental crisis to resilience. The stages are iterative in practice.

5. Twelve Performance Indicators

The twelve indicators translate the framework into an evidence dashboard. They are deliberately heterogeneous because environmental resilience cannot be reduced to one metric.

1. Waste generation intensity — tonnes of municipal and relevant industrial waste per capita and per unit of economic output.
2. Material circularity — share of material inputs supplied through secondary materials, together with absolute virgin-material demand.
3. Methane emissions — CH₄ emissions from landfills, wastewater, and relevant waste pathways, reported in tonnes CH₄ and CO₂-equivalent using a stated GWP.
4. Greenhouse-gas emissions — life-cycle CO₂e emissions from waste collection, treatment, transport, disposal, and displaced production.
5. Energy performance — energy use per tonne treated and net low-carbon energy recovered where applicable.
6. Recycling and recovery quality — actual material recovery, contamination, yield, and avoided virgin production rather than collection rate alone.
7. Organic-waste diversion — food and green waste prevention, separate collection, composting, anaerobic digestion, and methane avoidance.
8. Air and water quality — PM_{2.5}, toxic pollutants, leachate control, groundwater and surface-water quality near facilities.
9. Soil and biodiversity condition — soil organic carbon, erosion, habitat condition, connectivity, and biodiversity indicators.
10. Ecological restoration function — restored area plus measurable changes in ecosystem services and

ecological integrity. 11. Human well-being and economic resilience — occupational safety, inclusion, affordability, employment, municipal fiscal sustainability, and resilience to shocks. 12. Governance and stewardship — compliance, transparency, data quality, participation, enforcement, procurement standards, and long-term planning.

A key methodological principle is to report both absolute and intensity metrics. A country can improve recycling intensity while total waste and virgin material consumption continue to rise. Likewise, an energy-from-waste plant can generate electricity while still producing substantial emissions. The dashboard therefore prevents one favorable percentage from concealing deterioration elsewhere.

Table 1. Twelve proposed performance indicators

No.	Indicator	Examples of measurement	Preferred direction
1	Waste generation intensity	t/person/year; t/GDP	↓
2	Material circularity	secondary input share + virgin material demand	↑ circularity; ↓ virgin demand
3	Methane emissions	t CH ₄ ; tCO ₂ e with stated GWP	↓
4	Waste life-cycle GHGs	kgCO ₂ e/functional unit	↓
5	Energy performance	kWh/t; net low-carbon energy	↓ intensity; ↑ clean recovery
6	Recovery quality	yield; contamination; avoided virgin output	↑ quality
7	Organic diversion	food/green waste prevention & treatment	↑
8	Air & water quality	PM _{2.5} ; leachate; groundwater	↑ quality
9	Soil & biodiversity	SOC; erosion; habitat integrity	↑
10	Restoration function	functional condition, not area alone	↑
11	Well-being & economic resilience	safety; affordability; jobs; fiscal resilience	↑
12	Governance & stewardship	compliance; transparency; participation	↑

6. Data-Driven Evidence Base

6.1 Global waste trajectory. What a Waste 3.0 estimates 2.56 billion tonnes of municipal waste in 2022 and 3.86 billion tonnes in 2050 under business as usual [1]. UNEP's 2024 outlook uses a different reference year and estimates 2.1 billion tonnes in 2023, rising to 3.8 billion tonnes in 2050 [2]. These numbers should not be mechanically combined because definitions, base years, and estimation methods differ. Their convergence around approximately 3.8–3.9 billion tonnes by 2050 nevertheless demonstrates the scale of the projected increase.

6.2 Mismanagement and inequality. The World Bank reports that approximately one-third of global waste is uncollected or openly dumped and that the burden is highly uneven, with rapidly growing regions often having the weakest infrastructure [1]. This makes waste a governance and development issue, not simply an environmental-technology problem.

6.3 Economic costs. UNEP estimates direct global waste-management costs of US\$252 billion in 2020 and US\$361 billion after selected hidden pollution, health, and climate costs are included [2]. Its modeled circular-economy scenario indicates the possibility of a net annual gain of approximately US\$108.5 billion by 2050 [2]. Such figures should be treated as scenario outputs rather than guaranteed returns.

6.4 Waste-sector methane. UNEP's Global Methane Assessment identifies waste and wastewater as responsible for about one-fifth of human-caused methane emissions and highlights methane mitigation as a fast climate lever [3]. Methane reduction can also improve air quality because methane contributes to ozone formation. The climate benefit is strongest when interventions prevent methane formation or reliably capture and destroy or utilize landfill gas.

6.5 Methane accounting. IPCC AR6 reports GWP100 of 27.0 for biogenic methane and 29.8 for fossil methane from fugitive and process sources [4]. For policy communication, it is therefore preferable to state the metric explicitly rather than using the outdated generic “25 times” claim. For near-term climate analysis, GWP20 values are substantially higher, illustrating why methane deserves special attention in a resilience framework.

6.6 Circular economy. UNEP emphasizes the need for core circular-economy indicators and data to support policy-making [5]. Circularity must be evaluated against absolute material use and environmental outcomes. Recycling can be beneficial, but recycling alone cannot guarantee reduced extraction if total material demand continues to expand.

6.7 Waste-to-energy. Energy recovery can be useful for suitable residual waste when higher-value prevention, reuse, and material recovery are not feasible and when emissions controls are strong. It should not become a justification for creating waste streams that would otherwise be avoidable or recyclable. The appropriate metric is net life-cycle benefit relative to the realistic alternative, including displaced electricity or heat, avoided landfill emissions, transport, facility emissions, ash

management, and material recovery foregone.

6.8 Restoration. Ecological restoration can increase resilience, but success must be measured by ecological function rather than area alone. A planted hectare with low survival or poor ecological fit is not equivalent to a functioning restored ecosystem. Indicators should therefore include survival, biodiversity, soil condition, hydrology, carbon persistence, and ecosystem-service outcomes where relevant.

Figure 2. Proposed waste-climate-ecology feedback loop





Figure 2. Proposed reinforcing feedback loop linking waste proliferation, methane, climate pressure, ecological degradation, and resource loss.



Sources: World Bank What a Waste 3.0 (2026); UNEP Global Waste Management Outlook 2024. Values are not directly comparable units.

Figure 3. Selected global evidence anchors. Units differ by metric; the chart is intentionally a dashboard rather than a common-scale index.

7. Systems Dynamics and Causal Logic

The framework proposes a reinforcing loop: rising consumption increases material throughput; throughput generates waste; unmanaged or poorly treated waste creates methane and pollution; climate and ecological degradation reduce system resilience; reduced resilience increases damage and economic losses; and those losses can reinforce short-term cost-cutting and underinvestment.

A balancing loop can be deliberately created: prevention lowers waste generation; circular design increases product and material lifetime; source separation improves recovery; methane capture or avoidance reduces near-term warming; restoration improves ecological buffering; and resilience reduces future losses. These feedbacks can be strengthened by pricing externalities, extended producer responsibility, green public procurement, disclosure standards, performance-based finance, and community participation.

The framework therefore rejects the simplistic proposition that every waste stream should be converted into energy. Waste-to-energy is one treatment option, not the organizing principle of a circular economy. The highest-value intervention is generally to prevent unnecessary material use and preserve product/material utility before considering downstream recovery.

8. Life-Cycle Assessment and Decision Rules

Every major intervention under the framework should pass a life-cycle decision test.

Decision Rule A — Prevention test: Does the intervention reduce the quantity or toxicity of material entering the system?

Decision Rule B — Circularity test: Does it preserve product or material utility longer than the baseline?

Decision Rule C — Climate test: Does it reduce net life-cycle GHG emissions relative to the realistic counterfactual?

Decision Rule D — Methane test: Does it prevent, capture, oxidize, or otherwise reliably reduce methane formation or release?

Decision Rule E — Ecological integrity test: Does it avoid transferring pollution or ecological damage from one compartment to another?

Decision Rule F — Social resilience test: Does it protect workers, communities, affordability, health, and inclusion?

Decision Rule G — Financial resilience test: Can the system remain operational without dependence on unrealistic subsidies or volatile revenue assumptions?

Life-cycle assessment should be used wherever feasible. Functional units must be defined carefully. Comparing one tonne of waste treated is not always meaningful if treatment technologies produce different outputs, displace different energy sources, or affect material recovery differently. The functional unit may instead need to represent a service, such as “management of one tonne of mixed municipal waste while meeting specified environmental and health standards.”

9. Policy and Investment Architecture

For governments, the framework can become a cross-ministerial dashboard linking waste, climate, industry, agriculture, water, biodiversity, health, energy, and finance. National targets should combine absolute waste prevention, methane reduction, circularity, restoration, and social outcomes.

For municipalities, the framework can guide integrated waste plans: universal collection, source separation, organics management, controlled residual disposal, methane management, route optimization, data systems, worker safety, and local restoration projects.

For industry, the framework supports product-as-a-service models, durable design, repairability, recycled-content strategies where environmentally justified, take-back systems, industrial symbiosis, and transparent material accounting.

For investors, the twelve indicators can support screening of transition risk and resilience opportunities. Attractive projects are not simply those labeled “green”; they are those with measurable additional environmental benefits, credible baselines, robust monitoring, realistic financial assumptions, and limited risk of burden shifting.

For carbon markets, landfill methane projects require particular attention to additionality and measurement. Capturing gas that would otherwise be legally required or already economically valuable should not automatically be counted as additional climate benefit. Methane projects should also address the declining gas-generation curve of landfills and long-term monitoring.

10. Research Agenda and Validation

The 3–7–12 Environmental Resilience Framework should be tested empirically before being used as a formal composite score.

First, indicator validity should be assessed through expert review and statistical testing. Second, pilot applications should be conducted at city, regional, and national scales. Third, longitudinal datasets should test whether improvements in early-stage indicators predict later improvements in ecological and human outcomes. Fourth, system-dynamics models can test feedback structures under alternative policy scenarios. Fifth, life-cycle assessment can compare competing waste pathways. Sixth, sensitivity analysis should test whether conclusions remain stable when assumptions about methane GWP, electricity displacement, recycling yields, landfill capture efficiency, carbon permanence, or discount rates are changed.

A future quantitative version could define normalized indicator scores and aggregate them using transparent weights. However, a composite index should only be created after demonstrating robustness. If rankings change substantially under plausible weighting schemes, the dashboard should report a range or scenario set rather than a single authoritative score.

The most important research hypothesis is therefore: integrated interventions that simultaneously reduce waste generation, methane emissions, virgin material demand, and ecological degradation will produce greater long-term resilience than isolated interventions focused on downstream waste treatment alone.

11. Limitations

The framework is a proposed conceptual architecture and has not yet been independently validated. It should not be described as an established scientific theory, certified index, or proven solution.

Global waste datasets differ in definitions, geographic coverage, reporting quality, and estimation methods. The paper therefore avoids constructing a false single global “waste number.” Likewise, methane global-warming potential depends on source category and time horizon, so the metric must always be specified.

Waste-to-energy is context-dependent and can conflict with circularity when it competes with recycling or creates demand for combustible feedstock. Carbon sequestration also has risks involving permanence, leakage, land competition, biodiversity, and measurement uncertainty.

Ecological restoration is not universally reversible. Some ecological losses are permanent, and restoration can require decades or centuries. The framework consequently defines resilience as improved capacity and function, not a promise to recreate an exact historical ecosystem.

Finally, numerical frameworks can create false precision. The 3–7–12 architecture should be used to organize evidence and decisions, not to substitute a single score for scientific judgment.

12. Conclusion

Waste, climate change, and ecological degradation are not independent crises. They are manifestations of a coupled socio-technical metabolism in which materials are extracted, transformed, consumed, discarded, and returned to the environment. The scale of projected waste growth, the climate importance of methane, and the degradation of ecological systems demonstrate the need for integrated action.

The 3–7–12 Environmental Resilience Framework provides a structured response: three coupled pillars connect waste as a resource system, greenhouse-gas mitigation, and ecological restoration; seven stages describe the transition from awareness to stewardship; and twelve indicators create a practical evidence architecture.

The framework's central principle is that the objective should not be to manage ever-growing quantities of waste more efficiently. The deeper objective is to redesign the systems that generate waste, preserve material value, rapidly reduce methane and other greenhouse gases, and restore ecological functions that support human well-being.

The most credible path is therefore neither “waste-to-energy” alone nor “recycling” alone nor “carbon sequestration” alone. It is a hierarchy of prevention, circularity, climate mitigation, ecological restoration, resilience, and stewardship evaluated through transparent life-cycle evidence.

In this sense, environmental resilience is not a single technology. It is a systems capability: the capacity of human societies to meet needs while reducing material pressure, limiting climate forcing, restoring ecological function, and remaining adaptable under uncertainty. The 3–7–12 framework is offered as a research architecture for testing that proposition and translating it into measurable policy and investment decisions.

References

- [1] World Bank. What a Waste 3.0: Global Snapshot of Solid Waste Management toward Circularity until 2050. Washington, DC: World Bank; 2026.
- [2] United Nations Environment Programme (UNEP), International Environmental Technology Centre, and International Solid Waste Association (ISWA). Global Waste Management Outlook 2024: Beyond an Age of Waste—Turning Rubbish into a Resource. Nairobi: UNEP; 2024.

- [3] UNEP & Climate and Clean Air Coalition. Global Methane Assessment: Benefits and Costs of Mitigating Methane Emissions. Nairobi/Washington, DC; 2021.
- [4] IPCC. Climate Change 2021: The Physical Science Basis, Working Group I, Chapter 7 and supplementary material; and Climate Change 2022: Mitigation of Climate Change, Working Group III, Annex II. Cambridge University Press; 2021–2022.
- [5] UNEP. Circular Economy: From Indicators and Data to Policy-Making. Nairobi: United Nations Environment Programme; 2024.
- [6] Ellen MacArthur Foundation. Completing the Picture: How the Circular Economy Tackles Climate Change. Cowes: EMF; 2019.
- [7] ISO. ISO 14040:2006 Environmental Management—Life Cycle Assessment—Principles and Framework. Geneva: International Organization for Standardization; 2006.
- [8] ISO. ISO 14044:2006 Environmental Management—Life Cycle Assessment—Requirements and Guidelines. Geneva: International Organization for Standardization; 2006.
- [9] IPBES. Global Assessment Report on Biodiversity and Ecosystem Services. Bonn: Intergovernmental Science-Policy Platform on Biodiversity and Ecosystem Services; 2019.
- [10] United Nations Environment Programme. Global Environment Outlook 7: A Future We Choose. Nairobi: UNEP; 2025.
- [11] FAO. Global Forest Resources Assessment 2025. Rome: Food and Agriculture Organization of the United Nations; 2025.
- [12] World Meteorological Organization. State of the Global Climate 2024. Geneva: WMO; 2025.
- [13] UNEP. Emissions Gap Report 2025. Nairobi: United Nations Environment Programme; 2025.
- [14] International Energy Agency. World Energy Outlook 2024. Paris: IEA; 2024.
- [15] United Nations Environment Programme. Turning off the Tap: How the World Can End Plastic Pollution and Create a Circular Economy. Nairobi: UNEP; 2023.
- [16] Raworth K. Doughnut Economics: Seven Ways to Think Like a 21st-Century Economist. London: Random House; 2017.

Author Information

Vahid Nezamivand Chegane
ORCID: 0009-0003-6477-091X
Email: vahidmaykoltarh@yahoo.com

The 3–7–12 Environmental Resilience Framework is presented as a proposed research and policy architecture. Its empirical validity, indicator weighting, causal structure, and application at different geographic scales require independent testing.