

TIME-ACCELERATED GEOLOGY FOR RADIOACTIVE WASTE IMMOBILIZATION

A Nature-Inspired, Gate-Driven 3–7–12 Systems Framework for Wasteform Research, Validation and Translation


Vahid Nezamivand Chegane

Independent Researcher • Originator of the 3–7–12 Research Architecture

ORCID: 0009-0003-6477-091X

29 August 2026

Conceptual Architecture: Nature-Inspired Wasteform Stabilization



Conceptual only; not an operating procedure and not a substitute for a licensed nuclear safety case.

Figure 1. High-level system architecture. This figure is conceptual and deliberately excludes operational parameters for radioactive-material handling.

IMPORTANT: This manuscript proposes a research framework for immobilization and durability testing. It does not claim to eliminate radioactivity, accelerate radioactive decay by chemical means, replace geological disposal, or authorize handling of radioactive material.

Document Control, Intellectual Property and Scientific Status

Copyright © 2026 Vahid Nezamivand Chegane. All rights reserved. This manuscript is an original research and commercialization document. No license to reproduce, implement, manufacture, commercialize, or operationalize the proposed framework is granted by publication of this document.

The author should obtain jurisdiction-specific patent and IP counsel before any additional public disclosure of potentially patentable implementation details. Publication can affect novelty in some jurisdictions; therefore, this document intentionally emphasizes architecture, validation logic, governance and investment strategy rather than proprietary operating recipes.

Item	Status
Scientific maturity	Conceptual / pre-validation research framework
Evidence status	Natural-analogue literature + proposed validation program; no independent experimental proof claimed
Primary application	Radioactive-waste immobilization / wasteform research
Safety boundary	Non-operational; no handling recipe for radioactive material
Commercial status	R&D platform opportunity; not yet a qualified nuclear technology
Investment status	Milestone-based R&D proposition; no guaranteed financial return
Regulatory status	No regulatory approval claimed
IP posture	All rights reserved; implementation details should be protected before further disclosure

Executive Position

The central correction to the original manuscript is scientific and strategic: radioactive decay is a nuclear process governed by radionuclide half-life and is not made to disappear in days by ordinary mineral processing, pressure, temperature, microbes, or coatings. What engineering can realistically target is the immobilization of radionuclides inside durable wasteforms and the reduction of radionuclide release under defined environmental conditions. The revised framework therefore changes the central claim from “neutralization” to “immobilization, containment and evidence-based qualification.”

This distinction materially improves scientific defensibility, regulatory credibility and investability. Existing nuclear programs already use vitrification and ceramic wasteforms to immobilize radioactive constituents, while geological disposal remains a major endpoint for high-level and long-lived waste. The proposed contribution is not to deny these approaches, but to create a structured research architecture for comparing and improving candidate wasteforms using natural analogues, computational screening and independent validation. [Ncited0turn0search0Öturn0search34Ö](#)

Abstract

This paper proposes a nature-inspired research architecture for improving the long-term immobilization of radioactive waste in engineered glass, glass-ceramic and ceramic wasteforms. The framework, named the 3–7–12 architecture, is not presented as a law of radioactive decay and does not claim that radionuclides can be chemically neutralized within days. Instead, it organizes the research problem around three coupled domains—waste chemistry, engineered matrix and containment environment—seven validation gates, and twelve evidence controls spanning material characterization, durability, uncertainty, quality assurance and regulatory readiness.

The framework draws on natural analogues such as radiation-resistant minerals and the Oklo natural nuclear reactor, as well as established wasteform research including Synroc-type ceramics and vitrification. Current international practice demonstrates that immobilization in glass and mineral-like phases is a mature scientific field, while recent work continues to develop tailored ceramic and glass-ceramic forms for challenging waste streams.

The proposed research pathway is intentionally gate-driven: conceptual modelling and non-radioactive surrogate testing precede any regulated radioactive-material work. The commercial proposition is a staged R&D platform rather than a guaranteed revenue product. A screening-level 2026 investment envelope is provided for governments, utilities, nuclear-service companies, advanced-materials firms and strategic investors. The principal deliverable is a reproducible evidence pathway capable of determining whether the framework produces measurable improvements in wasteform performance relative to established baselines.

Keywords: radioactive waste immobilization; wasteforms; ceramic materials; glass-ceramics; natural analogues; Synroc; geological disposal; systems engineering; 3–7–12 framework; nuclear materials; translational research; technology readiness.

Plain-Language Significance

The proposal does not promise to make radioactive atoms disappear. It asks a more testable engineering question: can nature-inspired material architectures help keep radionuclides immobilized for longer and under more demanding conditions, while producing measurable evidence that regulators and operators can evaluate?

Claim Audit: What Was Corrected

Original framing	Revised scientific framing	Reason
Radioactive waste is “neutralized” in days	Radionuclides remain radioactive; the research target is immobilization and reduced release	Chemical/mineral processing does not change nuclear half-life
A universal 10-day process	A staged research program with no pre-claimed processing time	No validated kinetics or licensed process exists
Leach rate presented as a measured universal value	Leach performance is a test variable to be measured for each wasteform	Waste composition and test conditions matter
Simulation claimed complete decay	Simulation is limited to materials, transport and durability hypotheses	Decay cannot be replaced by an arbitrary acceleration factor
IAEA certification as a final step	Regulatory review is jurisdiction- and facility-specific	No single manuscript can confer certification

Open-source deployment	Controlled disclosure and IP review before commercialization	Protects novelty and avoids unsafe implementation claims
------------------------	--	--

1. Introduction: From “Neutralization” to Engineered Immobilization

Radioactive-waste management is a long-duration systems problem involving radiological hazard, chemistry, material durability, heat generation, containment, transport, institutional control and public confidence. International guidance classifies waste according to properties such as activity, half-life and heat generation, and different classes require different management and disposal strategies. High-level and long-lived waste generally require robust isolation and, in many national programs, deep geological disposal.

¶citeÖturn1search44Öturn1search49¶

The engineering opportunity addressed here is narrower and more defensible: improve the wasteform itself. A wasteform is the engineered solid matrix used to immobilize radioactive constituents before storage and/or disposal. Glass, glass-ceramic and ceramic systems are already investigated and used for difficult waste streams. The IAEA identifies mineral-like and ceramic phases as important research directions, while ANSTO continues to develop Synroc-derived technologies and tailored wasteforms.

¶citeÖturn0search34Öturn1search1Öturn1search11¶

The 3–7–12 framework is proposed as a systems-engineering layer above these materials technologies. Its purpose is to reduce fragmentation between natural-analogue science, computational materials screening, experimental characterization, safety assessment and commercialization.

1.1 Research Question

Can a structured, nature-inspired design and validation architecture identify wasteform compositions or architectures that improve radionuclide retention, chemical durability and resistance to environmental perturbations relative to an established baseline, without claiming any change in the underlying nuclear decay process?

1.2 Falsifiable Hypothesis

For a defined waste surrogate and a defined environmental envelope, a candidate wasteform selected using the 3–7–12 architecture will demonstrate statistically and practically meaningful improvements in one or more pre-specified performance metrics—such as normalized release, phase stability or damage tolerance—relative to a control wasteform, while maintaining acceptable manufacturing and safety constraints.

1.3 Non-Claims


- no claim of eliminating radioactivity;
- no claim of accelerating nuclear decay through ordinary chemical or materials processing;
- no claim that a wasteform alone eliminates the need for an appropriate disposal system;
- no claim of regulatory approval, clinical-style certification, or industrial qualification;
- no claim that the proposed architecture is superior to vitrification, Synroc or other established approaches before independent testing.

2. Natural Analogues: What Nature Actually Teaches

Natural analogues are useful because they provide long-duration observations of mineral stability, radionuclide incorporation and alteration. They are not direct industrial recipes. The correct inference is that certain mineral structures can retain radioactive elements under geological conditions—not that a laboratory can reproduce billions of years of nuclear decay in days.

Natural analogue / technology	Relevant lesson	What it does NOT prove
Oklo natural reactor	Long-term interaction of fission products with geological minerals can inform retention and migration studies	Does not prove rapid artificial decay or universal containment
Zircon / zirconolite-type phases	Crystal structures can incorporate actinides and tolerate radiation damage to varying degrees	Does not prove identical performance for arbitrary waste streams
Monazite and related minerals	Natural mineral hosts can retain actinides/rare-earth elements over geological time	Natural conditions are not equivalent to engineered disposal
Synroc-type ceramics	Engineered multiphase ceramics can immobilize difficult radioactive constituents	Does not eliminate the need for qualification and disposal
Vitrified waste	Glass matrices are an established industrial route for immobilizing high-level liquid waste	Does not mean glass is optimal for every waste chemistry

Current industrial evidence is important. The U.S. Department of Energy describes vitrification as a method that converts high-activity liquid waste into a solid glass form suitable for long-term storage and disposal. ANSTO's current Synroc program similarly focuses on immobilizing difficult waste streams in glass, glass-ceramic and ceramic forms. [Nc citeÖturn0search3Öturn1search4Ö](#)



The numbers are a design framework proposed by the author, not a discovered law of radioactive decay.

Figure 2. The 3–7–12 architecture is deliberately reframed as research governance, not a claimed natural law.

3. The 3–7–12 Research Architecture

3.1 Code 3 — Three Coupled Domains

Domain	Research question	Indicative evidence
Waste chemistry	What radionuclides, chemical species, impurities and physical states are present?	Composition, phase distribution, activity profile, heat generation, chemical compatibility
Engineered matrix	How are radionuclides incorporated and how stable is the host matrix?	Phase assemblage, microstructure, mechanical integrity, thermal and chemical durability
Containment environment	How will the wasteform behave during storage and disposal conditions?	Groundwater chemistry, temperature, pressure, radiation damage, mechanical stress, transport

3.2 Code 7 — Seven Validation Gates

The seven gates are not seven processing stations. They are decision gates that prevent premature claims:

1. Characterization — define the waste stream and uncertainties.
2. Modelling — establish testable material and transport hypotheses.
3. Surrogate validation — test candidate matrices without radioactive material where possible.
4. Durability validation — quantify chemical, thermal, mechanical and structural performance.
5. Integrated pilot — demonstrate controlled manufacturing and QA/QC under the applicable regulatory framework.
6. Independent review — replicate critical results and audit uncertainty.
7. Regulatory pathway — integrate the evidence into a jurisdiction-specific safety case.

3.3 Code 12 — Twelve Evidence Controls

#	Evidence control
1	Radiological profile
2	Chemical composition
3	Phase stability
4	Microstructure
5	Leach/release behaviour
6	Thermal stability
7	Mechanical integrity
8	Radiation-damage response
9	Long-term ageing model
10	Quality assurance / traceability
11	Uncertainty quantification
12	Safety case / regulatory evidence

Evidence Ladder for Translational Readiness




Figure 3. Evidence ladder. The current manuscript intentionally remains below pilot/qualification claims.

4. Candidate Materials Platform

The framework should be technology-neutral. It can compare established and emerging matrices rather than assuming a single material is correct.

Platform	Strength	Research question for 3–7–12
Borosilicate / other vitrified matrices	Established industrial experience for high-level liquid waste	Can tailored compositions improve durability or waste loading for specific chemistries?
Ceramic wasteforms	Potentially high chemical and radiation durability; tailored crystal hosts	Which phases retain which radionuclide families, and under what conditions?
Glass-ceramics	Combines glass processing with crystalline retention phases	Can phase distribution be controlled reproducibly without compromising manufacturability?
Composite / multilayer concepts	Potential for multiple containment functions	Does added complexity produce measurable safety benefit worth the cost and qualification burden?

ANSTO reports active work on tailored ceramic and glass-ceramic wasteforms, including recent research on challenging sulphate-bearing radioactive wastes. This demonstrates that wasteform engineering is an active field rather than an unoccupied technological space. The proposed differentiation must therefore be demonstrated through measurable performance, not branding alone. [Ncitem1search1Öturn1search4Ö](#)

4.1 What the Framework Adds

- an explicit separation between nuclear decay and radionuclide release;
- a gate-based architecture linking materials science to safety-case evidence;
- a common comparison framework for glass, ceramic and glass-ceramic candidates;
- an investment structure tied to evidence milestones rather than speculative scale-up;
- an IP strategy that protects implementation details while allowing scientific peer review of non-sensitive claims.

4.2 Conceptual Performance Metrics

Metric	Definition	Decision use
Normalized release	Radionuclide release normalized to sample area/time and test conditions	Primary durability comparison
Phase retention	Fraction incorporated in target host phases	Material design comparison
Damage tolerance	Performance after defined ageing/radiation/mechanical challenges	Long-term robustness
Manufacturing reproducibility	Variation between independent batches	Scale-up feasibility
Safety margin	Distance between measured performance and acceptance criteria	Regulatory readiness
Life-cycle cost	Cost per qualified wasteform unit / waste inventory	Investment and procurement decisions

5. Computational Layer

The original manuscript used a decay equation with an empirical acceleration factor. That formulation is removed because it conflated nuclear decay with chemical/material kinetics. The revised computational layer models quantities that materials engineering can legitimately influence: phase stability, diffusion, dissolution/release, microstructural evolution and uncertainty.

5.1 Conceptual Model

For a radionuclide inventory $N(t)$, the nuclear decay term remains governed by its decay constant λ : $N(t)=N_0 \exp(-\lambda t)$. An engineered wasteform can change the probability and rate at which radionuclides are released from the solid matrix, but it does not ordinarily change λ . The research therefore separates two functions: nuclear decay and environmental release.

5.2 Proposed Digital-Twin Variables


Layer	Variables	Output
Nuclear	nuclide inventory, half-life, heat generation	source term
Material	phase fractions, porosity, grain boundaries, defect density	retention state
Environment	temperature, aqueous chemistry, redox, mechanical stress	exposure state
Transport	diffusion / dissolution / sorption parameters	release estimate
Uncertainty	parameter distributions, model discrepancy	confidence interval

The computational program should use sensitivity analysis and uncertainty propagation rather than a single deterministic “acceleration factor.” Model outputs should be compared against independent experimental measurements, with failed predictions treated as useful scientific results.

5.3 Computational Deliverables

- candidate-material ranking
- uncertainty map
- failure-mode prediction
- accelerated-ageing hypothesis generation
- test prioritization
- life-cycle cost sensitivity
- evidence traceability

Seven-Gate Validation Program — No Gate Is Pre-Claimed



Each gate requires documented evidence before progression. This manuscript does not present unverified experimental results.

Figure 4. Seven validation gates. No experimental or regulatory gate is represented as already passed.

6. Experimental Validation Roadmap

The safe development sequence begins with non-radioactive surrogates and materials characterization. Any transition to radioactive materials must be performed by appropriately licensed institutions under approved radiation-protection, nuclear-safety and waste-management controls. The manuscript intentionally does not provide an operational recipe for handling or processing radioactive waste.

Phase	Purpose	Indicative output	Gate
Phase 0	Literature, IP and requirements baseline	Validated problem definition + prior-art map	Proceed / redesign
Phase 1	Non-radioactive surrogate screening	Candidate matrix shortlist	Material down-select
Phase 2	Independent laboratory replication	Reproducible durability evidence	Replication pass/fail
Phase 3	Regulated radioactive-material research	Waste-specific performance evidence	Safety + regulatory review
Phase 4	Integrated pilot	Manufacturing, QA/QC and lifecycle data	Pilot qualification
Phase 5	Demonstration / deployment	Site-specific safety case and business case	Regulator + operator decision

6.1 Minimum Evidence Package Before Any Scale-Up

- independent replication of key measurements;
- documented uncertainty and sensitivity analysis;
- comparison with at least one established baseline wasteform;
- failure-mode analysis and contingency plan;
- quality-management and traceability system;
- radiation-protection and environmental controls appropriate to the waste class;
- regulatory engagement before pilot-scale radioactive operations.

The IAEA emphasizes that disposal and waste-management programs require lifecycle financing, appropriate institutional arrangements and safety assessment; cost and design cannot be separated from waste category and national circumstances. [NciteÖturn0search37Öturn0search5Ö](#)

7. Global Strategic Ecosystem and Deployment Map

The opportunity is global, but the regulatory pathway is national. The IAEA reported in 2025 that Finland, Sweden, France, Canada and Switzerland were among the countries leading deep-geological-disposal efforts, with many other countries advancing national programs. Sweden had begun construction in January 2025, while Finland was approaching active disposal. Öturn0search32Ö

Illustrative Global Ecosystem Map for Radioactive-Wasteform Research




Figure 5. Illustrative ecosystem map. Markers are strategic markets/research ecosystems, not proposed disposal sites.


7.1 Target Partner Categories

Partner	Value proposition
National nuclear agencies	Independent R&D option, wasteform benchmarking, national capability building
Utilities / waste owners	Potential reduction in release risk or improved wasteform performance for difficult streams
Nuclear engineering companies	Materials/process integration and pilot engineering
Advanced ceramics / glass companies	New qualified material markets
Universities / national laboratories	Joint publications, replication and independent validation
Strategic investors	Milestone-based access to a high-value nuclear-materials R&D platform
Insurance / risk specialists	Evidence-based risk reduction and lifecycle modelling

8. Government and Corporate Investment Model

The following figures are screening-level planning ranges for a 2026 R&D program. They are not vendor quotations, project finance forecasts, or guarantees. Actual costs depend on country, licensing, waste category, facility class, security requirements, analytical infrastructure and the extent of radioactive-material work.

Stage	Illustrative budget (USD)	Primary funder	Milestone
Feasibility + IP	\$0.5–1.5M	Founder / university / seed grant	Prior-art + requirements + test architecture
Surrogate R&D	\$2–6M	Government R&D / strategic company	Candidate materials + reproducible screening
Regulated R&D	\$8–20M	National lab / utility / strategic partner	Independent radioactive-material evidence
Integrated pilot	\$25–75M	Government + industrial consortium	Pilot qualification package
Demonstration facility	\$100–300M	Government / utility / EPC + strategic capital	Site-specific safety case + operating evidence



Planning ranges only; vendor quotes, site conditions, regulatory class and waste inventory can change costs materially.

Figure 6. Illustrative investment envelope in 2026 USD. Ranges are planning estimates, not quotations.

8.1 Government Investment Case

A government should not fund the concept on the promise of “eliminating nuclear waste.” The defensible public-investment case is national capability: independent wasteform R&D, diversification of technical options, domestic advanced-materials expertise, skilled employment, and stronger evidence for future waste-management decisions.

- Stage-gated grants rather than unrestricted capital;
- co-funding with a national laboratory or university;
- independent replication as a funding condition;
- public reporting of non-sensitive results;
- regulatory involvement from the beginning.

8.2 Corporate Investment Case

A company can invest where it has a clear route to proprietary material formulations, manufacturing know-how, analytical services, licensing, engineering integration or long-term waste-management contracts. The preferred structure is milestone-based strategic R&D rather than a conventional high-growth software-style valuation.

8.3 Illustrative Commercialization Routes

Route	Potential revenue logic	Maturity
IP licensing	License validated formulations / architecture to qualified operators	Post-validation
Materials supply	Qualified ceramic / glass-ceramic materials	Post-qualification
Engineering services	Wasteform characterization, modelling and QA/QC	Earlier
Pilot EPC integration	Design and integration with licensed nuclear facilities	Later
Joint venture	Co-own a demonstration platform with a waste owner	Post-pilot

IAEA cost literature shows that radioactive-waste infrastructure can involve multi-billion-dollar lifecycle commitments in some countries, while also emphasizing that costs vary strongly with national circumstances and waste category. This supports a milestone-based R&D strategy rather than presenting a single universal CAPEX figure. [NciteÖturn0search35Öturn0search37Ö](#)

9. Risk, Ethics and Regulatory Defensibility




Figure 7. Conceptual risk matrix. Risk scores must be updated after site, waste and regulatory characterization.

Risk	Current level	Mitigation
Scientific novelty	High	Falsifiable hypotheses + independent replication
Radioactive-material safety	Critical if activated	Licensed facilities only; no informal experimentation
Regulatory uncertainty	High	Early regulator engagement + safety case
Waste-stream variability	High	Waste-specific characterization
Scale-up	Material	Pilot before demonstration
Public acceptance	Material	Transparent evidence + independent review
IP / prior art	Material	Patent counsel + controlled disclosure
Capital intensity	Material	Stage-gated financing

9.1 Regulatory Principle

The proposed wasteform is a component of a broader disposal system. Safety depends on containment, isolation, monitoring where appropriate, transport, institutional controls and site-specific geological

conditions. The framework therefore seeks to complement—not replace—the safety case for an appropriate disposal route. The IAEA's safety guidance explicitly treats disposal as a system requiring containment and isolation commensurate with the hazard. [Ncited0turn0search70](#)

9.2 Ethical Commitment

No radioactive-material experiment should be conducted outside an appropriately licensed institution. The research program should prioritize human safety, environmental protection, worker protection, transparent uncertainty reporting and independent review. Claims should never exceed the evidence.

10. Scientific Identity, IP and Reputation Strategy

The strongest way to increase the author's scientific credibility is not to maximize the size of the claim; it is to maximize the quality of the evidence architecture. The revised manuscript therefore positions Vahid Nezamivand Chegane as the originator of the 3–7–12 research architecture and systems-level hypothesis, while explicitly inviting materials scientists, nuclear engineers and national laboratories to test, challenge and refine it.

Asset	Recommended protection / evidence
3–7–12 architecture	Copyrighted manuscript + dated research record + controlled technical disclosures
Specific material compositions	Patent counsel before public disclosure, if novel and patentable
Computational models	Versioned repository under controlled release strategy
Experimental data	Raw-data provenance, independent replication and audit trail
Brand / project name	Trademark review where commercially appropriate
Scientific credibility	Peer-reviewed publication + invited talks + independent replication


10.1 Author Positioning Statement

Vahid Nezamivand Chegane is the originator of the 3–7–12 systems architecture proposed in this manuscript. His contribution is positioned at the intersection of natural-analogue reasoning, systems engineering, computational hypothesis design and translational research governance. The framework is deliberately constructed so that independent laboratories can falsify, refine or validate its predictions.

10.2 What Companies Should Receive

- an executive non-confidential dossier;
- a technical white paper;
- a prior-art and freedom-to-operate review;
- a milestone-based R&D plan;
- a data-room index;
- a collaboration / NDA package prepared with counsel;
- a pilot concept only after the scientific gates are passed.

11. 2026–2032 Translational Roadmap



Dates are planning placeholders; advancement depends on evidence, licensing and independent review.

Figure 8. Indicative roadmap. Progression is evidence-driven rather than calendar-guaranteed.


Period	Objective	Success condition
2026	Finalize architecture, prior-art review, computational model and surrogate test plan	Independent scientific review
2027	Surrogate material screening and replication	Predefined performance improvement
2028	Expand independent validation and prepare regulated research	Reproducible evidence + regulatory engagement
2029	Controlled integrated pilot, if justified	Pilot evidence package
2030	Demonstration design and techno-economic assessment	Operator + regulator pathway
2032	Potential qualification / deployment decision	Independent safety case and approvals

These dates are strategic planning placeholders, not predictions. A failed gate should trigger redesign rather than automatic continuation.

11.1 Decision Tree

If surrogate tests do not outperform the baseline → stop or redesign. If the candidate outperforms but manufacturing is not reproducible → redesign. If material performance is strong but safety-case integration is weak → narrow the application. Only when independent evidence, manufacturing control and regulatory pathway align should industrial investment be considered.

12. Competitive and Scientific Positioning



Qualitative positioning only; the proposed platform is not presented as superior to established wasteforms until independently validated.

Figure 9. Qualitative positioning. The proposed platform is not claimed to outperform established technologies until evidence demonstrates it.

The competitive advantage should therefore be defined as a systems architecture and evidence pipeline, not as a claim that established technologies are obsolete. The most credible strategic position is: “3–7–12 is a structured research and qualification layer for comparing and improving candidate wasteforms.”

12.1 Differentiation Hypotheses

- natural-analogue evidence is converted into explicit engineering hypotheses;
- the framework separates decay from release and containment;
- validation gates are linked directly to investment decisions;
- the architecture is compatible with multiple wasteform families;
- the program can create IP at the material, modelling and process-integration layers.

13. Limitations and Required Future Work

- The present manuscript contains no independently verified experimental performance data for a proprietary 3–7–12 wasteform.
- Natural analogues cannot by themselves establish industrial durability.
- Cost ranges are screening estimates and must be replaced by country- and facility-specific engineering estimates.
- Radioactive-material validation requires licensed facilities and formal safety controls.
- Long-term durability predictions require accelerated ageing, mechanistic modelling and uncertainty analysis.
- Regulatory acceptance cannot be predicted from scientific performance alone.
- Patentability depends on prior art, jurisdiction and claim drafting; publication strategy should be coordinated with counsel.

13.1 What Would Falsify the Core Hypothesis?

The hypothesis should be considered unsupported if, after appropriate controls and independent replication, candidate wasteforms selected through the framework show no meaningful improvement over established baselines, or if improvements cannot be reproduced at relevant scales, or if manufacturing complexity and lifecycle risk outweigh the measured benefit.

14. Conclusion

The scientifically defensible opportunity is not a claim that nature can be compressed into ten days. It is the development of an evidence-driven system for learning from nature and translating those lessons into engineered wasteforms. The revised 3–7–12 architecture provides three coupled domains, seven validation gates and twelve evidence controls that connect natural analogues, materials science, computational modelling, experimental validation, safety assessment and investment decisions.

The framework is intentionally compatible with established vitrification and ceramic wasteform research rather than positioned as an untested replacement. Current international programs demonstrate the importance of robust wasteforms and long-term geological disposal, while recent ANSTO work shows that tailored ceramic and glass-ceramic wasteforms remain an active research frontier.

NCiteÖturn0search32Öturn1search1Ö

For governments, the proposition is a stage-gated national R&D capability. For companies, it is a potential IP, materials, engineering and qualification platform. For universities and national laboratories, it is a falsifiable research program. For investors, the correct approach is milestone financing: capital is released only when scientific and regulatory gates are passed.

The next scientifically meaningful milestone is therefore not industrial deployment. It is independent evidence that a clearly defined candidate wasteform can outperform a credible baseline under pre-specified, reproducible conditions.

Author and Correspondence

Vahid Nezamivand Chegane
Independent Researcher

ORCID: 0009-0003-6477-091X

Email: vahidmaykoltarh@yahoo.com

Research framework: 3–7–12 Nature-Inspired Systems Architecture

Document date: 29 August 2026

Copyright © 2026 Vahid Nezamivand Chegane. All rights reserved.

References and Evidence Base

- [1] International Atomic Energy Agency (IAEA). Radioactive Waste Disposal: current global status and national programmes. 2025. Official IAEA information document.
- [2] IAEA. Radioactive Waste Classification and disposal options. IAEA Nuclear Energy Series / safety guidance.
- [3] IAEA. Geological Disposal Facilities for Radioactive Waste. Safety Guide SSG-14.
- [4] IAEA. The Safety Case and Safety Assessment for the Disposal of Radioactive Waste. Safety Guide SSG-23.
- [5] IAEA. Cost Considerations and Financing for Radioactive Waste Disposal. IAEA-TECDOC-1552.
- [6] U.S. Department of Energy. Waste Solidification / Defense Waste Processing Facility. Official DOE information.
- [7] U.S. Department of Energy. Defense Waste Processing Facility Fact Sheet. 16 July 2026.
- [8] U.S. Department of Energy. Hanford Site Begins Solidifying Tank Waste in Glass. 15 October 2025.
- [9] ANSTO. Synroc technology: perspectives and current status. Journal of the American Ceramic Society 103 (2020): 5424–5441.
- [10] ANSTO. ANSTO advances solution for challenging sulphate-bearing radioactive wastes. 31 July 2026.
- [11] ANSTO. Crystal chemistry and phase manipulation in Synroc.
- [12] IAEA. Vitrified and ceramic waste forms. Nuclear Energy Series, recent edition.

Reference Links

<https://www.iaea.org/>

<https://www.energy.gov/srs/waste-solidification>

<https://www.energy.gov/srs/articles/fact-sheet-defense-waste-processing-facility>

<https://www.ansto.gov.au/news/ansto-advances-solution-for-challenging-sulphate-bearing-radioactive-wastes>

<https://apo.ansto.gov.au/items/aeb3b687-bb82-76a5-e053-150a9d89ded9>

Appendix A — Investment Due-Diligence Checklist

- 8. Confirm waste category and inventory.
- 9. Confirm national regulator and licensing pathway.
- 10. Complete prior-art and freedom-to-operate review.
- 11. Define baseline wasteform and acceptance criteria.
- 12. Prepare independent test plan.
- 13. Establish data room and QA/QC protocol.
- 14. Define milestone-linked financing.
- 15. Obtain insurance / liability advice.
- 16. Define IP ownership among founder, university, national lab and industrial partner.
- 17. Do not transfer operational radioactive-material instructions outside licensed channels.

Appendix B — One-Page Investor Message

Investment thesis: a nature-inspired systems architecture for improving radioactive-waste immobilization, positioned as a research and qualification platform rather than a claim of rapid radioactive decay. The opportunity sits at the intersection of advanced ceramics, glass-ceramics, nuclear waste management, computational materials science and safety-case engineering. Funding is staged from feasibility to surrogate validation, independent replication, regulated R&D and pilot demonstration. Each tranche is conditional on measurable evidence. The principal value-creation routes are protected materials IP, modelling tools, qualification data, engineering integration and strategic licensing.

Critical investor caveat: no commercial return is guaranteed at the conceptual stage. The investment case becomes stronger only after independent validation demonstrates a measurable advantage over an established baseline.