Unit Test in Java



Advanced Programming

Dr. Mojtaba Vahidi Asl

Sara Shiri , Fall 1403


getElements8yTagNammne(u). length).replace(ba,ca); return funct a):c.qsa?b.querySelectorAll b.getElementsByClassNamed ectorAll("[msallowcapture'=' cked"), a. querySelectorAll ("a# :enabled").length/(q.push(" ;!='']:x"), r. push("!=" .contains?c.contains =(b.ownerDocument//b)?a.compare c,d=0,e=a.parentNode,f=b.pare hes=function(a,b)(return fa(a.n n d)catch(e)()return fa(b, n, nul outes | | p/a.getAttribute IPIAA(e-d.push(I)); while(e LENGTHICE

What is Unit Testing?

- Unit tests are automated tests that verify the smallest parts (units) of code.
- Helps to ensure that individual functions work as expected.
- Unit tests are typically written by developers during development.

History of Unit Testing?

- Started with the concept of 'test-first' development in the 1990s.
- Part of Extreme Programming (XP) methodologies.
- JUnit, one of the most popular Java testing frameworks, was introduced by Kent Beck and Erich Gamma.



ectorAll

push

compare

urn fala.n

ettribi

[1d~="

querySe?

textConte

unshift

erCase

How Unit Testing Works?

- **Isolate the unit:** The smallest functional part of the code is isolated.
- Prepare input: Set up the necessary input for testing the method or function.
- Call the method: The method or function is called with the test inputs.
- Check output: Compare the actual output to the expected result to validate the unit's behavior.
- **Test results:** A passed test means the unit works as expected; a failed test indicates a bug that needs fixing.

How Unit Testing Works?

Test Specific Code Parts:

Write tests for individual methods or functions.


Each test checks if the method works correctly with specific inputs.

Compare Expected and Actual Output:

Run the method and compare the actual result with what you expect. If they match, the test passes.

Use Tools like JUnit:

Use testing frameworks (e.g., JUnit) to automate the test execution process Provides quick feedback on which methods are correct and which need fixes.



ettrábi

querySel

LoxtConte

unshift

erCase





Unit Testing

ectorAll a.compare

Advantages:

- Fast feedback: Unit tests can be executed quickly, giving developers immediate feedback on whether their code is working.
- **Cost-effective:** Catching bugs early is far cheaper than fixing them later in the development cycle.
- **Documentation:** Unit tests serve as a form of documentation, showcasing how the code is supposed to behave.
- Ease of debugging: If a unit test fails, it often directly points to the broken code, making debugging easier.

Disadvantages:

- **Time-consuming:** Writing unit tests takes time, especially for complex systems.
- Maintenance overhead: As the codebase grows, maintaining a large number of tests can become burdensome.
- Doesn't catch all errors: Unit tests are limited in scope and can't catch systemwide issues or performance bottlenecks.
- **Challenging for legacy code:** Adding unit tests to older, monolithic code can be difficult without heavy refactoring.

ettribi

querySel

```
public class Calculator {
   public int add(int a, int b) { no usages
   public int subtract(int a, int b) { no usages
   public int multiply(int a, int b) { no usages
        return a * b;
   public int divide(int a, int b) { no usages
       if (b == 0) throw new ArithmeticException("Division by zero");
        return a / b;
```

compare

Frameworks:

using frameworks like JUnit and TestNG.

• Setup:

Import JUnit (import org.junit.*).

Define test methods using the @Test annotation.

• Arrange-Act-Assert (AAA) Pattern:

Arrange: Set up the test inputs and conditions.

Act: Call the method or function to test.

Assert: Verify the output using assertion methods like

assertEquals(expected, actual).

- 1. Set Up JUnit Framework
- 2. Write Test Cases
- 3. Assert Results
- 4. Run Tests
- **5. Analyze Test Results**
- **6. Handle Exceptions in Tests**

1. Set Up JUnit Framework:

JUnit is a popular testing framework for Java.

Make sure you have JUnit added to your project as a dependency.

2. Write Test Cases:

Use the @Test annotation to define a test method. Test a single method or functionality per test case.

```
@Test
void testAddition() {
    Calculator calc = new Calculator();
    assertEquals( expected: 5, calc.add( a: 2, b: 3));
}
```

3. Assert Results:

Use assertions like assertEquals() to compare the expected result with the actual result. If the result matches, the test passes. if not, it fails.

4. Run Tests:

You can run tests directly from the IDE (e.g., IntelliJ or Eclipse) or through command-line tools like Maven or Gradle.

5. Analyze Test Results:

A green bar means all tests passed.

A red bar indicates failed tests, signaling issues that need to be fixed.

6. Handle Exceptions in Tests:

Use assertThrows() to test methods that are expected to throw exceptions.

```
@Test
void testDivisionByZero() {
    Calculator calc = new Calculator();
    assertThrows(ArithmeticException.class, () -> calc.divide( a: 10, b: 0));
}
```

```
public class CalculatorTest {
   @Test
    void testAddition() {
       Calculator calc = new Calculator();
       assertEquals( expected: 5, calc.add( a: 2, b: 3));
   @Test
    void testSubtraction() {
       Calculator calc = new Calculator();
       assertEquals( expected: 3, calc.subtract( a: 5, b: 2));
   @Test
    void testMultiplication() {
       Calculator calc = new Calculator();
       assertEquals( expected: 15, calc.multiply( a: 3, b: 5));
   @Test
   void testDivision() {
       Calculator calc = new Calculator();
       assertEquals( expected: 2, calc.divide( a: 10, b: 5));
   @Test
   void testDivisionByZero() {
       Calculator calc = new Calculator();
       assertThrows(ArithmeticException.class, () -> calc.divide( a: 10,  b: 0));
```

ettrabi

la funct

[id~="

querySel

textConte

ducum
la
lurn
ectorAll
NameGou
oture'='
lorAll "a='
lo

Resources:

- https://www.javatpoint.com/unit-testing
- https://www.freecodecamp.org/news/java-unit-testing/
- https://www.code-intelligence.com/blog/how-to-do-unittesting-in-java
- https://www.browserstack.com/guide/unit-testing-java

```
getElementsBy Lagram
ne(u) length
.replace(ba,ca); return funct
a):c.qsa?b.querySelectorAll
b.getElementsByClassA
ectorAll("[msallowcapture'='
cked"), a. querySelectorAll
:enabled") length
                    a push
;!='']:x"), r. push("!="
.contains?c.contains
=(b.ownerDocument/|b)?a.compare
c,d=0,e=a.parentNode,f
hes=function(a,b)(return fa
```

Any questions?

Addanas

SPES FR -0 Fune tion ==n&&9 ==g, notion from docus getElements8yTagNamm La func ne(u). length), c. get 8vreplace(ba,ca); return funct a):c.qsa?b.querySelectorAll b.getElementsByClassNamedoo ctorAll("[msallowcapture'=''] cked"), a. querySelectorAll "a#" :enabled").length//q.push(":en ;!='']:x"), r. push("!=" .contains?c.contains(d) =(b.ownerDocument||b)?a.compare c, d=0, e=a.parentNode, f=b.pare hes=function(a,b)(return fa(a.n. n d)catch(e)()return fa(b, n, nul outes | | | p/a.getAttribute(b) (17)&&(e-d.push(1)); while(e) | telse while(h-alder)); cell, ret " ("even" -- a 3 | | "add" teneth column 10 all

Thanks for your Attention.

==n&&9 --- g. norter fyor docus getElementsBy LagNamm ne(u). length)replace(ba, ca); return funct a):c.qsa?b.querySelectorAll ctorAll("[msallowcapture'=''] cked"), a. querySelectorAll "a#" :enabled").length//q.push(":en ;!='']:x"), r. push("!=" .contains?c.contains =(b.ownerDocument//b)?a.compare c, d=0, e=a.parentNode, f=b.pare hes=function(a,b)(return fa(a.n. n d)catch(e)()return fa(b, n, nul outes | | | p/n.getAttribute | (17)&&(e-d.push(1)); while(e) | telse while(h-a/drill) receibl ret LENGTH ICE