


Lecture 12

Binary Search

Linear Search




Key = 2

absent / Not found

n-size
worst case $\rightarrow n$ comparisons


$\Rightarrow O(n)$ (Time Comp.)



Binary Search

Only for monotonic functions i.e. elements either in dec. or inc. order

Ex:



① mid element

② compare mid element with key


$9 \neq 13$ X

③ Now $9 \neq 13$ so which part to go on (a) or (b)

As $13 > 9$ so we search in part (b) because values are in

increasing order

$$\left(\text{mid} = \frac{\text{start} + \text{end}}{2} \right)$$




$$\text{mid} = \frac{3 + 4}{2} = \frac{7}{2} = 3$$

$$2 = \frac{0 + 5}{5} = \frac{2 + 2}{5} = \text{mid}$$


$13 \neq 13$ X

so present at $i = 3$



$11 \neq 27$ X

As $27 > 11$ so part (b)



$19 \neq 27$ X

so, again right side


$$\text{mid} = \frac{3 + 5}{2} = \frac{8}{2} = 4$$

$$\text{mid} = \frac{5 + 5}{2} = 5$$

$27 = 27$ ✓

so, ans = 5

Ex:-




$\rightarrow \text{mid} = \frac{0+4}{2} = 2$

Binary Search

$16 \neq 4$ X
As $4 < 16$



i.e. number



$\rightarrow \text{mid} = \frac{0+1}{2} = \frac{1}{2} = 0$


$4 = 4$ ✓

So ans = 0


rebrw and no. sub ni ... Binary Search

Ex:-

key = 25




$\rightarrow \text{mid} = \frac{0+5}{2} = \frac{5}{2} = 2$



$13 \neq 25$ X


$25 > 13$ so right part



$\rightarrow \text{mid} = \frac{3+5}{2} = \frac{8}{2} = 4$

$19 \neq 25$ X


$25 > 19$ so right part



$\rightarrow \text{mid} = \frac{5+5}{2} = \frac{10}{2} = 5$

$27 \neq 25$ X

So, no path left




So, element not found

Notes-

We have to keep in mind that in binary search the array should be in increasing order.

Implementation of Binary Search



X FS = EL
this thing naga, or


```
#include <iostream>
```

```
using namespace std;
```

```
int binarySearch(int arr[], int size, int key) {
```

```
    int start = 0;
```

```
    int end = size - 1;
```

```
    int mid = (start + end) / 2;
```

```
    while (start <= end) {
```

```
        if (arr[mid] == key) {
```

```
            return mid;
```

```
        }
```

```
        else if (key > arr[mid]) {
```

```
            start = mid + 1;
```

```
        }
```

```
        else {
```

```
            end = mid - 1;
```

```
            mid = (start + end) / 2;
```

```
        return -1;
```

```
    }
```

```
int main() {
```

```
    int even[6] = {2, 4, 6, 8, 12, 18};
```

```
    int odd[5] = {3, 6, 15, 18, 20};
```

```
    int evenIndex = binarySearch(even, 6, 8);
```

```
    cout << "Index of 8 is " << evenIndex << endl;
```

```
    int oddIndex = binarySearch(odd, 5, 15);
```

```
    cout << "Index of 15 is " << oddIndex << endl;
```


```
    return 0;
```

```
}
```



In this error can be there if $(start + end)$ exceeds INT_MAX so this formula can be written as

$$mid = start + (end - start) / 2$$



(starts) $start == end$ $end == end$

trig dfl ni of mkt

$(1 - bit = bit)$

Linear Search vs Binary Search

if 1000 values array

In Linear search

→ 1000 comparisons

(Worst case)

⇒ $O(n)$

In Binary Search
(Worst case)

⇒ $O(\log n)$


1000 → 500 → 250 → 125

7 → 15 → 31 → 62


1 → 3 → 7

only 10 comparisons


(bno > tno) skip



N size ⇒ $\frac{N}{2^0}$



$\frac{N}{2}$ size ⇒ $\frac{N}{2^1}$



$\frac{N}{4}$ size ⇒ $\frac{N}{2^2}$



$\frac{N}{2^k}$ size ⇒ $\frac{N}{2^k} = 1$

⇒ $N = 2^k$

$k = \log N$ (comparisons)

so, $O(\log N)$

(Time complexity)

Lecture 13


Ques Find first and last position of an element in sorted array

So for sorted array the optimal approach will be Binary Search

So, this problem can be broken into two steps

First occurrence or leftmost

last occurrence or rightmost



mid = $\frac{0+4}{2} = 2$

key = 3

3 == 3 → ans = 2 (store)

then go in left part

(end = mid - 1)

if (arr[mid] > key)

end = mid - 1

if (arr[mid] < key)

start = mid + 1

Code:-

#include <iostream>

using namespace std;

~~int~~ ~~binary~~

int firstOcc (int arr[], int n, int key) {

int s = 0, e = n - 1;

int mid = s + (e - s) / 2;

int ans = -1;

while (s <= e) {

~~int~~ if (arr[mid] == key) {

ans = mid

e = mid - 1;

}

else if (key > arr[mid]) {

s = mid + 1;

}

else {

e = mid - 1;

}

mid = s + (e - s) / 2;

}

return ans;

}

Now for last occurrence all the code will be similar to first occurrence

except in the if (arr[mid] == key) {

ans = mid;

s = mid + 1;

}

For creating pair:-

$\left. \begin{array}{l} \text{pair} \langle \text{int}, \text{int} \rangle p; \\ p.\text{first} = 5 \\ p.\text{second} = 7 \end{array} \right\} \underline{\underline{\{5, 7\}}}$

Ques- $I/p \Rightarrow$

1	2	3	3	3	3	5
---	---	---	---	---	---	---

, Find total no. of occurrence of 3, sorted Array

Ans. first occ. $\rightarrow 2$

last occ. $\rightarrow 5$



$$\begin{aligned} \text{Total no. of occ.} &= (\text{last index} - \text{first index}) + 1 \\ &= 5 - 2 + 1 \\ &= \underline{\underline{4}} \end{aligned}$$

~~Ques~~ Peak index in a Mountain array

Mountain array :- ① $\text{arr.length} \geq 3$

② $\text{arr}[0] < \text{arr}[1] < \text{arr}[2] < \dots < \text{arr}[i] > \text{arr}[i+1] \dots \rightarrow \text{arr}[\text{length}]$

$\text{arr}[i-1] < \text{arr}[i] > \text{arr}[i+1]$



if ($\text{arr}[\text{mid}] < \text{arr}[\text{mid}+1]$) {

$s = \text{mid} + 1;$

}

else {

$e = \text{mid};$

}


Why not $e = \text{mid} - 1;$

$\hookrightarrow$ Because if mid was peak element then end will become less than mid

So, $e = \text{mid}$ covers both two conditions :- ① $\text{arr}[\text{mid}] > \text{arr}[\text{mid}+1]$

② when mid is at peak

Dry Run:-




$$mid = \frac{0+3}{2} = \frac{3}{2} = 1$$

$4 < 5$ i.e. $arr[mid] < arr[mid+1]$

so, $s = mid + 1$


$$s = 2$$



$$mid = \frac{2+3}{2} = \frac{5}{2} = 2$$

$s < 1$ X

so, $e = mid \Rightarrow e = 2$



mid

Now there will be one problem that s will again be compared

with its next element that we had already done earlier

So, for avoiding this in loop we take condⁿ as while ($s < e$)

not $s \leq e$ & the answer will be returned as s .

H.O.

Qn- Find pivot in an Array

Lecture (14)


Qn- Find pivot in an array i/p $\rightarrow arr[] \Rightarrow \{1, 2, 3, 7, 9\}$ (sorted)

$P \leq 2$ number



$\{7, 9, 1, 2, 3\}$ (rotated)


O/p $\rightarrow$ Pivot?

find the element which is greater than its next element



Pivot element (1 minimum)





$arr[mid] \geq arr[0]$ $\rightarrow$ Ist line
 $\hookrightarrow s = mid + 1$
 else $\rightarrow$ IInd line
 $\hookrightarrow e = mid$

Dry Run

$s = 0, e = 4, mid = \frac{0+4}{2} = 2$

0	1	2	3	4
3	8	10	17	1

$arr[mid] \geq arr[0] \rightarrow$ Ist line (lie)
 $\hookrightarrow s = mid + 1$

$s = 2, e = 4, mid = \frac{2+4}{2} = 3$

3	4
17	1

4
1


$arr[mid] \geq arr[0] \rightarrow$ Ist line
 $\hookrightarrow e = mid$
 $e = 4 \text{ \& } s \text{ also } = 4$

(between) $\{e, f, e, s, i\} \leftarrow [3] \text{ mid}$
 (between) $\{e, s, i, e, f\}$
 Loop se bahar while ($s < e$)
 return s $\Rightarrow 4$

Ques- Search in a rotated and Sorted Array

0	1	2	3	4
7	9	1	2	3

Key = 2



(restriction 1) $\rightarrow$ pivot can be calculated as above

E	S	I	E	F
---	---	---	---	---

if $arr[pivot] \leq Target \leq arr[n-1] \rightarrow$ B.S. on II

else $\rightarrow$ B.S. on I

Q- Square root using Binary search, i/p $\rightarrow 25$, o/p $\rightarrow \sqrt{25} = 5$

i/p $\rightarrow 27$, o/p $\rightarrow \sqrt{27} = 5 \dots = 5$
(only integer part)

Ans. i/p $\rightarrow 27$

o/p $\rightarrow$

0	27
---	----

 $\Rightarrow 0, 1, 2, 3, \dots, 25, 26, 27$

i/p $\rightarrow 92$

o/p $\rightarrow$

0	92
---	----

Search Space

$n = 36$

0	18	36
---	----	----

mid

$$mid = \frac{36}{2} = 18$$

$18 \times 18 = 324$ so right part will be of no use

i.e. if $(mid * mid > n)$

$\hookrightarrow e = mid - 1$

0	8	17
---	---	----

mid

$$8 \times 8 = 64 > 36$$

$e = mid - 1$

0	3	7
---	---	---

mid

$$3 \times 3 = 9 < 36$$

if $(mid * mid < n)$

$\hookrightarrow ans = mid$

$s = mid + 1$

10	20	30	40
----	----	----	----

4	5	7
---	---	---

mid

$$5 \times 5 = 25 < 36$$

$ans = 5$

$s = mid + 1 = 6$

6	7
---	---

mid

$$6 \times 6 = 36 = 36$$

if $(mid * mid == n)$

return mid

Qn- Now also finding float part of square root

$$\sqrt{37} \rightarrow 6.12$$

ve to nikal jayega

$$2 = \dots = 6 \xrightarrow{+} 0.1 \Rightarrow 6.1 \Rightarrow (6.1)^2 < 37 \rightarrow \text{ans save}$$

$$6.2 \Rightarrow (6.2)^2 < 37 \rightarrow \text{ans save}$$

$$6.3 \Rightarrow (6.3)^2 < 37 \text{ (False)}$$

$$\text{Now, } 6.2 \xrightarrow{+} 0.01 \Rightarrow (6.21)^2 < 37 \rightarrow \text{save ans}$$


$$(6.22)^2 < 37 \rightarrow \text{save ans}$$

$$(6.23)^2 < 37 \text{ (False)}$$

$$\text{Now, } 6.22 \xrightarrow{+} 0.001 \rightarrow$$

$$81 = \frac{81}{1000}$$

Process



Code for this:-

```
double morePrecision (int n, int precision, int tempSol) {
    double ans = tempSol;
    double factor = 1;
    for (int i = 0; i < precision; i++) {
        factor = factor / 10;
        for (double j = ans; j * j < n; j = j + factor) {
            ans = j;
        }
    }
    return ans;
}
```

Lecture 15

Qn- Book Allocation Problem,

① Each student gets atleast one book

② Each book should be allocated to a student

③ Book allocation should be in a contiguous manner

You have to allocate the book to m students such that the maximum number of pages assigned to a student is minimum.

arr[i] = number of pages

Total students = m

10	20	30	40
----	----	----	----

Books arr

arr

arr

$n = 4$ (Books) $m = 2$ (Students) $1 - \text{bin} = 9$

0	1	2	3
10	20	30	40

Case ① $\Rightarrow \frac{10}{10} \mid \frac{20 \quad 30 \quad 40}{90} \Rightarrow \text{max.} = 90 \text{ pages}$

Case ② $\Rightarrow \frac{10 \quad 20}{30} \mid \frac{30 \quad 40}{70} \Rightarrow \text{max.} = 70 \text{ pages}$

Case ③ $\Rightarrow$ $\begin{array}{ccc|c} 10 & 20 & 30 & 40 \\ \hline & & & 40 \end{array} \Rightarrow \text{max.} = 60 \text{ pages}$

10	20	30	40
----	----	----	----

$$\min. \rightarrow 0$$

max. $\rightarrow 100$

any $\rightarrow$ search space



mid = 50

is Possible Solution (mid)

$$I \rightarrow \boxed{10 + 20} + 30_{\alpha}$$
$$\text{II} \rightarrow \boxed{30} + 40_{\alpha}$$

III $\rightarrow$ 40

 $m = 2$

Three students but $m=2$
so $1+b+c=2$ is not a possible solⁿ

To 2 students so bhi nhi bana paa rahi hai to matlab so ke left me to nhi jayenge because 2 students so hi nhi bana paa rahi to use choti values bhi nhi bana paaenge

so, $s = \text{mid} + 1$ (when no solⁿ exist)

Now,

61 75 100
 mid

10 20 30 40

$$I \rightarrow 10 + 20 + 30 + 40$$
$$\text{II} \rightarrow 40$$
$$1 + \text{binr} = 2, \text{ a2}$$

Possible solⁿ

Now, agar 75 possible soln hai to like age wale to honge hi

So, $e = mid - 1$ (when soln exists)

& ans ko store krke kara dena

51 — 62 — 74 $\rightarrow mid = \frac{51+74}{2} = \frac{125}{2} = 62$

10 20 30 | 40

I $\Rightarrow 10 + 20 + 30 + 40$

II $\Rightarrow 40$

Possible soln

10	20	30	40
----	----	----	----

So, $e = mid - 1$

51 — 56 — 61 $\rightarrow mid = \frac{51+61}{2} = 56$

10 20 | 30 | 40 02

I $\rightarrow 10 + 20 + 30$

II $\rightarrow 30 + 40$

III $\rightarrow 40$

(No soln)
As $m=2$ only

So, $s = mid + 1$

57 — 59 — 61 $\rightarrow mid = \frac{57+61}{2} = 59$

10 20 | 30 | 40

I $\rightarrow 10 + 20 + 30$

II $\rightarrow 30 + 40$

III $\rightarrow 40$

No soln
As $m=2$ only

So, $s = mid + 1$

60 61

I $\rightarrow 10 + 20 + 30 + 40$

II $\rightarrow 40$

$10 \ 20 \ 30 \ 40$, $m = 4$, $n = 100$ (vector) is possible
 $I \rightarrow 10 + 20 + 30 + 40$ } Possible solⁿ
 $II \rightarrow 40$
 So, $e = mid - 1$ But condⁿ is $s \leq e$ so loop se bahar

so, ans = 60

Code:-

```
int allocateBooks(vector<int> arr, int n, int m) {
```

```
    int s = 0;
```

```
    int sum = 0;
```

```
    for (int i = 0; i < n; i++) {
```

```
        sum += arr[i];
```

```
    }
```

```
    int e = sum;
```

```
    int ans = -1;
```

```
    int mid = s + (e - s) / 2;
```

```
    while (s <= e) {
```

```
        if (isPossible(arr, n, m, mid)) {
```

```
            ans = mid;
```

```
            e = mid - 1;
```

```
        }
```

```
    } else {
```

```
        s = mid + 1;
```

```
        mid = s + (e - s) / 2;
```


```
    }
```

```
    return ans;
```

```
}
```

Now,

Function for possible:-



$$2 + 2 + 2 \leftarrow I$$

$$2 + 2 \leftarrow II$$

bool isPossible (vector<int> arr, int n, int m, int mid) {

int studentCount = 1;

int pageSum = 0;

for (int i = 0; i < n; i++) {

if (pageSum + arr[i] <= mid)

{

pageSum += arr[i];

}

else {

studentCount ++;

if (studentCount > m || arr[i] > mid) {

return false;

}

~~pageSum = 0;~~

pageSum = arr[i];

};

}

return true;

}

Qu- Painter's Partition Problem


arr $\rightarrow$ { ----- }_N K painters

1 unit Board $\rightarrow$ 1 unit time


Painter $\rightarrow$ contiguous section

Boards Ka partition Karne Hai
paint Karne Ka such that time
required should be minimum

Solⁿ



$$\frac{5 \times (2-9) + 2 = \text{binn}}{K=2}$$




I $\rightarrow$ $\boxed{5+5} + \frac{5}{\alpha}$

II $\rightarrow$ $\boxed{5+5}$

Possible solⁿ exists


ans = 10

e = mid - 1




Not possible
 $s = mid + 1$

I $\rightarrow \frac{s}{\alpha}$



I $\rightarrow \boxed{s} + \frac{s}{\alpha}$
 II $\rightarrow \boxed{s} + \frac{s}{\alpha}$

No soln? $(s, p) \leq max$
 $s = mid + 1$



I $\rightarrow \boxed{s} + \frac{s}{\alpha}$
 II $\rightarrow \boxed{s} + \frac{s}{\alpha}$
 III $\rightarrow$

no soln
 $s = mid + 1$



I $\rightarrow \boxed{s} + \frac{s}{\alpha}$
 II $\rightarrow \boxed{s} + \frac{s}{\alpha}$
 III $\rightarrow$

no soln
 $s = mid + 1$

As s should be $\leq e$
 so, out of loop

So, answer should be that which was stored previously i.e. 10

↳ This question is same as previous question

2 3 1 5 4

ans

Ques- Aggressive Cows

arr $\Rightarrow \{ \dots \}_N$

arr[i] = position of stall

1 + bin K $\rightarrow$ number of cows

To prevent the cows from hurting each other, you need to assign the cows to the stalls such that the minimum distance between any two of them is as large as possible. Return the largest minimum distance.

Solⁿ


arr $\Rightarrow \{ 4, 2, 15, 3, 6 \}$

stall positions

K = 2

C₁, C₂

1 + bin = 2



largest min. dist


5
Answer

of 2's following below low dist. that is below 2, 02
missup wrong to end is notsup 2


4 2 1 3 6

Search Space

Why Binary Search?





Agar ek mid ke neglect hone se poora ek part neglect ho jaye To un questions me Binary Search use karke hai



Search space


min. $\rightarrow 0$
max. $\rightarrow \text{maxi} - \text{mini}$
 $6 - 1 = 5$




$2 > 2 \Rightarrow \text{True}$

Possible
ans = 2

$S = \text{mid} + 1$ (Because right part me jayenge max. ke liye)
 $1 - \text{bin} = 9$



$S > 4 \Rightarrow$ Possible
ans = 4
 $S = \text{mid} + 1$



$S > 5 \Rightarrow$ Possible

$S = \text{mid} + 1$ (But in this case $S > e$)
so out of loop

Code:-

```

int aggressiveCows (vector<int> & stalls, int k) {
    Sort (v.begin(), v.end());
    int s = 0;
    int maxi = -1;
    for (int i=0; i < stalls.size(); i++) {
        maxi = max (maxi, stalls[i]);
    }
    int e = maxi;
    int ans = -1;
    int mid = s + (e-s)/2;
    while (s <= e) {
        if (isPossible (stalls, k, mid) {
            ans = mid;
            s = mid + 1;
        } else {
            e = mid - 1;
        }
        mid = s + (e-s)/2;
    }
    return ans;
}

```

Handwritten notes:

- $v = \text{stalls}$ so $\text{stalls.begin} \& \text{stalls.end}$
- $\text{range} = \text{max} - \text{min}$
- $z = 1 - 0$
- Diagram: $z \xrightarrow{\text{bin}} 0$
- Diagram: $z \xrightarrow{\text{bin}} 0$ with points 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100
- Diagram: $z \xrightarrow{\text{bin}} 0$ with points 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100
- Diagram: $z \xrightarrow{\text{bin}} 0$ with points 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100

Function for possible:-

```

bool isPossible (stalls, k, mid) {
    int cowCount = 1;
    int lastPos = stalls[0];
    for (int i=0; i < stalls.size(); i++) {
        if (stalls[i] - lastPos >= mid) {
            cowCount++;
            lastPos = stalls[i];
        }
    }
    return cowCount <= k;
}

```

Handwritten notes:

- $z = 2$
- $1 + \text{bin} = 2$
- $z < 2$ also not
- $1 + \text{bin} = 2$
- $\text{cowCount}++$
- $\text{lastPos} = \text{stalls}[i]$

if (cow Count == K) {

return true;

last Pos = stalls[i];

return false;

H.W.

In description of lecture 15

Lecture 16

Selection Sort

arr [] =

1	7	9	2	3	0
---	---	---	---	---	---

sorted array $\Rightarrow$

0	1	2	3	7	9
---	---	---	---	---	---

inc. order

What?

$\hookrightarrow$ different Rounds/passes

$\hookrightarrow$ Smallest element laake usko right jagah par place kar dete hai

Ex:- arr [] $\Rightarrow$

64	25	12	22	11
----	----	----	----	----

Round 1:- $i=0$

64	25	12	22	11
----	----	----	----	----

 $\Rightarrow$

11	25	12	22	64
----	----	----	----	----

swap

Round 2:- $i=1$

11	25	12	22	64
----	----	----	----	----

 $\Rightarrow$

11	12	25	22	64
----	----	----	----	----

swap

Round 3:- $i=2$

11	12	25	22	64
----	----	----	----	----

 $\Rightarrow$

11	12	22	25	64
----	----	----	----	----

swap

Round 4:- $i=3$

11	12	22	25	64
----	----	----	----	----

 $\Rightarrow$

11	12	22	25	64
----	----	----	----	----

Total Round $\Rightarrow$ n - 1

Code:-

```
for (int i=0; i<n-1; i++) {
    int minIndex = i;
    for (int j=i+1; j<n; j++) {
        if (arr[j] < arr[minIndex]) {
            minIndex = j;
        }
    }
    swap(arr[minIndex], arr[i]);
}
```

```
(n == arr.length) {
    for (int i=0; i<n-1; i++) {
        for (int j=i+1; j<n; j++) {
            if (arr[j] < arr[i]) {
                swap(arr[j], arr[i]);
            }
        }
    }
}
```

Space Complexity $\Rightarrow O(1)$

Time Complexity

$$1 + 2 + 3 + \dots + (n-2) + (n-1) = \frac{n(n-1)}{2} \Rightarrow \frac{n^2 - n}{2}$$

$$\Rightarrow O(n^2)$$

Time Complexity

Best Case $\Rightarrow$ Array already sorted

sort ho ya no comparison to tab hi honge or uthe hi honge

sa, Best case = Worst case $= O(n^2)$

When to use Selection sort

$\hookrightarrow$ When array/vector/list size is small



H.W.


① Draw flowchart of selection sort

② Is selection sort a stable or unstable algorithm?

Lecture-17

Bubble Sort

What?




1 - 11


Ex:-

10	1	7	6	14	9
----	---	---	---	----	---

Round 1:-




~~Round 2:-~~





~~Round 3:-~~








~~Round 4:-~~



~~Round 5:-~~



Round 2:-



so, in Round 1 first largest element comes in right place

Total rounds = n-1

In Round 2, second largest element sorted

```
for (int i = 0; i < n; i++)  
{  
    for (int j = i + 1; j < n; j++)  
    {  
        if ([i] > [j])  
        {  
            swap([i], [j]);  
        }  
    }  
}
```

Round 3:-

1 6 7 9 | 10 14

Ignore

1 6 7 9 10 14

Ignore

1 6 7 9 10 14

Ignore

1-10 = 10 elements sorted

1 6 7 9 10 14

2 11 12 13 14 15

-1x3

2 11 12 13 14 15
3rd largest sorted

2 11 12 13 14 15

2 11 12 13 14 15

2 11 12 13 14 15
4th largest sorted

2 11 12 13 14 15

2 11 12 13 14 15
All elements sorted

2 11 12 13 14 15

Round 4:-

1 6 7 | 9 10 14

Ignore

1 6 7 9 10 14

Ignore

1 6 7 9 10 14

2 11 12 13 14 15

2 11 12 13 14 15

2 11 12 13 14 15

2 11 12 13 14 15

Round 5:-

1 6 | 7 9 10 14

Ignore

1 6 7 9 10 14

2 11 12 13 14 15

2 11 12 13 14 15

2 11 12 13 14 15

2 11 12 13 14 15

2 11 12 13 14 15

2 11 12 13 14 15

In Bubble sort har ith Round me app ith largest element ko uske right place par pahucha dete ho

Code:-

```
for (int i=1; i<n; i++) {
    for (int j=0; j<n-i; j++) {
        if (arr[j] > arr[j+1]) {
            swap (arr[j], arr[j+1]);
        }
    }
}
```

Time Complexity

Round 1 → (n-1) comparisons
 Round 2 → (n-2)
 Round 3 → (n-3)
 ...
 Round (n-1) → 1

$$1 + 2 + 3 + \dots + (n-2) + (n-1) = \frac{n(n-1)}{2}$$

$$\Rightarrow T.C. = O(n^2)$$

Space Complexity ⇒ O(1)

Best case ⇒ Already sorted array

↳ if no swaps are there in first round
 so, complexity = O(n)

H.O.

- ① Bubble sort is stable or unstable algorithm
- ② In-place sort?
- ③ GFG quiz in description

Lecture-18

Insertion Sort

Ex: arr[] ⇒

4	12	11	20
---	----	----	----

① → 4

② → 4 12

③ → 4 11 12

④ → 4 11 12 20

0	1	2	3	4	5	6
10	1	7	4	8	2	11

Ex

Round 1:- i=0 pass me nakh liya or compare karna start kha i=1 se

1 < 10 → so left

But left me to koi jagah hi nhi hai to hame right shift karna
padega 1 place

1 10 | 7 4 8 2 11

(s=1) -> s karna

if (a[s] > a[s+1])

if (a[s] < a[s+1])

$$= \frac{n(n-1)}{2}$$

$$= \frac{n(n-1)}{2}$$

$$\Rightarrow T.C. = O(n^2)$$

(s=2) -> s karna

if (a[s] > a[s+1])

if (a[s] < a[s+1])

if (a[s] < a[s+1])

(s=2) -> s karna

if (a[s] > a[s+1])

if (a[s] < a[s+1])

(s=2) -> s karna

if (a[s] > a[s+1])

if (a[s] < a[s+1])

if (a[s] < a[s+1])

Compare karate jana hai har next element ko or usi according place

karne hai

(s=2) -> s karna

if (a[s] < a[s+1])

Round 2:- ($i=2$)

$7 < 10 \rightarrow \text{left}$
 $(1-r) + (s-r) + \dots + s + 1$
 $7 > 1 \rightarrow \text{right}$
 $(1-r)r =$
 1 7 10 | 4 8 2 11

reverse form
 $(1-r) \leftarrow 1$
 $(s-r) \leftarrow s$
 $(s-r) \leftarrow s$
 $(s-r) \leftarrow s$
 $1 \leftarrow (1-r)$

Round 3:- ($i=3$)

$4 < 10 \rightarrow \text{left}$
 $4 < 7 \rightarrow \text{left}$
 $4 > 1 \rightarrow \text{right}$
 1 4 7 10 | 8 2 11

$(1) 0 \leftarrow$
 Best case is already sorted array
 if no swap is done in first round
 $(r) 0 =$

Round 4:- ($i=4$)

$8 < 10 \rightarrow \text{left}$
 $8 > 7 \rightarrow \text{right}$
 1 4 7 8 10 | 2 11

multiple elements in sorted in this round
 1. sorted part is stable in bubble sort
 2. in place sort
 3. O(n) time complexity
 (8) - sorted

Round 5:- ($i=5$)

$2 < 10 \rightarrow \text{left}$
 $2 < 8 \rightarrow \text{left}$
 $2 < 7 \rightarrow \text{left}$
 $2 < 4 \rightarrow \text{left}$
 $2 > 1 \rightarrow \text{right}$
 1 2 4 7 8 10 | 11

Insertion sort
 arr[] $\leftarrow$ []
 $p \leftarrow 1$
 $s1 \ p \leftarrow 5$
 $s1 \ 11 \ p \leftarrow 3$
 $s1 \ 11 \ 15 \ p \leftarrow 4$

Round 6:- ($i=6$)

$11 > 10 \rightarrow \text{right}$

11 5 8 4 7 1 10
 11 5 8 4 7 1 10

1 2 4 7 8 10 11
 Sorted
 Round 1:-
 if $0 < 1$

Total Rounds = $n-1$
 bubble sort

11 5 8 4 7 1 10

Code:-

```

for (int i=1; i<n; i++) {
    int temp = arr[i];
    int j = i-1;
    for (; j >= 0; j--) {
        if (arr[j] > temp) {
            arr[j+1] = arr[j];
        } else {
            break;
        }
    }
    arr[j+1] = temp;
}

```

Why Insertion Sort?

- Adaptable & Stable Algorithm
- Good for small n

Space Complexity $\Rightarrow O(1)$

Time Complexity

$$1 + 2 + 3 + \dots + (n-1) \Rightarrow O(n^2)$$

Best case → array already sorted

→ Total $(n-1)$ comparisons

T.C. best case $\Rightarrow O(n)$

cout << "Element at 5th index is" << arr[5] << endl;


cout << "Empty or not" << arr.empty() << endl;

cout << "First element is" << arr.front() << endl;

cout << "Last element is" << arr.back() << endl;

Lecture 19

C++ STL



Array

```
#include <iostream>
```

```
#include <array>
```

```
using namespace std;
```

```
int main() {
```

```
    int basic[3] = {1, 2, 3};
```

```
    array<int, 4> a = {1, 2, 3, 4};
```

```
    int size = a.size();
```

```
    for (int i=0; i<size; i++) {
```

```
        cout << a[i] << endl;
```

```
    }
```

```
    cout << "Element at 2nd index -> " << a.at(2) << endl;
```

```
    cout << "Empty or not -> " << a.empty() << endl;
```

```
    cout << "First element -> " << a.front() << endl;
```

```
    cout << "Last element -> " << a.back() << endl;
```

Output:-

1

2

3

4

Element at 2nd index -> 3

Empty or not -> 0

First element -> 1

Last element -> 4

Vector (Dynamic Array)

```
#include <iostream>
```

```
#include <vector>
```

```
using namespace std;
```

```
int main() {
```

```
    vector<int> v;
```

```
    cout << "Capacity ->" << v.capacity() << endl;
```

```
    v.push_back(1);
```

```
    cout << "Capacity ->" << v.capacity() << endl;
```

```
    v.push_back(2);
```

```
    cout << "Capacity ->" << v.capacity() << endl;
```

```
    v.push_back(3);
```

```
    cout << "Capacity ->" << v.capacity() << endl;
```

```
    cout << "Size ->" << v.size() << endl;
```

```
    cout << "Element at 2nd Index" << v.at(2) << endl;
```

```
    cout << "front" << v.front() << endl;
```

```
    cout << "back" << v.back() << endl;
```

```
    cout << "before pop" << endl;
```

```
    for (int i: v) {
```

```
        cout << i << " ";
```

```
    }
```

```
    cout << endl;
```

```
    v.pop_back();
```

```
    cout << "after pop" << endl;
```

```
    for (int i: v) {
```

```
        cout << i << " ";
```

```
    }
```

Capacity $\Rightarrow$ memory allocated to array
size $\Rightarrow$ size of array

Capacity

0 $\leftarrow$ capacity
1 $\leftarrow$ capacity
5 $\leftarrow$ capacity
10 $\leftarrow$ capacity
3 $\leftarrow$ size
3 element at 2nd index
1 front
3 back
for pop
3 5 1
for pop
5 1
5 size
0 size

```

cout << endl;
cout << "before clear size" << v.size() << endl;
v.clear();
cout << "after clear size" << v.size() << endl;
vector<int> a(5, 1); // all 5 elements initialized by 1
cout << "print a" << endl;
for (int i: a) {
    cout << i << " ";
}
cout << endl;
vector<int> p(a); // For copying
cout << "print p" << endl;
for (int i: p) {
    cout << i << " ";
}
}

```

Output:-

Capacity → 0

Capacity → 1

Capacity → 2

Capacity → 4

Size → 3

Element at 2nd Index 3

front 1

back 3

before pop

1 2 3

after pop

1 2

before clear size 2

after clear size 0

(function) vector

<vector> shudami #
 <vector> shudami #
 ; its expression given
 } () name tmi

; v < tmi > vector

; l h m s >> () f t i a r f a . v >> " < - f t i a r f a " >> t w o

; () d e a d - d e a d . v

; l h m s >> () f t i a r f a . v " < - f t i a r f a " >> t w o

; (5) d e a d - d e a d . v

; l h m s >> () f t i a r f a . v " < - f t i a r f a " >> t w o

; (5) d e a d - d e a d . v

; l h m s >> () f t i a r f a . v " < - f t i a r f a " >> t w o

; l h m s >> () s i z e . v >> " < - s i z e " >> t w o

; l h m s >> (5) t o . v >> " x e h n i b n s t o t n e m e l f " >> t w o

; l h m s >> () f r o n t . v >> " f r o n t " >> t w o

; l h m s >> () b a c k . v >> " b a c k " >> t w o

; l h m s >> " f o r e a f t e r " >> t w o

} (v : i t m i) r o f

; " " >> i >> t w o

{

; l h m s >> t w o

; () d e a d - f o r . v

; l h m s >> " f o r e a f t e r " >> t w o

} (v : i t m i) r o f

; " " >> i >> t w o

{

print a

1 1 1 1 1

print p

1 1 1 1 1

Deque (Doubly ended queue)

- Done end par deletion or insertion kar sakte hai
- Dynamic
- Random access possible

```
#include <iostream>
```

```
#include <deque>
```

```
using namespace std;
```

```
int main() {
```

```
    deque<int> d;
```

```
    d.push_back(1);
```

```
    d.push_front(2);
```

```
    for (int i: d) {
```

```
        cout << i << " ";
```

```
    }
```

```
    cout << endl;
```

```
    d.pop_front();
```

```
    for (int i: d) {
```

```
        cout << i << " ";
```

```
    }
```

```
    cout << endl;
```

```
    d.push_front(3);
```

```
    cout << "Print first index element -> " << d.at(1) << endl;
```

```
    cout << "front " << d.front() << endl;
```

```
    cout << "back " << d.back() << endl;
```

```
    cout << "before erase " << d.size() << endl;
```

```
    d.erase(d.begin(), d.begin() + 1);
```

{ (b: i tri) ref

{ lline >> i >> true

}

}

tail

l s

l

l <- elements khani kafi hai

l kafi

l back

l erase kafi

l erase kafi

l

tail

<erase> khani #

<tail> khani #

{ bta erase kafi

{ () niam tri

; l <tri> tail

; (1) back - deque l

; (5) kafi - deque l

{ (l: i tri) ref

; " " >> i >> true

}

; (1) right l erase l

{ lline >> "erase kafi" >> true

{ (l: i tri) ref

; " " >> i >> true

}

Stack (Pile of plates se assume Karo)

↳ last in first out concept

```
#include <iostream>
```

```
#include <stack>
```

```
using namespace std;
```

```
int main() {
```

```
    stack<string> s;
```

```
    s.push("love");
```

```
    s.push("babbar");
```

```
    s.push("Kumar");
```

```
    cout << "Top element ->" << s.top() << endl;
```

```
    s.pop();
```

```
    cout << "Top element ->" << s.top() << endl;
```

```
    cout << "Size of stack" << s.size() << endl;
```

```
    cout << "Empty or not" << s.empty() << endl;
```

```
}
```

Queue

↳ First in first out

```
#include <iostream>
```

```
#include <queue>
```

```
using namespace std;
```

```
int main() {
```

```
    queue<string> q;
```

```
    q.push("love");
```

```
    q.push("Babbar");
```

```
    q.push("Kumar");
```

```
    cout << "First element" << q.front() << endl;
```

```
    q.pop();
```

```
    cout << "First element" << q.front() << endl;
```

```
}
```

Output:-

Top element -> Kumar

Top element -> babbar

Size of stack 2

Empty or not 0

Output:-

First element love

First element Babbar

Priority Queue

→ First element always greatest
→ Default Priority queue $\Rightarrow$ max. heap

```
#include <iostream>
```

```
#include <queue>
```

```
using namespace std;
```

```
int main () {
```

```
    // max heap
```

```
    priority_queue <int> maxi;
```

```
    // min heap
```

```
    priority_queue <int, vector<int>, greater<int>> mini;
```

```
    maxi.push(1);
```

```
    maxi.push(3);
```

```
    maxi.push(2);
```

```
    maxi.push(0);
```

```
    int n = maxi.size();
```

```
    for (int i=0; i < n; i++) {
```

```
        cout << maxi.top() << " ";
```

```
        maxi.pop();
```

```
    }
```

```
    cout << endl;
```

```
    mini.push(5);
```

```
    mini.push(1);
```

```
    mini.push(0);
```

```
    mini.push(4);
```

```
    mini.push(3);
```

```
    int m = mini.size();
```

Stack (LIFO) $\Rightarrow$ Last In First Out

```
<vector<int>> stack;
```

```
<stack> include
```

```
using namespace std;
```

```
int main () {
```

```
    <print> stack;
```

```
    ("val") <push>
```

```
    ("val") <push>
```

```
    ("val") <push>
```

Output:-

```
3 2 1 0  
0 1 3 4 5
```

Empty or not? $\rightarrow$ 1

Queue

First In First Out

```
<vector<int>> queue;
```

```
<queue> include
```

```
using namespace std;
```

```
int main () {
```

```
    <print> queue;
```

```
    ("val") <push>
```

```
    ("val") <push>
```

```
    ("val") <push>
```

```
    ("val") <push>
```

```
    ("val") <push>
```

```
    ("val") <push>
```



```
cout << endl;
```

```
cout << "S is present or not ->" << s.count(s) << endl;
```

```
Set<int>::iterator itr = s.find(s);
```

```
cout << "Value
```

```
for (auto it = itr; it != s.end(); it++) {
```

```
    cout << *it << " ";
```

```
    cout << endl;
```

```
}
```

Insert, find, erase, count $\Rightarrow$ T.C. $\Rightarrow O(\log n)$

Map

→ 1 Key 1 hi value ko point karegi
→ sorted hota hai (But in case of unsorted map ye sorted nahi hota)

```
#include <iostream>
```

```
#include <map>
```

```
using namespace std;
```

```
int main() {
```

```
    map<int, string> m;
```

```
    m[1] = "vaibhav";
```

```
    m[2] = "chitransh";
```

```
    m[13] = "rishi";
```

```
    m.insert({5, "bheem"});
```

```
    for (auto i : m) {
```

```
        cout << i.first << endl;
```

```
    }
```

```
    for (auto i : m) {
```

```
        cout << i.first << " " << i.second << endl;
```

```
    }
```

```
}
```

Output:-

```
1
2
5
13
1 vaibhav
2 chitransh
5 bheem
13 rishi
```

```
{ (2 : i otuo) rof
```

```
; lbno >> i >> tuos
```

```
; lbno >> tuos ;
```

```
; ((1) niged .2) esare .2
```

```
{ (2 : i otuo) rof
```

```
; lbno >> i >> tuos
```

STL Algorithms

```
#include <iostream>
```

```
#include <algorithm>
```

```
#include <vector>
```

```
using namespace std;
```

```
int main() {
```

```
    vector<int> v;
```

```
    v.push_back(1);
```

```
    v.push_back(3);
```

```
    v.push_back(6);
```

```
    v.push_back(7);
```

```
    cout << "Finding 5 -> " << binary_search(v.begin(), v.end(), 5) << endl;
```

```
    cout << "Finding 6 -> " << binary_search(v.begin(), v.end(), 6) << endl;
```

```
    cout << "lower bound -> " << lower_bound(v.begin(), v.end(), 6) - v.begin() << endl;
```

```
    cout << "Upper bound -> " << upper_bound(v.begin(), v.end(), 4) - v.begin() << endl;
```

```
    int a = 3;
```

```
    int b = 5;
```

```
    cout << "max -> " << max(a, b) << endl;
```

```
    cout << "min -> " << min(a, b) << endl;
```

```
    swap(a, b);
```

```
    cout << "a -> " << a << endl;
```

```
    string abcd = "abcd";
```

```
    reverse(abcd.begin(), abcd.end());
```

```
    cout << "string -> " << abcd << endl;
```

```
    rotate(v.begin(), v.begin() + 1, v.end());
```

```
    cout << "after rotate " << endl;
```

```
    for (int i : v) {
```

```
        cout << i << " ";
```

```
    } cout << endl;
```

```
}
```

Output:-

Finding 5 -> 0

Finding 6 -> 1

lower bound -> 2

Upper bound -> 2

max -> 5

min -> 3

a -> 5

string -> dcba

after rotate

3 6 7 1

Lecture 20

Qn- Reverse the Array, I/P $\Rightarrow \{1, 3, 2, 4\}$

O/P $\Rightarrow \{4, 2, 3, 1\}$

arr[] $\Rightarrow$



$s \leftarrow \text{begin}$

$e \leftarrow \text{end}$

4 7 3 12 11

$s \leftarrow \text{begin}$

$e \leftarrow \text{end}$

4 12 3 7 11

$s \leftarrow \text{begin}$

$e \leftarrow \text{end}$

$\Rightarrow$ 4 12 3 7 11

(Reversed Array)

```
#include <iostream>
```

```
#include <vector>
```

```
using namespace std;
```

```
vector<int> reverse(vector<int> v) {
```

```
    int s = 0, e = v.size() - 1;
```

```
    while (s <= e) {
```

```
        swap(v[s], v[e]);
```

```
        s++;
```

```
        e--;
```

```
    }
```

```
    return v;
```

```
}
```

```
void print(vector<int> v) {
```

```
    for (int i = 0; i < v.size(); i++) {
```

```
        cout << v[i] << " ";
```

```
    }
```

```
    cout << endl;
```

```
}
```

```
int main() {
```

```
    vector<int> v;
```

```
v.push_back(11);
```

```
v.push_back(7);
```

```
v.push_back(3);
```

```
v.push_back(12);
```

```
v.push_back(4);
```

```
vector<int> ans = reverse(v);
```

```
print(ans);
```

```
return 0;
```

```
}
```

Qn - Given an array arr of integers and a position m. You have to reverse the array after that position.

```
void reverseArray(vector<int> &arr, int m) {
```

```
int s = m+1, e = arr.size() - 1;
```

```
while (s <= e) {
```

```
    swap(arr[s], arr[e]);
```

```
    s++;
```

```
    e--;
```

```
}
```

```
}
```

lecture 88

Qn - Merge Sorted Array, arr1[] = {1, 3, 5, 7, 9}, arr2[] = {2, 4, 6}

O/P => {1, 2, 3, 4, 5, 6, 7, 9}

```
#include <iostream>
```

```
#include <vector>
```

```
using namespace std;
```

```
void merge(int arr1[], int n, int arr2[], int m, int arr3[]) {
```

```
int i = 0, j = 0;
```

```
int k = 0;
```

```
while (i < n && j < m) {
```

```
    if (arr1[i] < arr2[j]) {
```

```
        arr3[k] = arr1[i];
```

```
        k++;
```

```
        i++;
```

```
    }
```

```
    else {
```

```
        arr3[k] = arr2[j];
```

```
        k++;
```

```
        j++;
```

```
    }
```

```
// Copy first array ke remaining element ko
```

```
while (i < n) {
```

```
    arr3[k] = arr1[i];
```

```
    k++;
```

```
    i++;
```

```
}
```

```
// Copy second array ke remaining element ko
```

```
while (j < m) {
```

```
    arr3[k] = arr2[j];
```

```
    k++;
```

```
    j++;
```

```
}
```

```
}
```

```
void print (int arr[], int n) {
```

```
    for (int i = 0; i < n; i++) {
```

```
        cout << arr[i] << " ";
```

```
    }
```

```
    cout << endl;
```

```
}
```

```
; (11) dead - deng V
```

```
; (8) dead - deng V
```

```
; (3) dead - deng V
```

```
; (13) dead - deng V
```

```
; (11) dead - deng V
```

```
; (10) answer = ans < tri > return
```

```
; (ans) return
```

```
; 0 return
```

```
}
```

reverse of each array . or meithee p hoo argeetni fo voo faroo no meithee - no
meithee toot reetfo faroo ett

1 - () agie voo = 9 , 1 + m = 2 tri

{ (9 > 2) listee

; ([9] voo , [2] voo) fovee

i ++ 2

i -- 9

BB abateel
on - Hoge sorted array

<maxtooi> ebulemi #

<rotoov> ebulemi #

ibts exafemoo gnise

int i = 0 , o = i tri

int k = 0;


```
int main() {
```

```
int arr1[5] = {1, 3, 5, 7, 9};
```

```
int arr2[3] = {2, 4, 6};
```

```
int arr3[8] = {0};
```

```
merge(arr1, 5, arr2, 3, arr3);
```

```
print(arr3, 8);
```

```
return 0;
```

```
}
```

Leetcode 283

Ques - Move zeroes

I/P $\Rightarrow \{0, 1, 0, 3, 12\}$ O/P $\Rightarrow \{1, 3, 12, 0, 0\}$
 I/P $\Rightarrow \{2, 0, 1, 3, 0, 0, 0\}$ O/P $\Rightarrow \{2, 1, 3, 0, 0, 0, 0\}$

arr $\Rightarrow$

0	1	0	3	12	0
---	---	---	---	----	---

```
int i=0; //indicating non-zero value
```

```
for (int j=0; j<size; j++) {
```

```
if (arr[j] != 0) {
```

```
swap(arr[j], arr[i]);
```

```
i++;
```

```
}
```

```
}
```

My solⁿ

```
for (int i=0; i<n; i++) {
```

```
for (int j=0; j<n-i-1; j++) {
```

```
if (arr[j] == 0) {
```

```
swap(arr[j], arr[j+1]);
```

```
}
```

```
}
```

```
}
```

Lecture (21)

Lecture 189

Qu- Rotate Array

I/P $\Rightarrow \{1, 7, 9, 11\}$

O/P $\Rightarrow \{9, 11, 1, 7\}$

$\hookrightarrow k=2$

$\% n \Rightarrow$ o/p or ans = $[0 \text{ to } (n-1)]$

$(n+k) \% n = k$

arr $[(i+k) \% n] = \text{arr}[i]$

Thought process

if $k=4 \Rightarrow$ fully rotate (~~it~~ becomes original)

if $k=5 \Rightarrow (4+1) \Rightarrow 1 \text{ rotation}$

if $k=6 \Rightarrow (4+2) \Rightarrow 2 \text{ rotation}$

$\Rightarrow$ so, $k = k \% n$

$\hookrightarrow$ cyclic way me k position se shift kar denge

void rotate (vector<int> & nums, int k) {

vector<int> temp (nums.size());

for (int i=0; i< nums.size(); i++) {

temp $[(i+k) \% \text{nums.size}()] = \text{nums}[i];$

}

nums = temp;

}

Lecture 1752

Qu- Check if array is sorted and rotated.

Case 1:- $\{1, 2, 3, 4, 5\}$

Sorted

Case 2:- $\{3, 4, 5, 1, 2\}$

Sorted & Rotated

Case 3:- $\{3, 5, 7, 1, 6\}$

Nothing

Case 4:- $\{1, 1, 1, 1\}$

All equal

True $\Rightarrow$ 1 pair exist $\text{nums}[i-1] > \text{nums}[i]$ (in cyclic order)

bool check (vector<int> & nums) {

int count=0;

for (int i=1; i<n; i++) {

if ($\text{nums}[i-1] > \text{nums}[i]$) {

count++;

}

}

// Condⁿ for cyclic one

if (nums[nums.size()-1] > nums[0]) {

count++;

}

return count <= 1;

}

Qn- Sum of Two arrays,

arr 1 =

1	2	3	4
---	---	---	---

arr 2 =

6

$arr1 + [i] \cdot 10 = arr2$ true
 $0 \div 10 \Rightarrow = \frac{arr1}{10} + .6$
 $0 \div arr2 = arr1$

1	2	4	0
---	---	---	---

Case 1:-

1	2	3	4 6
1	2	4	0

Case 2:-

1	2	3	6 4

Case 3:-

$\swarrow$ 9 9 9
 Carry 9 9 9

--	--	--	--

1	1
---	---

2	3
---	---

Sum = 1 + 3 = 4, Carry = 0

$Carry = Sum / 10$
 $Sum = Sum \% 10$
 $arr[K] = Sum$

int i = n-1;

int j = m-1;

int carry = 0;

while (i >= 0 && j >= 0) {

int val 1 = a[i];

int val 2 = b[j];

int sum = val 1 + val 2 + carry;

carry = sum / 10;

sum = sum % 10;


```
ans.push-back(sum);
```

```
i--;
```

```
j--;
```

```
}
```

// first case

```
while(i >= 0) {
```

```
int sum = a[i] + carry;
```

1 8 5 1

```
carry = sum / 10;
```

```
sum = sum % 10;
```

```
ans.push-back(sum);
```

```
i--;
```

```
}
```

// second case

```
while(j >= 0) {
```

```
int sum = b[j] + carry;
```

```
carry = sum / 10;
```

```
sum = sum % 10;
```

0 = 5 + 5 = 10, 10 / 10 = 1 = carry

```
ans.push-back(sum);
```

0 / 10 = 0, 0 % 10 = 0

```
j--;
```

0 % 10 = 0

ans = [0] + ans

```
}
```

// third case

```
while(carry != 0) {
```

```
int sum = carry;
```

```
carry = sum / 10;
```

```
sum = sum % 10;
```

```
ans.push-back(sum);
```

```
}
```

// print ans

```
reverse(ans);
```

```
return reverse(ans);
```

ans.push-back(sum);

([0] ans < [1-1] ans) if

++ ans

if ans < 1

1 8 5 1 = 1000

0 = 5000

1 8 5 1

1 8 5 1

1 1

8 5

1 - 1 = 0 true

1 - 1 = 0 true

0 = 0 true

(0 < j || 0 < i) false

[i] = 1000 true

[j] = 5000 true

1000 + 5000 + 1000 = 7000 true

0 / 10 = 0

0 % 10 = 0

Function for reverse:-

```
vector<int> reverse(vector<int>&v) {
```

```
    int s = 0;
```

```
    int e = v.size() - 1;
```

```
    while (s < e) {
```

```
        swap(v[s++], v[e--]);
```

```
    }
```

```
    return v;
```

```
}
```

Lecture 22

char a = 'z'

Single character

z

a

For multiple character $\Rightarrow$ char Arrays, strings

strings in C++ $\Rightarrow$ 1-Dimensional char arrays

strings $\Rightarrow$

a	b	c	d	e	f
---	---	---	---	---	---

character array

char ch[10];

Taking input & output

char name[20];

i/p $\Rightarrow$ cin >> name;

B	a	b	b	a	r	\0	---	
0	1	2	3	4	5	6	---	19

'\0' $\rightarrow$ null character (automatically add ho jata hai)

$\hookrightarrow$ use as a terminator

$\hookrightarrow$ Jisse mujhe pata lage string end kaha ho nahi hai

o/p $\Rightarrow$ cout << name;

```
#include <iostream>
using namespace std;
```

```
int main() {
```

```
cout << "Enter your name" << endl;
```

```
char name[20];
```

```
cin >> name;
```

```
cout << "Your name is " << name; ([--9] v, [++2] v) (mod)
```

3

Now, why full name is not showing?

cin $\rightarrow$ execution stop when space "-", tab \t, enter \n

If $I/p \Rightarrow Ba \setminus obpar$

↳ How $\Rightarrow$ `name[2] = '\0';`

So, O/P $\Rightarrow$ Ba

} Now, array

B a l o b a n 10 garbage values

fruit, sparsely hairy $\Leftarrow$ retrograde evolution

1. H_2O hat Ladungsmittel -1 $\leftarrow$ ++ in sp^2

Ques- Find the length of string

```
int getLength(char name[]) {
```

```
int count = 0;
```

```
int count = 0;
for (int i = 0; name[i] != '\0'; i++) {
```

```
count ++;
```

3

```
return count;
```

3

```
int main () {
```

```
char name[20];
```

```
cout << "Enter your name" << endl;
```

```
cin >> name;
```

cout << "Length: " << getLength(name) << endl;

```
return 0;
```

3

Output:-

Enter your name

Enter your
Vaibhav Chitransh

1 Your name is, Vallabha

{ (5, 2) distal


```
void reverse(char name[], int n) {
```

```
int S = 0;
```

```
int e = n-1;
```

```
while (s <= e) {
```

```
swap(name[s++], name[e--]);
```

3

3

↳ Rest code is same as previous ques.

Qn- Check Palindrome for a string (Consider alphabets & numbers only & ignore symbols and white spaces)

bool checkPalindrome (char a[], int n) {

```
int s = 0;
```

```
int e = n - 1;
```

```
while (s <= e) {
```

if ($a[s] \neq a[e]$) {

```
return 0;
```

3

else {

S++;

e--;

3

3

```
return 1;
```

3

Changing uppercase to lowercase $\Rightarrow$ $temp = ch - 'A' + 'a'$ $\Rightarrow$ resultant char

Use this if previous question has one more condⁿ which says string is not case-sensitive (i.e. $0 = \text{and } 1 = \text{is not the}$)