

1) What is Select Class?

- Select class is a Selenium class .
- Which having some predefined methods and it is used to perform select and deselect actions on drop down menu.
- Syntax : `Select ref_var=new Select(webElement);`

Types of dropdown menu

- single select : which we can perform only select action
- multi select : which we can perform both select and deselect

2) Methods in Select class?

- `selectByIndex();`
- `selectByValue();`
- `selectByVisibleText();`
- `deselectByIndex();`
- `deselectByValue();`
- `deselectByVisibleText();`
- `deSelectAll();`
- `isMultiple();`
- `getOptions();`
- `getFirstSelectOption();`
- `getAllSelectedOptions();`
- `getWrappedElement();`
- `hashCode();`
- `equals();`

3) what is Actions Class?

- Actions class is a Selenium class
- Which is having some predefined methods and it is used to perform keyboard and mouse action on the browser.
- Syntax : `Actions ref_var=new Action(driver);`

4) Methods for Mouse Actions?

- `moveToElement();`
- `doubleClick();`
- `dragAndDrop();`
- `contextClick();`
- `clickAndHold();`
- `click();`

5) Methods in KeyBoard Actions ?

- `sendKeys();`
- `KeyDown();`
- `KeyUp();`

6) Types of PopUp?

- Child window PopUp
- JavaScript PopUp/Alert PopUp
- Notification PopUp
- File Upload PopUp
- File Download PopUp

- Calendar PopUp

7) How to handle Child Window PopUp?

- To handle , first we need to switch the controller to the particular child window
- To switch , we have to follow a syntax
- Syntax : `driver.switchTo.window(window handle);`
- Window handle is a unique one, each and every window having their own handle, that handle can be found by using `getWindowHandle()` and `getWindowHandles();`

8) how to handle Alert Pop?

- To handle alert pop , first we need to switch the controller to the alert
- To switch , we have to follow a syntax
- `Alert ref_var=driver.switchTo.alert();`

9) Types of alert PopUp?

- There are 3 types
- Simple alert
- Confirmation alert
- Prompt alert

10) how to handle or avoid notification PopUp?

To handle

- We need to use Robot class

To avoid

- We need to use ChromeOptions

11) how to handle or avoid file Upload PopUp?

To avoid

- By using `sendKeys` Methods
- Syntax : `WebElement.sendKeys("path of the file").`

To handle

- By using 3rd part tool called Autoid.

12) Methods present in Alert ?

- `accept();`
- `dismiss();`
- `getText();`
- `sendKeys();`

13)What is iframe?

- An iFrame (Inline Frame) is an HTML document embedded inside the current HTML document on a website.
- Frame or iFrame HTML tag will be used to insert one html page in another html page.
- iFrame HTML element is used to insert content from another source, such as an advertisement, into a Web page.
- iFrame is defined by an <iFrame></iFrame> tag in HTML. With this tag you can identify an iFrame while inspecting the HTML tree.
- In order to embed (include) a web page inside another web page developer uses 'iFrame' or 'Frame' html tag.
- But, if an element is inside the frame then web driver cannot find the element.
- Webdriver can't perform an action on web element automatically when object or web element are inside the frame.

There are three ways we can pass driver control to frame.

Int (0, 1, 2)

String (ID/Name)

Web Element (Address)

Syntax :

- Iframes - Switch by index
`driver.switchTo().frame(0); // # frameid starts from index zero`
- Iframes - Switch by name
`driver.switchTo().frame("frame-name");`
- //Iframes - Switch by WebElement

```
driver.switchTo().frame(driver.findElement(By.tagName("")));
```

In order to give the control back to the main page, i.e. Change the control from frame or to exit from the frame we use the following methods.

```
driver.switchTo().defaultContent();  
driver.switchTo().parentFrame();
```


