

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

File Structure Directory

EtherFund/

- | — crowdfundingcontracts/ # Smart contract source files
- | — lib
- | — src/
 - | — Crowdfunding.sol
 - | — EtherFundFactory.sol
- | — test
- | — foundry.toml
- | — package.json
- |
- | — src/ # Source code (React + TypeScript)
 - | — App/ # Next.js pages
 - | | | api/rss | — route.ts
 - | | | campaign/[campaignAddress]/ | — contracts.ts
 - | | | constants/ | — contracts.ts
 - | | | dashboard/[walletAddress] | — page.tsx
 - | | | news/[walletAddress] | — page.tsx
 - | | | — client.ts
 - | | | — globals.css
 - | | | — layout.tsx
 - | | | — page.tsx
 - | — components/ # Reusable UI components
 - | | — CampaignCard.tsx
 - | | — MyCampaignCard.tsx
 - | | — Navbar.tsx
 - | | — TierCard.tsx
 - | — hooks/ # Custom React hooks (if any)
 - | — utils/ # Helper functions

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
|
| — public/          # Static assets (logos, images)
| — test/            # Unit and integration tests
| — node_modules/    # Dependencies (installed via npm/yarn)
|
| — .eslintrc.json    # ESLint configuration
| — .prettierrc       # Prettier formatting config
| — next.config.js    # Next.js configuration
| — tailwind.config.ts # Tailwind CSS configuration
| — tsconfig.json     # TypeScript configuration
| — package.json      # Project dependencies
| — yarn.lock / package-lock.json # Dependency lock file
| — foundry.toml      # Foundry (for Solidity testing)
| — postcss.config.js # PostCSS configuration
```

Web3 Smart Contracts: -

1. src/Crowdfunding.sol

```
// SPDX-License-Identifier: MIT
```

```
pragma solidity ^0.8.0;

contract Crowdfunding {

    string public name;

    string public description;

    uint256 public goal;

    uint256 public deadline;

    address public owner;

    bool public paused;

    enum CampaignState { Active, Successful, Failed }

    CampaignState public state;
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
struct Tier {  
    string name;  
    uint256 amount;  
    uint256 backers;  
}
```

```
struct Backer {  
    uint256 totalContribution;  
    mapping(uint256 => bool) fundedTiers;  
}
```

```
Tier[] public tiers;  
mapping(address => Backer) public backers;
```

```
modifier onlyOwner() {  
    require(msg.sender == owner, "Not the owner");  
    _;  
}
```

```
modifier campaignOpen() {  
    require(state == CampaignState.Active, "Campaign is not active.");  
    _;  
}
```

```
modifier notPaused() {  
    require(!paused, "Contract is paused.");  
    _;  
}
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
constructor(
    address _owner,
    string memory _name,
    string memory _description,
    uint256 _goal,
    uint256 _duratyionInDays
) {
    name = _name;
    description = _description;
    goal = _goal;
    deadline = block.timestamp + (_duratyionInDays * 1 days);
    owner = _owner;
    state = CampaignState.Active;
}

function checkAndUpdateCampaignState() internal {
    if(state == CampaignState.Active) {
        if(block.timestamp >= deadline) {
            state = address(this).balance >= goal ? CampaignState.Successful :
CampaignState.Failed;
        } else {
            state = address(this).balance >= goal ? CampaignState.Successful :
CampaignState.Active;
        }
    }
}

function fund(uint256 _tierIndex) public payable campaignOpen notPaused {
    require(_tierIndex < tiers.length, "Invalid tier.");
    require(msg.value == tiers[_tierIndex].amount, "Incorrect amount.");
}
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
tiers[_tierIndex].backers++;

backers[msg.sender].totalContribution += msg.value;
backers[msg.sender].fundedTiers[_tierIndex] = true;


checkAndUpdateCampaignState();
}


function addTier(
    string memory _name,
    uint256 _amount
) public onlyOwner {
    require(_amount > 0, "Amount must be greater than 0.");
    tiers.push(Tier(_name, _amount, 0));
}


function removeTier(uint256 _index) public onlyOwner {
    require(_index < tiers.length, "Tier does not exist.");
    tiers[_index] = tiers[tiers.length - 1];
    tiers.pop();
}


function withdraw() public onlyOwner {
    checkAndUpdateCampaignState();
    require(state == CampaignState.Successful, "Campaign not successful.");

    uint256 balance = address(this).balance;
    require(balance > 0, "No balance to withdraw");
}
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
    payable(owner).transfer(balance);  
}
```

```
function getContractBalance() public view returns (uint256) {  
    return address(this).balance;  
}
```

```
function refund() public {  
    checkAndUpdateCampaignState();  
    require(state == CampaignState.Failed, "Refunds not available.");  
    uint256 amount = backers[msg.sender].totalContribution;  
    require(amount > 0, "No contribution to refund");  
  
    backers[msg.sender].totalContribution = 0;  
    payable(msg.sender).transfer(amount);  
}
```

```
function hasFundedTier(address _backer, uint256 _tierIndex) public view returns (bool) {  
    return backers[_backer].fundedTiers[_tierIndex];  
}
```

```
function getTiers() public view returns (Tier[] memory) {  
    return tiers;  
}
```

```
function togglePause() public onlyOwner {  
    paused = !paused;  
}
```

```
function getCampaignStatus() public view returns (CampaignState) {  
    if (state == CampaignState.Active && block.timestamp > deadline) {
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
        return address(this).balance >= goal ? CampaignState.Successful :
CampaignState.Failed;

    }

    return state;
}

function extendDeadline(uint256 _daysToAdd) public onlyOwner campaignOpen {
    deadline += _daysToAdd * 1 days;
}
}
```

2. scr/EtherFundFactory.sol

```
// SPDX-License-Identifier: MIT
```

```
pragma solidity ^0.8.0;
```

```
import "./Crowdfunding.sol"; // Import Crowdfunding contract
```

```
// Interface to interact with Crowdfunding contract
```

```
interface IEtherFund {
    function getDonors() external view returns (address[] memory);
}
```

```
contract EtherFundFactory {
```

```
    address public owner;
```

```
    bool public paused;
```

```
    struct Campaign {
```

```
        address campaignAddress;
```

```
        address owner;
```

```
        string name;
```

```
        uint256 creationTime;
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
}
```

```
Campaign[] public campaigns;
```

```
mapping(address => Campaign[]) public userCampaigns;
```

```
modifier onlyOwner() {
```

```
    require(msg.sender == owner, "Not owner.");
```

```
    _;
```

```
}
```

```
modifier notPaused() {
```

```
    require(!paused, "Factory is paused");
```

```
    _;
```

```
}
```

```
constructor() {
```

```
    owner = msg.sender;
```

```
}
```

```
function createCampaign(
```

```
    string memory _name,
```

```
    string memory _description,
```

```
    uint256 _goal,
```

```
    uint256 _durationInDays
```

```
) external notPaused {
```

```
    EtherFund newCampaign = new EtherFund(
```

```
        msg.sender,
```

```
        _name,
```

```
        _description,
```


EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
        _goal,
        _durationInDays
    );
    address campaignAddress = address(newCampaign);

    Campaign memory campaign = Campaign({
        campaignAddress: campaignAddress,
        owner: msg.sender,
        name: _name,
        creationTime: block.timestamp
    });

    campaigns.push(campaign);
    userCampaigns[msg.sender].push(campaign);
}

function getUserCampaigns(address _user) external view returns (Campaign[] memory) {
    return userCampaigns[_user];
}

function getAllCampaigns() external view returns (Campaign[] memory) {
    return campaigns;
}

function togglePause() external onlyOwner {
    paused = !paused;
}

// Function to delete all campaigns (Only Owner)
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
function deleteAllCampaigns() external onlyOwner {
    delete campaigns;
}

// Function to get all donors of a specific campaign
function getDonors(address _campaignAddress) external view returns (address[] memory)
{
    IEtherFund campaign = IEtherFund(_campaignAddress);
    return campaign.getDonors();
}
}
```

EtherFund Web based application (NextJS): -

1. api/rss->route.ts

```
import { NextResponse } from "next/server";
import { parseString } from "xml2js";

const RSS_FEEDS = [
    "https://www.crowdfundinsider.com/feed/",
    "https://www.kickstarter.com/blog?format=rss",
    "https://go.indiegogo.com/blog/feed",
    "https://www.coindesk.com/arc/outboundfeeds/rss/?outputType=xml",
    "https://cointelegraph.com/rss",
    "https://bitcoinmagazine.com/.rss/full",
];
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
export async function GET() {  
  try {  
    console.log("🔍 Fetching multiple RSS feeds...");  
  
    const timestamp = new Date().getTime();  
    const requests = RSS_FEEDS.map((url) =>  
      fetch(`${url}?t=${timestamp}`, {  
        method: "GET",  
        headers: {  
          "User-Agent": "Mozilla/5.0",  
          "Accept": "application/rss+xml, application/xml, text/xml",  
        },  
        cache: "no-store",  
      }).then((res) => res.text())  
    );  
  
    const responses = await Promise.all(requests);  
    let allNews: any[] = [];  
  
    responses.forEach((text, index) => {  
      parseString(text, (err: any, result: any) => {  
        if (err) {  
          console.error(`❌ Error parsing RSS from ${RSS_FEEDS[index]}:`, err);  
          return;  
        }  
  
        if (result?.rss?.channel?.[0]?.item) {  
          const items = result.rss.channel[0].item
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
.map((news: any) => {  
  let imageUrl = "";  
  
  if (news.enclosure && news.enclosure[0].$.url) {  
    imageUrl = news.enclosure[0].$.url;  
  } else if (news["media:content"] && news["media:content"][0].$.url) {  
    imageUrl = news["media:content"][0].$.url;  
  } else {  
    return null; // 🚫 Skip items without images  
  }  
  
  return {  
    title: news.title?.[0] || "No title",  
    link: news.link?.[0] || "#",  
    contentSnippet: news.description ? news.description[0].replace(/<[^>]+>/g, "") :  
    "No description available",  
    image: imageUrl,  
  };  
})  
  
.filter((item) => item !== null); // ✅ Filter out news without images  
  
allNews.push(...items);  
}  
});  
});  
  
allNews = allNews.sort(() => Math.random() - 0.5);  
  
console.log("✅ Fetched & Parsed News:", allNews.slice(0, 5));
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
return NextResponse.json(allNews);

} catch (error) {

  console.error(" ❌ API Error:", error.message);

  return NextResponse.json({ error: error.message }, { status: 500 });

}

}
```

2. campaign/[campaignAddress]-> page.tsx

```
'use client';

import { client } from "@app/client";

import { TierCard } from "@components/TierCard";

import { useParams } from "next/navigation";

import { useState } from "react";

import { getContract, prepareContractCall, ThirdwebContract } from "thirdweb";

import { baseSepolia } from "thirdweb/chains";

import { lightTheme, TransactionButton, useActiveAccount, useReadContract } from
"thirdweb/react";

import { Bar, Line, Doughnut, Radar } from 'react-chartjs-2';

import { Chart as ChartJS, CategoryScale, LinearScale, BarElement, LineElement,
PointElement, Title, Tooltip, Legend, ArcElement, RadialLinearScale } from 'chart.js';

// Register necessary components from Chart.js
ChartJS.register(
  CategoryScale,
  LinearScale,
  BarElement,
  LineElement,
  PointElement,
  Title,
  Tooltip,
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

Legend,

ArcElement,

RadialLinearScale // Required for Radar chart

);

import html2pdf from 'html2pdf.js';

```
export default function CampaignPage() {
```

```
  const account = useActiveAccount();
```

```
  const { campaignAddress } = useParams();
```

```
  const [isEditing, setIsEditing] = useState<boolean>(false);
```

```
  const [isModalOpen, setIsModalOpen] = useState<boolean>(false);
```

```
  const contract = getContract({
```

```
    client: client,
```

```
    chain: baseSepolia,
```

```
    address: campaignAddress as string,
```

```
  });
```

```
  // Name of the campaign
```

```
  const { data: name, isLoading: isLoadingName } = useReadContract({
```

```
    contract: contract,
```

```
    method: "function name() view returns (string)",
```

```
    params: [],
```

```
  });
```

```
  // Description of the campaign
```

```
  const { data: description } = useReadContract({
```

```
    contract,
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
method: "function description() view returns (string)",
params: []
});

// Campaign deadline
const { data: deadline, isLoading: isLoadingDeadline } = useReadContract({
  contract: contract,
  method: "function deadline() view returns (uint256)",
  params: [],
});

// Convert deadline to a date
const deadlineDate = new Date(parseInt(deadline?.toString() as string) * 1000);

// Check if deadline has passed
const hasDeadlinePassed = deadlineDate < new Date();

// Goal amount of the campaign
const { data: goal, isLoading: isLoadingGoal } = useReadContract({
  contract: contract,
  method: "function goal() view returns (uint256)",
  params: [],
});

// Total funded balance of the campaign
const { data: balance, isLoading: isLoadingBalance } = useReadContract({
  contract: contract,
  method: "function getContractBalance() view returns (uint256)",
  params: [],
});
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
// Calculate the total funded balance percentage

const totalBalance = balance?.toString();

const totalGoal = goal?.toString();

let balancePercentage = (parseInt(totalBalance as string) / parseInt(totalGoal as string)) *
100;
```

```
// If balance is greater than or equal to goal, percentage should be 100
```

```
if (balancePercentage >= 100) {
    balancePercentage = 100;
}
```

```
// Get tiers for the campaign
```

```
const { data: tiers, isLoading: isLoadingTiers } = useReadContract({
    contract: contract,
    method: "function getTiers() view returns ((string name, uint256 amount, uint256
backers)[])",
    params: [],
});
```

```
// Get owner of the campaign
```

```
const { data: owner, isLoading: isLoadingOwner } = useReadContract({
    contract: contract,
    method: "function owner() view returns (address)",
    params: [],
});
```

```
// Get status of the campaign
```

```
const { data: status } = useReadContract({
    contract,
    method: "function state() view returns (uint8)",
});
```


EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
    params: []

  });

const downloadPageAsPDF = () => {

  const element = document.getElementById('analysis-content'); // Wrap your analysis
  content in this ID

  const button = document.getElementById('download-button');

  if (button) button.style.display = 'none';

  const opt = {
    margin: 0.5,
    filename: 'Campaign_Page_Analysis.pdf',
    image: { type: 'jpeg', quality: 0.98 },
    html2canvas: { scale: 2, scrollY: 0 },
    jsPDF: { unit: 'in', format: 'letter', orientation: 'portrait' },
  };

  html2pdf()
    .set(opt)
    .from(element)
    .save()
    .then(() => {
      if (button) button.style.display = 'block';
    })
    .catch((err) => {
      console.error('Error generating PDF:', err);
      if (button) button.style.display = 'block';
    });
};
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
return (  
  <div className="mx-auto max-w-7xl px-2 mt-4 sm:px-6 lg:px-8">  
    <div className="flex flex-row justify-between items-center">  
      {!isLoadingName && (  
        <p className="text-4xl font-semibold">{name}</p>  
      )}  
      {owner === account?.address && (  
        <div className="flex flex-row">  
          {isEditing && (  
            <p className="px-4 py-2 bg-gray-500 text-white rounded-md mr-2">  
              Status:  
  
              {status === 0 ? " Active" :  
                status === 1 ? " Successful" :  
                status === 2 ? " Failed" : "Unknown"}  
            </p>  
          )}  
          <button  
            className="px-4 py-2 bg-blue-500 text-white rounded-md"  
            onClick={() => setIsEditing(!isEditing)}  
            >{isEditing ? "Done" : "Edit"}</button>  
        </div>  
      )}  
    </div>  
    <div className="my-4">  
      <p className="text-lg font-semibold">Description:</p>  
      <p>{description}</p>  
    </div>  
  )
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
<div className="mb-4">

  <p className="text-lg font-semibold">Deadline</p>

  {!!isLoadingDeadline && (

    <p>{deadlineDate.toString()}</p>

  )}

</div>

{!!isLoadingBalance && (

  <div className="mb-4">

    <p className="text-lg font-semibold">Campaign Goal:
    <div className="relative w-full h-6 bg-gray-200 rounded-full dark:bg-gray-
700">

      <div className="h-6 bg-blue-600 rounded-full dark:bg-blue-500 text-right"
style={{ width: `${balancePercentage.toString()}%` }}>

        <p className="text-white dark:text-white text-xs p-
1">{balance.toString()}</p>

      </div>

      <p className="absolute top-0 right-0 text-white dark:text-white text-xs p-1">
        {balancePercentage >= 100 ? "" : `${balancePercentage.toString()}%` }
      </p>

    </div>

  </div>

)}

<div>

  <p className="text-lg font-semibold">Tiers:</p>

  <div className="grid grid-cols-3 gap-4">

    {isLoadingTiers ? (

      <p>Loading...</p>

    ) : (
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
tiers && tiers.length > 0 ? (  
  tiers.map((tier, index) => (  
    <TierCard  
      key={index}  
      tier={tier}  
      index={index}  
      contract={contract}  
      isEditing={isEditing}  
    />  
  ))  
): (  
  !isEditing && (  
    <p>No tiers available</p>  
  )  
)  
))  
{isEditing && (  
  // Add a button card with text centered in the middle  
  <button  
    className="max-w-sm flex flex-col text-center justify-center items-center  
font-semibold p-6 bg-blue-500 text-white border border-slate-100 rounded-lg shadow"  
    onClick={() => setIsModalOpen(true)}  
  >+ Add Tier</button>  
  )}  
</div>  
</div>  
  
{isModalOpen && (  
  <CreateCampaignModal
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
        setIsModalOpen={setIsModalOpen}

        contract={contract}

    />

    )}

    <div className="mt-6">

    <p className="text-lg font-semibold">Analysis: Tiers and Goal Amount</p>

    {!isLoadingTiers && tiers && tiers.length > 0 ? (

        <div className="flex flex-col space-y-2">

            {tiers.map((tier, index) => (

                <div key={index} className="flex justify-between">

                    <p>{tier.name}</p>

                    <p>฿{tier.amount.toString()}</p>

                </div>

            ))}

            <div className="flex justify-between font-bold mt-4">

                <p>Total Goal:</p>

                <p>฿{goal?.toString()}</p>

            </div>

        </div>

    ) : (

        <p>No tiers available for analysis.</p>

    )}

    </div>

    <div className="mt-6">

    <p className="text-lg font-semibold">Analysis: User and Tiers with Amount</p>

    {tiers && tiers.length > 0 && owner && account ? (

        <div className="flex flex-col space-y-4">

            {tiers.map((tier, index) => (

                <div key={index} className="border border-gray-300 p-4 rounded-lg">
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
<p className="font-semibold">Tier Name: {tier.name}</p>

<p>Amount: ð {tier.amount.toString()}</p>

<p>Donator's: {tier.backers.toString()}</p>

</div>

)}}

<div className="border border-gray-300 p-4 rounded-lg mt-4">

  <p className="font-semibold">Campaign Owner</p>

  <p>Address: {owner}</p>

</div>

<div className="border border-gray-300 p-4 rounded-lg">

  <p className="font-semibold">Current User</p>

  <p>Address: {account.address}</p>

</div>

</div>

):(

<p>Loading user and tiers data for analysis...</p>

)}

</div>

{/* visualAnalysis */}

<div className="flex items-center justify-center min-h-screen bg-gray-50 mt-6">

  <div className="grid grid-cols-2 gap-6 p-4 mt-6">

    {/* Line Chart */}

    {/* Line Chart: Goal Amount and Backers Over Tiers */}

  </div>

  <div className="bg-white shadow-md p-4 rounded-lg">

    <p className="text-lg font-semibold">Analysis: Goal Amount and Donator Over Tiers (Line Chart)</p>

    {!isLoadingTiers && tiers && tiers.length > 0 ? (

      <Line
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
data={{
  labels: tiers.map((tier) => tier.name), // Labels for each tier
  datasets: [
    {
      label: 'Goal Amount',
      data: tiers.map((tier) => Number(tier.amount)), // Goal amount data
      fill: false,
      borderColor: 'rgba(75, 192, 192, 1)', // Line color
      tension: 0.1,
    },
    {
      label: 'Donator',
      data: tiers.map((tier) => Number(tier.backers)), // Backers data
      fill: false,
      borderColor: 'rgba(255, 99, 132, 1)', // Line color for backers
      tension: 0.1,
    },
  ],
}}
options={{
  responsive: true,
  plugins: {
    title: {
      display: true,
      text: 'Goal Amount and Donator Over Tiers',
    },
  },
  scales: {
    y: {
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
beginAtZero: true, // Ensure y-axis starts from zero

    },

    },

  }}

/>

): (

  <p>No tiers available for analysis.</p>

)}

</div>


{/* Bar Chart */}

<div className="bg-white shadow-md p-4 rounded-lg">

  <p className="text-xl font-semibold text-center">Analysis: Donator per Tier (Bar
Chart)</p>

  {!isLoadingTiers && tiers && tiers.length > 0 ? (

    <Bar

      data={{

        labels: tiers.map((tier) => tier.name),

        datasets: [

          {

            label: 'Donator',

            data: tiers.map((tier) => Number(tier.backers)), // Convert BigInt to number

            backgroundColor: 'rgba(153, 102, 255, 0.2)',

            borderColor: 'rgba(153, 102, 255, 1)',

            borderWidth: 1,

          },

        ],

      }}

      options={{
```


EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
    responsive: true,
    plugins: {
      title: {
        display: true,
        text: 'Donator per Tier',
      },
    },
  },
}
width={400}
height={300}
/>
): (
  <p className="text-center">No tiers available for analysis.</p>
)
</div>

{/* Donut Chart */}
<div className="bg-white shadow-md p-4 rounded-lg">
  <p className="text-xl font-semibold text-center">Analysis: Amount Distribution Across
Tiers (Donut Chart)</p>
  {!isLoadingTiers && tiers && tiers.length > 0 ? (
    <Doughnut
      data={{
        labels: tiers.map((tier) => tier.name),
        datasets: [
          {
            label: 'Tier Amounts',
            data: tiers.map((tier) => Number(tier.amount)), // Convert BigInt to number
            backgroundColor: ['rgba(255, 99, 132, 0.2)', 'rgba(54, 162, 235, 0.2)', 'rgba(255,
206, 86, 0.2)', 'rgba(75, 192, 192, 0.2)'],
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
borderColor: ['rgba(255, 99, 132, 1)', 'rgba(54, 162, 235, 1)', 'rgba(255, 206, 86, 1)', 'rgba(75, 192, 192, 1)'],
```

```
borderWidth: 1,
```

```
},
```

```
],
```

```
}}
```

```
options={{
```

```
responsive: true,
```

```
plugins: {
```

```
title: {
```

```
display: true,
```

```
text: 'Amount Distribution Across Tiers',
```

```
},
```

```
},
```

```
}}
```

```
width={400}
```

```
height={300}
```

```
): (
```

```
<p className="text-center">No tiers available for analysis.</p>
```

```
)}
```

```
</div>
```

```
{/* Radar Chart */}
```

```
<div className="bg-white shadow-md p-4 rounded-lg">
```

```
<p className="text-xl font-semibold text-center">Analysis: Donator Distribution Across Tiers (Radar Chart)</p>
```

```
{!isLoadingTiers && tiers && tiers.length > 0 ? (
```

```
<Radar
```

```
data={{
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
labels: tiers.map((tier) => tier.name),
datasets: [
  {
    label: 'Donator Distribution',
    data: tiers.map((tier) => Number(tier.backers)), // Convert BigInt to number
    backgroundColor: 'rgba(54, 162, 235, 0.2)',
    borderColor: 'rgba(54, 162, 235, 1)',
    pointBackgroundColor: 'rgba(54, 162, 235, 1)',
  },
],
}}
options={{
  responsive: true,
  plugins: {
    title: {
      display: true,
      text: 'Donator Distribution Across Tiers',
    },
  },
  scales: {
    r: {
      suggestedMin: 0,
      suggestedMax: Math.max(...tiers.map((tier) => Number(tier.backers))) + 5,
    },
  },
}}
width={400}
height={300}
/>
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
) : (  
  <p className="text-center">No tiers available for analysis.</p>  
)  
})  
</div>  
  
</div>  
  
</div>  
  
{/*download receipt*/}  
{owner === account?.address && (  
  <div>  
    <div>  
      <p className="text-lg font-semibold mt-4 mb-4">View and Download EtherFund  
Receipt</p>  
    </div>  
    <div id="analysis-content">  
      {/* The two analysis sections here */}  
      <div className="mt-4 bg-white shadow-md p-4 rounded-lg p mb-4">  
        <p className="text-3xl font-bold text-center underline">EtherFund Receipt</p>  
        <p className="text-lg text-center">Built with NextJS | Web3 | Solidity</p>  
        <p className="text-lg font-semibold">Campaign Name</p><p>{name}</p>  
        <p className="text-lg font-semibold">Description</p><p>{description}</p>  
        <div className="mb-4">  
          <p className="text-lg font-semibold">Deadline</p> {isLoadingDeadline && (  
<p>{deadlineDate.toString()}</p> )}  
        </div>  
        <p className="absolute top-0 right-0 text-white dark:text-white text-xs p-1">  
{balancePercentage >= 100 ? "" : `${balancePercentage?.toString()}%`} </p>  
        <p className="text-lg font-semibold">Tiers and Goal Amount</p>  
        {isLoadingTiers && tiers && tiers.length > 0 ? (  
          <div className="flex flex-col space-y-2">
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
{tiers.map((tier, index) => (  
  <div key={index} className="flex justify-between">  
    <p>{tier.name}</p>  
    <p>฿{tier.amount.toString()}</p>  
  </div>  
))}  
  
<div className="flex justify-between font-bold mt-4">  
  <p>Total Goal:</p>  
  <p>฿{goal?.toString()}</p>  
</div>  
</div>  
) : (  
  <p>No tiers available for analysis.</p>  
)}  
  
<div className="mt-6">  
  <p className="text-lg font-semibold">User and Tiers with Amount</p>  
  {tiers && tiers.length > 0 && owner && account ? (  
    <div className="flex flex-col space-y-4 mt-2">  
      {tiers.map((tier, index) => (  
        <div key={index} className="border border-gray-300 p-4 rounded-lg">  
          <p className="font-semibold">Tier Name: {tier.name}</p>  
          <p>Amount: ${tier.amount.toString()}</p>  
          <p>Donator's: {tier.backers.toString()}</p>  
        </div>  
      ))}  
    <div className="border border-gray-300 p-4 rounded-lg mt-4">  
      <p className="font-semibold">Campaign Owner</p>  
      <p>Address: {owner}</p>
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
</div>

{ /*<div className="border border-gray-300 p-4 rounded-lg">

  <p className="font-semibold">Current User</p>

  <p>Address: {account.address}</p>

</div> */ }

</div>

) : (

  <p>Loading user and tiers data for analysis...</p>

)}

</div>

<p className="text-lg font-semibold mt-4">Designed & Developed by Group 11
</p><p>Saaras Gaikwad</p><p>Sanskruti Chavan</p><p>Harshad Raurale</p>

<div className="mx-auto max-w-7xl px-2 mt-4 sm:px-6 lg:px-8 items-center text-center">

  { /* Button to download the page as PDF */ }

  <div className="flex justify-end mt-6 items-center text-center">

    <button

      id="download-button"

      className="text-center items-center px-4 py-2 bg-green-500 text-white rounded-lg shadow-md hover:bg-green-600"

      onClick={downloadPageAsPDF}

    >

      Download Receipt

    </button>

  </div>

  { /* Rest of the content */ }

</div>

</div>
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
</div>

</div>

)}}

</div>

);
}

type CreateTierModalProps = {
  setIsModalOpen: (value: boolean) => void
  contract: ThirdwebContract
}

const CreateCampaignModal = (
  { setIsModalOpen, contract }: CreateTierModalProps
) => {
  const [tierName, setTierName] = useState<string>("");
  const [tierAmount, setTierAmount] = useState<bigint>(1n);

  return (
    <div className="fixed inset-0 bg-black bg-opacity-75 flex justify-center items-center backdrop-blur-md">
      <div className="w-1/2 bg-slate-100 p-6 rounded-md">
        <div className="flex justify-between items-center mb-4">
          <p className="text-lg font-semibold">Create a Funding Tier</p>
          <button
            className="text-sm px-4 py-2 bg-slate-600 text-white rounded-md"
            onClick={() => setIsModalOpen(false)}
          />
        </div>
      </div>
    </div>
  )
}
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
>Close</button>

</div>

<div className="flex flex-col">

  <label>Tier Name:</label>

  <input

    type="text"

    value={tierName}

    onChange={(e) => setTierName(e.target.value)}

    placeholder="Tier Name"

    className="mb-4 px-4 py-2 bg-slate-200 rounded-md"

  />

  <label>Tier Cost:</label>

  <input

    type="number"

    value={parseInt(tierAmount.toString())}

    onChange={(e) => setTierAmount(BigInt(e.target.value))}

    className="mb-4 px-4 py-2 bg-slate-200 rounded-md"

  />

  <TransactionButton

    transaction={() => prepareContractCall({

      contract: contract,

      method: "function addTier(string _name, uint256 _amount)",

      params: [tierName, tierAmount]

    })}

    onTransactionConfirmed={async () => {

      alert("Tier added successfully!")

      setIsModalOpen(false)

    }}

    onError={(error) => alert(`Error: ${error.message}`)}
```


EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
        theme={lightTheme()}
      >Add Tier</TransactionButton>
    </div>
  </div>
</div>
)
}
```

3. constants-> contracts.ts

```
export const CROWDFUNDING_FACTORY =
"0xbe339ab131fe181e4dbb818883b043697251cd7b";//factory address

//above is contract address, deployed one
```

4. dashboard/[walletAddress]-> page.tsx

```
'use client';

import { client } from "@app/client";
import { CROWDFUNDING_FACTORY } from "@app/constants/contracts";
import { MyCampaignCard } from "@components/MyCampaignCard";
import { useState } from "react";
import { getContract } from "thirdweb";
import { baseSepolia } from "thirdweb/chains";
import { deployPublishedContract } from "thirdweb/deploy";
import { useActiveAccount, useReadContract } from "thirdweb/react";

export default function DashboardPage() {
  const account = useActiveAccount();

  const [isModalOpen, setIsModalOpen] = useState<boolean>(false);

  const contract = getContract({
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
client: client,

chain: baseSepolia,

address: CROWDFUNDING_FACTORY,

});

// Get Campaigns

const { data: myCampaigns, isLoading: isLoadingMyCampaigns, refetch } =
useReadContract({

  contract: contract,

  method: "function getUserCampaigns(address _user) view returns ((address
campaignAddress, address owner, string name, uint256 creationTime)[])",

  params: [account?.address as string]

});

return (

  <div className="mx-auto max-w-7xl px-6 mt-16 sm:px-8 lg:px-10 text-gray-800">

    <div className="flex flex-row justify-between items-center mb-8">

      <p className="text-4xl font-bold bg-gradient-to-r from-indigo-500 via-purple-500
to-pink-500 text-transparent bg-clip-text">Dashboard</p>

      <button

        className="rounded-md px-5 py-3 text-sm font-medium text-white bg-gradient-
to-r from-blue-500 to-indigo-600 hover:scale-105 transition-transform border border-white"

        onClick={() => setIsModalOpen(true)}

        >Create Campaign</button>

      </div>

      <p className="text-2xl font-semibold mb-4 bg-gradient-to-r from-indigo-500 via-
purple-500 to-pink-500 text-transparent bg-clip-text">My Campaigns:</p>

      <div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-3 gap-6">

        {!isLoadingMyCampaigns && (

          myCampaigns && myCampaigns.length > 0 ? (

            myCampaigns.map((campaign, index) => (
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
        <MyCampaignCard
            key={index}
            contractAddress={campaign.campaignAddress}
        />
    ))
): (
    <p className="text-gray-500 text-lg">No campaigns found.</p>
)
)}
</div>

{isModalOpen && (
    <CreateCampaignModal
        setIsModalOpen={setIsModalOpen}
        refetch={refetch}
    />
)}
</div>

);
}
```

```
const CreateCampaignModal = ({ setIsModalOpen, refetch }) => {
    const account = useActiveAccount();
    const [isDeployingContract, setIsDeployingContract] = useState(false);
    const [campaignName, setCampaignName] = useState("");
    const [campaignDescription, setCampaignDescription] = useState("");
    const [campaignGoal, setCampaignGoal] = useState(1);
    const [campaignDeadline, setCampaignDeadline] = useState(1);
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
const handleDeployContract = async () => {
  setIsDeployingContract(true);
  try {
    console.log("Deploying contract...");
    await deployPublishedContract({
      client: client,
      chain: baseSepolia,
      account: account!,
      contractId: "Crowdfunding",
      contractParams: [campaignName, campaignDescription, campaignGoal,
campaignDeadline],
      publisher: "0x57e5f74c4E413B3ccB5B27dd90740D95d7da2616",
      version: "1.0.4",
    });
    alert("Contract deployed successfully!");
  } catch (error) {
    console.error(error);
  } finally {
    setIsDeployingContract(false);
    setIsModalOpen(false);
    refetch();
  }
};

return (
  <div className="fixed inset-0 flex items-center justify-center bg-black bg-opacity-70
backdrop-blur-md p-4">
    <div className="w-full max-w-lg bg-white p-6 rounded-lg shadow-xl">
      <div className="flex justify-between items-center mb-4">
        <p className="text-lg font-semibold text-gray-800">Create a Campaign</p>
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
<button
  className="rounded-md px-4 py-2 text-sm font-medium text-white bg-red-
600 hover:bg-red-700 transition-all border border-white"
  onClick={() => setIsModalOpen(false)}
>Close</button>
</div>
<div className="flex flex-col space-y-4">
  Campaign Name<input
    type="text"
    value={campaignName}
    onChange={(e) => setCampaignName(e.target.value)}
    placeholder="Campaign Name"
    className="px-4 py-2 border rounded-lg focus:ring-2 focus:ring-blue-500"
  />
  Campaign Description<textarea
    value={campaignDescription}
    onChange={(e) => setCampaignDescription(e.target.value)}
    placeholder="Campaign Description"
    className="px-4 py-2 border rounded-lg focus:ring-2 focus:ring-blue-500"
  ></textarea>
  Campaign Goal<input
    type="number"
    value={campaignGoal}
    onChange={(e) => setCampaignGoal(Math.max(1, parseInt(e.target.value)))}
    className="px-4 py-2 border rounded-lg focus:ring-2 focus:ring-blue-500"
  />
  Number of Day's<input
    type="number"
    value={campaignDeadline}
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
      onChange={(e) => setCampaignDeadline(Math.max(1,
parseInt(e.target.value)))}}

      className="px-4 py-2 border rounded-lg focus:ring-2 focus:ring-blue-500"
    />

    <button

      className="rounded-md px-4 py-2 text-sm font-medium text-white bg-
gradient-to-r from-blue-500 to-indigo-600 hover:scale-105 transition-transform border
border-white"

      onClick={handleDeployContract}

    >{isDeployingContract ? "Creating..." : "Create Campaign"}</button>

  </div>

</div>

</div>

);

};
```

5. news/[walletAddress]-> page.tsx

"use client";

```
import { useState, useEffect } from "react";

export default function NewsPage() {
  const [news, setNews] = useState<any[]>([]);
  const [loading, setLoading] = useState(true);
  const [error, setError] = useState<string | null>(null);

  useEffect(() => {
    fetch("/api/rss")
      .then((res) => {
        if (!res.ok) throw new Error("Failed to fetch news");
        return res.json();
      })
      .catch((err) => setError(err.message));
  }, []);
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
    })
    .then((data) => {
      console.log(" 🚀 API Response:", data);
      setNews(data);
    })
    .catch((err) => {
      console.error(" ❌ Error fetching news:", err);
      setError(err.message);
    })
    .finally(() => setLoading(false));
  }, []);

return (
  <div className="mx-auto max-w-7xl px-4 mt-8 sm:px-6 lg:px-8">
    <h2 className="text-2xl font-semibold mb-4 bg-gradient-to-r from-indigo-500 via-purple-500 to-pink-500 text-transparent bg-clip-text">Latest Crowdfunding News</h2>

    {loading && <p className="text-gray-500">Loading news...</p>}
    {error && <p className="text-red-500">Error: {error}</p>}

    {news.length > 0 ? (
      news.map((item, index) => (
        <div key={index} className="p-4 border rounded mb-4 flex flex-col md:flex-row
items-center">
          { /* 🖼️ Display Image */}
          {item.image ? (
            <img
              src={item.image}
              alt={item.title}
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
        className="w-40 h-40 object-cover mr-4 rounded"

        onError={(e) => {

            e.currentTarget.src = "https://via.placeholder.com/150"; // Fallback image

        }}

    />

): (

    <div className="w-40 h-40 bg-gray-300 flex items-center justify-center text-gray-500 rounded">

        No Image

    </div>

)}

<div>

    <h3 className="font-semibold text-lg">{item.title}</h3>

    <p className="text-sm text-gray-700">{item.contentSnippet || "No description available"}</p>

    <a href={item.link} className="text-blue-500 mt-2 inline-block" target="_blank" rel="noopener noreferrer">

        Read more

    </a>

</div>

</div>

))

): (

    !loading && !error && <p className="text-gray-500">No news available at the moment.</p>

)}

</div>

);

}
```


EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

6. src/client.ts

```
import { createThirdwebClient } from "thirdweb";

// Replace this with your client ID string

// refer to https://portal.thirdweb.com/typescript/v5/client on how to get a client ID

//const clientId = 'a980f7430b54e2cbcd0d2a18651ec48d'; //Web3 project ID

const clientId = '71fe643506a32e2d03d622e9acf6bd48'; //Web3 project ID

if (!clientId) {

  throw new Error("No client ID provided");

}

export const client = createThirdwebClient({

  clientId: clientId,

});
```

7. src/global.css

```
@tailwind base;

@tailwind components;

@tailwind utilities;

:root {

  line-height: 1.5;

  font-weight: 400;

  font-synthesis: none;

  text-rendering: optimizeLegibility;

  -webkit-font-smoothing: antialiased;

  -moz-osx-font-smoothing: grayscale;

  font-family: 'Inter', sans-serif;

  font-optical-sizing: auto;

  font-style: normal;

  font-variation-settings: 'slnt' 0;

}
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
@layer base {  
  body {  
    @apply bg-zinc-950 text-neutral-200;  
  }  
}  
  
@layer components {  
  .btn-primary {  
    @apply rounded-md px-4 py-2 text-sm font-medium text-white bg-gradient-to-r from-indigo-500 via-purple-500 to-pink-500 hover:bg-white hover:text-purple-700 transition duration-300 border border-white shadow-md;  
  }  
  
  .btn-secondary {  
    @apply rounded-md px-4 py-2 text-sm font-medium text-white bg-gray-700 hover:bg-gray-600 transition duration-300 border border-gray-500 shadow-md;  
  }  
  
  .modal-overlay {  
    @apply fixed inset-0 flex items-center justify-center bg-black bg-opacity-70 z-50 p-4;  
  }  
  
  .modal-content {  
    @apply bg-white p-6 rounded-xl shadow-2xl w-96 relative text-black;  
  }  
}
```

8. src/layout.tsx

```
import type { Metadata } from "next";  
  
import { Inter } from "next/font/google";
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
import './globals.css';

import { ThirdwebProvider } from 'thirdweb/react';

import Navbar from '@components/Navbar';

const inter = Inter({ subsets: ['latin'] });

export const metadata: Metadata = {
  title: 'EtherFund',
  description:
    'Starter template for using thirdweb SDK with Next.js App router',
};

export default function RootLayout({
  children,
}: Readonly<{
  children: React.ReactNode;
}>) {
  return (
    <html lang="en">
      <body className="bg-slate-100 text-slate-700">
        <ThirdwebProvider>
          <Navbar />
          {children}
        </ThirdwebProvider>
      </body>
    </html>
  );
}
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

9. src/page.tsx

```
'use client';

import { useReadContract } from "thirdweb/react";

import { client } from "../client";

import { baseSepolia } from "thirdweb/chains";

import { getContract } from "thirdweb";

import { CampaignCard } from "@components/CampaignCard";

import { CROWDFUNDING_FACTORY } from "../constants/contracts";

import { Loader2 } from "lucide-react";

export default function Home() {

  // Get CrowdfundingFactory contract

  const contract = getContract({

    client: client,

    chain: baseSepolia,

    address: CROWDFUNDING_FACTORY,

  });

  // Get all campaigns deployed with CrowdfundingFactory

  const { data: campaigns, isLoading: isLoadingCampaigns, refetch: refetchCampaigns } =
    useReadContract({

      contract: contract,

      method: "function getAllCampaigns() view returns ((address campaignAddress, address owner, string name)[])",

      params: []

    });

  return (

    <div>

      <div>
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
<main className="mx-auto max-w-7xl px-6 mt-4 sm:px-8 lg:px-12 mb-6">
  <div className="py-12 text-center">
    <h1 className="text-5xl font-extrabold bg-gradient-to-r from-indigo-500 via-purple-500 to-pink-500 text-transparent bg-clip-text">
      Explore EtherFund Campaigns
    </h1>
    <p className="mt-4 text-lg font-extrabold bg-gradient-to-r from-indigo-500 via-purple-500 to-pink-500 text-transparent bg-clip-text">Support or start your journey with decentralized fundraising.</p>
  </div>
```

```
{/* Campaigns Section */}
<div className="mt-4">
  {/* Loading State */}
  {isLoadingCampaigns ? (
    <div className="flex justify-center py-10">
      <Loader2 className="w-8 h-8 animate-spin text-indigo-400" />
    </div>
  ) : (
    <div className="grid grid-cols-1 sm:grid-cols-2 md:grid-cols-3 gap-6">
      {campaigns && campaigns.length > 0 ? (
        campaigns.map((campaign) => (
          <CampaignCard
            key={campaign.campaignAddress}
            campaignAddress={campaign.campaignAddress}
          />
        ))
      ) : (
        <p className="col-span-full text-center text-gray-400 text-lg">
          No active campaigns at the moment. Start one today!
        </p>
      )
    </div>
  )
}
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
        </p>
      )}
    </div>
  )}
</div>
</main>
</div>
</div>
);
}
```

10. Components-> CampaignCard.tsx

```
import { client } from "@app/client";
import { getContract } from "thirdweb";
import { baseSepolia } from "thirdweb/chains";
import { useReadContract } from "thirdweb/react";
import React, { useState } from "react";
import Link from "next/link";
import { FaFacebook, FaTwitter, FaWhatsapp, FaInstagram, FaLinkedin, FaSnapchat } from "react-icons/fa";

type CampaignCardProps = {
  campaignAddress: string;
};

export const CampaignCard: React.FC<CampaignCardProps> = ({ campaignAddress }) => {
  const contract = getContract({
    client: client,
    chain: baseSepolia,
    address: campaignAddress,
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
});
```

```
const { data: campaignName } = useReadContract({  
  contract: contract,  
  method: "function name() view returns (string)",  
  params: [],  
});
```

```
const { data: campaignDescription } = useReadContract({  
  contract: contract,  
  method: "function description() view returns (string)",  
  params: [],  
});
```

```
const { data: goal } = useReadContract({  
  contract: contract,  
  method: "function goal() view returns (uint256)",  
  params: [],  
});
```

```
const { data: balance } = useReadContract({  
  contract: contract,  
  method: "function getContractBalance() view returns (uint256)",  
  params: [],  
});
```

```
const [isModalOpen, setIsModalOpen] = useState(false);  
const toggleModal = () => setIsModalOpen(!isModalOpen);
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
const totalBalance = balance?.toString();

const totalGoal = goal?.toString();

let balancePercentage = (parseInt(totalBalance as string) / parseInt(totalGoal as string)) *
100;
```

```
if (balancePercentage >= 100) {
    balancePercentage = 100;
}
```

```
return (
```

```
    <
```

```
    <div className="flex flex-col justify-between max-w-sm p-6 bg-gradient-to-r from-
indigo-500 via-purple-500 to-pink-500 border border-gray-400 rounded-2xl shadow-2xl
transition-transform duration-300 hover:scale-105 hover:shadow-3xl relative text-white">
```

```
        <div>
```

```
            <div className="mb-4">
```

```
                <div className="relative w-full h-6 bg-gray-300 rounded-full overflow-hidden
shadow-inner">
```

```
                    <div
```

```
                        className="h-6 bg-gradient-to-r from-green-400 to-blue-500 rounded-full
transition-all duration-500"
```

```
                            style={{ width: `${balancePercentage?.toString()}%` }}
```

```
                    ></div>
```

```
                <p className="absolute inset-0 flex items-center justify-center text-xs font-
semibold text-black">
```

```
                    {balancePercentage >= 100 ? "Goal Reached" :
`${balancePercentage?.toFixed(2)}%`}
```

```
                </p>
```

```
            </div>
```

```
        </div>
```

```
        <h5 className="mb-2 text-2xl font-extrabold tracking-tight text-white drop-shadow-
lg">
```


EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
    {campaignName}
  </h5>

  <p className="mb-3 text-gray-300 text-sm leading-relaxed">
    {campaignDescription}
  </p>
</div>

<div className="flex justify-between">
  <Link href={` /campaign/${campaignAddress}`} passHref>
    <button className="rounded-md px-4 py-2 text-sm font-medium text-white
    hover:bg-white hover:text-purple-700 transition duration-300 border border-white">
      View Campaign
    </button>
  </Link>
  <button
    onClick={toggleModal}
    className="rounded-md px-4 py-2 text-sm font-medium text-white hover:bg-white
    hover:text-purple-700 transition duration-300 border border-white"
  >
    Share
  </button>
</div>
</div>

{isModalOpen && (
  <div className="fixed inset-0 flex items-center justify-center bg-black bg-opacity-70
  z-50 p-4">
    <div className="bg-white p-6 rounded-xl shadow-2xl w-96 relative text-black">
      <h2 className="text-lg font-bold mb-4">Share Campaign</h2>
      <div className="flex flex-col space-y-4">
        <a
          href={` https://www.facebook.com/sharer/sharer.php?u=https://yourdomain.com/campaign/${
            campaignAddress}`} target="_blank" rel="noopener noreferrer" className="flex items-
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
center space-x-2 px-3 py-2 text-sm font-medium text-white bg-blue-600 rounded-lg
hover:bg-blue-700 transition-all hover:shadow-md">
```

```
<FaFacebook /> <span>Share on Facebook</span>
```

```
</a>
```

```
<a
```

```
href={`https://twitter.com/intent/tweet?url=https://yourdomain.com/campaign/${campaignAd
dress}&text=Check out this campaign!`} target="_blank" rel="noopener noreferrer"
className="flex items-center space-x-2 px-3 py-2 text-sm font-medium text-white bg-blue-
400 rounded-lg hover:bg-blue-500 transition-all hover:shadow-md">
```

```
<FaTwitter /> <span>Share on Twitter</span>
```

```
</a>
```

```
<a href={`https://api.whatsapp.com/send?text=Check out this campaign!
https://yourdomain.com/campaign/${campaignAddress}`} target="_blank" rel="noopener
noreferrer" className="flex items-center space-x-2 px-3 py-2 text-sm font-medium text-
white bg-green-500 rounded-lg hover:bg-green-600 transition-all hover:shadow-md">
```

```
<FaWhatsapp /> <span>Share on WhatsApp</span>
```

```
</a>
```

```
<a href={`https://www.instagram.com/`} target="_blank" rel="noopener noreferrer"
className="flex items-center space-x-2 px-3 py-2 text-sm font-medium text-white bg-pink-
600 rounded-lg hover:bg-pink-700 transition-all hover:shadow-md">
```

```
<FaInstagram /> <span>Share on Instagram</span>
```

```
</a>
```

```
<a
```

```
href={`https://www.linkedin.com/shareArticle?url=https://yourdomain.com/campaign/${cam
paignAddress}`} target="_blank" rel="noopener noreferrer" className="flex items-center
space-x-2 px-3 py-2 text-sm font-medium text-white bg-blue-800 rounded-lg hover:bg-blue-
900 transition-all hover:shadow-md">
```

```
<FaLinkedin /> <span>Share on LinkedIn</span>
```

```
</a>
```

```
<a href={`https://www.snapchat.com`} target="_blank" rel="noopener noreferrer"
className="flex items-center space-x-2 px-3 py-2 text-sm font-medium text-white bg-
yellow-500 rounded-lg hover:bg-yellow-600 transition-all hover:shadow-md">
```

```
<FaSnapchat /> <span>Share on Snapchat</span>
```

```
</a>
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
    </div>

    <button onClick={toggleModal} className="mt-4 px-3 py-2 text-sm font-medium
text-white bg-red-600 rounded-lg hover:bg-red-700 transition-all hover:shadow-md w-full">

      Close

    </button>

  </div>

</div>

  )}

</>

);

};
```

11. Components-> MyCampaignCard.tsx

```
'use client';

import { client } from "@app/client";

import Link from "next/link";

import { getContract } from "thirdweb";

import { baseSepolia } from "thirdweb/chains";

import { useReadContract } from "thirdweb/react";

import React, { useState } from "react";

import { FaFacebook, FaTwitter, FaWhatsapp, FaInstagram, FaLinkedin, FaSnapchat } from
"react-icons/fa";

type MyCampaignCardProps = {

  contractAddress: string;

};

export const MyCampaignCard: React.FC<MyCampaignCardProps> = ({ contractAddress })
=> {

  const contract = getContract({

    client: client,
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
chain: baseSepolia,  
address: contractAddress,  
});
```

```
// Get Campaign Name
```

```
const { data: name } = useReadContract({  
  contract,  
  method: "function name() view returns (string)",  
  params: []  
});
```

```
const { data: description } = useReadContract({  
  contract,  
  method: "function description() view returns (string)",  
  params: []  
});
```

```
const [isModalOpen, setIsModalOpen] = useState(false);  
const toggleModal = () => setIsModalOpen(!isModalOpen);
```

```
return (  
  <
```

```
    <
```

```
      <div className="flex flex-col justify-between max-w-sm p-6 bg-gradient-to-r from-indigo-500 via-purple-500 to-pink-500 border border-gray-400 rounded-2xl shadow-2xl transition-transform duration-300 hover:scale-105 hover:shadow-3xl text-white">
```

```
        <div>
```

```
          <h5 className="mb-2 text-2xl font-extrabold tracking-tight text-white drop-shadow-lg">{name}</h5>
```

```
          <p className="mb-3 text-gray-300 text-sm leading-relaxed">{description}</p>
```

```
        </div>
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
<div className="flex gap-4">

  <Link href={` /campaign/${contractAddress}`} passHref>

    <button className="rounded-md px-4 py-2 text-sm font-medium text-white
hover:bg-white hover:text-purple-700 transition duration-300 border border-white">

      View Campaign

    </button>

  </Link>

  <button

    onClick={toggleModal}

    className="rounded-md px-4 py-2 text-sm font-medium text-white hover:bg-
white hover:text-purple-700 transition duration-300 border border-white"

  >

    Share

  </button>

</div>

</div>

{isModalOpen && (

  <div className="fixed inset-0 flex items-center justify-center bg-black bg-opacity-
70 z-50 p-4">

    <div className="bg-white p-6 rounded-xl shadow-2xl w-96 relative text-
black">

      <h2 className="text-lg font-bold mb-4">Share Campaign</h2>

      <div className="flex flex-col space-y-4">

        <a

href={`https://www.facebook.com/sharer/sharer.php?u=https://yourdomain.com/campaign/${
contractAddress}`} target="_blank" rel="noopener noreferrer" className="flex items-center
space-x-2 px-3 py-2 text-sm font-medium text-white bg-blue-600 rounded-lg hover:bg-blue-
700 transition-all hover:shadow-md">

          <FaFacebook /> <span>Share on Facebook</span>

        </a>
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
<a
href={`https://twitter.com/intent/tweet?url=https://yourdomain.com/campaign/${contractAdd
ress}&text=Check out this campaign!`} target="_blank" rel="noopener noreferrer"
className="flex items-center space-x-2 px-3 py-2 text-sm font-medium text-white bg-blue-
400 rounded-lg hover:bg-blue-500 transition-all hover:shadow-md">

    <FaTwitter /> <span>Share on Twitter</span>

</a>

<a href={`https://api.whatsapp.com/send?text=Check out this campaign!
https://yourdomain.com/campaign/${contractAddress}`} target="_blank" rel="noopener
noreferrer" className="flex items-center space-x-2 px-3 py-2 text-sm font-medium text-
white bg-green-500 rounded-lg hover:bg-green-600 transition-all hover:shadow-md">

    <FaWhatsapp /> <span>Share on WhatsApp</span>

</a>

<a href={`https://www.instagram.com/`} target="_blank" rel="noopener
noreferrer" className="flex items-center space-x-2 px-3 py-2 text-sm font-medium text-
white bg-pink-600 rounded-lg hover:bg-pink-700 transition-all hover:shadow-md">

    <FaInstagram /> <span>Share on Instagram</span>

</a>

<a
href={`https://www.linkedin.com/shareArticle?url=https://yourdomain.com/campaign/${cont
ractAddress}`} target="_blank" rel="noopener noreferrer" className="flex items-center
space-x-2 px-3 py-2 text-sm font-medium text-white bg-blue-800 rounded-lg hover:bg-blue-
900 transition-all hover:shadow-md">

    <FaLinkedin /> <span>Share on LinkedIn</span>

</a>

<a href={`https://www.snapchat.com`} target="_blank" rel="noopener
noreferrer" className="flex items-center space-x-2 px-3 py-2 text-sm font-medium text-
white bg-yellow-500 rounded-lg hover:bg-yellow-600 transition-all hover:shadow-md">

    <FaSnapchat /> <span>Share on Snapchat</span>

</a>

</div>

<button onClick={toggleModal} className="mt-4 px-3 py-2 text-sm font-
medium text-white bg-red-600 rounded-lg hover:bg-red-700 transition-all hover:shadow-md
w-full">

    Close
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```

</button>

</div>

</div>

)}

</>

);

};

```

12. Components->Navbar.tsx

```
'use client';

import { client } from "@app/client";

import Link from "next/link";

import { ConnectButton, lightTheme, useActiveAccount } from "thirdweb/react";

import Image from 'next/image';

import thirdwebIcon from "@public/thirdweb.svg";


const Navbar = () => {

    const account = useActiveAccount();



    return (
        <nav className="bg-gradient-to-r from-indigo-500 via-purple-500 to-pink-500 shadow-lg border-b-2 border-purple-300">
            <div className="mx-auto max-w-7xl px-2 sm:px-6 lg:px-8">
                <div className="relative flex h-16 items-center justify-between">
                    <div className="absolute inset-y-0 left-0 flex items-center sm:hidden">
                        <button type="button" className="relative inline-flex items-center justify-center rounded-md p-2 text-white hover:bg-purple-700 focus:outline-none focus:ring-2 focus:ring-inset focus:ring-white" aria-controls="mobile-menu" aria-expanded="false">
                            <span className="absolute -inset-0.5"></span>
                            <span className="sr-only">Open main menu</span>
                        </button>
                    </div>

```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
<svg className="block h-6 w-6" fill="none" viewBox="0 0 24 24"
strokeWidth="1.5" stroke="currentColor" aria-hidden="true">

  <path strokeLinecap="round" strokeLinejoin="round" d="M3.75
6.75h16.5M3.75 12h16.5m-16.5 5.25h16.5" />

</svg>

</button>

</div>

<div className="flex flex-1 items-center justify-center sm:items-stretch
sm:justify-start">

  {/*<div className="flex flex-shrink-0 items-center">

    <Image

      src={thirdwebIcon}

      alt="Your Company"

      width={32}

      height={32}

      className="drop-shadow-xl"

    />

  </div>*/}

  <div className="hidden sm:ml-6 sm:block">

    <div className="flex space-x-4">

      <Link href={"/"}>

        <p className="rounded-md px-4 py-2 text-sm font-medium text-
white hover:bg-white hover:text-purple-700 transition duration-300">Home</p>

      </Link>

      {account && (

        <Link href={` /dashboard/${account?.address}`} >

          <p className="rounded-md px-4 py-2 text-sm font-medium text-
white hover:bg-white hover:text-purple-700 transition duration-300">Dashboard</p>

        </Link>

      )}

      <Link href={` /news/${account?.address}`} >
```


EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
<p className="rounded-md px-4 py-2 text-sm font-medium text-white hover:bg-white hover:text-purple-700 transition duration-300">News Feed</p>
```

```
</Link>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
<div className="absolute inset-y-0 right-0 flex items-center pr-2 sm:static sm:inset-auto sm:ml-6 sm:pr-0">
```

```
<ConnectButton
```

```
  client={client}
```

```
  theme={lightTheme()}
```

```
  detailsButton={{
```

```
    style: {
```

```
      maxHeight: "50px",
```

```
      borderRadius: "8px",
```

```
      backgroundColor: "white",
```

```
      color: "#6b46c1"
```

```
    }
```

```
  }}  
/>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
</nav>
```

```
)
```

```
};
```

```
export default Navbar;
```

13. Components-> TierCard.tsx

```
import { prepareContractCall, ThirdwebContract } from "thirdweb";
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
import { TransactionButton } from "thirdweb/react";
```

```
type Tier = {  
  name: string;  
  amount: bigint;  
  backers: bigint;  
};
```

```
type TierCardProps = {  
  tier: Tier;  
  index: number;  
  contract: ThirdwebContract  
  isEditing: boolean;  
}
```

```
export const TierCard: React.FC<TierCardProps> = ({ tier, index, contract, isEditing }) => {  
  return (  
    <div className="max-w-sm flex flex-col justify-between p-6 bg-white border border-slate-100 rounded-lg shadow">  
      <div>  
        <div className="flex flex-row justify-between items-center">  
          <p className="text-2xl font-semibold">{tier.name}</p>  
          <p className="text-2xl font-semibold">฿ {tier.amount.toString()}</p>  
        </div>  
      </div>  
      <div className="flex flex-row justify-between items-end">  
        <p className="text-xs font-semibold">Total Donator's:  
{tier.backers.toString()}</p>  
        <TransactionButton  
          transaction={() => prepareContractCall({
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
        contract: contract,
        method: "function fund(uint256 _tierIndex) payable",
        params: [BigInt(index)],
        value: tier.amount,
    }}}
    onError={({error}) => alert(`Error: ${error.message}`)}
    onTransactionConfirmed={async () => alert("Funded successfully!")}
    style={{
        marginTop: "1rem",
        backgroundColor: "#2563EB",
        color: "white",
        padding: "0.5rem 1rem",
        borderRadius: "0.375rem",
        cursor: "pointer",
    }}
    >Select</TransactionButton>
</div>
{isEditing && (
    <TransactionButton
        transaction={() => prepareContractCall({
            contract: contract,
            method: "function removeTier(uint256 _index)",
            params: [BigInt(index)],
        })}
        onError={({error}) => alert(`Error: ${error.message}`)}
        onTransactionConfirmed={async () => alert("Removed successfully!")}
        style={{
            marginTop: "1rem",
            backgroundColor: "red",
```

EtherFund – Transforming Crowdfunding through Blockchain

Language of work - Solidity | TypeScript

```
        color: "white",
        padding: "0.5rem 1rem",
        borderRadius: "0.375rem",
        cursor: "pointer",
    }}
    >Remove</TransactionButton>
  )}
</div>
)
};
```