

RAKSHITH P

```
drop database if exists order_processing;  
create database order_processing;  
use order_processing;
```

```
create table if not exists Customers (  
  cust_id int primary key,  
  cname varchar(35) not null,  
  city varchar(35) not null  
);
```

```
create table if not exists Orders (  
  order_id int primary key,  
  odate date not null,  
  cust_id int,  
  order_amt int not null,  
  foreign key (cust_id) references Customers(cust_id) on delete cascade  
);
```

```
create table if not exists Items (  
  item_id int primary key,  
  unitprice int not null  
);
```

```
create table if not exists OrderItems (  
  order_id int not null,  
  item_id int not null,  
  qty int not null,  
  foreign key (order_id) references Orders(order_id) on delete cascade,  
  foreign key (item_id) references Items(item_id) on delete cascade  
);
```

```
create table if not exists Warehouses (  
  warehouse_id int primary key,  
  city varchar(35) not null  
);
```

```
create table if not exists Shipments (  
  order_id int not null,  
  warehouse_id int not null,  
  ship_date date not null,  
  foreign key (order_id) references Orders(order_id) on delete cascade,  
  foreign key (warehouse_id) references Warehouses(warehouse_id) on delete cascade  
);
```

```
INSERT INTO Customers VALUES  
  (0001, "Customer_1", "Mysuru"),  
  (0002, "Customer_2", "Bengaluru"),  
  (0003, "Kumar", "Mumbai"),  
  (0004, "Customer_4", "Dehli"),  
  (0005, "Customer_5", "Bengaluru");
```

INSERT INTO Orders VALUES

(001, "2020-01-14", 0001, 2000),
 (002, "2021-04-13", 0002, 500),
 (003, "2019-10-02", 0003, 2500),
 (004, "2019-05-12", 0005, 1000),
 (005, "2020-12-23", 0004, 1200);

INSERT INTO Items VALUES

(0001, 400),
 (0002, 200),
 (0003, 1000),
 (0004, 100),
 (0005, 500);

INSERT INTO Warehouses VALUES

(0001, "Mysuru"),
 (0002, "Bengaluru"),
 (0003, "Mumbai"),
 (0004, "Dehli"),
 (0005, "Chennai");

INSERT INTO OrderItems VALUES

(001, 0001, 5),
 (002, 0005, 1),
 (003, 0005, 5),
 (004, 0003, 1),
 (005, 0004, 12);

INSERT INTO Shipments VALUES

(001, 0002, "2020-01-16"),
 (002, 0001, "2021-04-14"),
 (003, 0004, "2019-10-07"),
 (004, 0003, "2019-05-16"),
 (005, 0005, "2020-12-23");

SELECT * FROM Customers;

cust_id	cname	city
1	Customer_1	Mysuru
2	Customer_2	Bengaluru
3	Kumar	Mumbai
4	Customer_4	Dehli
5	Customer_5	Bengaluru

SELECT * FROM Orders;

order_id	odate	cust_id	order_amt
1	2020-01-14	1	2000
2	2021-04-13	2	500
3	2019-10-02	3	2500
4	2019-05-12	5	1000
5	2020-12-23	4	1200

SELECT * FROM OrderItems;

order_id	item_id	qty
1	1	5
2	5	1
3	5	5
4	3	1
5	4	12

SELECT * FROM Items;

item_id	unitprice
1	400
2	200
3	1000
4	100
5	500

SELECT * FROM Shipments;

order_id	warehouse_id	ship_date
1	2	2020-01-16
2	1	2021-04-14
3	4	2019-10-07
4	3	2019-05-16
5	5	2020-12-23

SELECT * FROM Warehouses;

warehouse_id	city
1	Mysuru
2	Bengaluru
3	Mumbai
4	Dehli
5	Chennai

-- List the Order# and Ship_date for all orders shipped from Warehouse# "0001".

```
select order_id,ship_date from Shipments where warehouse_id=0001;
```

order_id	ship_date
2	2021-04-14

-- List the Warehouse information from which the Customer named "Kumar" was supplied his orders. Produce a listing of Order#, Warehouse#

```
select order_id,warehouse_id from Warehouses natural join Shipments where order_id in
(select order_id from Orders where cust_id in (Select cust_id from Customers where cname
like "%Kumar%"));
```

order_id	warehouse_id
3	4

--Produce a listing: Cname, #ofOrders, Avg_Order_Amt, where the middle column is the total number of orders by the customer and the last column is the average order amount for that customer. (Use aggregate functions)

```
select cname, COUNT(*) as no_of_orders, AVG(order_amt) as avg_order_amt
from Customers c, Orders o
where c.cust_id=o.cust_id
group by cname;
```

cname	no_of_orders	avg_order_amt
Customer_1	1	2000.0000
Customer_2	1	500.0000
Kumar	1	2500.0000
Customer_4	1	1200.0000
Customer_5	1	1000.0000

-- Delete all orders for customer named "Kumar".

```
delete from Orders where cust_id = (select cust_id from Customers where cname like
"%Kumar%");
```

```
SELECT * FROM Orders;
```

order_id	odate	cust_id	order_amt
3	2019-10-02	3	2500

```
SELECT * FROM OrderItems;
```

order_id	item_id	qty
3	5	5

```
SELECT * FROM Shipments;
```

order_id	warehouse_id	ship_date
3	4	2019-10-07

```
-- Find the item with the maximum unit price.
```

```
select max(unitprice) from Items;
```

max(unitprice)
1000

```
-- A trigger that updates order_amount based on quantity and unit price of order_item
```

```
DELIMITER $$
```

```
create trigger UpdateOrderAmt
```

```
after insert on OrderItems
```

```
for each row
```

```
BEGIN
```

```
update Orders set order_amt=(new.qty*(select distinct unitprice from Items
```

```
NATURAL JOIN OrderItems where item_id=new.item_id)) where
```

```
Orders.order_id=new.order_id;
```

```
END; $$
```

```
DELIMITER;
```

```
INSERT INTO Orders VALUES
```

```
(006, "2020-12-23", 0004, 1200);
```

```
SELECT * FROM Orders;
```

order_id	odate	cust_id	order_amt
1	2020-01-14	1	2000
2	2021-04-13	2	500
4	2019-05-12	5	1000
5	2020-12-23	4	1200
6	2020-12-23	4	2000

```
INSERT INTO OrderItems VALUES
(006, 0001, 5);
SELECT * FROM OrderItems;
```

order_id	item_id	qty
1	1	5
2	5	1
4	3	1
5	4	12
6	1	5

-- Create a view to display orderID and shipment date of all orders shipped from a warehouse 5.

```
create view ShipmentDatesFromWarehouse5 as
select order_id, ship_date
from Shipments
where warehouse_id=5;
select * from ShipmentDatesFromWarehouse5;
```

order_id	ship_date
5	2020-12-23