WEEK - 08 FORWARD REASONING ALGORITHM

```
def fol fc ask(KB, query):
   Implements the Forward Chaining algorithm.
   :param KB: The knowledge base, a list of first-order definite clauses.
   :param query: The query, an atomic sentence.
   :return: True if the query can be proven, otherwise False.
  inferred = set()
                    # Keep track of inferred facts
   agenda = [fact for fact in KB if not fact.get('premises')] # Initial
facts
   rules = [rule for rule in KB if rule.get('premises')] # Rules with
premises
   # Debugging output: Initial agenda and inferred facts
   print(f"Initial agenda: {[fact['conclusion'] for fact in agenda]}")
   print(f"Initial inferred: {inferred}")
   while agenda:
       fact = agenda.pop(0)
       print(f"\nProcessing fact: {fact['conclusion']}")
       # Check if this fact matches the query
       if fact['conclusion'] == query:
           print(f"Found query match: {fact['conclusion']}")
           return True
       # Infer new facts if this fact hasn't been inferred before
       if fact['conclusion'] not in inferred:
           inferred.add(fact['conclusion'])
           print(f"Inferred facts: {inferred}")
           # Process rules that match this fact as a premise
           for rule in rules:
               if fact['conclusion'] in rule['premises']:
                   print(f"Rule premise satisfied: {rule['premises']} ->
{rule['conclusion']}")
                   rule['premises'].remove(fact['conclusion'])
satisfied premise
```

```
if not rule['premises']: # All premises satisfied
                       new fact = {'conclusion': rule['conclusion']}
                       agenda.append(new fact) # Add new fact to agenda
                       print(f"New fact inferred:
{new fact['conclusion']}")
       # Debugging output after each iteration
       print(f"Current agenda: {[fact['conclusion'] for fact in agenda]}")
       print(f"Current inferred: {inferred}")
   # If the loop finishes without finding the query
  print(f"Query {query} not found.")
   return False
# Example Knowledge Base
KB = [
  {'premises': [], 'conclusion': 'American(Robert)'},
   {'premises': [], 'conclusion': 'Missile(T1)'},
   {'premises': [], 'conclusion': 'Owns(A, T1)'},
   {'premises': [], 'conclusion': 'Enemy(A, America)'},
   {'premises': ['Missile(T1)'], 'conclusion': 'Weapon(T1)'},
   {'premises': ['American(Robert)', 'Weapon(T1)', 'Sells(Robert, T1, A)',
'Hostile(A)'], 'conclusion': 'Criminal(Robert)'},
   {'premises': ['Owns(A, T1)', 'Enemy(A, America)'], 'conclusion':
'Hostile(A)'},
   {'premises': [], 'conclusion': 'Sells(Robert, T1, A)'}
1
# Query
query = 'Criminal(Robert)'
# Run the algorithm
result = fol fc ask(KB, query)
print("\nFinal Result:", result)
print("Vaibhav Urs A N")
print ("1BM22CS315")
```

OUTPUT

```
Initial agenda: ['American(Robert)', 'Missile(T1)', 'Owns(A, T1)', 'Enemy(A, America)', 'Sells(Robert, T1, A)']
Initial inferred: set()
Processing fact: American(Robert)
Inferred facts: {'American(Robert)'}
Rule premise satisfied: ['American(Robert)', 'Weapon(T1)', 'Sells(Robert, T1, A)', 'Hostile(A)'] -> Criminal(Robert) Current agenda: ['Missile(T1)', 'Owns(A, T1)', 'Enemy(A, America)', 'Sells(Robert, T1, A)']
Current inferred: {'American(Robert)'}
Processing fact: Missile(T1)
Inferred facts: {'Missile(T1)', 'American(Robert)'}
Rule premise satisfied: ['Missile(T1)'] -> Weapon(T1)
New fact inferred: Weapon(T1)
Current agenda: ['Owns(A, T1)', 'Enemy(A, America)', 'Sells(Robert, T1, A)', 'Weapon(T1)']
Current inferred: {'Missile(T1)', 'American(Robert)'}
Processing fact: Owns(A, T1)
Inferred facts: {'Owns(A, T1)', 'Missile(T1)', 'American(Robert)'}
Rule premise satisfied: ['Owns(A, T1)', 'Enemy(A, America)'] -> Hostile(A)
Current agenda: ['Enemy(A, America)', 'Sells(Robert, T1, A)', 'Weapon(T1)']
Current inferred: {'Owns(A, T1)', 'Missile(T1)', 'American(Robert)'}
Processing fact: Enemy(A, America) Inferred facts: {'Owns(A, T1)', 'Missile(T1)', 'Enemy(A, America)', 'American(Robert)'} Rule premise satisfied: ['Enemy(A, America)'] \rightarrow Hostile(A)
New fact inferred: Hostile(A)
Current agenda: ['Sells(Robert, T1, A)', 'Weapon(T1)', 'Hostile(A)']
Current inferred: {'Owns(A, T1)', 'Missile(T1)', 'Enemy(A, America)', 'American(Robert)'}
Processing fact: Sells(Robert, T1, A)
Inferred facts: {'Owns(A, T1)', 'American(Robert)', 'Missile(T1)', 'Sells(Robert, T1, A)', 'Enemy(A, America)'}
Rule premise satisfied: ['Weapon(T1)', 'Sells(Robert, T1, A)', 'Hostile(A)'] -> Criminal(Robert)
Current agenda: ['Weapon(T1)', 'Hostile(A)']
Current inferred: {'Owns(A, T1)', 'American(Robert)', 'Missile(T1)', 'Sells(Robert, T1, A)', 'Enemy(A, America)'}
Processing fact: Weapon(T1)
Inferred facts: "Reapon(T1), 'American(Robert)', 'Weapon(T1)', 'Missile(T1)', 'Sells(Robert, T1, A)', 'Enemy(A, America)'}
Rule premise satisfied: ['Weapon(T1)', 'Hostile(A)'] -> Criminal(Robert)
Current agenda: ['Hostile(A)']
Current inferred: {'Owns(A, T1)', 'American(Robert)', 'Weapon(T1)', 'Missile(T1)', 'Sells(Robert, T1, A)', 'Enemy(A, America)'}
Processing fact: Hostile(A)
Inferred facts: {'Hostile(A)', 'Owns(A, T1)', 'American(Robert)', 'Weapon(T1)', 'Missile(T1)', 'Sells(Robert, T1, A)', 'Enemy(A, America)'}
Rule premise satisfied: ['Hostile(A)'] -> Criminal(Robert)
New fact inferred: Criminal(Robert)
Current agenda: ['Criminal(Robert)']
Current inferred: {'Hostile(A)', 'Owns(A, T1)', 'American(Robert)', 'Weapon(T1)', 'Missile(T1)', 'Sells(Robert, T1, A)', 'Enemy(A, America)'}
Processing fact: Criminal(Robert)
Found query match: Criminal(Robert)
Final Result: True
Vaibhav Urs A N
1BM22CS315
```