

ASSIGNMENT 14

```
mysql> INSERT INTO SALESPEOPLE (CITY, SNAME, COMM, SNUM)
-> VALUES ('San Jose', 'Blanco', NULL, 1100);
Query OK, 1 row affected (0.05 sec)

mysql> DELETE FROM ORDERS WHERE CNUM =
-> (SELECT CNUM FROM CUSTOMERS WHERE CNAME = 'CLEMENS');
Query OK, 2 rows affected (0.03 sec)

mysql> UPDATE Customers
-> SET rating = rating + 100
-> WHERE city = 'Rome';
Query OK, 2 rows affected (0.00 sec)
Rows matched: 2 Changed: 2 Warnings: 0

mysql> UPDATE CUSTOMERS
-> SET SNUM = (SELECT SNUM FROM SALESPEOPLE WHERE SANME = 'Motika')
-> WHERE SNUM = (SELECT SNUM FROM SALESPEOPLE WHERE SNAME = 'Serres');
ERROR 1054 (42S22): Unknown column 'SANME' in 'where clause'
mysql> UPDATE CUSTOMERS
-> SET SNUM = (SELECT SNUM FROM SALESPEOPLE WHERE SNAME = 'Motika')
-> WHERE SNUM = (SELECT SNUM FROM SALESPEOPLE WHERE SNAME = 'Serres');
Query OK, 2 rows affected (0.03 sec)
Rows matched: 2 Changed: 2 Warnings: 0

mysql> show tables;
+-----+
| Tables_in_assignment1 |
+-----+
| customers              |
| orders                 |
| salespeople            |
+-----+
3 rows in set (0.00 sec)
```

```
mysql> SELECT * FROM salespeople;
+-----+-----+-----+-----+
| Snum | sname  | City      | comm |
+-----+-----+-----+-----+
| 1001 | peel   | London    | 0.12 |
| 1002 | serres | san jose  | 0.13 |
| 1004 | Rifkin | Barcelona | 0.14 |
| 1003 | Axelrod | New York  | 0.15 |
| 1001 | jose   | London    | 0.11 |
| 1100 | Blanco | San Jose  | NULL  |
+-----+-----+-----+-----+
6 rows in set (0.00 sec)

mysql> |
```