

EXP 5 OUTPUT:

The screenshot shows a C program being executed in a development environment. The source code in `exp5.c` defines a process scheduling algorithm. It prompts the user to enter the number of processes (`n`), then for each process `Pi`, it asks for its burst time and priority. The processes are then sorted by priority (highest first) to determine the execution order. In this case, the order is P3, P1, and then P2.

```
1 #include <stdio.h>
2
3 int main() {
4     int n, i, j;
5     int pid[10], burst[10], priority[10];
6     int temp;
7     printf("Enter number of processes: ");
8     scanf("%d", &n);
9     for (i = 0; i < n; i++)
10
11
12 {
13     pid[i] = i + 1;
14     printf("\nEnter burst time for P%d: ", pid[i]);
15     scanf("%d", &burst[i]);
16     printf("Enter priority for P%d: ", pid[i]);
17     scanf("%d", &priority[i]);
18
19 }
20
21 for (i = 0; i < n - 1; i++)
22
23
24
```

The console window shows the following interaction:

```
Enter burst time for P1: 3
Enter priority for P1: 2

Enter burst time for P2: 4
Enter priority for P2: 3

Enter burst time for P3: 5
Enter priority for P3: 1

Process Burst Time      Priority
P3          5             1
P1          3             2
P2          4             3

Execution Order: P3->P1->P2->

-----
Process exited after 12.72 seconds with return value 0
Press any key to continue . . .
```

The compile log at the bottom indicates a successful compilation with no errors or warnings.

```
-----
- Errors: 0
- Warnings: 0
- Output Filename: C:\Users\User\OneDrive\Documents\OPERATING SYSTEM LAB EXPERIMENTS\exp5.exe
- Output Size: 138.6 KiB
- Compilation Time: 3.44s
```