

**SIMATS ENGINEERING
ASSESSMENT TOOL 2**

COURSE NAME: COMPUTER NETWORKS
COURSE CODE: CSA0714
NAME:VAIBHAV A LAKSHMI K
REG. NO:192511310

COURSE OUTCOME COVERED

CO4:

Design network topologies star, mesh, bus, and hybrid using networking devices, transmission media, and cabling standards
(BL2,BL6)

Assessment Tool Weightage: 30%

Annexure A

Industry Problem-Solving Task

1. A star topology is ideal for a 20-person startup because all devices connect to a central switch, making the network easy to manage and troubleshoot. At the core sits a Layer 2/Layer 3 managed switch (such as a Cisco Catalyst or Netgear ProSafe) with at least 24 ports to accommodate all workstations, printers, and VoIP phones with room to grow. Each device connects to the switch using Cat6 UTP cables, which support Gigabit speeds up to 100 meters — more than sufficient for any typical office floor plan. The switch uplinks to a router/firewall (such as a Cisco RV series or pfSense appliance) that handles internet access, DHCP, and network address translation. A Wi-Fi access point connected to the switch extends wireless coverage for laptops and mobile devices.

The key advantage of this design is fault isolation: if one workstation's cable fails, only that single node goes offline, leaving all other 19 employees unaffected. Centralised cable management also simplifies future moves, adds, and changes.

2. A bank demands near-zero downtime, making a full or partial mesh topology the right choice. In a full mesh, every core network device — routers, core switches, and servers — connects directly to every other device, so no single link or node failure can bring down the network. For a bank, a partial mesh is typically deployed at the core layer (connecting all core switches and firewalls to each other) while the distribution and access layers use redundant uplinks to at least two core switches. Dual enterprise-grade routers (such as Cisco ASR or Juniper MX series) provide BGP-based redundant internet connectivity. All links between core devices use fiber optic cables — either single-mode for long distances between buildings or multi-mode OM4 within the data center — because fiber is immune to electromagnetic interference, supports very high bandwidth, and is essential for maintaining low-latency financial transactions. Redundant power supplies, UPS systems, and RAID storage arrays further complement the mesh design. The justification is straightforward: when a link fails in a mesh, traffic automatically reroutes through alternative paths in milliseconds using protocols like OSPF or BGP, satisfying regulatory requirements for uptime and data integrity.

- 3.** For a small classroom lab with a tight budget, bus topology offers the lowest hardware cost because all computers share a single common communication line — the bus — eliminating the need for a central switch or hub. A single coaxial cable (RG-58, 50-ohm) or, in a modern variation, a single Cat5e/Cat6 cable daisy-chained through an inexpensive unmanaged hub runs along the length of the room. Each computer connects to the backbone using a T-connector and a BNC connector in a classic coaxial setup, with terminators (50-ohm) placed at both ends of the cable to absorb signals and prevent reflection. For a more contemporary low-cost implementation, a single inexpensive 8- or 16-port unmanaged switch replaces the terminators and uses Cat5e UTP patch cables to each workstation — achieving bus-like simplicity at minimal cost. The primary limitation is that the network is susceptible to collisions and a single cable break disrupts all connected machines, but for a supervised classroom environment with light usage (internet browsing, file sharing), this trade-off is entirely acceptable. No dedicated server is required; a teacher's PC can share resources using built-in Windows/Linux file sharing.
- 4.** A large university campus serves thousands of users across multiple buildings — lecture halls, labs, libraries, dormitories, and administration — making a single topology inadequate. A hybrid topology combines the best elements of multiple designs: a fiber-based ring or mesh at the campus backbone level for redundancy, a star topology within each building for manageability, and bus or

tree structures within individual labs for cost-efficiency. At the campus core, high-speed fiber optic cables (single-mode, 10 Gbps or 40 Gbps) interconnect core routers and multilayer switches using a ring or partial mesh arrangement, ensuring that no single link failure isolates an entire building. Each building has its own distribution switch connected to the campus core via dual fiber uplinks. Within each building, a traditional star topology branches from the distribution switch to floor-level access switches, which then connect individual devices via Cat6 cables. This hierarchical three-layer model — core, distribution, and access — is the industry standard for enterprise and campus networks because adding a new building simply means installing a new distribution switch and running fiber to the core, with no disruption to existing infrastructure. Wireless access points throughout the campus connect via PoE (Power over Ethernet) to access switches, eliminating the need for separate power cabling. The hybrid design thus delivers redundancy at the backbone, simplicity at the building level, and scalability campus-wide.

5. Designing a network for a company with multiple departments involves creating a structured and scalable architecture using switches and routers to ensure efficient communication and security. Each department (such as HR, Finance, Sales, and IT) is connected through dedicated Layer 2 switches that form the access layer, allowing devices like computers and printers to communicate within the same department. These switches are then

connected to a central Layer 3 switch or router, which acts as the core layer and enables communication between different departments through inter-VLAN routing. Virtual LANs (VLANs) are configured to logically separate each department's network, improving security and reducing broadcast traffic. A router is also used to connect the internal network to external networks such as the internet, often with firewall functionality for security. Redundant links and backup paths can be included to ensure reliability, while proper IP addressing and subnetting are applied for efficient network management. This hierarchical design improves performance, enhances security, and allows easy expansion as the company grows.

3. For a small classroom lab with a tight budget, bus topology offers the lowest hardware cost because all computers share a single common communication line — the bus — eliminating the need for a central switch or hub. A single coaxial cable (RG-58, 50-ohm) or, in a modern variation, a single Cat5e/Cat6 cable daisy-chained through an inexpensive unmanaged hub runs along the length of the room. Each computer connects to the backbone using a T-connector and a BNC connector in a classic coaxial setup, with terminators (50-ohm) placed at both ends of the cable to absorb signals and prevent reflection. For a more contemporary low-cost implementation, a single inexpensive 8- or 16-port unmanaged switch replaces the terminators and uses Cat5e UTP patch cables to each workstation — achieving bus-like simplicity at minimal cost. The primary limitation is that the network is susceptible to collisions and a single cable break disrupts all connected machines, but for a supervised classroom environment with light usage (internet browsing, file sharing), this trade-off is entirely acceptable. No dedicated server is required; a teacher's PC can share resources using built-in Windows/Linux file sharing.

ANSWER:

Problem Analysis

A small classroom laboratory requires a computer network to connect multiple computers for basic activities such as:

- Internet browsing
- File sharing
- Sharing learning materials
- Communication between computers

The laboratory has a **tight budget**, so the network should use minimum networking hardware.

A **bus topology** is suitable because all computers share a single common communication line. In the traditional implementation, an RG-58 50-ohm coaxial cable is used as the backbone, with T-connectors, BNC connectors, and 50-ohm terminators at both ends

Proposed Network Design

A classroom with four computers (PC0, PC1, PC2 and PC3) is considered. The computers share a common backbone cable. The two ends of the backbone are terminated with 50-ohm terminators.




FIGURE: BUS TOPOLOGY

Hardware and Software Requirements

Component	Quantity	Purpose
Computer / PC	4	Workstations in the classroom
RG-58 50-ohm coaxial cable	As required	Common bus backbone
BNC T-connectors	4	Connect each PC to the backbone
BNC connectors	As required	Connect coaxial cable
50-ohm terminators	2	Terminate both ends and prevent signal reflection
Network Interface Card	1 per PC	Provides network connectivity
Cisco Packet Tracer	1	Simulation and connectivity testing

IP Addressing Plan


The following private IPv4 addressing scheme is used for the classroom LAN:

Computer	IP Address	Subnet Mask	Default Gateway
PC0	192.168.10.1	255.255.255.0	Not required for local LAN testing
PC1	192.168.10.2	255.255.255.0	Not required for local LAN testing
PC2	192.168.10.3	255.255.255.0	Not required for local LAN testing
PC3	192.168.10.4	255.255.255.0	Not required for local LAN testing

Physical Implementation of the Bus Topology

The traditional bus implementation is constructed as follows:

1. Run one RG-58 coaxial cable along the length of the classroom.
2. Place a 50-ohm terminator at the first end of the backbone.
3. Use a BNC T-connector for each workstation.
4. Connect each computer's network interface to the T-connector using the BNC connection.
5. Continue the same backbone cable through all workstation connections.
6. Place a second 50-ohm terminator at the other end of the backbone.
7. Ensure that all computers are configured within the same IP network



Connectivity Testing and Validation:

After configuring the IP addresses, open PC0 → Desktop → Command Prompt and execute the ping commands.

Example test:

```
C:\> ping 192.168.10.2
```

Pinging 192.168.10.2 with 32 bytes of data:

Reply from 192.168.10.2: bytes=32 time<1ms TTL=128

Reply from 192.168.10.2: bytes=32 time<1ms TTL=128

Reply from 192.168.10.2: bytes=32 time<1ms TTL=128

Reply from 192.168.10.2: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.10.2:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss)

The same test is performed for PC2 and PC3. A successful response with zero packet loss indicates successful communication between the source and destination computers.

Test	Command	Expected Result
PC0 → PC1	ping 192.168.10.2	Reply received / 0% loss
PC0 → PC2	ping 192.168.10.3	Reply received / 0% loss
PC0 → PC3	ping 192.168.10.4	Reply received / 0% loss
IP verification	ipconfig	Correct IP and subnet mask displayed

Comparison of Traditional and Modern Options

Feature	Traditional Bus	Modern Low-Cost Alternative
Topology	Bus	Star using unmanaged switch
Main cable	RG-58 coaxial	Cat5e/Cat6 UTP
Central switch	Not required	8/16-port unmanaged switch
Termination	50-ohm terminators	Not applicable
Cost	Low	Low
Maintenance	More difficult	Easier
Modern availability	Limited/outdated	High
Assessment use	True bus implementation	Practical modern alternative

RUBRICS FOR CALCULATION

Criteria	Weightage	Exemplary (4)	Proficient (3)	Developing (2)	Beginning (1)
Problem Analysis	15%	Clearly identifies and deeply analyzes the industry problem with all factors	Good understanding with minor gaps	Basic understanding; some key aspects missing	Poor or incorrect understanding of the problem
Solution Design	20%	Innovative, practical, and industry-relevant solution	Effective solution with minor limitations	Partially suitable solution	Inappropriate or unclear solution
Technical Implementation	20%	Fully functional, accurate, and well-executed implementation	Mostly functional with minor errors	Partially implemented solution	Incomplete or non-functional implementation
Use of Tools & Technologies	10%	Appropriate and advanced use of relevant tools and technologies	Correct use of tools	Limited or basic use of tools	Incorrect or no use of tools
Problem-Solving Approach	10%	Logical, systematic, and well-structured approach	Mostly logical approach	Somewhat disorganized approach	No clear approach
Innovation & Creativity	10%	Highly creative and original solution	Some creativity	Limited originality	No creativity
Testing & Validation	5%	Thorough testing with real-world scenarios	Adequate testing	Minimal testing	No testing

Documentation & Presentation	5%	Clear, professional, and well-documented	Good documentation	Basic documentation	Poor or no documentation
Teamwork / Collaboration	5%	Excellent coordination and contribution (if team-based)	Good collaboration	Limited participation	No collaboration or contribution