

WPT Mock 1 Batch FEB 2026

Total points 39/61 ?

The respondent's email (**vaibhavkharche4328@gmail.com**) was recorded on submission of this form.

PRN *

260245920079

NAME *

Vaibhav Ashok Kharche

✓ **Q1: Which HTTP method is used to request data from a specified resource in a stateless manner?**

*1/1

- ☐ A) POST
- ☒ B) GET
- ☐ C) PUT
- ☐ D) DELETE



✓ **Q2: Which HTTP status code indicates that the request was successful and the server has fulfilled the request?** *1/1

- ☒ A) 200
- ☐ B) 404
- ☐ C) 500
- ☐ D) 301



✗ **Q3: What is the difference between HTTP 1.0 and HTTP 2.0? *** 0/1

- ☐ A) HTTP 2.0 allows multiplexing, reducing latency
- ☐ B) HTTP 1.0 is faster
- ☒ C) HTTP 2.0 uses TCP for communication, unlike HTTP 1.0
- ☐ D) There is no difference



Correct answer

- ☒ A) HTTP 2.0 allows multiplexing, reducing latency

✓ **Q4: Which of the following protocols is used to encrypt communication over the web, ensuring secure data transfer?** *1/1

- ☐ A) HTTP
- ☒ B) HTTPS
- ☐ C) FTP
- ☐ D) SSH



✓ **Q5: Which of the following web servers supports running JavaScript applications?** *1/1

- ☐ A) Apache
- ☐ B) Nginx
- ☐ C) IIS
- ☒ D) Node.js



✓ **Q6: What is the purpose of the <canvas> tag in HTML5? *** 1/1

- ☒ A) To draw graphics dynamically via JavaScript
- ☐ B) To display a video
- ☐ C) To structure a webpage
- ☐ D) To embed an interactive form



✗ **Q7: Which HTML5 attribute is used to specify the validation pattern for form input fields?** *0/1

- ☐ A) pattern
- ☐ B) regex
- ☒ C) required
- ☐ D) validate



Correct answer

- ☒ A) pattern



✗ **Q8: Which of the following is NOT a new feature introduced in HTML5? *** 0/1

- ☐ A) Geolocation
- ☒ B) Local storage
- ☐ C) WebSockets
- ☐ D) <frame>

✗

Correct answer

- ☒ D) <frame>

✓ **Q9: What is the default value of the type attribute for the <input> tag in HTML5? *** 1/1

- ☒ A) text
- ☐ B) password
- ☐ C) submit
- ☐ D) radio

✓

✓ **Q10: Which of the following elements is used to create an ordered list in HTML? *** 1/1

- ☐ A) <list>
- ☐ B) <unordered>
- ☐ C) <order>
- ☒ D)

✓



✓ **Q11: In CSS, what is the purpose of the box-sizing property? ***

1/1

- ☐ A) To define the dimensions of an element
- ☒ B) To include padding and border in the element's total width and height ✓
- ☐ C) To manage element margins
- ☐ D) To define the background size

✗ **Q12: Which CSS property is used to control the stacking order of elements?**

*0/1

- ☐ A) z-index
- ☐ B) position
- ☒ C) margin ✗
- ☐ D) display

Correct answer

- ☒ A) z-index



✗ **Q13: How can you make a webpage responsive across different screen sizes using CSS?** *0/1

- ☐ A) Use media queries
- ☒ B) Use viewport units
- ☐ C) Apply fixed widths for all elements
- ☐ D) Set a constant height for all elements

✗

Correct answer

- ☒ A) Use media queries

✓ **Q14: What is the purpose of the @media rule in CSS? ***

1/1

- ☐ A) To target specific HTML elements based on conditions
- ☐ B) To include external media files like images
- ☒ C) To apply CSS rules only when certain conditions are met (e.g., screen width) ✓
- ☐ D) To animate elements on a webpage



✗ **Q15: In CSS, which property is used to set the space between the content and the border of an element?**

*0/1

- ☐ A) margin
- ☐ B) padding
- ☒ C) border-width
- ☐ D) spacing

✗

Correct answer

- ☒ B) padding

✓ **Q16: Which of the following is a JavaScript feature introduced in ECMAScript 6 (ES6)?**

*1/1

- ☐ A) var keyword
- ☒ B) let and const keywords
- ☐ C) Function declarations
- ☐ D) String concatenation

✓



✗ **Q17: Which of the following is true about JavaScript functions? ***

0/1

- ☐ A) Functions can return values
- ☐ B) Functions cannot have parameters
- ☐ C) Functions do not support closures
- ☒ D) Functions are always anonymous

✗

Correct answer

- ☒ A) Functions can return values

✓ **Q18: What is the purpose of JSON.parse() in JavaScript? ***

1/1

- ☐ A) To convert an object to a JSON string
- ☒ B) To parse a JSON string and convert it to a JavaScript object
- ☐ C) To store JSON data in a variable
- ☐ D) To validate the structure of a JSON object

✓



✗ Q19: In JavaScript, what does the this keyword refer to inside a method? * 0/1

- ☐ A) The global object
- ☐ B) The object the method is called on
- ☐ C) The function itself
- ☒ D) The parent object

✗

Correct answer

- ☒ B) The object the method is called on

✗ Q20: Which of the following is true about promises in JavaScript? * 0/1

- ☐ A) Promises are used for handling synchronous operations
- ☒ B) A promise can have only one state (pending, resolved, or rejected) at a time
- ☐ C) Promises are used for handling asynchronous operations
- ☐ D) Promises do not need to be handled with .then() or .catch()

✗

Correct answer

- ☒ C) Promises are used for handling asynchronous operations



✓ **Q21: In React, which of the following hooks is used to manage the state of a functional component?** *1/1

- ☐ A) useEffect
- ☒ B) useState
- ☐ C) useReducer
- ☐ D) useMemo



✗ **Q22: Which of the following is true about React components? *** 0/1

- ☐ A) Components cannot be reused
- ☐ B) Components can be either class-based or functional
- ☒ C) Class components are slower than functional components
- ☐ D) React only supports functional components



Correct answer

- ☒ B) Components can be either class-based or functional

✓ **Q23: Which method is used to update the state in a React class component?** *1/1

- ☒ A) this.setState()
- ☐ B) this.updateState()
- ☐ C) this.changeState()
- ☐ D) this.modifyState()



✓ **Q24: What is the purpose of Redux in a React application? ***

1/1

- ☐ A) To handle component lifecycle methods
- ☐ B) To manage local component state
- ☒ C) To manage the global application state
- ☐ D) To directly manipulate the DOM



✓ **Q25: In Redux, what is the role of the "reducer"? ***

1/1

- ☒ A) To update the state based on actions
- ☐ B) To send actions to the store
- ☐ C) To trigger side-effects
- ☐ D) To create actions



✓ **Q26: Which of the following is true about the useEffect hook in React? ***

1/1

- ☐ A) It is used to manage the state of a component
- ☒ B) It is used to perform side-effects like fetching data
- ☐ C) It is used to create new components
- ☐ D) It is only available in class components



✓ **Q27: How is data passed from a parent component to a child component in React?** *1/1

- ☒ A) Through props
- ☐ B) Through state
- ☐ C) Through context
- ☐ D) Through Redux



✓ **Q28: What is the purpose of React's useContext hook?** * 1/1

- ☐ A) To pass data between sibling components
- ☒ B) To share data between components without passing props
- ☐ C) To directly update the component's state
- ☐ D) To handle form submissions



✓ **Q29: What is the Redux store responsible for?** * 1/1

- ☐ A) Handling component lifecycle
- ☐ B) Fetching data from APIs
- ☒ C) Storing the global state of the application
- ☐ D) Rendering the UI



✓ **Q30: In React, what does JSX stand for? ***

1/1

- ☒ A) JavaScript XML
- ☐ B) JavaScript Extension
- ☐ C) JavaScript Executable
- ☐ D) JavaScript Excerpt



✓ **Q31: Which of the following actions can be dispatched in a Redux application?**

*1/1

- ☐ A) Only synchronous actions
- ☐ B) Only asynchronous actions
- ☒ C) Both synchronous and asynchronous actions
- ☐ D) Only actions that modify the UI



✗ **Q32: In React-Redux, which function is used to connect a component to the Redux store? ***0/1

- ☐ A) connect()
- ☐ B) useState()
- ☐ C) useEffect()
- ☒ D) createStore()



Correct answer

- ☒ A) connect()



✓ **Q33: What is the purpose of the require() function in Node.js? ***

1/1

- ☒ A) To import external modules
- ☐ B) To initialize the Node.js server
- ☐ C) To execute JavaScript code
- ☐ D) To start an event listener



✓ **Q34: Which method is used to create an HTTP server in Node.js? ***

1/1

- ☒ A) http.createServer()
- ☐ B) server.create()
- ☐ C) server.start()
- ☐ D) node.create()



✓ **Q35: In Node.js, what does the fs module provide? ***

1/1

- ☐ A) Database functionality
- ☒ B) File system-related operations
- ☐ C) HTTP request/response handling
- ☐ D) Real-time web sockets



✓ **Q36: What is the purpose of the package.json file in a Node.js project? *** 1/1

- ☐ A) To define the folder structure
- ☐ B) To manage environment variables
- ☒ C) To list project dependencies and scripts
- ☐ D) To configure Node.js server settings



✓ **Q37: What is the role of the npm command in Node.js development? *** 1/1

- ☐ A) To manage database queries
- ☐ B) To compile JavaScript code
- ☒ C) To install, update, and manage packages
- ☐ D) To serve web pages



✓ **Q38: What does the callback function in Node.js refer to? *** 1/1

- ☒ A) A function that is invoked at a later time after an operation completes
- ☐ B) A function that handles errors only
- ☐ C) A function that processes API responses
- ☐ D) A function that sets up event listeners



✗ Q39: How does Node.js handle asynchronous I/O operations? *

0/1

- ☐ A) Using an event-driven, non-blocking I/O model
- ☒ B) By blocking the main thread until I/O completes
- ☐ C) Using the multi-threaded processing model
- ☐ D) Using synchronous I/O operations only

✗

Correct answer

- ☒ A) Using an event-driven, non-blocking I/O model

✓ Q40: What is the role of middleware in Express.js? *

1/1

- ☐ A) To handle database connections
- ☒ B) To process HTTP requests and responses before they reach the route handler
- ☐ C) To handle routing for different HTTP methods
- ☐ D) To manage server performance

✓



✗ Q41: Which of the following is a correct way to start an Express.js server?

*0/1

- ☐ A) app.listen(3000)
- ☐ B) server.listen(3000)
- ☐ C) http.createServer(app).listen(3000)
- ☒ D) express.start(3000)

✗

Correct answer

- ☒ A) app.listen(3000)

✗ Q42: What is the role of the express.Router() in Express.js? *

0/1

- ☒ A) To handle HTTP requests
- ☐ B) To connect to the database
- ☐ C) To define and manage route handling logic
- ☐ D) To serve static files

✗

Correct answer

- ☒ C) To define and manage route handling logic



✓ **Q43: Which HTTP method would you use to update an existing resource on the server?** *1/1

- ☐ A) POST
- ☐ B) DELETE
- ☒ C) PUT
- ☐ D) GET



✓ **Q44: What is the main benefit of using Node.js for web development?** * 1/1

- ☐ A) It is based on a multi-threaded processing model
- ☐ B) It allows real-time interactions using WebSockets
- ☒ C) It uses a single-threaded, non-blocking event loop for efficient I/O operations ✓
- ☐ D) It is primarily designed for server-side rendering

✓ **Q45: What is the role of the next() function in Express.js middleware?** * 1/1

- ☒ A) It passes control to the next middleware function ✓
- ☐ B) It ends the request-response cycle
- ☐ C) It starts the server
- ☐ D) It triggers a route handler



✗ **Q46: What does the use() method in Express.js do? ***

0/1

- ☐ A) Creates routes for HTTP requests
- ☐ B) Defines a server's static files
- ☐ C) Mounts middleware functions
- ☒ D) Configures the port

✗

Correct answer

- ☒ C) Mounts middleware functions

✓ **Q47: In React-Redux, what is an action? ***

1/1

- ☒ A) An object that describes an event to be processed by the reducer
- ☐ B) A function that triggers a state change
- ☐ C) A way to modify component state directly
- ☐ D) A component responsible for rendering UI

✓

✓ **Q48: In Redux, what is the role of the store? ***

1/1

- ☐ A) To handle asynchronous actions
- ☐ B) To dispatch actions
- ☒ C) To hold the application's state
- ☐ D) To interact with the server

✓



✗ **Q49: Which of the following is true about React-Redux's `mapStateToProps` function?**

*0/1

- ☐ A) It is used to dispatch actions
- ☐ B) It maps the Redux state to component props
- ☒ C) It provides middleware functionality
- ☐ D) It renders the component with the state

✗

Correct answer

- ☒ B) It maps the Redux state to component props

✓ **Q50: What is the primary purpose of `useSelector` in React-Redux? ***

1/1

- ☐ A) To dispatch actions to the Redux store
- ☐ B) To modify the Redux store
- ☒ C) To extract data from the Redux store
- ☐ D) To map Redux state to props

✓



✗ **Q 51: Which of the following is the correct way to embed a video in HTML5?**

*0/1

<video controls>

<source src="video.mp4" type="video/mp4">

Your browser does not support the video tag.

</video>

- ☐ A) <embed src="video.mp4" type="video/mp4">
- ☐ B) <video src="video.mp4" controls>
- ☐ C) <video controls><source src="video.mp4"></video>
- ☒ D) <video><source src="video.mp4" type="video/mp4"></video>

✗

Correct answer

- ☒ C) <video controls><source src="video.mp4"></video>

✓ **Q 52 Which CSS property is used to define the space between the content and the border of an element?**

*1/1

```
.box {  
padding: 20px;  
}
```

- ☐ A) margin
- ☐ B) border
- ☒ C) padding
- ☐ D) spacing

✓



✓ **Q 53: What will the following JavaScript code output? ***

1/1

```
let a = [1, 2, 3];a[5] = 10;  
console.log(a.length);
```

- ☐ A)5
- ☒ B)6
- ☐ C)3
- ☐ D)undefined

✓ **Q 54 Which of the following methods is used to remove a child node from a parent in the DOM?**

*1/1

```
let parent = document.getElementById('parent');let child =  
document.getElementById('child');
```

- ☒ A)parent.removeChild(child)
- ☐ B)parent.deleteChild(child)
- ☐ C)child.removeNode()
- ☐ D)parent.remove(child)



✓ **Q55** In React, what is the output of the following code?

* 1/1

```
const MyComponent = () => {return <h1>Hello, {name}</h1>;};  
ReactDOM.render(<MyComponent />, document.getElementById('root'));
```

- ☐ A) Hello, {name}
- ☒ B) Hello, undefined
- ☐ C) Hello, world
- ☐ D) Compilation Error

✗ **Q 56:** How would you update the state of a React component in a functional component using hooks?

*0/1

```
const [count, setCount] = useState(0);  
const handleClick = () => {  
  // Update state here  
};  
return (<div><button onClick={handleClick}>Increment</button><p>{count}</p></div>);
```

- ☐ A) setCount(count + 1)
- ☒ B) this.setState(count + 1)
- ☐ C) setCount(() => count + 1)
- ☐ D) count += 1



Correct answer

- ☒ A) setCount(count + 1)



✗ Q 57 What is the role of an action in Redux?

*

0/1

```
const action = { type: 'ADD_ITEM', payload: 'Item 1' };
```

- ☐ A) To modify the Redux store directly
- ☐ B) To dispatch a state change request to the reducer
- ☒ C) To store the current state
- ☐ D) To call the API for data fetching

✗

Correct answer

- ☒ B) To dispatch a state change request to the reducer

✗ Q 58 Which of the following is the correct way to implement a reducer function in Redux?

*0/1

```
const initialState = { items: [] }; const itemsReducer = (state = initialState, action) => { switch (action.type) { case 'ADD_ITEM': return { ...state, items: [...state.items, action.payload] }; default: return state; } };
```

- ☐ A) state.items.push(action.payload)
- ☐ B) state.items = state.items.concat(action.payload)
- ☒ C) return { state.items.push(action.payload) }
- ☐ D) return { ...state, action.payload }

✗

Correct answer

- ☒ B) state.items = state.items.concat(action.payload)



✗ Q 59 What is the result of the following Node.js code snippet? *

0/1

```
console.log('A');setTimeout(() =>console.log('B'), 0);console.log('C');
```

☒ A) A B C

✗

☐ B) A C B

☐ C) B A C

☐ D) C B A

Correct answer

☒ B) A C B

✓ Q 60 In Express.js, what does the following middleware function do? *

1/1

```
app.use((req, res, next) => {console.log('Request received');next();});
```

☐ A) Logs the request and sends the response

☐ B) Prevents the request from being processed further

☒ C) Logs the request and passes control to the next middleware

✓

☐ D) Sends a response immediately after logging the request



✗ **Q 61: Which of the following is a correct way to pass a prop to a child component in React?** *0/1

`constParentComponent = () => {return<ChildComponentname="John" />;};`

- ☒ A)ChildComponent.name = "John" ✗
- ☐ B)name = "John"
- ☐ C)ChildComponent({ name: "John" })
- ☐ D)name="John" in <ChildComponent

Correct answer

- ☒ D)name="John" in <ChildComponent

This content is neither created nor endorsed by Google. - [Contact form owner](#) - [Terms of Service](#) - [Privacy Policy](#).

Does this form look suspicious? [Report](#)

Google Forms



