

WPT Mock 2 Batch FEB 2026

Total points 40/62 ?

The respondent's email (**vaibhavkharche4328@gmail.com**) was recorded on submission of this form.

PRN *

260245920079

NAME *

Vaibhav Ashok Kharche

✗ **Q 61: Which of the following is a correct way to pass a prop to a child component in React?** *0/1

```
constParentComponent = () => {return<ChildComponentname="John" />;};
```

- ☐ A)ChildComponent.name = "John"
- ☐ B)name = "John"
- ☒ C)ChildComponent({ name: "John" })
- ☐ D)name="John" in <ChildComponent

✗

Correct answer

- ☒ D)name="John" in <ChildComponent



✗ **Q 62 Which HTML element is used to create a dropdown list in a form?** *0/1

`<select><option value="1">Option 1</option><option value="2">Option 2</option></select>`

- ☐ A) `<input type="dropdown">`
- ☐ B) `<select>`
- ☒ C) `<option>`
- ☐ D) `<dropdown>`

✗

Correct answer

- ☒ B) `<select>`

✗ **Q 63: What will the following Node.js code do?** *0/1

`const http = require('http'); const server = http.createServer((req, res) => {res.write('Hello World');res.end();}); server.listen(3000);`

- ☒ A) Start an HTTP server and display "Hello World" on port 3000
- ☐ B) Display "Hello World" in the console
- ☐ C) Listen to HTTP requests on port 3000
- ☐ D) Both A and C

✗

Correct answer

- ☒ D) Both A and C



✓ **Q 64 Which of the following Axios methods sends a GET request to the given URL?** *1/1

```
axios.get('/api/data') .then(response => console.log(response.data))  
.catch(error => console.error(error));
```

- ☒ A) axios.get('/api/data')
- ☐ B) [axios.post](#)('/api/data')
- ☐ C) axios.fetch('/api/data')
- ☐ D) axios.query('/api/data')



✗ **Q 65 What will be the output of the following JavaScript code? *** 0/1

```
function greet(name = 'Guest') {return `Hello, ${name}`;}  
console.log(greet());  
console.log(greet('John'));
```

- ☒ A) Hello, undefined, Hello, Guest
- ☐ B) Hello, Guest, Hello, John
- ☐ C) Hello, John, Hello, Guest
- ☐ D) Hello, John, Hello, undefined



Correct answer

- ☒ B) Hello, Guest, Hello, John



✓ **Q 66 Which of the following React hooks is used to handle side effects in functional components?** *1/1

- ☒ A)useEffect()
- ☐ B)useState()
- ☐ C)useContext()
- ☐ D)useRef()



✓ **Q 67 What will the following code output?** *1/1

```
const jsonData = '{"name": "John", "age": 30}';  
const obj = JSON.parse(jsonData);  
console.log(obj.name);
```

- ☒ A)"John"
- ☐ B)name
- ☐ C)undefined
- ☐ D)30



✓ **Q 68 What does the following jQuery code do?** * 1/1

```
$('#myButton').click(function() {alert('Button clicked!');});
```

- ☐ A) Changes the background color of the button
- ☒ B) Adds an event listener to the button
- ☐ C) Hides the button
- ☐ D) Changes the text of the button



✗ **Q 69 Which lifecycle method in React is called after a component has been rendered to the screen?** *0/1

- ☐ A)componentDidMount()
- ☐ B)componentWillMount()
- ☒ C)render()
- ☐ D)getDerivedStateFromProps()

✗

Correct answer

- ☒ A)componentDidMount()

✓ **Q 70 What is the correct way to validate a form input field in HTML5? *** 1/1

```
<form>  
<input type="text" required><button type="submit">Submit</button>  
</form>
```

- ☐ A) Using JavaScript to check if the field is empty
- ☒ B) Adding the required attribute to the input field
- ☐ C) Using the validate() function
- ☐ D) Using the validate() event handler

✓



✓ **Q 71 What is the purpose of React Context? ***

1/1

- ☐ A) To manage local component state
- ☒ B) To manage global state for all components
- ☐ C) To handle side effects
- ☐ D) To render a component tree



✓ **Q 72 Which HTTP method is used to update a resource? ***

1/1

- ☐ A) GET
- ☐ B) POST
- ☒ C) PUT
- ☐ D) DELETE



✗ **Q 73: In Redux, which method is used to dispatch an action? ***

0/1

`const action = { type: 'ADD_ITEM', payload: 'Item 1' };`

- ☐ A) store.dispatch(action)
- ☒ B) dispatch(action)
- ☐ C) store.add(action)
- ☐ D) store.create(action)



Correct answer

- ☒ A) store.dispatch(action)



✓ **Q 74 How can you create an HTTP server in Node.js that listens for POST requests?** *1/1

```
const http = require('http');const server = http.createServer((req, res) => {if (req.method === 'POST') {res.write('POST request received');res.end();}});server.listen(3000);
```

- ☐ A)http.listen()
- ☒ B)server.listen() ✓
- ☐ C)server.on('POST')
- ☐ D)req.method('POST')

✓ **Q 75 How do you define a route for handling GET requests in Express.js?** *1/1

```
app.get('/home', (req, res) => {res.send('Welcome to Home');});
```

- ☐ A)app.route('/home').get()
- ☒ B)app.get('/home', handler) ✓
- ☐ C)router.get('/home')
- ☐ D)app.listen('/home')



✓ **Q 76 What will be the result of the following HTML code if the user tries to submit the form without filling the input field?** *1/1

```
<form>
<label for="username">Username:</label>
<input type="text" id="username" name="username" required>
<button type="submit">Submit</button>
</form>
```

- ☐ A) Form will submit successfully without validation.
- ☒ B) Browser will show an error message asking the user to fill the input. ✓
- ☐ C) The form will be reset automatically.
- ☐ D) Form will submit without any message.

✓ **Q 77 Given the following CSS and HTML, what will be the result of the layout?** *1/1

```
<div class="container">
  <div class="item">Item 1</div>
  <div class="item">Item 2</div>
  <div class="item">Item 3</div>
</div>

.container {
  display: flex;
  justify-content: space-between;}
.item {
  background-color: lightblue;
  padding: 10px;}
```

- ☒ A) The items will be arranged in a single row, with equal spacing between each. ✓
- ☐ B) The items will stack vertically with space between them.
- ☐ C) All items will be centered in the container.
- ☐ D) The items will be stacked with no space between them.



✓ **Q 78 What will be the output of the following JavaScript code? ***

1/1

```
const greeting = (name) => {  
  let message = `Hello, ${name}!`;   
  console.log(message);  
  greeting('Alice');  
  console.log(message);  
}
```

- ☐ A) Hello, Alice! and message is not defined
- ☐ B) Hello, Alice! and undefined
- ☐ C) Hello, Alice! and Hello, Alice!
- ☒ D) Error: message is not defined outside the function

✓ **Q 79 What will be the output of the following JavaScript code?**

*1/1

```
const nums = [1, 2, 3, 4, 5];  
const result = nums.map(num => num * 2).filter(num => num > 6);  
console.log(result);
```

- ☐ A) [2, 4, 6, 8, 10]
- ☒ B) [8, 10]
- ☐ C) [1, 2, 3, 4, 5]
- ☐ D) [6, 8, 10]



✖ Q 80 What will be the output of the following code? *

0/1

```
const person = {  
  name: 'John',  
  age: 30,  
  address: {city: 'New York',country: 'USA' }};  
const { name,  
  address: { city } } = person;  
console.log(name, city);
```

- ☐ A)John New York
- ☐ B)undefined New York
- ☐ C)John USA
- ☒ D)John undefined

✖

Correct answer

- ☒ A)John New York



✓ **Q 81 What will be the output of the following React component? ***

1/1

```
import React, { useState } from 'react';
const Counter = () => {
  const [count, setCount] = useState(0);
  return (
    <div>
      <button onClick={() => setCount(count + 1)}>Increment</button>
      <p>Count: {count}</p>
    </div>
  );
};
export default Counter;
```

- ☐ A) The count will always be 1 after the button is clicked.
- ☒ B) The count will increase by 1 each time the button is clicked. ✓
- ☐ C) The count will always remain 0 regardless of button clicks.
- ☐ D) Error: setCount is undefined.



✓ Q 82 What is the result of the following React code? *

1/1

```
import React, { useState } from 'react';
const ShowMessage = () => {
  const [isVisible, setIsVisible] = useState(false);
  return (
    <div>
      <button onClick={() => setIsVisible(!isVisible)}>Toggle
    </button> {isVisible} <p>This is a message.</p> </div> );
  };
export default ShowMessage;
```

- ☐ A) The message will be displayed initially.
- ☒ B) Clicking the button will toggle the visibility of the message. ✓
- ☐ C) The message will never be displayed.
- ☐ D) Error: isVisible is not defined.



✗ Q 83 How would you capture user input from a form in React?***0/1**

```
import React, { useState } from 'react';
const FormComponent = () => {
  const [name, setName] = useState('');
  const handleSubmit = (e) => {
    e.preventDefault();
    console.log(name);
  };
  return (
    <form onSubmit={handleSubmit}>
      <input type="text" value={name} onChange={(e) => setName(e.target.value)} />
      <button type="submit">Submit</button>
    </form>
  );
};
export default FormComponent;
```

- ☒ A) This code will log the input value on every keystroke. **✗**
- ☐ B) This code will log the input value only when the form is submitted.
- ☐ C) The input value will not change.
- ☐ D) Error: setName is not a function

Correct answer

- ☒ B) This code will log the input value only when the form is submitted.



✓ Q 84 What will be the result of the following code? *

1/1

```
import React from 'react';
import { connect } from 'react-redux';
const Counter = ({ count }) => {
  return <p>Count: {count}</p>;
};
const mapStateToProps = (state) => {
  return { count: state.count };
};
export default connect(mapStateToProps)(Counter);
```

- ☒ A) The component will render count from the Redux store. ✓
- ☐ B) The component will render a static value of count (0 by default).
- ☐ C) The component will not render anything due to missing store configuration.
- ☐ D) Error: connect is not a valid function.

✓ Q 85 What will be the result of the following Node.js code? *

1/1

```
const fs = require('fs');
fs.readFile('file.txt', 'utf8',
(err, data) => {if (err) throw err;
console.log(data);
});
```

- ☐ A) The content of the file file.txt will be printed to the console.
- ☐ B) An error will be thrown if file.txt doesn't exist.
- ☐ C) The code will not run because fs is not a valid module.
- ☒ D) Both A and B. ✓



✓ **Q 86** What will be the output of the following code? *

1/1

```
console.log('Start');  
setTimeout(() =>  
  console.log('Middle'), 0);  
console.log('End');
```

- ☐ A) Start Middle End
- ☒ B) Start End Middle
- ☐ C) Middle Start End
- ☐ D) End Middle Start



✓ **Q 87** What will be the result of the following Express code? *

1/1

```
const express = require('express');  
const app = express();  
app.get('/user/:id', (req, res) => {  
  res.send(`User ID: ${req.params.id}`);  
});  
app.listen(3000);
```

- ☐ A) It will send the User ID as a parameter in the URL.
- ☐ B) The URL must include a parameter id to get the User ID.
- ☐ C) It will respond with a 404 error if no parameter is passed.
- ☒ D) Both A and B.



✗ **Q 88 Which of the following correctly describes the origin of the Internet and its development into a global network?** *0/1

- ☐ A) The Internet originated as ARPANET in the 1980s, initially used for academic research and military communication. It became publicly accessible in the late 1990s when the World Wide Web (WWW) was introduced.
- ☐ B) The Internet was originally developed as the WWW by Tim Berners-Lee in the early 1990s, with the goal of connecting businesses globally.
- ☒ C) The Internet was developed in the late 1990s as a commercial project by a consortium of global corporations, focusing on the use of browsers to navigate information. ✗
- ☐ D) The Internet was created in 2001 by the United Nations to facilitate global digital communication between countries.

Correct answer

- ☒ A) The Internet originated as ARPANET in the 1980s, initially used for academic research and military communication. It became publicly accessible in the late 1990s when the World Wide Web (WWW) was introduced.

✓ **Q 89 Which of the following is a key difference between HTTP/1.0 and HTTP/2?** *1/1

- ☒ A) HTTP/2 introduced multiplexing to allow multiple requests and responses to be sent simultaneously over a single connection, while HTTP/1.0 only allowed one request-response at a time. ✓
- ☐ B) HTTP/1.0 uses binary data encoding, while HTTP/2 relies on text-based encoding for faster data transmission.
- ☐ C) HTTP/2 allows for statelessness in communication, unlike HTTP/1.0 which is stateful.
- ☐ D) HTTP/2 requires fewer headers in each request compared to HTTP/1.0, making it less efficient.



✗ Q 90 Which of the following HTTP methods is idempotent? *

0/1

- ☐ A) GET
- ☐ B) POST
- ☐ C) PUT
- ☒ D) DELETE

✗

Correct answer

- ☒ C) PUT

✗ Q 91 Which of the following statements accurately describes HTTPS compared to HTTP?

*0/1

- ☐ A) HTTPS uses SSL/TLS to encrypt the data between the client and the server, whereas HTTP transmits data in plaintext.
- ☒ B) HTTPS is used only for sending secure passwords, while HTTP is used for sending other types of information.
- ☐ C) HTTPS operates over port 8080, while HTTP uses port 80.
- ☐ D) HTTPS is a newer protocol, developed as an alternative to HTTP, and it does not require any security certificates

✗

Correct answer

- ☒ A) HTTPS uses SSL/TLS to encrypt the data between the client and the server, whereas HTTP transmits data in plaintext.



✗ **Q 92 Which of the following correctly describes the function of a web server like Apache or IIS?** *0/1

- ☐ A) A web server manages the network protocols and routes data from users to appropriate DNS servers.
- ☐ B) A web server processes requests from browsers and delivers content (HTML, CSS, images) to the client, handling HTTP requests and responses.
- ☒ C) A web server serves as a middleman between the client's browser and the router, forwarding packets between the two. ✗
- ☐ D) A web server's main role is to maintain the domain name registration and map IP addresses to domain names.

Correct answer

- ☒ B) A web server processes requests from browsers and delivers content (HTML, CSS, images) to the client, handling HTTP requests and responses.

✓ **Q 93 Which of the following is a new element introduced in HTML5? *** 1/1

- ☐ A)<frame>
- ☒ B)<video>
- ☐ C)<blink>
- ☐ D)



✓ **Q 94 Which property is used to change the background color of a webpage in CSS?**

*1/1

- ☐ A)bgcolor
- ☒ B)background-color
- ☐ C)color
- ☐ D)background



✓ **Q.95**

*

1/1

Which CSS property is used to change the font size?

- ☐ a) font-style
- ☒ b) font-size
- ☐ c) text-size
- ☐ d) font-weight



✓ **Q.96**

*

1/1

What does the display: flex; CSS property do?

- ☐ a) Aligns the text
- ☒ b) Makes the element a flexible container
- ☐ c) Makes the element transparent
- ☐ d) Adds space between elements



✓ Q.97

*

1/1

Which of the following statements is true about JavaScript functions?

- ☐ a) Functions can only return one value.
- ☒ b) Functions can be called multiple times.
- ☐ c) Functions cannot accept parameters.
- ☐ d) Functions must be declared before they are called.

✓

✗ Q.98

*

0/1

Which method is used to parse a JSON string in JavaScript?

- ☒ a) JSON.stringify()
- ☐ b) JSON.parse()
- ☐ c) JSON.convert()
- ☐ d) JSON.decode()

✗

Correct answer

- ☒ b) JSON.parse()



✓ Q.99

*

1/1

What is the result of the following JavaScript expression: 5 + '5'?

- ☐ a) 10
- ☒ b) 55
- ☐ c) NaN
- ☐ d) undefined

✓

✗ Q.100

*

0/1

What is the purpose of event.preventDefault() in JavaScript?

- ☐ a) Prevents an event from executing.
- ☐ b) Stops an event from propagating to other elements.
- ☐ c) Stops the browser's default action for the event.
- ☒ d) All of the above.

✗

Correct answer

- ☒ c) Stops the browser's default action for the event.



✓ Q.101

*1/1

Which method is used to add an item to the end of an array in JavaScript?

- ☒ a) push()
- ☐ b) pop()
- ☐ c) shift()
- ☐ d) unshift()



✗ Q.102

*

0/1

What is the purpose of npm in Node.js?

- ☐ a) To install JavaScript libraries.
- ☐ b) To manage Node.js packages.
- ☐ c) To run JavaScript code.
- ☒ d) All of the above.



Correct answer

- ☒ b) To manage Node.js packages.



✗ Q.103

*

0/1

Which command is used to install a package globally using npm?

- ☒ a) npm install
- ☐ b) npm install -g
- ☐ c) npm update -g
- ☐ d) npm install --global

✗

Correct answer

- ☒ b) npm install -g

✗ Q.104

*

0/1

What is the purpose of the `express.Router()` in Express?

- ☐ a) To define the basic routing for the application.
- ☒ b) To create a middleware stack.
- ☐ c) To handle HTTP requests for a specific group of routes.
- ☐ d) To start the Express server.

✗

Correct answer

- ☒ c) To handle HTTP requests for a specific group of routes.



✗ Q.105***0/1**

Which of the following is true about asynchronous programming in Node.js?

- ☐ a) Asynchronous functions block the execution of other code.
- ☐ b) Asynchronous functions are executed after all synchronous code completes.
- ☒ c) Asynchronous functions are run in parallel with synchronous functions. **✗**
- ☐ d) Asynchronous functions do not exist in Node.js.

Correct answer

- ☒ b) Asynchronous functions are executed after all synchronous code completes.

✓ Q.106*******1/1**

Which method is used to start a server in Express?

- ☒ a) app.listen() **✓**
- ☐ b) server.listen()
- ☐ c) app.start()
- ☐ d) express.listen()



✓ Q.107

*

1/1

What is the primary purpose of React's useState hook?

- ☐ a) To handle side effects in functional components.
- ☒ b) To manage component state in functional components.
- ☐ c) To render components.
- ☐ d) To manage the lifecycle of a component.

✓

✓ Q.108

*1/1

Which of the following is a correct way to define a functional component in React?

- ☐ a) `functionMyComponent() { return <div>Hello</div>; }`
- ☐ b) `constMyComponent = function() { return <div>Hello</div>; }`
- ☐ c) `constMyComponent = () => { return <div>Hello</div>; }`
- ☒ d) All of the above

✓



✗ Q.109

*

0/1

What is the use of useEffect in React?

- ☐ a) To manage the state of the component.
- ☐ b) To handle component lifecycle methods in functional components.
- ☒ c) To render components conditionally. ✗
- ☐ d) To create reusable components.

Correct answer

- ☒ b) To handle component lifecycle methods in functional components.

✓ Q.110

*

1/1

In React, what is the main purpose of Redux?

- ☐ a) To handle the component lifecycle.
- ☒ b) To manage global state for the application. ✓
- ☐ c) To optimize rendering performance.
- ☐ d) To define routes and navigation



✗ Q.111

*

0/1

Which of the following are Redux building blocks?

- ☐ a) Actions, Reducers, Store
- ☐ b) State, Dispatcher, Middleware
- ☐ c) Store, Components, Dispatcher
- ☒ d) Actions, Dispatchers, Components

✗

Correct answer

- ☒ a) Actions, Reducers, Store

✓ Q.112

*

1/1

What is AJAX primarily used for in web development?

- ☒ a) To send asynchronous requests to the server without reloading the page.
- ☐ b) To render dynamic HTML content on the server.
- ☐ c) To send synchronous requests to the server.
- ☐ d) To manage the state of the client-side application.

✓



✓ **Q.113**

*

1/1

Which method is used to send an AJAX request using jQuery?

- ☐ a) \$.ajax()
- ☐ b) \$.post()
- ☐ c) \$.get()
- ☒ d) All of the above

✗ **Q.114**

*

0/1

What is the purpose of the XMLHttpRequest object in JavaScript?

- ☐ a) To send data to the server asynchronously.
- ☐ b) To make synchronous API calls.
- ☒ c) To manipulate the DOM.
- ☐ d) To manage session storage.



Correct answer

- ☒ a) To send data to the server asynchronously.



✓ Which of the following is used to parse a JSON object into a JavaScript object? *1/1

- ☒ a) JSON.parse()
- ☐ b) JSON.stringify()
- ☐ c) JSON.objectify()
- ☐ d) JSON.toObject()



✓ Q.116 * 1/1

What does the axios.get() method do?

- ☒ a) Sends a GET request to the server.
- ☐ b) Sends a POST request to the server.
- ☐ c) Sends a PUT request to the server.
- ☐ d) Sends a DELETE request to the server.



✓ Q.117

* 1/1

Code Snippet:

```
<form>
```

```
<label for="name">Name:</label>
```

```
<input type="text" id="name" name="name" required>
```

```
<input type="submit" value="Submit">
```

```
</form>
```

Question: What type of form element is used to gather the user's name?

- ☐ a) <input type="password">
- ☒ b) <input type="text">
- ☐ c) <input type="email">
- ☐ d) <input type="number">



✓ Q.118

*

1/1

Code Snippet:

```
button {  
  
background-color: blue;  
  
color: white;  
  
border-radius: 5px;  
  
padding: 10px 20px;  
  
}  
  
button:hover {  
  
background-color: darkblue;  
  
}
```

Question: What happens when the user hovers over the button?

- ☐ a) The button changes to a yellow background.
- ☒ b) The button's background color changes to dark blue.
- ☐ c) The button turns transparent.
- ☐ d) Nothing happens on hover.



✓ Q.119

*1/1

Code Snippet:

```
const greet = (name) => {  
  
  console.log("Hello, " + name + "!");  
  
};
```

```
greet("Alice"); // Output: Hello, Alice!
```

Question: What will be printed to the console when the function is called with "Alice"?

- ☒ a) Hello, Alice!
- ☐ b) Hello
- ☐ c) undefined
- ☐ d) Alice



✓ Q.120

*

1/1

Code Snippet:

```
const express = require('express');

const app = express();

app.get('/', (req, res) => {

  res.send('Hello, World!');

});

app.listen(3000, () => {

  console.log('Server is running on port 3000');

});
```

Question: What does this code do?

- ☒ a) It creates a basic server that listens on port 3000 and sends "Hello, World!" when accessed. ✓
- ☐ b) It creates a database connection on port 3000.
- ☐ c) It defines a route for the /home URL.
- ☐ d) It runs a JavaScript function on the server.



✓ Q.121

*

1/1

Code Snippet:

```
import React, { useState } from 'react';

const Counter = () => {

  const [count, setCount] = useState(0);

  return (

    <div>

      <p>Count: {count}</p>

      <button onClick={() =>setCount(count + 1)}>Increment</button>

    </div>

  );

};

export default Counter;
```

Question: What does the button in this React component do?

- ☐ a) Decreases the count by 1.
- ☒ b) Increases the count by 1.
- ☐ c) Resets the count to 0.
- ☐ d) Logs the count to the console.



✖ Q.122

*0/1

Code Snippet:

```
const initialState = { count: 0 };

const counterReducer = (state = initialState, action) => {

  switch (action.type) {

    case 'INCREMENT':

      return { count: state.count + 1 };

    default:

      return state;

  }

};

export default counterReducer;
```

Question: What happens when an action with the type 'INCREMENT' is dispatched to this reducer?

- ☒ a) The count will remain the same. ✖
- ☐ b) The count will decrease by 1.
- ☐ c) The count will increase by 1.
- ☐ d) The state will be reset to { count: 0 }.

Correct answer

- ☒ c) The count will increase by 1.

This content is neither created nor endorsed by Google. - [Contact form owner](#) - [Terms of Service](#) - [Privacy Policy](#)

Does this form look suspicious? [Report](#)



Google Forms



