

## Read the data

```
julia> data = read_pumas(simdf,cvs=[:isPM, :wt])
Population
   Subjects: 10
   Covariates: isPM, wt
   Observables: dv
```

Use this data to estimate the parameters of our model.

```
julia> res = fit(model,data,param,Pumas.FOCEI())
FittedPumasModel
Successful minimization:
                                      true
Likelihood approximation: Pumas.FOCEI
Objective function value:
                                   8084.54
Total number of observation records:
                                      1210
Number of active observation records:
                                      1210
Number of subjects:
                                        10
      Estimate
tvcl 4.8809
      89.739
tvv
pmoncl -0.73558
\Omega_1, 1
    0.10822
Ω2,2
      0.051508
σ_prop 0.042149
```



```
julia> infer(res)
Calculating: variance-covariance matrix
. Done.
FittedPumasModelInference
Successful minimization:
                                   true
Likelihood approximation: Pumas.FOCEI
Objective function value: 8084.54
Total number of observation records: 1210
Number of active observation records: 1210
Number of subjects:
                                  10
      Estimate RSE 95.0% C.I.
tvcl 4.8809 12.932 [ 3.6438 ; 6.1181
tvv 89.739 7.3011 [76.898 ; 102.58
pmoncl -0.73558 -7.9587 [-0.85032 ; -0.62084
\Omega_{1,1} 0.10822 26.546 [ 0.051913 ; 0.16452 ]
\Omega_{2}, 2 0.051508 41.275 [ 0.0098391; 0.093176]
σ prop 0.042149 3.3957 [ 0.039344 ; 0.044954]
```

https://docs.pumas.ai/dev/analysis/diagnostics/#The-infer-Function-1