


WEEK 01 MODULE
Programming Practice

TOPIC : 2 'Number Pattern'

19. SAME NUMBER HALF DIAMOND



1. Problem Analysis :-

i. Pattern Structure:

- The output forms a same numbered half diamond

- Unlike the Diamond Pattern, this pattern is not centered and does not require leading spaces.

Instead, it consists of two separate parts:

Upper same number Half Right Angled Triangle + Lower same number half Inverted Triangle

- The upper half expands downwards
- The lower half contracts downwards

ii. Execution Flow:

Step 1: Observe the Grid Concept:

- For $n = 5$

```
1
2 2
3 3 3
4 4 4 4
5 5 5 5 5
4 4 4 4
3 3 3
2 2
1
```

Upper Half Diamond :-

```
1
2 2
3 3 3
4 4 4 4
5 5 5 5 5
```

Lower Half Diamond :-

```
4 4 4 4
3 3 3
2 2
1
```

- Each cell in the grid represents a unique coordinate (i, j), where i denotes the row index and j denotes the column index.

-The pattern consist of only one visible region

✦ **Region 1: Numbers**

These form the visible half diamond

For n = 5

Row 0 : [1]

Row 1 : [2 2]

Row 2 : [3 3 3]

Row 3 : [4 4 4 4]

Row 4 : [5 5 5 5 5]

Row 3 : [4 4 4 4]

Row 2 : [3 3 3]

Row 1 : [2 2]

Row 0 : [1]

UPPER HALF :-

- Stars increase by 1 in every row.

LOWER HALF :-

- Stars decrease by 1 in every row.

-> Row Analysis :-

Upper Half :-

Row Index (I)	0	1	2	3	4
numbers	1	2 2	3 3 3	4 4 4 4	5 5 5 5 5

RELATIONSHIP :-

- number = i + 1

Lower Half :-

Row Index (I)	3	2	1	0
Stars	4 4 4 4	3 3 3	2 2	1

RELATIONSHIP :-

- $\text{number} = i + 1$

The formulas remain exactly the same for both halves.

Only the direction of row traversal changes.

Upper Half:

$i = 0 \rightarrow n - 1$

Lower Half:

$i = n - 2 \rightarrow 0$

Step 2: Traverse the grid row by row.

- The outer loop is responsible for generating rows.

Generate the upper half using the Upper Half Right Angled Triangle.

- Traverse rows from 0 to $n-1$.
- Print the required number.

After the upper diamond is completed, generate the lower half.

- Traverse rows from $n-2$ down to 0.
- Print the required number.

Step 3: After all numbers of the current row have been printed, move the cursor to the next line.

Step 4: Repeat the process for all rows until the outer loop terminates.

2. Condition Analysis

No conditional statements are required.

There is no need for `if(...)`

- Every position visited by the star loop prints a number.
- The pattern is controlled entirely through loop limits.

3. Core Logic Transformation

Right Angled Triangle Pattern:-

```
for(int j = 0; j < i + 1; j++)
```

- Meaning:

number increase by 1 in every row.

Inverted Triangle Pattern:-

```
for(int j = 0; j < n - i; j++)
```

- Meaning:

number decrease by 1 in every row.

Half Diamond Pattern:-

```
for(int i = 0; i < n; i++)
```

- Meaning:

Generates the expanding upper triangle.

```
for(int i = n - 2; i >= 0; i--)
```

- Meaning:

Generates the shrinking lower triangle.

The formula for printing numbers remains:

```
for(int j = 1; j <= i + 1; j++)
```

Only the row traversal direction changes.

This creates the complete half diamond shape

4. Program :-

```
package week1_module;
import java.util.Scanner;
    public class SameNumberHalfDiamond {

        public static void main(String[] args) {
            Scanner sc = new Scanner(System.in);

            System.out.print("Enter the number of rows: ");
            int n = sc.nextInt();
            // Upper Half
            for(int i = 0; i < n; i++) {

                for(int j = 1; j <= i + 1; j++) {
                    System.out.print(i+1 + " ");
                }

                System.out.println();
            }

            // Lower Half
            for(int i = n - 2; i >= 0; i--) {

                for(int j = 1; j <= i + 1; j++) {
                    System.out.print(i+ 1 + " ");
                }

                System.out.println();
            }

            sc.close();
        }
    }
```

✦ Why n - 2?

Many students write:

```
for(int i = n - 1; i >= 0; i--)
```

and get:

```
1
2 2
3 3 3
4 4 4 4
5 5 5 5 5
5 5 5 5 5
4 4 4 4
3 3 3
2 2
1
```

here the Middle row is printed twice
as Upper half already printed:

```
5 5 5 5 5
```

So we start from: $i = n - 2$

which skips the duplicate middle row.

hence obtained figure:-

```
1
2 2
3 3 3
4 4 4 4
5 5 5 5 5
4 4 4 4
3 3 3
2 2
1
```

5. Program Output :-


Enter the number of rows: 5

```
1
2 2
3 3 3
4 4 4 4
5 5 5 5 5
4 4 4 4
3 3 3
2 2
```

1


6. ScreenShot :-

i. Program :-



```
1 package week1_module;
2 import java.util.Scanner;
3 public class SameNumberHalfDiamond {
4
5     public static void main(String[] args) {
6         Scanner sc = new Scanner(System.in);
7
8         System.out.print("Enter the number of rows: ");
9         int n = sc.nextInt();
10
11         // Upper Half
12         for(int i = 0; i < n; i++) {
13
14             for(int j = 1; j <= i + 1; j++) {
15                 System.out.print(i+1+" ");
16             }
17
18             System.out.println();
19         }
20
21         // Lower Half
22         for(int i = n - 2; i >= 0; i--) {
23
24             for(int j = 1; j <= i + 1; j++) {
25                 System.out.print(i+1+" ");
26             }
27
28             System.out.println();
29         }
30
31         sc.close();
32     }
33 }
34
```

ii. Program's Output :-



```
<terminated> SameNumberHalfDiamond [Java Application] /Library/Java/JavaVirtual
Enter the number of rows: 5
1
2 2
3 3 3
4 4 4 4
5 5 5 5 5
4 4 4 4
3 3 3
2 2
1
```