

Database Assignment 8

Q1) Write a query that uses a subquery to obtain all orders for the customer named Cisneros. Assume you do not know his customer number (cnum).

```
w1_99099_vaibhavi>SELECT *
-> FROM orders
-> WHERE cnum = ( SELECT cnum FROM customers WHERE cname = 'Cisneros');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3001 | 18.69 | 1990-10-03 | 2008 | 1007 |
| 3006 | 1098.16 | 1990-10-03 | 2008 | 1007 |
+-----+-----+-----+-----+-----+
2 rows in set (0.03 sec)

w1_99099_vaibhavi>
```

Q2) Write a query that will find all salespeople who have no customers located in their city.
(Hint: Choose the correct keyword ANY/ALL).

```
w1_99099_vaibhavi>SELECT s.SNAME, s.SNUM, s.CITY
-> FROM Salespeople s
-> WHERE s.CITY != ALL (
->     SELECT c.CITY
->     FROM Customers c
->     WHERE c.SNUM = s.SNUM
-> );
+-----+-----+-----+
| SNAME | SNUM | CITY |
+-----+-----+-----+
| Motika | 1004 | London |
| Rifkin | 1007 | Barcelona |
| Axelrod | 1003 | New York |
+-----+-----+-----+
3 rows in set (0.02 sec)
```

Q3) Extract all the orders of Motika.

```
w1_99099_vaibhavi>SELECT * FROM orders
-> WHERE snum = (SELECT snum FROM salespeople
-> WHERE sname = 'Motika');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10 | 1990-10-03 | 2007 | 1004 |
+-----+-----+-----+-----+-----+
1 row in set (0.00 sec)

w1_99099_vaibhavi>
```

Q4) Find all the orders of salespeople servicing customers in London.

```
w1_99099_vaibhavi>SELECT *
-> FROM orders
-> WHERE cnum IN (SELECT cnum FROM customers WHERE city = 'London');
+-----+-----+-----+-----+-----+
| onum | amt   | odate   | cnum | snum |
+-----+-----+-----+-----+-----+
| 3003 | 767.19 | 1990-10-03 | 2001 | 1001 |
| 3008 | 4723.00 | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88 | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
3 rows in set (0.03 sec)

w1_99099_vaibhavi>
```

Q5) Find names and numbers of all salesperson who have more than one customer.

```
w1_99099_vaibhavi>SELECT sname, snum
-> FROM salespeople
-> WHERE snum IN (
-> SELECT snum
-> FROM customers
-> GROUP BY snum
-> HAVING COUNT(*) > 1);
+-----+-----+
| sname | snum |
+-----+-----+
| Peel  | 1001 |
| Serres | 1002 |
+-----+-----+
2 rows in set (0.01 sec)

w1_99099_vaibhavi>
```

Q6) Select customers who have a greater rating than any other customer in Rome.

```
w1_99099_vaibhavi>SELECT *
-> FROM customers
-> WHERE rating > ANY (
-> SELECT rating
-> FROM customers
-> WHERE city = 'Rome'
-> );
```

cnum	cname	city	rating	snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007

```
4 rows in set (0.00 sec)

w1_99099_vaibhavi>
```

Q7) Select all orders that had amounts that were greater than at least one of the orders from '1990-10-04'

```
w1_99099_vaibhavi>SELECT *
-> FROM orders
-> WHERE amt > ANY (
-> SELECT amt
-> FROM orders
-> WHERE odate = '1990-10-04'
-> );
```

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

```
8 rows in set (0.01 sec)

w1_99099_vaibhavi>
```

Q8) Select those customers whose rating are higher than every customer in London

```
w1_99099_vaibhavi>SELECT *  
-> FROM customers  
-> WHERE rating > ALL (  
-> SELECT rating  
-> FROM customers  
-> WHERE city = 'London'  
-> );
```

cnum	cname	city	rating	snum
2002	Giovanni	Rome	200	1003
2003	Liu	San Jose	200	1002
2004	Grass	Berlin	300	1002
2008	Cisneros	San Jose	300	1007

4 rows in set (0.00 sec)

```
w1_99099_vaibhavi>
```