

Database Technologies – Assignment 2

Q1) Write a query that produces all rows from the Customers table for which the salesperson's number is 1001.

```
w1_99099_Vaibhavi>USE SALES_DB;
Database changed
w1_99099_Vaibhavi>SELECT *
  -> FROM Customers
  -> WHERE snum = 1001;
+-----+-----+-----+-----+-----+
| cnum | cname   | city   | rating | snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100    | 1001 |
| 2006 | Clemens | London | 100    | 1001 |
+-----+-----+-----+-----+-----+
2 rows in set (0.01 sec)

w1_99099_Vaibhavi>|
```

Q2) Write a select command that produces the rating followed by the name of each customer in San Jose.

```
w1_99099_Vaibhavi> SELECT rating, cname
  -> FROM Customers
  -> WHERE city = 'San Jose';
+-----+-----+
| rating | cname   |
+-----+-----+
| 200    | Liu     |
| 300    | Cisneros |
+-----+-----+
2 rows in set (0.00 sec)
```

Q3) Write a query that will produce the snum values of all salespeople from the Orders table (with the duplicate values suppressed).

```
w1_99099_Vaibhavi>SELECT DISTINCT snum
-> FROM Orders;
+-----+
| snum |
+-----+
| 1001 |
| 1002 |
| 1003 |
| 1004 |
| 1007 |
+-----+
5 rows in set (0.00 sec)

w1_99099_Vaibhavi>
```

Q4) Write a query that will display all the orders for amount more than Rs. 1,000.

```
w1_99099_Vaibhavi> SELECT *
-> FROM Orders
-> WHERE amt > 1000;
+-----+-----+-----+-----+-----+
| onum | amt      | odate      | cnum | snum |
+-----+-----+-----+-----+-----+
| 3002 | 1900.10  | 1990-10-03 | 2007 | 1004 |
| 3005 | 5160.45  | 1990-10-03 | 2003 | 1002 |
| 3006 | 1098.16  | 1990-10-03 | 2008 | 1007 |
| 3009 | 1713.23  | 1990-10-04 | 2002 | 1003 |
| 3008 | 4723.00  | 1990-10-04 | 2006 | 1001 |
| 3011 | 9891.88  | 1990-10-04 | 2006 | 1001 |
+-----+-----+-----+-----+-----+
6 rows in set (0.00 sec)
```

Q5) Write a query that will give you the names and cities of all salespeople in London with a commission above 0.10.

```
w1_99099_Vaibhavi>SELECT sname, city
-> FROM Salespeople
-> WHERE city = 'London' AND comm > 0.10;
+-----+-----+
| sname  | city   |
+-----+-----+
| Peel   | London |
| Motika | London |
+-----+-----+
2 rows in set (0.01 sec)

w1_99099_Vaibhavi>
```

Q6) Write an SQL query that returns all customers who have a rating greater than 100, along with the customers located in Rome regardless of their rating.

```
w1_99099_Vaibhavi>SELECT *
-> FROM Customers
-> WHERE rating > 100 OR city = 'Rome';
+-----+-----+-----+-----+-----+
| cnum  | cname   | city      | rating | snum  |
+-----+-----+-----+-----+-----+
| 2002  | Giovanni | Rome      | 200    | 1003  |
| 2003  | Liu      | San Jose  | 200    | 1002  |
| 2004  | Grass    | Berlin    | 300    | 1002  |
| 2008  | Cisneros | San Jose  | 300    | 1007  |
| 2007  | Pereira  | Rome      | 100    | 1004  |
+-----+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```

Q7) What will be the output from the following query? Select * from Orders where (amt < 1000 OR NOT (odate = '1990-10- 03' AND cnum > 2003));

```
w1_99099_Vaibhavi> SELECT *
-> FROM Orders
-> WHERE (amt < 1000 OR NOT (odate = '1990-10-03' AND cnum > 2003));
```

onum	amt	odate	cnum	snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3005	5160.45	1990-10-03	2003	1002
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

```
8 rows in set (0.00 sec)
```

Q8) What will be the output of the following query? Select * from Orders where NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;

```
w1_99099_Vaibhavi>SELECT *
-> FROM Orders
-> WHERE NOT (odate = '1990-10-03' OR snum >1006) AND amt >= 1500;
```

onum	amt	odate	cnum	snum
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3011	9891.88	1990-10-04	2006	1001

```
3 rows in set (0.01 sec)

w1_99099_Vaibhavi>
```

Q9) What is a simpler way to write this query? Select snum, sname, city, comm from Salespeople Where (comm >= .12 AND comm <= .14);

```
w1_99099_Vaibhavi>SELECT snum, sname, city, comm from Salespeople  
-> WHERE (comm >= .12 AND comm <= .14);
```

snum	sname	city	comm
1001	Peel	London	0.12
1002	Serres	San Jose	0.13

2 rows in set (0.00 sec)

```
w1_99099_Vaibhavi>
```

Q10) Write a query that selects all orders except those with amount less than 100.

```
w1_99099_Vaibhavi>SELECT *  
-> FROM Orders  
-> WHERE amt >= 100;
```

onum	amt	odate	cnum	snum
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3008	4723.00	1990-10-04	2006	1001
3010	309.95	1990-10-04	2004	1002
3011	9891.88	1990-10-04	2006	1001

8 rows in set (0.00 sec)

```
w1_99099_Vaibhavi>
```