

Database Technologies – Assignment 4

Q1. Display the PNAME and COLOR from the P table for the CITY="London".

```
w1_99099_Vaibhavi>SELECT PNAME, COLOR
-> FROM P
-> WHERE CITY = 'London';
+-----+-----+
| PNAME | COLOR |
+-----+-----+
| Nut   | Red   |
| Screw | Red   |
| Cog   | Red   |
+-----+-----+
3 rows in set (0.00 sec)

w1_99099_Vaibhavi>
```

2. Display all the Suppliers from London.

```
w1_99099_Vaibhavi>SELECT *
-> FROM S
-> WHERE CITY = 'London';
+----+-----+-----+-----+
| S# | Sname | status | city |
+----+-----+-----+-----+
| S1 | Smith | 20     | London |
| S4 | Clark | 20     | London |
+----+-----+-----+-----+
2 rows in set (0.00 sec)

w1_99099_Vaibhavi>
```

3. Display all the Suppliers from Paris or Athens.

```
w1_99099_Vaibhavi>SELECT *
-> FROM S
-> WHERE CITY IN ('Paris', 'Athens');
+-----+-----+-----+-----+
| S# | Sname | status | city |
+-----+-----+-----+-----+
| S2 | Jones | 10 | Paris |
| S3 | Blake | 30 | Paris |
| S5 | Adams | 30 | Athens |
+-----+-----+-----+-----+
3 rows in set (0.00 sec)

w1_99099_Vaibhavi>|
```

4. Display all the Jobs in Athens.

```
w1_99099_Vaibhavi>SELECT *
-> FROM J
-> WHERE CITY = 'Athens';
+-----+-----+-----+
| J# | Jname | City |
+-----+-----+-----+
| J3 | Reader | Athens |
| J4 | Console | Athens |
+-----+-----+-----+
2 rows in set (0.00 sec)

w1_99099_Vaibhavi>|
```

5. Display all the Part names with the weight between 12 and 14 (inclusive of both).

```
w1_99099_Vaibhavi>SELECT PNAME
-> FROM P
-> WHERE WEIGHT >= 12 AND WEIGHT <= 14;
+-----+
| PNAME |
+-----+
| Nut   |
| Screw|
| Cam   |
+-----+
3 rows in set (0.00 sec)

w1_99099_Vaibhavi>|
```

6. Display all the Suppliers with a Status greater than or equal to 20.

```
w1_99099_Vaibhavi>SELECT *
-> FROM S
-> WHERE STATUS >= 20;
+---+-----+-----+-----+
| S# | Sname | status | city  |
+---+-----+-----+-----+
| S1 | Smith | 20     | London|
| S3 | Blake | 30     | Paris |
| S4 | Clark | 20     | London|
| S5 | Adams | 30     | Athens|
+---+-----+-----+-----+
4 rows in set (0.00 sec)

w1_99099_Vaibhavi>|
```

7. Display all the Suppliers except the Suppliers from London.

```
w1_99099_Vaibhavi>SELECT *
-> FROM S
-> WHERE CITY != 'London';
```

S#	Sname	status	city
S2	Jones	10	Paris
S3	Blake	30	Paris
S5	Adams	30	Athens

```
3 rows in set (0.00 sec)

w1_99099_Vaibhavi>|
```

8. Display only the Cities from where the Suppliers come from.

```
w1_99099_Vaibhavi>SELECT DISTINCT CITY
-> FROM S;
```

CITY
London
Paris
Athens

```
3 rows in set (0.03 sec)

w1_99099_Vaibhavi>|
```

9. Display the Supplier table in the descending order of CITY.

```
w1_99099_Vaibhavi>SELECT *
-> FROM S
-> ORDER BY CITY DESC;
```

S#	Sname	status	city
S2	Jones	10	Paris
S3	Blake	30	Paris
S1	Smith	20	London
S4	Clark	20	London
S5	Adams	30	Athens

```
5 rows in set (0.00 sec)

w1_99099_Vaibhavi>|
```

10. Display the Part Table in the ascending order of CITY and within the city in the ascending order of Part names.

```
w1_99099_Vaibhavi>SELECT *  
-> FROM P  
-> ORDER BY CITY ASC, PNAME ASC;  
+-----+-----+-----+-----+  
| P# | Pname | color | weight | city |  
+-----+-----+-----+-----+  
| P6 | Cog   | Red   | 19     | London |  
| P1 | Nut   | Red   | 12     | London |  
| P4 | Screw | Red   | 14     | London |  
| P2 | Bolt  | Green | 17     | Paris  |  
| P5 | Cam   | Blue  | 12     | Paris  |  
| P3 | Screw | Blue  | 17     | Rome   |  
+-----+-----+-----+-----+  
6 rows in set (0.00 sec)
```

11. Display all the Suppliers with a status between 10 and 20.

```
w1_99099_Vaibhavi>SELECT *  
-> FROM S  
-> WHERE STATUS BETWEEN 10 AND 20;  
+-----+-----+-----+-----+  
| S# | Sname | status | city |  
+-----+-----+-----+-----+  
| S1 | Smith | 20     | London |  
| S2 | Jones | 10     | Paris  |  
| S4 | Clark | 20     | London |  
+-----+-----+-----+-----+  
3 rows in set (0.03 sec)  
  
w1_99099_Vaibhavi>
```

12. Display all the Parts and their Weight, which are not in the range of 10 and 15

```
w1_99099_Vaibhavi>SELECT PNAME, WEIGHT  
-> FROM P  
-> WHERE WEIGHT < 10 OR WEIGHT > 15;
```

PNAME	WEIGHT
Bolt	17
Screw	17
Cog	19

```
3 rows in set (0.00 sec)
```

```
w1_99099_Vaibhavi>
```