

Title: - Text Classification for Sentiment Analysis using K-Nearest Neighbors (KNN)

Aim/Objective: - To perform text classification for sentiment analysis using the K-Nearest Neighbors (KNN) algorithm and predict whether a given text (tweet) has a positive or negative sentiment.

Software Required:

- Python programming environment (Jupyter Notebook, Google Colab, or any Python IDE)
- Libraries: pandas, scikit-learn, nltk

Hardware Required:

- 4GB RAM
- Intel i3 or higher / AMD equivalent
- GPU for accelerated computations (if using deep learning frameworks)
- 120 GB SSD

Theory:

Sentiment Analysis is a type of natural language processing (NLP) where the aim is to determine the sentiment expressed in a piece of text — whether positive, negative, or neutral.

K-Nearest Neighbors (KNN) is a supervised machine learning algorithm that classifies a data point based on how its neighbors are classified. It doesn't build a model explicitly; instead, it stores the entire training dataset and classifies new instances based on similarity measures (like Euclidean distance).

In **text classification**, we first need to:

- Preprocess text (cleaning, removing stopwords & punctuations)
- Convert text into numeric features (using techniques like Bag of Words or TF-IDF)
- Train KNN on these numeric features.

Procedure:

Procedure

1. **Import Libraries:** Import necessary Python libraries.
2. **Load Dataset:** Load a Twitter Sentiment dataset (or any text dataset).
3. **Preprocessing Text:**
 - Lowercasing, removing special characters, stopwords removal.
4. **Feature Extraction:**

- Convert cleaned text into numerical features using TF-IDF Vectorizer.

5. Model Training:

- Train KNN Classifier on the training data.

6. Model Testing:

- Test the KNN Classifier on the unknown data given

Observations:

1. Text data was successfully preprocessed and transformed into numerical format.
2. KNN classified the tweets into positive or negative sentiments.
3. Model performance varied depending on the value of k.

Code:

```
# Import Required Libraries
import pandas as pd
import string
import nltk
from sklearn.model_selection import train_test_split
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.neighbors import KNeighborsClassifier

# Load Dataset
df = pd.read_csv("Tweets.csv")

# Feature Selection
df = df.iloc[:, [10, 1]] # Select only relevant columns: 'text' and the
                          'label' column

#Print Before Preprocessing
print("Before Preprocessing")
print(df[['text', 'airline_sentiment']].head())
print("\n")

# Preprocessing Text: It involves 2 Step: 1. Removing (Stopwords &
Punctuations) & Cleaning, 2. Text to numerical form
# Step 1: Removing Stopwords & Punctuations
# Step 1.1: Pre-requisite - Download list of stopwords & punctuations from
nltk library
#Note: - One Time download after then comment line no.19,21,22
#nltk.download('stopwords') # Stopwords are commonly used words in a language
(like "is", "the", "and", "to")
                                # that don't contribute significant meaning in
text analysis.
#nltk.download('punct')      # Punctuation list for tokenization
#nltk.download('punct_tab')  # To reduce noise and standardize the text data.
```

```

# Step 1.2: Remove Stopwords & Punctuation from the text and tokenize the
words from text
from nltk.corpus import stopwords
from nltk.tokenize import word_tokenize

# Get the list of stopwords
stop_words = set(stopwords.words('english'))

# Function to clean text by removing stopwords and punctuation
def clean_text(text):
    # Tokenize the text
    tokens = word_tokenize(text)
    # Remove stopwords and punctuation
    cleaned_text = [word for word in tokens if word.lower() not in stop_words
and word not in string.punctuation]
    # Join the cleaned words back into a sentence
    return ' '.join(cleaned_text)

# Step 1.3: Apply the clean_text function to the 'text' column
df['text'] = df['text'].apply(clean_text)

#Print After Cleaning of Text
print("After Cleaning of Text Column")
print(df[['text', 'airline_sentiment']].head())
print("\n")

#Step 2: Feature Extraction: Using TF-IDF to convert text to numerical
features
vectorizer = TfidfVectorizer()
X = vectorizer.fit_transform(df['text'])
#After Pre-Processing now we need to do Model Training

#Print After Pre-Processing
print("After Preprocessing")
print(df[['text', 'airline_sentiment']].head())
print("\n")

#Note:- During we Processing, X is obtained therefore
# Target variable
y=df['airline_sentiment']

# Model Training: K-Nearest Neighbors Classifier
knn = KNeighborsClassifier(n_neighbors=5) # You can experiment with different
values of k
knn.fit(X, y)

#Print After Model Training
print("After Model Training")

```

```

print(df[['text','airline_sentiment']].head())
print("\n")

# Predict Sentiment for Unknown Reviews
def predict_sentiment(review):
    # Preprocess the review (clean and vectorize)
    cleaned_review = clean_text(review)
    review_vectorized = vectorizer.transform([cleaned_review])

    # Predict using the trained KNN model
    prediction = knn.predict(review_vectorized)
    return prediction[0]

# Example usage: Predict sentiment for an unknown review
unknown_review = "The product was amazing, I really loved it!"
predicted_sentiment = predict_sentiment(unknown_review)
#Note you can even give a feature to test via importing another dataset or use
Input function to manually write
print(unknown_review)
print(f"Predicted Sentiment: {predicted_sentiment}")

```

Output:

Before Preprocessing

	text	airline_sentiment
0	@American Airlines What @dhepburn said.	neutral
1	@American Airlines plus you've added commercia...	positive
2	@American Airlines I didn't today... Must mean...	neutral
3	@American Airlines it's really aggressive to b...	negative
4	@American Airlines and it's a really big bad t...	negative

After Cleaning of Text Column

	text	airline_sentiment
0	American Airlines dhepburn said	neutral
1	American Airlines plus 've added commercials e...	positive
2	American Airlines n't today ... Must mean need...	neutral
3	American Airlines 's really aggressive blast o...	negative
4	American Airlines 's really big bad thing	negative

After Preprocessing

	text	airline_sentiment
0	American Airlines dhepburn said	neutral
1	American Airlines plus 've added commercials e...	positive
2	American Airlines n't today ... Must mean need...	neutral
3	American Airlines 's really aggressive blast o...	negative
4	American Airlines 's really big bad thing	negative

After Preprocessing

<Compressed Sparse Row sparse matrix of dtype 'float64'
with 148669 stored elements and shape (14640, 14990)>

Coords	Values
(0, 2234)	0.330773183694217
(0, 2102)	0.3215259391192515
(0, 4794)	0.7783726836816176
(0, 11610)	0.42584755103270444
(1, 2234)	0.22334860171858958
(1, 2102)	0.21710456729445177
(1, 10402)	0.345879408294751
(1, 14146)	0.23800068676554115
(1, 1964)	0.40072991873717007
(1, 4021)	0.45906348064200664

After Model Training

<Compressed Sparse Row sparse matrix of dtype 'float64'
with 148669 stored elements and shape (14640, 14990)>

Coords	Values		
(0, 2234)	0.330773183694217	1	positive
(0, 2102)	0.3215259391192515	2	neutral
(0, 4794)	0.7783726836816176	3	negative
(0, 11610)	0.42584755103270444	4	negative
(1, 2234)	0.22334860171858958		...
(1, 2102)	0.21710456729445177	14635	positive
(1, 10402)	0.345879408294751	14636	negative
(1, 14146)	0.23800068676554115	14637	neutral
(1, 1964)	0.40072991873717007	14638	negative
(1, 4021)	0.45906348064200664	14639	neutral

Conclusion:

Through this experiment, the Titanic dataset was successfully pre-processed by selecting relevant features, handling missing values, encoding categorical variables, and normalizing continuous features. Pre-processing ensures that the dataset is clean and

ready for further analysis or model building, thereby improving the efficiency and performance of machine learning models.