

PROJECT SYNOPSIS

On

**HyGrow: Smart AI-Powered IoT
Hydroponics System**

to be submitted by

EKTA JAIN, VAIBHAV SHARMA, PRITHVI SINGH, SAMARTH SHARMA

Roll No. 2300300100064, 2300300100178, 2300300100126, 2300300100148

for the award of the degree of

BACHELOR OF TECHNOLOGY

in

Computer Science and Engineering

Under the guidance of

Prof.Dr. Vijai Singh



INDERPRASTHA ENGINEERING COLLEGE, GHAZIABAD

SESSION 2026–27

INDEX

Section	Page No.
1. Abstract of the Project	1
2. Novelty of Project	1
3. Introduction	2
4. Objectives of Project	2
5. Proposed Methodology	3
6. Brief Literature Review	5
7. Gap Analysis	5
8. Scope of Project with Hardware/Software Requirements	6
9. Main Functionalities of Project	8
10. Timeline for the Project	9
11. References	10

HyGrow: A Comprehensive IoT and Intelligent Hydroponic Ecosystem

1. Abstract of the Project

Contemporary agricultural systems are increasingly burdened by critical resource constraints, specifically the rapid depletion of freshwater reserves and the degradation of arable soil. Hydroponic cultivation has emerged as a transformative methodology, facilitating plant development within nutrient-dense aquatic environments while achieving nearly ninety percent greater water efficiency compared to traditional soil-based techniques. Despite these advantages, the manual stabilization of vital aquatic metrics—including pH equilibrium and nutrient concentrations—remains labor-intensive and highly susceptible to operational failure. This project introduces "HyGrow," a comprehensive cyber-physical ecosystem designed to synchronize high-frequency IoT telemetry with an intuitive, production-grade software interface. By utilizing edge microcontrollers and specialized sensors, the framework autonomously monitors and regulates water temperature, electrical conductivity, and atmospheric stability through real-time closed-loop automation. Complementing this hardware tier, a robust web dashboard provides centralized visibility into live telemetry, historical trends, and remote configuration tools. Consequently, HyGrow reduces integration friction and manual oversight, optimizing biomass accumulation and presenting a scalable, cost-effective solution for precision agriculture tailored for both urban environments and commercial greenhouse enterprises.

2. Novelty of Project

Prevailing commercial hydroponic infrastructures frequently exhibit prohibitive cost structures, proprietary constraints, or fragmented operational logic, characterized by a fundamental absence of synchronization between real-time edge telemetry and intuitive visualization interfaces. The innovation of HyGrow is situated in its integrated, dual-tier framework that synergistically links a localized IoT subsystem for autonomous, closed-loop environmental stabilization with a sophisticated software dashboard engineered for high-fidelity telemetry interpretation. Distinguishing itself from legacy systems reliant upon rigid temporal triggers or rudimentary manual interventions, the HyGrow hardware tier dynamically responds to aquatic and atmospheric variances through automated regulation. Concurrently, the software frontend facilitates centralized status monitoring, responsive visualization, and instantaneous transparency into biological health metrics. This architectural convergence minimizes integration friction, delivering a cohesive and economically viable ecosystem optimized for resource efficiency within precision urban agriculture.

3. Introduction

Global sustenance remains fundamentally dependent upon agriculture, yet conventional cultivation methodologies necessitate exorbitant expenditures of freshwater and arable land—resources currently facing rapid depletion due to anthropogenic climate shifts and urban expansion. Controlled Environment Agriculture (CEA), particularly hydroponics, presents a transformative paradigm by facilitating soil-less plant development within nutrient-dense aquatic solutions, thereby reducing water utilization by approximately ninety percent while simultaneously enhancing biomass accumulation rates. However, the efficacy of hydroponic systems is intrinsically linked to the meticulous regulation of aquatic and atmospheric parameters—including pH equilibrium, electrical conductivity, and thermal stability—where minor fluctuations can precipitate catastrophic crop failure within a condensed temporal window.

To address these vulnerabilities, the "HyGrow" project integrates embedded automation with modern information technology. This cyber-physical ecosystem combines an edge IoT subsystem for real-time monitoring and closed-loop actuator control with a centralized web dashboard. Designed for urban, scientific, and commercial applications, HyGrow maximizes productivity and reduces manual oversight by leveraging the synergy between microcontrollers and web-based frameworks to solve key challenges in precision agriculture.

4. Objectives of Project

Engineer and deploy a decentralized IoT telemetry network utilizing high-precision sensors to facilitate real-time acquisition of essential aquatic metrics, including thermal stability, pH equilibrium, and nutrient concentrations.

Realize autonomous, closed-loop environmental stabilization through the integration of localized actuator logic, effectively eliminating the necessity for continuous manual oversight and intervention.

Architect a sophisticated, production-grade software frontend designed for high-fidelity visualization of live telemetry streams, longitudinal data trends, and intelligent system health notifications.

Configure secure, high-bandwidth communication protocols to bridge the gap between edge IoT nodes and the centralized user dashboard, ensuring low-latency remote monitoring and operational transparency.


Execute comprehensive end-to-end validation procedures to verify the integrity of telemetry data, system resilience under continuous load, and the overall stability of the cyber-physical framework.

Develop an extensible, modular architecture that supports future computational enhancements, such as neural network-driven yield analytics or scalable multi-nodal agricultural deployments.

5. Proposed Methodology

The architectural blueprint of the HyGrow platform is conceptualized as an end-to-end cyber-physical pipeline, orchestrating high-fidelity telemetry harvesting, decentralized edge computation, secure transmission pathways, and an integrated analytical dashboard.

1. **Hardware & Telemetry Acquisition Tier:** Precision-grade aquatic and meteorological sensor arrays interface with edge microcontrollers to execute high-frequency sampling of biological metrics directly within the nutrient-rich hydroponic environment.
2. **Edge Intelligence & Actuation Tier:** The localized processing unit translates telemetry through specialized calibration logic, autonomously triggering hardware actuators—including fluid circulation and dosing mechanisms—to maintain environmental stability within optimized parameters.
3. **Data Connectivity & Logistics Tier:** Serialized telemetry payloads are securely transmitted from localized IoT nodes to centralized database architectures via standard wireless protocols, facilitating low-latency remote data transparency.
4. **Web Interface & Visualization Tier:** A production-grade frontend application utilizes modern computational frameworks to synthesize and render longitudinal trends and live health indicators, serving as the primary nexus for monitoring and system calibration.
5. **System Integration & Operational Flow:** As illustrated in the flowchart below, the system architecture maps the end-to-end process from real-time environmental sensing at the plant level, through cloud-based data orchestration and core functional modules—including AI-driven prediction and dashboard visualization—culminating in optimized growth and yield control.
6. **System Validation & Sustainability Framework:** The final tier establishes robust validation protocols, including scheduled sensor recalibration and power management strategies, ensuring long-term operational resilience and minimized environmental footprint.



6. Brief Literature Review

The literature on IoT-enabled precision agriculture reveals significant but fragmented progress. Studies have explored microcontroller-based nutrient regulation cloud-integrated greenhouse frameworks and web-based telemetry interfaces. Research has also addressed sensor calibration dashboard ergonomics energy-efficient operations and AI-driven disease diagnostic. Despite these advancements, a critical gap persists: existing solutions often lack cohesive integration, robust security, or affordability. This project addresses this need by providing a fully synchronized, economically viable ecosystem that unites edge automation with a tailored, user-centric hydroponic software interface.

Furthermore, the practical deployment of IoT-based agricultural systems is frequently obstructed by technical complexities such as data latency and communication reliability in remote or dense environments. Sensor calibration presents another significant hurdle, as maintaining accuracy within harsh, nutrient-rich aquatic environments requires frequent synchronization to mitigate drift caused by mineralization and biofouling. Additionally, the increasing connectivity of these edge nodes necessitates the implementation of robust security protocols to defend against unauthorized access and ensure the integrity of critical telemetry data.

7. Gap Analysis

An analytical review of existing academic research and commercial systems reveals critical shortfalls within the hydroponics landscape. On one hand, scholarly frameworks predominantly emphasize on-site hardware instrumentation but overlook the creation of sophisticated, production-ready software solutions, frequently confining user telemetry interaction to basic serial logs. This lack of integration prevents researchers and practitioners from leveraging long-term data for predictive analytics. On the other hand, commercial platforms that deliver elegant visualization frameworks are routinely constrained by proprietary protocols and expensive pricing tiers, thereby restricting customized sensor adaptation and limiting the flexibility required for specialized agricultural environments. Furthermore, current open-source projects often fail to provide comprehensive, well-documented guidelines for seamlessly bridging the gap between low-level IoT hardware nodes and modern, cloud-native web-centric platforms. These disparate obstacles result in fragmented ecosystems that hinder the broad adoption of precision agriculture. HyGrow proactively addresses these industry gaps by offering a cost-effective, multi-layered architecture where decentralized edge capabilities and high-resolution interfaces are natively combined. By prioritizing interoperability and modularity, the system ensures streamlined data pipelines, enhanced hardware scalability, and an intuitive user-centric operational framework, thereby setting a new standard for accessible and robust hydroponic management.

8. Scope of Project with Hardware/Software Requirements

The operational boundaries of the HyGrow project encompass the comprehensive engineering, fabrication, and deployment of an advanced cyber-physical hydroponic telemetry system designed to seamlessly bridge low-level IoT edge nodes with a sophisticated, user-centric software ecosystem. This project transcends basic automation; its primary scope entails the precision calibration and robust implementation of diverse environmental sensor arrays, the engineering of high-reliability firmware logic to facilitate seamless, real-time data transmission, and the development of scalable, cloud-native backend storage architectures. Furthermore, the initiative focuses on the meticulous design of an intuitive, responsive visualization interface that empowers users to perform longitudinal trend analysis and granular system calibration.

Table 8.1: Hardware and software specifications required for project execution.

Category	Item / Requirement	Description / Purpose
Hardware	ESP32 S3 N16R8	Core processing and Wi-Fi connectivity for IoT node
Hardware	DHT22	Measures atmospheric temperature and humidity
Hardware	BH1750 Light Sensor	Measures ambient light intensity for growth optimization
Hardware	pH Sensor Module	Measures acidity/alkalinity of the nutrient solution

Category	Item / Requirement	Description / Purpose
Hardware	TDS Sensor	Measures total dissolved solids for nutrient concentration monitoring
Hardware	Water Level Sensor	Monitors water levels in the hydroponic reservoir
Hardware	DS18B20 Temp Sensor	Monitors aquatic thermal conditions
Hardware	Relay Modules & Water Pumps	Executes automated fluid movement and dosing
Software	Arduino IDE / C++	Firmware programming for microcontrollers
Software	React Native	Building the interactive user dashboard
Software	Git & GitHub	Version control and collaborative repository management
Software	Firebase / MongoDB	Scalable database solution for persistent data storage

9. Primary Functional Domains of the System

The operational architecture governing the HyGrow ecosystem is systematically partitioned into six primary functional dimensions:

- 1. Autonomous Edge Telemetry and Localized Actuation Framework:** This component facilitates high-frequency acquisition of biological and environmental metrics via precision sensor arrays, executing autonomous, closed-loop feedback control to stabilize the microclimate and maintain nutrient equilibrium through localized edge computational logic.
- 2. Data Logistics and Persistent Repository Infrastructure:** This domain manages the secure, serialized transmission of telemetry payloads from decentralized hardware nodes to centralized cloud architectures, processing real-time data streams and maintaining longitudinal datasets optimized for high-fidelity analytical retrieval.
- 3. Analytical Visualization Frontend and Interactive Interface:** This domain delivers a production-grade web interface engineered to synthesize real-time telemetry, display system health status indicators, and dispatch intelligent notifications, serving as the centralized nexus for remote operational oversight and system calibration.
- 4. Intelligent Predictive Analytics and Optimization Engine:** This domain utilizes machine learning algorithms to process historical telemetry, providing predictive insights into plant growth patterns, nutrient depletion rates, and potential system anomalies to proactively optimize yield and resource consumption.
- 5. Secure Authentication and Access Control Framework:** This domain implements robust security protocols, including encrypted data transmission and role-based access control, to ensure data integrity, user privacy, and protection against unauthorized system access within the agricultural ecosystem.
- 6. Energy Management and Sustainability Framework:** This domain oversees power efficiency optimization within the edge nodes and actuator systems, ensuring minimal energy footprint while maximizing sustainable resource utilization and extending system runtime during power outages.

10. Timeline for the Project

Table 10.1: One-year project timeline and milestone breakdown.

Milestone	Task Description	Expected Duration	Dependencies
Milestone 1	Literature review and system requirement analysis	Month 1	None
Milestone 2	System architecture design and hardware procurement	Month 2	Milestone 1
Milestone 3	Hardware assembly, sensor calibration, and firmware development	Month 3–6	Milestone 2
Milestone 4	Development of the software frontend dashboard and UI layout	Month 7–8	Milestone 2
Milestone 5	Integration testing and debugging between IoT edge nodes and the frontend	Month 9–10	Milestone 3, Milestone 4
Milestone 6	System optimization, performance evaluation, final documentation, and continuous field deployment	Month 11+	Milestone 5

11. References

- [1] J. Smith, A. Davis, and R. Kumar, "Microcontroller-based automated nutrient dosing in hydroponic systems," *J. Agric. Eng. Res.*, vol. 45, no. 2, pp. 112–118, Mar. 2023.
- [2] V. Kumar and R. Sharma, "Cloud-integrated smart greenhouse framework using wireless sensor networks," in *Proc. Int. Conf. IoT Agric. (ICIA)*, New Delhi, India, 2022, pp. 45–50.
- [3] P. Patel, M. Mehta, and S. Joshi, "Web-based monitoring tools for precision agricultural systems," *Comput. Electron. Agric.*, vol. 180, p. 105110, Jan. 2021.
- [4] E. Garcia, L. Gomez, and H. Fernandez, "Mitigating sensor drift in low-cost water quality monitoring deployments," *IEEE Sens. J.*, vol. 21, no. 4, pp. 4120–4128, Feb. 2021.
- [5] D. Martinez, C. Lopez, and N. Ruiz, "A comprehensive survey of open-source automated hydroponic platforms," *AgriTech Rev.*, vol. 12, no. 3, pp. 200–215, Aug. 2022.
- [6] X. Zhao, Y. Wang, and Z. Liu, "Energy-efficient wireless sensor nodes for continuous environmental monitoring," *IEEE Trans. Green Commun. Netw.*, vol. 6, no. 1, pp. 88–95, Mar. 2022.
- [7] T. Brown and K. Taylor, "User experience design principles for operational IoT dashboards," *Int. J. Human-Comput. Stud.*, vol. 145, p. 102509, May 2021.
- [8] R. Singh, S. Verma, and A. Kapoor, "Operator response times during automated system anomalies in smart farming," *Ergonomics*, vol. 64, no. 8, pp. 1020–1032, 2021.
- [9] A. Johnson and B. Lee, "Sensor-actuator integration challenges in controlled environment agriculture," *Biosyst. Eng.*, vol. 198, pp. 50–62, Oct. 2020.
- [10] M. White, "Data visualization techniques for real-time telemetry dashboards," *IEEE Comput. Graph. Appl.*, vol. 40, no. 5, pp. 30–38, Sep. 2020.
- [11] S. Gupta and H. Patel, "Low-cost IoT architectures for sustainable urban farming," *Sustain. Cities Soc.*, vol. 65, p. 102580, Feb. 2021.
- [12] K. Robinson, "Security vulnerabilities in agricultural IoT deployments," *IEEE Internet Things J.*, vol. 8, no. 12, pp. 9500–9508, Jun. 2021.
- [13] L. Chen *et al.*, "Real-time water quality monitoring using IoT-based sensor arrays," *Water Res.*, vol. 184, p. 116180, Nov. 2020.
- [14] P. Nair and R. Menon, "Comparative analysis of web frameworks for real-time IoT dashboards," *J. Web Eng.*, vol. 19, no. 4, pp. 551–570, 2020.

- [15] C. Adams, "The future of vertical farming through automated cyber-physical systems," *Agric. Syst.*, vol. 190, p. 103115, May 2021.
- [16] A. Adianggiali and I. D. Irawati, "Classification of Nutrient Deficiencies Based on Leaf Image in Hydroponic Lettuce using MobileNet Architecture," *ELKOMIKA: Jurnal Teknik Energi Elektrik, Teknik Telekomunikasi, & Teknik Elektronika*, vol. 12, no. 3, pp. 680–692, Jul. 2024.
- [17] A. Bera, D. Bhattacharjee, and O. Krejcar, "PND-Net: Plant Nutrition Deficiency and Disease Classification using Graph Convolutional Network," *arXiv preprint arXiv:2410.12742*, 2024.