



XC936

WHEEL LOADER

Rated Bucket Capacity m ³	2.1/1.8
Rated Load kg	3500
Engine Power	92KW



MAIN SPECIFICATION

Main Components

Item		Parameter	Parameter
Rated Bucket Capacity m ³		2.1	1.8 (Small-Height Dumping)
Rated load kg		3500	3000
Operating Weight kg		10300±200	10400±200
Dumping Height mm		2900	3240
Dumping Range mm		1030	1075
Wheel Base mm		2900	2900
Wheel Track mm		1850	1850
Min Ground Clearance mm		365	365
Overall Length mm		7250	7450
Overall Height mm		3100	3100
Bucket Width mm		2482	2482
Dumping Angle (°)		45	45
Max Breakout Force kN		125±5	120±5
Max Tractive Force kN		95±5	95±5
Center of tyre (Turning Radius) mm		5100	5100
Boom Lifting Time S		≤5.0	≤5.0
Total Cycle Time S		≤8.5	≤8.5
Engine	Nominal Power KW	92	92
	Nominal Speed r/min	2200	2200
Travel Speed Km/h	1 forward/reverse Gear	8/10	8/10
	2 Forward/reverse Gear	14/31	14/31
	3 Forward Gear	26	26
	4 Forward Gear	43	43

The technology of XCMG loader is subject to constant improvement and upgrading. In case the specifications or detailed appearance contained in this brochure differ from actual products, the latter shall prevail;

XCMG reserves the right of final interpretation for the above. Our products may be modified without prior notice to users.



Drivetrain System

Engine: China II turbocharged engine integrated with three-stage desert air filter suitable for dusty conditions, and mechanical pump with simple structure to ensure high reliability and excellent power performance, features not only higher reliability and adaptability, but also lower fuel consumption and emission. It can be configured with an optional low-temperature start unit.

Transmission: The fixed shaft power-shift transmission is connected with a single-stage single-phase three-element hydraulic torque converter, designed with multiple gears (4 forward and 2 reverse) to meet the speed requirements under different operating conditions. This fixed shaft transmission features numerous advantages, including outstanding reliability, high transmission efficiency, simple structure, convenient maintenance, and easy shifting.

Drive axle: It is configured with heavy-duty drive axles for construction machinery, featuring stable quality, reliable performance and easy maintenance.



Hydraulic System

Integrated with sophisticated and reliable single-pump shunt and load-sensing full hydraulic steering technology, improving the lifting capacity by increasing the pressure of the operating system up to 20.5MPa. Reducing the total cycle time through the design of high pressure and small displacement. Integrated distribution valve with manually-operated actuator, improving the system efficiency, and reducing energy and fuel consumption. In addition, the pipelines are optimized and upgraded to facilitate installation and connection, while reducing the pressure loss in the pipelines, and minimizing the heat generation of the hydraulic system to reduce failures of the vehicle.



Brake System

The vehicle is configured with service brake and parking brake. The air over hydraulic brake system based on caliper-disc four-wheel brake features advantages of smooth braking, excellent safety and reliability, simple structure and convenient maintenance. The application of dust-proof high-flow respirator on the booster pump is easy to maintain and improve the cleanliness of the interior of the pump and the like component.



Cab & Steering System

XCMG's innovative micro-pressurized cab is featured with spacious, bright and enclosed space. The high-quality shock absorber is connected to the frame, which greatly reduces the vibration of the cab. The airbag shock-absorbing seat with composite control can improve the riding comfort; and the high-power air conditioner designed with heating and cooling modes supports intelligent temperature control to provide the operator with a suitable temperature all the time.

Designed with spacious, bright and well-enclosed room and fully-covered aesthetic interior, the cab can ensure lower noise level around the operator's ears due to sound-proof structure of the cab and hood, and create comfortable and quiet environment for the operator. The large-arc hyperboloid glass featuring a wider view of field and minimized blind areas around the machine, enables the operator to easily observe the rear of the machine and the edges of the bucket, and improve the productivity thanks to comfortable driving and operating experience.



Operating Unit & Bucket

- Optimized operating tools designed with Z-type reverse six-linkage structure integrated with single rocker arm, short tie rod and horizontal boom cylinder, featuring superior operating performance and efficiency.
- The boom beam adopting rectangular tube structure can effectively avoid stress concentration, welding defect and the like phenomena, and improve the structural strength. All pins adopt special heat treatment process of special material with high strength, good wear resistance and long service life.
- All hinge pins designed with dust-proof lubrication structure to prevent grease from dust and contamination, and provide reliable protection for hinge pins and bushings, and configured with centralized lubrication system as standard to minimize maintenance time.
- Bucket made of high-strength wear-resistant plates and teeth supplied by world-class brands to ensure higher durability.

SOLID TO SUCCEED



FOR MORE INFO:



UNITED HEAVY EQUIPMENT & EARTH MOVERS PVT. LTD.

VOITH Complex | Ananda Nagar, Dhumbarahi, Nepal
Tel.: +977 01 4542901-05, Cell : +977 98512 17690
Fax : +977 01 4008813, P.O. Box: 233/2640
Email: info@uheem.com.np, Web: www.uheem.com.np