Name: VAISHAAL RAJHA T C G
231901502

EX NO :1B Linux Networking Commands

AIM:

Every computer is connected to some other computer through a network whether internally or externally to exchange some information. This network can be small as some computers connected in your home or office, or can be large or complicated as in large University or the entire Internet.

PROCEDURE:

Maintaining a system's network is a task of System/Network administrator. Their task includes network configuration and troubleshooting.

Here is a list of Networking and Troubleshooting commands:

ifconfig	Display and manipulate route and network interfaces.
ip	It is a replacement of ifconfig command.
traceroute	Network troubleshooting utility.
tracepath	Similar to traceroute but doesn't require root privileges.
ping	To check connectivity between two nodes.
netstat	Display connection information.
ss	It is a replacement of netstat.
dig	Query DNS related information.
nslookup	Find DNS related query.
route	Shows and manipulate IP routing table.
host	Performs DNS lookups.

Name: VAISHAAL RAJHA T C G
231901502

arp	View or add contents of the kernel's ARP table.
iwconfig	Used to configure wireless network interface.

hostname	To identify a network name.
curl or wget	To download a file from internet.
mtr	Combines ping and tracepath into a single command.
whois	Will tell you about the website's whois.
ifplugstatus	Tells whether a cable is plugged in or not.

Explanation of the above commands:

1. **ifconfig:** ifconfig is short for interface configurator. This command is utilized in network inspection, initializing the interface, enabling or disabling an IP address, and configuring an interface with an IP address. Also, it is used to show the network and route interface.

The basic details shown with ifconfig are:

- MTU
- MAC address
- IP address

Syntax:

Ifconfig

Name: VAISHAAL RAJHA T C G
231901502



2. **ip:** It is the updated and latest edition of ifconfig command. The command provides the information of every network, such as ifconfig. Also, it can be used to get informationabout a particular interface.

Syntax:

1. ip a
2. ip addr

Name: VAISHAAL RAJHA T C G
231901502



3. **traceroute:** The traceroute command is one of the most helpful commands in the networking field. It's used to balance the network. It identifies the delay and decides the pathway to our target. Basically, it aids in the below ways:

- It determines the location of the network latency and informs it.
- It follows the path to the destination.
- It gives the names and recognizes all devices on the path.

Syntax:

traceroute **<destination>**

Name: VAISHAAL RAJHA T C G
231901502

4. **tracepath:** The tracepath command is the same as the traceroute command, and it is used to find network delays. Besides, it does not need root privileges. By default, it comes pre-installed in Ubuntu. It traces the path to the destination and recognizes all hops in it. It identifies the point at which the network is weak if our network is not strong enough.

Syntax:

tracepath **<destination>**

Name: VAISHAAL RAJHA T C G
231901502



5. **ping:** It is short for Packet Internet Groper. The ping command is one of the widely used commands for network troubleshooting. Basically, it inspects the network connectivity between two different nodes.

Syntax:

ping **<destination>**

Name: VAISHAAL RAJHA T C G
231901502

6.



netstat: It is short for network statistics. It gives statistical figures of many interfaces,which contain open sockets, connection information, and routing tables.

Syntax:
Netstat

Name: VAISHAAL RAJHA T C G
231901502



7. **ss:** This command is the substitution for the netstat command. The ss command is more informative and much faster than netstat. The ss command's faster response is possible because it fetches every information from inside the kernel userspace.

Syntax:
Ss

Name: VAISHAAL RAJHA T C G
231901502



8. **nsloopup:** The nslookup command is an older edition of the dig command. Also,it is utilized for DNS related problems.

Name: VAISHAAL RAJHA T C G
231901502



Syntax:
nslookup **<domainname>**

9. **dig:** dig is short for Domain Information Groper. The dig command is an improvised edition of the nslookup command. It is utilized in DNS lookup to reserve the DNS name server. Also, it is used to balance DNS related problems. Mainly, it is used to authorize DNS mappings, host addresses, MX records, and every other DNS record for the best DNS topography understanding.

Syntax:
dig **<domainname>**

Name: VAISHAAL RAJHA T C G
231901502



10. **route:** The route command shows and employs the routing table available for our system. Basically, a router is used to detect a better way to transfer the packets around a destination.

Syntax:
Route

11. **host:** The host command shows the IP address for a hostname and the domain name for an IP address. Also, it is used to get DNS lookup for DNS related issues.

Syntax:
host -t **<resourceName>**

arp: The arp command is short for Address Resolution Protocol. This commandis used
Syntax:

1. Arp

1. **iwconfig:** It is a simple command which is used to see and set the system's hostname.

Syntax:
Hostname

2. **curl and wget:** These commands are used to download files from CLI from the internet. curl must be specified with the "O" option to get the file, while wget is directly used.

curl Syntax:

1. curl -O **<fileLink>**

Name: VAISHAAL RAJHA T C G
231901502

3. **wget**

Syntax:

1. wget **<fileLink>**

1. **mtr:** The mtr command is a mix of the traceroute and ping commands. It regularly shows to see and include content in the ARP table of the kernel. information related to the packets transferred using the ping time of all hops. Also, it is used to see network problems.

Syntax:

1. mtr **<path>**

2. **whois:** The whois command fetches every website related information. We can get every information of a website, such as an owner and the registration information.

Syntax:

1. mtr **<websiteName>**

3. **ifplugstatus:** The ifplugstatus command checks whether a cable is currently plugged into a network interface. It is not available in Ubuntu directly. We can install it with the help of the below command:

1. sudo apt-get install ifplugd

Syntax:

1. Ifplugstatus

iftop: The iftop command is utilized in traffic monitoring.

tcpdump: The tcpdump command is widely used in network analysis with other commands of the Linux network. It analyses the traffic passing from the network interface and shows it. When balancing the network, this type of packet access will be crucial.

SYNTAX:

1. $ tcpdump -i **<network_device>**

Name: VAISHAAL RAJHA T C G
231901502